



API Reference

Amazon Athena



API Version 2017-05-18

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon Athena: API Reference

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
BatchGetNamedQuery	5
Request Syntax	5
Request Parameters	5
Response Syntax	5
Response Elements	6
Errors	6
See Also	7
BatchGetPreparedStatement	8
Request Syntax	8
Request Parameters	8
Response Syntax	9
Response Elements	9
Errors	9
See Also	10
BatchGetQueryExecution	11
Request Syntax	11
Request Parameters	11
Response Syntax	11
Response Elements	13
Errors	14
See Also	14
CancelCapacityReservation	15
Request Syntax	15
Request Parameters	15
Response Elements	15
Errors	15
See Also	16
CreateCapacityReservation	17
Request Syntax	17
Request Parameters	17
Response Elements	18
Errors	18

See Also	18
CreateDataCatalog	20
Request Syntax	20
Request Parameters	20
Response Elements	22
Errors	22
See Also	23
CreateNamedQuery	24
Request Syntax	24
Request Parameters	24
Response Syntax	26
Response Elements	26
Errors	26
See Also	27
CreateNotebook	28
Request Syntax	28
Request Parameters	28
Response Syntax	29
Response Elements	29
Errors	30
See Also	30
CreatePreparedStatement	32
Request Syntax	32
Request Parameters	32
Response Elements	33
Errors	33
See Also	33
CreatePresignedNotebookUrl	35
Request Syntax	35
Request Parameters	35
Response Syntax	35
Response Elements	35
Errors	36
See Also	37
CreateWorkGroup	38
Request Syntax	38

Request Parameters	39
Response Elements	40
Errors	40
See Also	40
DeleteCapacityReservation	42
Request Syntax	42
Request Parameters	42
Response Elements	42
Errors	42
See Also	43
DeleteDataCatalog	44
Request Syntax	44
Request Parameters	44
Response Elements	44
Errors	44
See Also	45
DeleteNamedQuery	46
Request Syntax	46
Request Parameters	46
Response Elements	46
Errors	46
See Also	47
DeleteNotebook	48
Request Syntax	48
Request Parameters	48
Response Elements	48
Errors	48
See Also	49
DeletePreparedStatement	50
Request Syntax	50
Request Parameters	50
Response Elements	50
Errors	51
See Also	51
DeleteWorkGroup	52
Request Syntax	52

Request Parameters	52
Response Elements	52
Errors	52
See Also	53
ExportNotebook	54
Request Syntax	54
Request Parameters	54
Response Syntax	54
Response Elements	55
Errors	55
See Also	56
GetCalculationExecution	57
Request Syntax	57
Request Parameters	57
Response Syntax	57
Response Elements	58
Errors	59
See Also	60
GetCalculationExecutionCode	61
Request Syntax	61
Request Parameters	61
Response Syntax	61
Response Elements	61
Errors	62
See Also	62
GetCalculationExecutionStatus	64
Request Syntax	64
Request Parameters	64
Response Syntax	64
Response Elements	65
Errors	65
See Also	66
GetCapacityAssignmentConfiguration	67
Request Syntax	67
Request Parameters	67
Response Syntax	67

Response Elements	68
Errors	68
See Also	68
GetCapacityReservation	70
Request Syntax	70
Request Parameters	70
Response Syntax	70
Response Elements	71
Errors	71
See Also	71
GetDatabase	73
Request Syntax	73
Request Parameters	73
Response Syntax	74
Response Elements	74
Errors	74
See Also	75
GetDataCatalog	76
Request Syntax	76
Request Parameters	76
Response Syntax	76
Response Elements	77
Errors	77
See Also	77
GetNamedQuery	79
Request Syntax	79
Request Parameters	79
Response Syntax	79
Response Elements	80
Errors	80
See Also	80
GetNotebookMetadata	82
Request Syntax	82
Request Parameters	82
Response Syntax	82
Response Elements	83

Errors	83
See Also	83
GetPreparedStatement	85
Request Syntax	85
Request Parameters	85
Response Syntax	85
Response Elements	86
Errors	86
See Also	87
GetQueryExecution	88
Request Syntax	88
Request Parameters	88
Response Syntax	88
Response Elements	90
Errors	90
See Also	91
GetQueryResults	92
Request Syntax	92
Request Parameters	92
Response Syntax	93
Response Elements	94
Errors	95
See Also	95
GetQueryRuntimeStatistics	96
Request Syntax	96
Request Parameters	96
Response Syntax	96
Response Elements	97
Errors	98
See Also	98
GetSession	99
Request Syntax	99
Request Parameters	99
Response Syntax	99
Response Elements	100
Errors	102

See Also	102
GetSessionStatus	104
Request Syntax	104
Request Parameters	104
Response Syntax	104
Response Elements	105
Errors	105
See Also	106
GetTableMetadata	107
Request Syntax	107
Request Parameters	107
Response Syntax	108
Response Elements	109
Errors	109
See Also	110
GetWorkGroup	111
Request Syntax	111
Request Parameters	111
Response Syntax	111
Response Elements	112
Errors	113
See Also	113
ImportNotebook	114
Request Syntax	114
Request Parameters	114
Response Syntax	116
Response Elements	116
Errors	116
See Also	117
ListApplicationDPUSizes	118
Request Syntax	118
Request Parameters	118
Response Syntax	118
Response Elements	119
Errors	119
See Also	120

ListCalculationExecutions	121
Request Syntax	121
Request Parameters	121
Response Syntax	122
Response Elements	123
Errors	123
See Also	124
ListCapacityReservations	125
Request Syntax	125
Request Parameters	125
Response Syntax	125
Response Elements	126
Errors	126
See Also	127
ListDatabases	128
Request Syntax	128
Request Parameters	128
Response Syntax	129
Response Elements	129
Errors	130
See Also	131
ListDataCatalogs	132
Request Syntax	132
Request Parameters	132
Response Syntax	133
Response Elements	133
Errors	134
See Also	134
ListEngineVersions	135
Request Syntax	135
Request Parameters	135
Response Syntax	135
Response Elements	136
Errors	136
See Also	137
ListExecutors	138

Request Syntax	138
Request Parameters	138
Response Syntax	139
Response Elements	140
Errors	140
See Also	141
ListNamedQueries	142
Request Syntax	142
Request Parameters	142
Response Syntax	143
Response Elements	143
Errors	144
See Also	144
ListNotebookMetadata	145
Request Syntax	145
Request Parameters	145
Response Syntax	146
Response Elements	146
Errors	147
See Also	147
ListNotebookSessions	149
Request Syntax	149
Request Parameters	149
Response Syntax	150
Response Elements	150
Errors	151
See Also	151
ListPreparedStatements	153
Request Syntax	153
Request Parameters	153
Response Syntax	154
Response Elements	154
Errors	155
See Also	155
ListQueryExecutions	156
Request Syntax	156

Request Parameters	156
Response Syntax	157
Response Elements	157
Errors	158
See Also	158
ListSessions	159
Request Syntax	159
Request Parameters	159
Response Syntax	160
Response Elements	161
Errors	162
See Also	162
ListTableMetadata	163
Request Syntax	163
Request Parameters	163
Response Syntax	165
Response Elements	165
Errors	166
See Also	166
ListTagsForResource	168
Request Syntax	168
Request Parameters	168
Response Syntax	169
Response Elements	169
Errors	169
See Also	170
ListWorkGroups	171
Request Syntax	171
Request Parameters	171
Response Syntax	171
Response Elements	172
Errors	172
See Also	173
PutCapacityAssignmentConfiguration	174
Request Syntax	174
Request Parameters	174

Response Elements	175
Errors	175
See Also	175
StartCalculationExecution	176
Request Syntax	176
Request Parameters	176
Response Syntax	178
Response Elements	178
Errors	179
See Also	179
StartQueryExecution	181
Request Syntax	181
Request Parameters	181
Response Syntax	183
Response Elements	184
Errors	184
See Also	184
StartSession	186
Request Syntax	186
Request Parameters	186
Response Syntax	188
Response Elements	188
Errors	189
See Also	190
StopCalculationExecution	191
Request Syntax	191
Request Parameters	191
Response Syntax	191
Response Elements	192
Errors	192
See Also	193
StopQueryExecution	194
Request Syntax	194
Request Parameters	194
Response Elements	194
Errors	194

See Also	195
TagResource	196
Request Syntax	196
Request Parameters	196
Response Elements	197
Errors	197
See Also	197
TerminateSession	199
Request Syntax	199
Request Parameters	199
Response Syntax	199
Response Elements	199
Errors	200
See Also	201
UntagResource	202
Request Syntax	202
Request Parameters	202
Response Elements	202
Errors	203
See Also	203
UpdateCapacityReservation	204
Request Syntax	204
Request Parameters	204
Response Elements	204
Errors	205
See Also	205
UpdateDataCatalog	206
Request Syntax	206
Request Parameters	206
Response Elements	208
Errors	208
See Also	208
UpdateNamedQuery	209
Request Syntax	209
Request Parameters	209
Response Elements	210

Errors	210
See Also	210
UpdateNotebook	212
Request Syntax	212
Request Parameters	212
Response Elements	213
Errors	214
See Also	214
UpdateNotebookMetadata	215
Request Syntax	215
Request Parameters	215
Response Elements	216
Errors	216
See Also	217
UpdatePreparedStatement	218
Request Syntax	218
Request Parameters	218
Response Elements	219
Errors	219
See Also	220
UpdateWorkGroup	221
Request Syntax	221
Request Parameters	222
Response Elements	223
Errors	223
See Also	223
Data Types	225
AclConfiguration	228
Contents	228
See Also	228
ApplicationDPUSizes	229
Contents	229
See Also	229
AthenaError	230
Contents	230
See Also	231

BatchGetNamedQueryInput	232
Contents	232
See Also	232
BatchGetQueryExecutionInput	233
Contents	233
See Also	233
CalculationConfiguration	234
Contents	234
See Also	234
CalculationResult	235
Contents	235
See Also	236
CalculationStatistics	237
Contents	237
See Also	237
CalculationStatus	238
Contents	238
See Also	239
CalculationSummary	240
Contents	240
See Also	240
CapacityAllocation	242
Contents	242
See Also	242
CapacityAssignment	244
Contents	244
See Also	244
CapacityAssignmentConfiguration	245
Contents	245
See Also	245
CapacityReservation	246
Contents	246
See Also	247
Column	248
Contents	248
See Also	248

ColumnInfo	250
Contents	250
See Also	252
CustomerContentEncryptionConfiguration	253
Contents	253
See Also	253
Database	254
Contents	254
See Also	254
DataCatalog	256
Contents	256
See Also	258
DataCatalogSummary	259
Contents	259
See Also	259
Datum	260
Contents	260
See Also	260
EncryptionConfiguration	261
Contents	261
See Also	261
EngineConfiguration	262
Contents	262
See Also	263
EngineVersion	264
Contents	264
See Also	264
ExecutorsSummary	265
Contents	265
See Also	266
FilterDefinition	267
Contents	267
See Also	267
IdentityCenterConfiguration	268
Contents	268
See Also	268

ListNamedQueriesInput	269
Contents	269
See Also	269
ListQueryExecutionsInput	271
Contents	271
See Also	271
NamedQuery	273
Contents	273
See Also	274
NotebookMetadata	275
Contents	275
See Also	276
NotebookSessionSummary	277
Contents	277
See Also	277
PreparedStatement	278
Contents	278
See Also	279
PreparedStatementSummary	280
Contents	280
See Also	280
QueryExecution	281
Contents	281
See Also	283
QueryExecutionContext	285
Contents	285
See Also	285
QueryExecutionStatistics	286
Contents	286
See Also	288
QueryExecutionStatus	289
Contents	289
See Also	290
QueryResultsS3AccessGrantsConfiguration	291
Contents	291
See Also	291

QueryRuntimeStatistics	293
Contents	293
See Also	293
QueryRuntimeStatisticsRows	295
Contents	295
See Also	295
QueryRuntimeStatisticsTimeline	297
Contents	297
See Also	298
QueryStage	299
Contents	299
See Also	300
QueryStagePlanNode	301
Contents	301
See Also	301
ResultConfiguration	303
Contents	303
See Also	304
ResultConfigurationUpdates	305
Contents	305
See Also	307
ResultReuseByAgeConfiguration	308
Contents	308
See Also	308
ResultReuseConfiguration	309
Contents	309
See Also	309
ResultReuseInformation	310
Contents	310
See Also	310
ResultSet	311
Contents	311
See Also	311
ResultSetMetadata	312
Contents	312
See Also	312

Row	313
Contents	313
See Also	313
SessionConfiguration	314
Contents	314
See Also	315
SessionStatistics	316
Contents	316
See Also	316
SessionStatus	317
Contents	317
See Also	318
SessionSummary	319
Contents	319
See Also	320
TableMetadata	321
Contents	321
See Also	322
Tag	323
Contents	323
See Also	324
UnprocessedNamedQueryId	325
Contents	325
See Also	325
UnprocessedPreparedStatementName	327
Contents	327
See Also	328
UnprocessedQueryExecutionId	329
Contents	329
See Also	329
WorkGroup	331
Contents	331
See Also	332
WorkGroupConfiguration	334
Contents	334
See Also	337

WorkGroupConfigurationUpdates	338
Contents	338
See Also	341
WorkGroupSummary	342
Contents	342
See Also	343
Common Parameters	344
Common Errors	347

Welcome

Amazon Athena is an interactive query service that lets you use standard SQL to analyze data directly in Amazon S3. You can point Athena at your data in Amazon S3 and run ad-hoc queries and get results in seconds. Athena is serverless, so there is no infrastructure to set up or manage. You pay only for the queries you run. Athena scales automatically—executing queries in parallel—so results are fast, even with large datasets and complex queries. For more information, see [What is Amazon Athena](#) in the *Amazon Athena User Guide*.

If you connect to Athena using the JDBC driver, use version 1.1.0 of the driver or later with the Amazon Athena API. Earlier version drivers do not support the API. For more information and to download the driver, see [Accessing Amazon Athena with JDBC](#).

This document was last published on July 2, 2024.

Actions

The following actions are supported:

- [BatchGetNamedQuery](#)
- [BatchGetPreparedStatement](#)
- [BatchGetQueryExecution](#)
- [CancelCapacityReservation](#)
- [CreateCapacityReservation](#)
- [CreateDataCatalog](#)
- [CreateNamedQuery](#)
- [CreateNotebook](#)
- [CreatePreparedStatement](#)
- [CreatePresignedNotebookUrl](#)
- [CreateWorkGroup](#)
- [DeleteCapacityReservation](#)
- [DeleteDataCatalog](#)
- [DeleteNamedQuery](#)
- [DeleteNotebook](#)
- [DeletePreparedStatement](#)
- [DeleteWorkGroup](#)
- [ExportNotebook](#)
- [GetCalculationExecution](#)
- [GetCalculationExecutionCode](#)
- [GetCalculationExecutionStatus](#)
- [GetCapacityAssignmentConfiguration](#)
- [GetCapacityReservation](#)
- [GetDatabase](#)
- [GetDataCatalog](#)
- [GetNamedQuery](#)
- [GetNotebookMetadata](#)

- [GetPreparedStatement](#)
- [GetQueryExecution](#)
- [GetQueryResults](#)
- [GetQueryRuntimeStatistics](#)
- [GetSession](#)
- [GetSessionStatus](#)
- [GetTableMetadata](#)
- [GetWorkGroup](#)
- [ImportNotebook](#)
- [ListApplicationDPUSizes](#)
- [ListCalculationExecutions](#)
- [ListCapacityReservations](#)
- [ListDatabases](#)
- [ListDataCatalogs](#)
- [ListEngineVersions](#)
- [ListExecutors](#)
- [ListNamedQueries](#)
- [ListNotebookMetadata](#)
- [ListNotebookSessions](#)
- [ListPreparedStatements](#)
- [ListQueryExecutions](#)
- [ListSessions](#)
- [ListTableMetadata](#)
- [ListTagsForResource](#)
- [ListWorkGroups](#)
- [PutCapacityAssignmentConfiguration](#)
- [StartCalculationExecution](#)
- [StartQueryExecution](#)
- [StartSession](#)
- [StopCalculationExecution](#)

- [StopQueryExecution](#)
- [TagResource](#)
- [TerminateSession](#)
- [UntagResource](#)
- [UpdateCapacityReservation](#)
- [UpdateDataCatalog](#)
- [UpdateNamedQuery](#)
- [UpdateNotebook](#)
- [UpdateNotebookMetadata](#)
- [UpdatePreparedStatement](#)
- [UpdateWorkGroup](#)

BatchGetNamedQuery

Returns the details of a single named query or a list of up to 50 queries, which you provide as an array of query ID strings. Requires you to have access to the workgroup in which the queries were saved. Use [ListNamedQueriesInput](#) to get the list of named query IDs in the specified workgroup. If information could not be retrieved for a submitted query ID, information about the query ID submitted is listed under [UnprocessedNamedQueryId](#). Named queries differ from executed queries. Use [BatchGetQueryExecutionInput](#) to get details about each unique query execution, and [ListQueryExecutionsInput](#) to get a list of query execution IDs.

Request Syntax

```
{
  "NamedQueryIds": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[NamedQueryIds](#)

An array of query IDs.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: \S+

Required: Yes

Response Syntax

```
{
  "NamedQueries": [
```

```
{
  "Database": "string",
  "Description": "string",
  "Name": "string",
  "NamedQueryId": "string",
  "QueryString": "string",
  "WorkGroup": "string"
},
"UnprocessedNamedQueryIds": [
  {
    "ErrorCode": "string",
    "ErrorMessage": "string",
    "NamedQueryId": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NamedQueries

Information about the named query IDs submitted.

Type: Array of [NamedQuery](#) objects

UnprocessedNamedQueryIds

Information about provided query IDs.

Type: Array of [UnprocessedNamedQueryId](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

BatchGetPreparedStatement

Returns the details of a single prepared statement or a list of up to 256 prepared statements for the array of prepared statement names that you provide. Requires you to have access to the workgroup to which the prepared statements belong. If a prepared statement cannot be retrieved for the name specified, the statement is listed in `UnprocessedPreparedStatementNames`.

Request Syntax

```
{
  "PreparedStatementNames": [ "string" ],
  "WorkGroup": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

PreparedStatementNames

A list of prepared statement names to return.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z_][a-zA-Z0-9_@:]{1,256}`

Required: Yes

WorkGroup

The name of the workgroup to which the prepared statements belong.

Type: String

Pattern: `[a-zA-Z0-9._-]{1,128}`

Required: Yes

Response Syntax

```
{
  "PreparedStatements": [
    {
      "Description": "string",
      "LastModifiedTime": number,
      "QueryStatement": "string",
      "StatementName": "string",
      "WorkGroupName": "string"
    }
  ],
  "UnprocessedPreparedStatementNames": [
    {
      "ErrorCode": "string",
      "ErrorMessage": "string",
      "StatementName": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

PreparedStatements

The list of prepared statements returned.

Type: Array of [PreparedStatement](#) objects

UnprocessedPreparedStatementNames

A list of one or more prepared statements that were requested but could not be returned.

Type: Array of [UnprocessedPreparedStatementName](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

BatchGetQueryExecution

Returns the details of a single query execution or a list of up to 50 query executions, which you provide as an array of query execution ID strings. Requires you to have access to the workgroup in which the queries ran. To get a list of query execution IDs, use [ListQueryExecutions:WorkGroup](#). Query executions differ from named (saved) queries. Use [BatchGetNamedQueryInput](#) to get details about named queries.

Request Syntax

```
{
  "QueryExecutionIds": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[QueryExecutionIds](#)

An array of query execution IDs.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: \S+

Required: Yes

Response Syntax

```
{
  "QueryExecutions": [
    {
      "EngineVersion": {
        "EffectiveEngineVersion": "string",
```



```

    "SelectedEngineVersion": "string"
  },
  "ExecutionParameters": [ "string" ],
  "Query": "string",
  "QueryExecutionContext": {
    "Catalog": "string",
    "Database": "string"
  },
  "QueryExecutionId": "string",
  "QueryResultsS3AccessGrantsConfiguration": {
    "AuthenticationType": "string",
    "CreateUserLevelPrefix": boolean,
    "EnableS3AccessGrants": boolean
  },
  "ResultConfiguration": {
    "AclConfiguration": {
      "S3AclOption": "string"
    },
    "EncryptionConfiguration": {
      "EncryptionOption": "string",
      "KmsKey": "string"
    },
    "ExpectedBucketOwner": "string",
    "OutputLocation": "string"
  },
  "ResultReuseConfiguration": {
    "ResultReuseByAgeConfiguration": {
      "Enabled": boolean,
      "MaxAgeInMinutes": number
    }
  },
  "StatementType": "string",
  "Statistics": {
    "DataManifestLocation": "string",
    "DataScannedInBytes": number,
    "EngineExecutionTimeInMillis": number,
    "QueryPlanningTimeInMillis": number,
    "QueryQueueTimeInMillis": number,
    "ResultReuseInformation": {
      "ReusedPreviousResult": boolean
    },
    "ServicePreProcessingTimeInMillis": number,
    "ServiceProcessingTimeInMillis": number,
    "TotalExecutionTimeInMillis": number
  }
}

```

```

    },
    "Status": {
      "AthenaError": {
        "ErrorCategory": number,
        "ErrorMessage": "string",
        "ErrorType": number,
        "Retryable": boolean
      },
      "CompletionDateTime": number,
      "State": "string",
      "StateChangeReason": "string",
      "SubmissionDateTime": number
    },
    "SubstatementType": "string",
    "WorkGroup": "string"
  }
],
"UnprocessedQueryExecutionIds": [
  {
    "ErrorCode": "string",
    "ErrorMessage": "string",
    "QueryExecutionId": "string"
  }
]
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

QueryExecutions

Information about a query execution.

Type: Array of [QueryExecution](#) objects

UnprocessedQueryExecutionIds

Information about the query executions that failed to run.

Type: Array of [UnprocessedQueryExecutionId](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CancelCapacityReservation

Cancels the capacity reservation with the specified name. Cancelled reservations remain in your account and will be deleted 45 days after cancellation. During the 45 days, you cannot re-purpose or reuse a reservation that has been cancelled, but you can refer to its tags and view it for historical reference.

Request Syntax

```
{  
  "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

The name of the capacity reservation to cancel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9._-]+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateCapacityReservation

Creates a capacity reservation with the specified name and number of requested data processing units.

Request Syntax

```
{
  "Name": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "TargetDpus": number
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

The name of the capacity reservation to create.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9._-]+

Required: Yes

Tags

The tags for the capacity reservation.

Type: Array of [Tag](#) objects

Required: No

TargetDpus

The number of requested data processing units.

Type: Integer

Valid Range: Minimum value of 24.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateDataCatalog

Creates (registers) a data catalog with the specified name and properties. Catalogs created are visible to all users of the same AWS account.

Request Syntax

```
{
  "Description": "string",
  "Name": "string",
  "Parameters": {
    "string" : "string"
  },
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "Type": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Description

A description of the data catalog to be created.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

Name

The name of the data catalog to create. The catalog name must be unique for the AWS account and can use a maximum of 127 alphanumeric, underscore, at sign, or hyphen characters. The remainder of the length constraint of 256 is reserved for use by Athena.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFF\uD800\uDC00-\uDBFF\uDFFF\t]*`

Required: Yes

Parameters

Specifies the Lambda function or functions to use for creating the data catalog. This is a mapping whose values depend on the catalog type.

- For the HIVE data catalog type, use the following syntax. The `metadata-function` parameter is required. The `sdk-version` parameter is optional and defaults to the currently supported version.

```
metadata-function=lambda_arn, sdk-version=version_number
```

- For the LAMBDA data catalog type, use one of the following sets of required parameters, but not both.
 - If you have one Lambda function that processes metadata and another for reading the actual data, use the following syntax. Both parameters are required.

```
metadata-function=lambda_arn, record-function=lambda_arn
```

- If you have a composite Lambda function that processes both metadata and data, use the following syntax to specify your Lambda function.

```
function=lambda_arn
```

- The GLUE type takes a catalog ID parameter and is required. The `catalog_id` is the account ID of the AWS account to which the AWS Glue Data Catalog belongs.

```
catalog-id=catalog_id
```

- The GLUE data catalog type also applies to the default `AwsDataCatalog` that already exists in your account, of which you can have only one and cannot modify.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 255.

Key Pattern: `[\u0020-\uD7FF\uE000-\uFFFF\uD800\uDC00-\uDBFF\uDFFF\t]*`

Value Length Constraints: Maximum length of 51200.

Required: No

Tags

A list of comma separated tags to add to the data catalog that is created.

Type: Array of [Tag](#) objects

Required: No

Type

The type of data catalog to create: LAMBDA for a federated catalog, HIVE for an external hive metastore, or GLUE for an AWS Glue Data Catalog.

Type: String

Valid Values: LAMBDA | GLUE | HIVE

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateNamedQuery

Creates a named query in the specified workgroup. Requires that you have access to the workgroup.

Request Syntax

```
{
  "ClientRequestToken": "string",
  "Database": "string",
  "Description": "string",
  "Name": "string",
  "QueryString": "string",
  "WorkGroup": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClientRequestToken

A unique case-sensitive string used to ensure the request to create the query is idempotent (executes only once). If another `CreateNamedQuery` request is received, the same response is returned and another query is not created. If a parameter has changed, for example, the `QueryString`, an error is returned.

Important

This token is listed as not required because AWS SDKs (for example the AWS SDK for Java) auto-generate the token for users. If you are not using the AWS SDK or the AWS CLI, you must provide this token or the action will fail.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 128.

Required: No

Database

The database to which the query belongs.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Description

The query description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

Name

The query name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

QueryString

The contents of the query with all query statements.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 262144.

Required: Yes

WorkGroup

The name of the workgroup in which the named query is being created.

Type: String

Pattern: `[a-zA-Z0-9._-]{1,128}`

Required: No

Response Syntax

```
{  
  "NamedQueryId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NamedQueryId

The unique ID of the query.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `\S+`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateNotebook

Creates an empty `ipynb` file in the specified Apache Spark enabled workgroup. Throws an error if a file in the workgroup with the same name already exists.

Request Syntax

```
{
  "ClientRequestToken": "string",
  "Name": "string",
  "WorkGroup": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClientRequestToken

A unique case-sensitive string used to ensure the request to create the notebook is idempotent (executes only once).

Important

This token is listed as not required because AWS SDKs (for example the AWS SDK for Java) auto-generate the token for you. If you are not using the AWS SDK or the AWS CLI, you must provide this token or the action will fail.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Pattern: `[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`

Required: No

Name

The name of the `ipynb` file to be created in the Spark workgroup, without the `.ipynb` extension.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `(?!.*[/:\])[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDC00-\uDBFF\uDFFF\t]+`

Required: Yes

WorkGroup

The name of the Spark enabled workgroup in which the notebook will be created.

Type: String

Pattern: `[a-zA-Z0-9._-]{1,128}`

Required: Yes

Response Syntax

```
{
  "NotebookId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NotebookId

A unique identifier for the notebook.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Pattern: `[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

TooManyRequestsException

Indicates that the request was throttled.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreatePreparedStatement

Creates a prepared statement for use with SQL queries in Athena.

Request Syntax

```
{  
  "Description": "string",  
  "QueryStatement": "string",  
  "StatementName": "string",  
  "WorkGroup": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Description

The description of the prepared statement.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

QueryStatement

The query string for the prepared statement.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 262144.

Required: Yes

StatementName

The name of the prepared statement.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z_][a-zA-Z0-9_@:]{1,256}`

Required: Yes

WorkGroup

The name of the workgroup to which the prepared statement belongs.

Type: String

Pattern: `[a-zA-Z0-9._-]{1,128}`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreatePresignedNotebookUrl

Gets an authentication token and the URL at which the notebook can be accessed. During programmatic access, `CreatePresignedNotebookUrl` must be called every 10 minutes to refresh the authentication token. For information about granting programmatic access, see [Grant programmatic access](#).

Request Syntax

```
{
  "SessionId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[SessionId](#)

The session ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

Response Syntax

```
{
  "AuthToken": "string",
  "AuthTokenExpirationTime": number,
  "NotebookUrl": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AuthToken

The authentication token for the notebook.

Type: String

Length Constraints: Maximum length of 2048.

AuthTokenExpirationTime

The UTC epoch time when the authentication token expires.

Type: Long

NotebookUrl

The URL of the notebook. The URL includes the authentication token and notebook file name and points directly to the opened notebook.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

ResourceNotFoundException

A resource, such as a workgroup, was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateWorkGroup

Creates a workgroup with the specified name. A workgroup can be an Apache Spark enabled workgroup or an Athena SQL workgroup.

Request Syntax

```
{
  "Configuration": {
    "AdditionalConfiguration": "string",
    "BytesScannedCutoffPerQuery": number,
    "CustomerContentEncryptionConfiguration": {
      "KmsKey": "string"
    },
    "EnableMinimumEncryptionConfiguration": boolean,
    "EnforceWorkGroupConfiguration": boolean,
    "EngineVersion": {
      "EffectiveEngineVersion": "string",
      "SelectedEngineVersion": "string"
    },
    "ExecutionRole": "string",
    "IdentityCenterConfiguration": {
      "EnableIdentityCenter": boolean,
      "IdentityCenterInstanceArn": "string"
    },
    "PublishCloudWatchMetricsEnabled": boolean,
    "QueryResultsS3AccessGrantsConfiguration": {
      "AuthenticationType": "string",
      "CreateUserLevelPrefix": boolean,
      "EnableS3AccessGrants": boolean
    },
    "RequesterPaysEnabled": boolean,
    "ResultConfiguration": {
      "AclConfiguration": {
        "S3AclOption": "string"
      },
      "EncryptionConfiguration": {
        "EncryptionOption": "string",
        "KmsKey": "string"
      },
      "ExpectedBucketOwner": "string",
      "OutputLocation": "string"
    }
  }
}
```

```
},
  "Description": "string",
  "Name": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Configuration

Contains configuration information for creating an Athena SQL workgroup or Spark enabled Athena workgroup. Athena SQL workgroup configuration includes the location in Amazon S3 where query and calculation results are stored, the encryption configuration, if any, used for encrypting query results, whether the Amazon CloudWatch Metrics are enabled for the workgroup, the limit for the amount of bytes scanned (cutoff) per query, if it is specified, and whether workgroup's settings (specified with `EnforceWorkGroupConfiguration`) in the `WorkGroupConfiguration` override client-side settings. See [WorkGroupConfiguration:EnforceWorkGroupConfiguration](#).

Type: [WorkGroupConfiguration](#) object

Required: No

Description

The workgroup description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

Name

The workgroup name.

Type: String

Pattern: [a-zA-Z0-9._-]{1,128}

Required: Yes

Tags

A list of comma separated tags to add to the workgroup that is created.

Type: Array of [Tag](#) objects

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteCapacityReservation

Deletes a cancelled capacity reservation. A reservation must be cancelled before it can be deleted. A deleted reservation is immediately removed from your account and can no longer be referenced, including by its ARN. A deleted reservation cannot be called by `GetCapacityReservation`, and deleted reservations do not appear in the output of `ListCapacityReservations`.

Request Syntax

```
{  
  "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

The name of the capacity reservation to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9._-]+`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteDataCatalog

Deletes a data catalog.

Request Syntax

```
{  
  "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

The name of the data catalog to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFF\uD800\uDC00-\uDBFF\uDFFF\t]*`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteNamedQuery

Deletes the named query if you have access to the workgroup in which the query was saved.

Request Syntax

```
{  
  "NamedQueryId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

NamedQueryId

The unique ID of the query to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: \S+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteNotebook

Deletes the specified notebook.

Request Syntax

```
{  
  "NotebookId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[NotebookId](#)

The ID of the notebook to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Pattern: `[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

TooManyRequestsException

Indicates that the request was throttled.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeletePreparedStatement

Deletes the prepared statement with the specified name from the specified workgroup.

Request Syntax

```
{  
  "StatementName": "string",  
  "WorkGroup": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

StatementName

The name of the prepared statement to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z_][a-zA-Z0-9_@:]{1,256}

Required: Yes

WorkGroup

The workgroup to which the statement to be deleted belongs.

Type: String

Pattern: [a-zA-Z0-9._-]{1,128}

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

ResourceNotFoundException

A resource, such as a workgroup, was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteWorkGroup

Deletes the workgroup with the specified name. The primary workgroup cannot be deleted.

Request Syntax

```
{
  "RecursiveDeleteOption": boolean,
  "WorkGroup": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[RecursiveDeleteOption](#)

The option to delete the workgroup and its contents even if the workgroup contains any named queries, query executions, or notebooks.

Type: Boolean

Required: No

[WorkGroup](#)

The unique name of the workgroup to delete.

Type: String

Pattern: [a-zA-Z0-9._-]{1,128}

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ExportNotebook

Exports the specified notebook and its metadata.

Request Syntax

```
{
  "NotebookId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

NotebookId

The ID of the notebook to export.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Pattern: [a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}

Required: Yes

Response Syntax

```
{
  "NotebookMetadata": {
    "CreationTime": number,
    "LastModifiedTime": number,
    "Name": "string",
    "NotebookId": "string",
    "Type": "string",
    "WorkGroup": "string"
  },
  "Payload": "string"
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NotebookMetadata

The notebook metadata, including notebook ID, notebook name, and workgroup name.

Type: [NotebookMetadata](#) object

Payload

The content of the exported notebook.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10485760.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

TooManyRequestsException

Indicates that the request was throttled.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetCalculationExecution

Describes a previously submitted calculation execution.

Request Syntax

```
{
  "CalculationExecutionId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

CalculationExecutionId

The calculation execution UUID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Required: Yes

Response Syntax

```
{
  "CalculationExecutionId": "string",
  "Description": "string",
  "Result": {
    "ResultS3Uri": "string",
    "ResultType": "string",
    "StdErrorS3Uri": "string",
    "StdOutS3Uri": "string"
  },
  "SessionId": "string",
  "Statistics": {
    "DpuExecutionInMillis": number,
    "Progress": "string"
  }
}
```

```
  },
  "Status": {
    "CompletionDateTime": number,
    "State": "string",
    "StateChangeReason": "string",
    "SubmissionDateTime": number
  },
  "WorkingDirectory": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CalculationExecutionId

The calculation execution UUID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Description

The description of the calculation execution.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Result

Contains result information. This field is populated only if the calculation is completed.

Type: [CalculationResult](#) object

SessionId

The session ID that the calculation ran in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Statistics

Contains information about the data processing unit (DPU) execution time and progress. This field is populated only when statistics are available.

Type: [CalculationStatistics](#) object

Status

Contains information about the status of the calculation.

Type: [CalculationStatus](#) object

WorkingDirectory

The Amazon S3 location in which calculation results are stored.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^(https|s3|S3)://[^(/)]+/?(.*)$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

ResourceNotFoundException

A resource, such as a workgroup, was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetCalculationExecutionCode

Retrieves the unencrypted code that was executed for the calculation.

Request Syntax

```
{
  "CalculationExecutionId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

CalculationExecutionId

The calculation execution UUID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Required: Yes

Response Syntax

```
{
  "CodeBlock": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CodeBlock

The unencrypted code that was executed for the calculation.

Type: String

Length Constraints: Maximum length of 68000.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

ResourceNotFoundException

A resource, such as a workgroup, was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetCalculationExecutionStatus

Gets the status of a current calculation.

Request Syntax

```
{  
  "CalculationExecutionId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

CalculationExecutionId

The calculation execution UUID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Required: Yes

Response Syntax

```
{  
  "Statistics": {  
    "DpuExecutionInMillis": number,  
    "Progress": "string"  
  },  
  "Status": {  
    "CompletionDateTime": number,  
    "State": "string",  
    "StateChangeReason": "string",  
    "SubmissionDateTime": number  
  }  
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Statistics

Contains information about the DPU execution time and progress.

Type: [CalculationStatistics](#) object

Status

Contains information about the calculation execution status.

Type: [CalculationStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

ResourceNotFoundException

A resource, such as a workgroup, was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetCapacityAssignmentConfiguration

Gets the capacity assignment configuration for a capacity reservation, if one exists.

Request Syntax

```
{  
  "CapacityReservationName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[CapacityReservationName](#)

The name of the capacity reservation to retrieve the capacity assignment configuration for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9._-]+

Required: Yes

Response Syntax

```
{  
  "CapacityAssignmentConfiguration": {  
    "CapacityAssignments": [  
      {  
        "WorkGroupNames": [ "string" ]  
      }  
    ],  
    "CapacityReservationName": "string"  
  }  
}
```


Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CapacityAssignmentConfiguration

The requested capacity assignment configuration for the specified capacity reservation.

Type: [CapacityAssignmentConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetCapacityReservation

Returns information about the capacity reservation with the specified name.

Request Syntax

```
{
  "Name": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

The name of the capacity reservation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9._-]+

Required: Yes

Response Syntax

```
{
  "CapacityReservation": {
    "AllocatedDpus": number,
    "CreationTime": number,
    "LastAllocation": {
      "RequestCompletionTime": number,
      "RequestTime": number,
      "Status": "string",
      "StatusMessage": "string"
    },
    "LastSuccessfulAllocationTime": number,
  },
}
```

```
    "Name": "string",
    "Status": "string",
    "TargetDpus": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CapacityReservation

The requested capacity reservation structure.

Type: [CapacityReservation](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDatabase

Returns a database object for the specified database and data catalog.

Request Syntax

```
{  
  "CatalogName": "string",  
  "DatabaseName": "string",  
  "WorkGroup": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

CatalogName

The name of the data catalog that contains the database to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFF\uD800\uDC00-\uDBFF\uDFFF\t]*`

Required: Yes

DatabaseName

The name of the database to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

WorkGroup

The name of the workgroup for which the metadata is being fetched. Required if requesting an IAM Identity Center enabled AWS Glue Data Catalog.

Type: String

Pattern: [a-zA-Z0-9._-]{1,128}

Required: No

Response Syntax

```
{
  "Database": {
    "Description": "string",
    "Name": "string",
    "Parameters": {
      "string" : "string"
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Database

The database returned.

Type: [Database](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

MetadataException

An exception that Athena received when it called a custom metastore. Occurs if the error is not caused by user input (`InvalidRequestException`) or from the Athena platform (`InternalServerErrorException`). For example, if a user-created Lambda function is missing permissions, the Lambda 4XX exception is returned in a `MetadataException`.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDataCatalog

Returns the specified data catalog.

Request Syntax

```
{  
  "Name": "string",  
  "WorkGroup": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

The name of the data catalog to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFF\uD800\uDC00-\uDBFF\uDFFF\t]*`

Required: Yes

WorkGroup

The name of the workgroup. Required if making an IAM Identity Center request.

Type: String

Pattern: `[a-zA-Z0-9._-]{1,128}`

Required: No

Response Syntax

```
{  
  "DataCatalog": {
```

```
    "Description": "string",
    "Name": "string",
    "Parameters": {
      "string" : "string"
    },
    "Type": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[DataCatalog](#)

The data catalog returned.

Type: [DataCatalog](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetNamedQuery

Returns information about a single query. Requires that you have access to the workgroup in which the query was saved.

Request Syntax

```
{
  "NamedQueryId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[NamedQueryId](#)

The unique ID of the query. Use [ListNamedQueries](#) to get query IDs.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: \S+

Required: Yes

Response Syntax

```
{
  "NamedQuery": {
    "Database": "string",
    "Description": "string",
    "Name": "string",
    "NamedQueryId": "string",
    "QueryString": "string",
    "WorkGroup": "string"
  }
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NamedQuery](#)

Information about the query.

Type: [NamedQuery](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetNotebookMetadata

Retrieves notebook metadata for the specified notebook ID.

Request Syntax

```
{  
  "NotebookId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

NotebookId

The ID of the notebook whose metadata is to be retrieved.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Pattern: [a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}

Required: Yes

Response Syntax

```
{  
  "NotebookMetadata": {  
    "CreationTime": number,  
    "LastModifiedTime": number,  
    "Name": "string",  
    "NotebookId": "string",  
    "Type": "string",  
    "WorkGroup": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NotebookMetadata

The metadata that is returned for the specified notebook ID.

Type: [NotebookMetadata](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

TooManyRequestsException

Indicates that the request was throttled.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetPreparedStatement

Retrieves the prepared statement with the specified name from the specified workgroup.

Request Syntax

```
{  
  "StatementName": "string",  
  "WorkGroup": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

StatementName

The name of the prepared statement to retrieve.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z_][a-zA-Z0-9_@:]{1,256}

Required: Yes

WorkGroup

The workgroup to which the statement to be retrieved belongs.

Type: String

Pattern: [a-zA-Z0-9._-]{1,128}

Required: Yes

Response Syntax

```
{
```

```
"PreparedStatement": {
  "Description": "string",
  "LastModifiedTime": number,
  "QueryStatement": "string",
  "StatementName": "string",
  "WorkGroupName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

PreparedStatement

The name of the prepared statement that was retrieved.

Type: [PreparedStatement](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

ResourceNotFoundException

A resource, such as a workgroup, was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetQueryExecution

Returns information about a single execution of a query if you have access to the workgroup in which the query ran. Each time a query executes, information about the query execution is saved with a unique ID.

Request Syntax

```
{
  "QueryExecutionId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

QueryExecutionId

The unique ID of the query execution.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: \S+

Required: Yes

Response Syntax

```
{
  "QueryExecution": {
    "EngineVersion": {
      "EffectiveEngineVersion": "string",
      "SelectedEngineVersion": "string"
    },
    "ExecutionParameters": [ "string" ],
    "Query": "string",
    "QueryExecutionContext": {
      "Catalog": "string",
```

```

    "Database": "string"
  },
  "QueryExecutionId": "string",
  "QueryResultsS3AccessGrantsConfiguration": {
    "AuthenticationType": "string",
    "CreateUserLevelPrefix": boolean,
    "EnableS3AccessGrants": boolean
  },
  "ResultConfiguration": {
    "AclConfiguration": {
      "S3AclOption": "string"
    },
    "EncryptionConfiguration": {
      "EncryptionOption": "string",
      "KmsKey": "string"
    },
    "ExpectedBucketOwner": "string",
    "OutputLocation": "string"
  },
  "ResultReuseConfiguration": {
    "ResultReuseByAgeConfiguration": {
      "Enabled": boolean,
      "MaxAgeInMinutes": number
    }
  },
  "StatementType": "string",
  "Statistics": {
    "DataManifestLocation": "string",
    "DataScannedInBytes": number,
    "EngineExecutionTimeInMillis": number,
    "QueryPlanningTimeInMillis": number,
    "QueryQueueTimeInMillis": number,
    "ResultReuseInformation": {
      "ReusedPreviousResult": boolean
    },
    "ServicePreProcessingTimeInMillis": number,
    "ServiceProcessingTimeInMillis": number,
    "TotalExecutionTimeInMillis": number
  },
  "Status": {
    "AthenaError": {
      "ErrorCategory": number,
      "ErrorMessage": "string",
      "ErrorType": number,

```

```
    "Retryable": boolean
  },
  "CompletionDateTime": number,
  "State": "string",
  "StateChangeReason": "string",
  "SubmissionDateTime": number
},
"SubstatementType": "string",
"WorkGroup": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

QueryExecution

Information about the query execution.

Type: [QueryExecution](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetQueryResults

Streams the results of a single query execution specified by `QueryExecutionId` from the Athena query results location in Amazon S3. For more information, see [Working with query results, recent queries, and output files](#) in the *Amazon Athena User Guide*. This request does not execute the query but returns results. Use [StartQueryExecution](#) to run a query.

To stream query results successfully, the IAM principal with permission to call `GetQueryResults` also must have permissions to the Amazon S3 `GetObject` action for the Athena query results location.

Important

IAM principals with permission to the Amazon S3 `GetObject` action for the query results location are able to retrieve query results from Amazon S3 even if permission to the `GetQueryResults` action is denied. To restrict user or role access, ensure that Amazon S3 permissions to the Athena query location are denied.

Request Syntax

```
{
  "MaxResults": number,
  "NextToken": "string",
  "QueryExecutionId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[MaxResults](#)

The maximum number of results (rows) to return in this request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

QueryExecutionId

The unique ID of the query execution.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: \S+

Required: Yes

Response Syntax

```
{
  "NextToken": "string",
  "ResultSet": {
    "ResultSetMetadata": {
      "ColumnInfo": [
        {
          "CaseSensitive": boolean,
          "CatalogName": "string",
          "Label": "string",
          "Name": "string",
          "Nullable": "string",
          "Precision": number,
          "Scale": number,
          "SchemaName": "string",
          "TableName": "string",
```

```
        "Type": "string"
      }
    ],
    "Rows": [
      {
        "Data": [
          {
            "VarCharValue": "string"
          }
        ]
      }
    ]
  },
  "UpdateCount": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

ResultSet

The results of the query execution.

Type: [ResultSet](#) object

UpdateCount

The number of rows inserted with a CREATE TABLE AS SELECT statement.

Type: Long

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

TooManyRequestsException

Indicates that the request was throttled.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetQueryRuntimeStatistics

Returns query execution runtime statistics related to a single execution of a query if you have access to the workgroup in which the query ran. Statistics from the `Timeline` section of the response object are available as soon as [QueryExecutionStatus:State](#) is in a `SUCCEEDED` or `FAILED` state. The remaining non-timeline statistics in the response (like stage-level input and output row count and data size) are updated asynchronously and may not be available immediately after a query completes. The non-timeline statistics are also not included when a query has row-level filters defined in Lake Formation.

Request Syntax

```
{
  "QueryExecutionId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[QueryExecutionId](#)

The unique ID of the query execution.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `\S+`

Required: Yes

Response Syntax

```
{
  "QueryRuntimeStatistics": {
    "OutputStage": {
      "ExecutionTime": number,
      "InputBytes": number,

```

```

    "InputRows": number,
    "OutputBytes": number,
    "OutputRows": number,
    "QueryStagePlan": {
      "Children": [
        "QueryStagePlanNode"
      ],
      "Identifier": "string",
      "Name": "string",
      "RemoteSources": [ "string" ]
    },
    "StageId": number,
    "State": "string",
    "SubStages": [
      "QueryStage"
    ]
  },
  "Rows": {
    "InputBytes": number,
    "InputRows": number,
    "OutputBytes": number,
    "OutputRows": number
  },
  "Timeline": {
    "EngineExecutionTimeInMillis": number,
    "QueryPlanningTimeInMillis": number,
    "QueryQueueTimeInMillis": number,
    "ServicePreProcessingTimeInMillis": number,
    "ServiceProcessingTimeInMillis": number,
    "TotalExecutionTimeInMillis": number
  }
}
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

QueryRuntimeStatistics

Runtime statistics about the query execution.

Type: [QueryRuntimeStatistics](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetSession

Gets the full details of a previously created session, including the session status and configuration.

Request Syntax

```
{
  "SessionId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

SessionId

The session ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

Response Syntax

```
{
  "Description": "string",
  "EngineConfiguration": {
    "AdditionalConfigs": {
      "string" : "string"
    },
    "CoordinatorDpuSize": number,
    "DefaultExecutorDpuSize": number,
    "MaxConcurrentDpus": number,
    "SparkProperties": {
      "string" : "string"
    }
  }
}
```



```
},
"EngineVersion": "string",
"NotebookVersion": "string",
"SessionConfiguration": {
  "EncryptionConfiguration": {
    "EncryptionOption": "string",
    "KmsKey": "string"
  },
  "ExecutionRole": "string",
  "IdleTimeoutSeconds": number,
  "WorkingDirectory": "string"
},
"SessionId": "string",
"Statistics": {
  "DpuExecutionInMillis": number
},
"Status": {
  "EndDateTime": number,
  "IdleSinceDateTime": number,
  "LastModifiedDateTime": number,
  "StartDateTime": number,
  "State": "string",
  "StateChangeReason": "string"
},
"WorkGroup": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Description

The session description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

EngineConfiguration

Contains engine configuration information like DPU usage.

Type: [EngineConfiguration](#) object

EngineVersion

The engine version used by the session (for example, PySpark engine version 3). You can get a list of engine versions by calling [ListEngineVersions](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

NotebookVersion

The notebook version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

SessionConfiguration

Contains the workgroup configuration information used by the session.

Type: [SessionConfiguration](#) object

SessionId

The session ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Statistics

Contains the DPU execution time.

Type: [SessionStatistics](#) object

Status

Contains information about the status of the session.

Type: [SessionStatus](#) object

WorkGroup

The workgroup to which the session belongs.

Type: String

Pattern: [a-zA-Z0-9._-]{1,128}

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

ResourceNotFoundException

A resource, such as a workgroup, was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetSessionStatus

Gets the current status of a session.

Request Syntax

```
{
  "SessionId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

SessionId

The session ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

Response Syntax

```
{
  "SessionId": "string",
  "Status": {
    "EndDateTime": number,
    "IdleSinceDateTime": number,
    "LastModifiedDateTime": number,
    "StartDateTime": number,
    "State": "string",
    "StateChangeReason": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

SessionId

The session ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Status

Contains information about the status of the session.

Type: [SessionStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

ResourceNotFoundException

A resource, such as a workgroup, was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTableMetadata

Returns table metadata for the specified catalog, database, and table.

Request Syntax

```
{  
  "CatalogName": "string",  
  "DatabaseName": "string",  
  "TableName": "string",  
  "WorkGroup": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

CatalogName

The name of the data catalog that contains the database and table metadata to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDC00-\uDBFF\uDFFF\t]*`

Required: Yes

DatabaseName

The name of the database that contains the table metadata to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

TableName

The name of the table for which metadata is returned.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

WorkGroup

The name of the workgroup for which the metadata is being fetched. Required if requesting an IAM Identity Center enabled AWS Glue Data Catalog.

Type: String

Pattern: [a-zA-Z0-9._-]{1,128}

Required: No

Response Syntax

```
{
  "TableMetadata": {
    "Columns": [
      {
        "Comment": "string",
        "Name": "string",
        "Type": "string"
      }
    ],
    "CreateTime": number,
    "LastAccessTime": number,
    "Name": "string",
    "Parameters": {
      "string" : "string"
    },
    "PartitionKeys": [
      {
        "Comment": "string",
        "Name": "string",
        "Type": "string"
      }
    ],
    "TableType": "string"
  }
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

TableMetadata

An object that contains table metadata.

Type: [TableMetadata](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

MetadataException

An exception that Athena received when it called a custom metastore. Occurs if the error is not caused by user input (`InvalidRequestException`) or from the Athena platform (`InternalServerError`). For example, if a user-created Lambda function is missing permissions, the Lambda 4XX exception is returned in a `MetadataException`.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetWorkGroup

Returns information about the workgroup with the specified name.

Request Syntax

```
{  
  "WorkGroup": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

WorkGroup

The name of the workgroup.

Type: String

Pattern: [a-zA-Z0-9._-]{1,128}

Required: Yes

Response Syntax

```
{  
  "WorkGroup": {  
    "Configuration": {  
      "AdditionalConfiguration": "string",  
      "BytesScannedCutoffPerQuery": number,  
      "CustomerContentEncryptionConfiguration": {  
        "KmsKey": "string"  
      },  
      "EnableMinimumEncryptionConfiguration": boolean,  
      "EnforceWorkGroupConfiguration": boolean,  
      "EngineVersion": {  
        "EffectiveEngineVersion": "string",
```

```
    "SelectedEngineVersion": "string"
  },
  "ExecutionRole": "string",
  "IdentityCenterConfiguration": {
    "EnableIdentityCenter": boolean,
    "IdentityCenterInstanceArn": "string"
  },
  "PublishCloudWatchMetricsEnabled": boolean,
  "QueryResultsS3AccessGrantsConfiguration": {
    "AuthenticationType": "string",
    "CreateUserLevelPrefix": boolean,
    "EnableS3AccessGrants": boolean
  },
  "RequesterPaysEnabled": boolean,
  "ResultConfiguration": {
    "AclConfiguration": {
      "S3AclOption": "string"
    },
    "EncryptionConfiguration": {
      "EncryptionOption": "string",
      "KmsKey": "string"
    },
    "ExpectedBucketOwner": "string",
    "OutputLocation": "string"
  }
},
"CreationTime": number,
"Description": "string",
"IdentityCenterApplicationArn": "string",
"Name": "string",
"State": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

WorkGroup

Information about the workgroup.

Type: [WorkGroup](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ImportNotebook

Imports a single ipynb file to a Spark enabled workgroup. To import the notebook, the request must specify a value for either `Payload` or `NoteBookS3LocationUri`. If neither is specified or both are specified, an `InvalidRequestException` occurs. The maximum file size that can be imported is 10 megabytes. If an ipynb file with the same name already exists in the workgroup, throws an error.

Request Syntax

```
{
  "ClientRequestToken": "string",
  "Name": "string",
  "NotebookS3LocationUri": "string",
  "Payload": "string",
  "Type": "string",
  "WorkGroup": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ClientRequestToken](#)

A unique case-sensitive string used to ensure the request to import the notebook is idempotent (executes only once).

Important

This token is listed as not required because AWS SDKs (for example the AWS SDK for Java) auto-generate the token for you. If you are not using the AWS SDK or the AWS CLI, you must provide this token or the action will fail.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Pattern: `[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`

Required: No

Name

The name of the notebook to import.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `(?!.*[/:\])[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDC00-\uDBFF\uDFFF\t]+`

Required: Yes

NotebookS3LocationUri

A URI that specifies the Amazon S3 location of a notebook file in ipynb format.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^(https|s3|S3)://[^(/)]+/?(\.*)$`

Required: No

Payload

The notebook content to be imported. The payload must be in ipynb format.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10485760.

Required: No

Type

The notebook content type. Currently, the only valid type is IPYNB.

Type: String

Valid Values: IPYNB

Required: Yes

WorkGroup

The name of the Spark enabled workgroup to import the notebook to.

Type: String

Pattern: `[a-zA-Z0-9._-]{1,128}`

Required: Yes

Response Syntax

```
{
  "NotebookId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NotebookId

The ID assigned to the imported notebook.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Pattern: `[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

TooManyRequestsException

Indicates that the request was throttled.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListApplicationDPUSizes

Returns the supported DPU sizes for the supported application runtimes (for example, Athena notebook version 1).

Request Syntax

```
{
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

Specifies the maximum number of results to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

Response Syntax

```
{
  "ApplicationDPUSizes": [
```

```
{
  "ApplicationRuntimeId": "string",
  "SupportedDPUSizes": [ number ]
},
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationDPUSizes

A list of the supported DPU sizes that the application runtime supports.

Type: Array of [ApplicationDPUSizes](#) objects

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

TooManyRequestsException

Indicates that the request was throttled.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListCalculationExecutions

Lists the calculations that have been submitted to a session in descending order. Newer calculations are listed first; older calculations are listed later.

Request Syntax

```
{
  "MaxResults": number,
  "NextToken": "string",
  "SessionId": "string",
  "StateFilter": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The maximum number of calculation executions to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Maximum length of 2048.

Required: No

SessionId

The session ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

StateFilter

A filter for a specific calculation execution state. A description of each state follows.

CREATING - The calculation is in the process of being created.

CREATED - The calculation has been created and is ready to run.

QUEUED - The calculation has been queued for processing.

RUNNING - The calculation is running.

CANCELING - A request to cancel the calculation has been received and the system is working to stop it.

CANCELED - The calculation is no longer running as the result of a cancel request.

COMPLETED - The calculation has completed without error.

FAILED - The calculation failed and is no longer running.

Type: String

Valid Values: CREATING | CREATED | QUEUED | RUNNING | CANCELING | CANCELED | COMPLETED | FAILED

Required: No

Response Syntax

```
{
  "Calculations": [
    {
      "CalculationExecutionId": "string",
```

```
    "Description": "string",
    "Status": {
      "CompletionDateTime": number,
      "State": "string",
      "StateChangeReason": "string",
      "SubmissionDateTime": number
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Calculations

A list of [CalculationSummary](#) objects.

Type: Array of [CalculationSummary](#) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

ResourceNotFoundException

A resource, such as a workgroup, was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListCapacityReservations

Lists the capacity reservations for the current account.

Request Syntax

```
{  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

Specifies the maximum number of results to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

Response Syntax

```
{  
  "CapacityReservations": [  
    ...  
  ]  
}
```

```
{
  "AllocatedDpus": number,
  "CreationTime": number,
  "LastAllocation": {
    "RequestCompletionTime": number,
    "RequestTime": number,
    "Status": "string",
    "StatusMessage": "string"
  },
  "LastSuccessfulAllocationTime": number,
  "Name": "string",
  "Status": "string",
  "TargetDpus": number
}
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CapacityReservations

The capacity reservations for the current account.

Type: Array of [CapacityReservation](#) objects

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDatabases

Lists the databases in the specified data catalog.

Request Syntax

```
{
  "CatalogName": "string",
  "MaxResults": number,
  "NextToken": "string",
  "WorkGroup": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

CatalogName

The name of the data catalog that contains the databases to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFF\uD800\uDC00-\uDBFF\uDFFF\t]*`

Required: Yes

MaxResults

Specifies the maximum number of results to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

WorkGroup

The name of the workgroup for which the metadata is being fetched. Required if requesting an IAM Identity Center enabled AWS Glue Data Catalog.

Type: String

Pattern: [a-zA-Z0-9._-]{1,128}

Required: No

Response Syntax

```
{
  "DatabaseList": [
    {
      "Description": "string",
      "Name": "string",
      "Parameters": {
        "string": "string"
      }
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DatabaseList

A list of databases from a data catalog.

Type: Array of [Database](#) objects

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

MetadataException

An exception that Athena received when it called a custom metastore. Occurs if the error is not caused by user input (`InvalidRequestException`) or from the Athena platform (`InternalServerErrorException`). For example, if a user-created Lambda function is missing permissions, the Lambda 4XX exception is returned in a `MetadataException`.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDataCatalogs

Lists the data catalogs in the current AWS account.

Note

In the Athena console, data catalogs are listed as "data sources" on the **Data sources** page under the **Data source name** column.

Request Syntax

```
{
  "MaxResults": number,
  "NextToken": "string",
  "WorkGroup": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

Specifies the maximum number of data catalogs to return.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 50.

Required: No

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

WorkGroup

The name of the workgroup. Required if making an IAM Identity Center request.

Type: String

Pattern: `[a-zA-Z0-9._-]{1,128}`

Required: No

Response Syntax

```
{
  "DataCatalogsSummary": [
    {
      "CatalogName": "string",
      "Type": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DataCatalogsSummary

A summary list of data catalogs.

Type: Array of [DataCatalogSummary](#) objects

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListEngineVersions

Returns a list of engine versions that are available to choose from, including the Auto option.

Request Syntax

```
{  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[MaxResults](#)

The maximum number of engine versions to return in this request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 10.

Required: No

[NextToken](#)

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

Response Syntax

```
{
```

```
"EngineVersions": [  
  {  
    "EffectiveEngineVersion": "string",  
    "SelectedEngineVersion": "string"  
  }  
],  
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

EngineVersions

A list of engine versions that are available to choose from.

Type: Array of [EngineVersion](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListExecutors

Lists, in descending order, the executors that joined a session. Newer executors are listed first; older executors are listed later. The result can be optionally filtered by state.

Request Syntax

```
{
  "ExecutorStateFilter": "string",
  "MaxResults": number,
  "NextToken": "string",
  "SessionId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ExecutorStateFilter

A filter for a specific executor state. A description of each state follows.

CREATING - The executor is being started, including acquiring resources.

CREATED - The executor has been started.

REGISTERED - The executor has been registered.

TERMINATING - The executor is in the process of shutting down.

TERMINATED - The executor is no longer running.

FAILED - Due to a failure, the executor is no longer running.

Type: String

Valid Values: CREATING | CREATED | REGISTERED | TERMINATING | TERMINATED | FAILED

Required: No

MaxResults

The maximum number of executors to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Maximum length of 2048.

Required: No

SessionId

The session ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

Response Syntax

```
{
  "ExecutorsSummary": [
    {
      "ExecutorId": "string",
      "ExecutorSize": number,
      "ExecutorState": "string",
      "ExecutorType": "string",
      "StartDateTime": number,
      "TerminationDateTime": number
    }
  ]
}
```



```
    }  
  ],  
  "NextToken": "string",  
  "SessionId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ExecutorsSummary

Contains summary information about the executor.

Type: Array of [ExecutorsSummary](#) objects

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Maximum length of 2048.

SessionId

The session ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

ResourceNotFoundException

A resource, such as a workgroup, was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListNamedQueries

Provides a list of available query IDs only for queries saved in the specified workgroup. Requires that you have access to the specified workgroup. If a workgroup is not specified, lists the saved queries for the primary workgroup.

Request Syntax

```
{
  "MaxResults": number,
  "NextToken": "string",
  "WorkGroup": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[MaxResults](#)

The maximum number of queries to return in this request.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 50.

Required: No

[NextToken](#)

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

WorkGroup

The name of the workgroup from which the named queries are being returned. If a workgroup is not specified, the saved queries for the primary workgroup are returned.

Type: String

Pattern: [a-zA-Z0-9._-]{1,128}

Required: No

Response Syntax

```
{
  "NamedQueryIds": [ "string" ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NamedQueryIds

The list of unique query IDs.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: \S+

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListNotebookMetadata

Displays the notebook files for the specified workgroup in paginated format.

Request Syntax

```
{
  "Filters": {
    "Name": "string"
  },
  "MaxResults": number,
  "NextToken": "string",
  "WorkGroup": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filters

Search filter string.

Type: [FilterDefinition](#) object

Required: No

MaxResults

Specifies the maximum number of results to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

WorkGroup

The name of the Spark enabled workgroup to retrieve notebook metadata for.

Type: String

Pattern: [a-zA-Z0-9._-]{1,128}

Required: Yes

Response Syntax

```
{
  "NextToken": "string",
  "NotebookMetadataList": [
    {
      "CreationTime": number,
      "LastModifiedTime": number,
      "Name": "string",
      "NotebookId": "string",
      "Type": "string",
      "WorkGroup": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

[NotebookMetadataList](#)

The list of notebook metadata for the specified workgroup.

Type: Array of [NotebookMetadata](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

TooManyRequestsException

Indicates that the request was throttled.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListNotebookSessions

Lists, in descending order, the sessions that have been created in a notebook that are in an active state like CREATING, CREATED, IDLE or BUSY. Newer sessions are listed first; older sessions are listed later.

Request Syntax

```
{
  "MaxResults": number,
  "NextToken": "string",
  "NotebookId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[MaxResults](#)

The maximum number of notebook sessions to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

[NextToken](#)

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

NotebookId

The ID of the notebook to list sessions for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Pattern: `[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`

Required: Yes

Response Syntax

```
{
  "NextToken": "string",
  "NotebookSessionsList": [
    {
      "CreationTime": number,
      "SessionId": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the `NextToken` from the response object of the previous page call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

NotebookSessionsList

A list of the sessions belonging to the notebook.

Type: Array of [NotebookSessionSummary](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

ResourceNotFoundException

A resource, such as a workgroup, was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPreparedStatements

Lists the prepared statements in the specified workgroup.

Request Syntax

```
{  
  "MaxResults": number,  
  "NextToken": "string",  
  "WorkGroup": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The maximum number of results to return in this request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

WorkGroup

The workgroup to list the prepared statements for.

Type: String

Pattern: [a-zA-Z0-9._-]{1,128}

Required: Yes

Response Syntax

```
{
  "NextToken": "string",
  "PreparedStatements": [
    {
      "LastModifiedTime": number,
      "StatementName": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

PreparedStatements

The list of prepared statements for the workgroup.

Type: Array of [PreparedStatementSummary](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListQueryExecutions

Provides a list of available query execution IDs for the queries in the specified workgroup. Athena keeps a query history for 45 days. If a workgroup is not specified, returns a list of query execution IDs for the primary workgroup. Requires you to have access to the workgroup in which the queries ran.

Request Syntax

```
{
  "MaxResults": number,
  "NextToken": "string",
  "WorkGroup": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The maximum number of query executions to return in this request.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 50.

Required: No

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

WorkGroup

The name of the workgroup from which queries are being returned. If a workgroup is not specified, a list of available query execution IDs for the queries in the primary workgroup is returned.

Type: String

Pattern: [a-zA-Z0-9._-]{1,128}

Required: No

Response Syntax

```
{
  "NextToken": "string",
  "QueryExecutionIds": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

A token to be used by the next request if this request is truncated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

QueryExecutionIds

The unique IDs of each query execution as an array of strings.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: \S+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListSessions

Lists the sessions in a workgroup that are in an active state like CREATING, CREATED, IDLE, or BUSY. Newer sessions are listed first; older sessions are listed later.

Request Syntax

```
{  
  "MaxResults": number,  
  "NextToken": "string",  
  "StateFilter": "string",  
  "WorkGroup": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The maximum number of sessions to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Maximum length of 2048.

Required: No

StateFilter

A filter for a specific session state. A description of each state follows.

CREATING - The session is being started, including acquiring resources.

CREATED - The session has been started.

IDLE - The session is able to accept a calculation.

BUSY - The session is processing another task and is unable to accept a calculation.

TERMINATING - The session is in the process of shutting down.

TERMINATED - The session and its resources are no longer running.

DEGRADED - The session has no healthy coordinators.

FAILED - Due to a failure, the session and its resources are no longer running.

Type: String

Valid Values: CREATING | CREATED | IDLE | BUSY | TERMINATING | TERMINATED | DEGRADED | FAILED

Required: No

WorkGroup

The workgroup to which the session belongs.

Type: String

Pattern: [a-zA-Z0-9._-]{1,128}

Required: Yes

Response Syntax

```
{
  "NextToken": "string",
  "Sessions": [
```

```
{
  "Description": "string",
  "EngineVersion": {
    "EffectiveEngineVersion": "string",
    "SelectedEngineVersion": "string"
  },
  "NotebookVersion": "string",
  "SessionId": "string",
  "Status": {
    "EndDateTime": number,
    "IdleSinceDateTime": number,
    "LastModifiedDateTime": number,
    "StartDateTime": number,
    "State": "string",
    "StateChangeReason": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Maximum length of 2048.

Sessions

A list of sessions.

Type: Array of [SessionSummary](#) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

ResourceNotFoundException

A resource, such as a workgroup, was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Expression

A regex filter that pattern-matches table names. If no expression is supplied, metadata for all tables are listed.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

MaxResults

Specifies the maximum number of results to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

WorkGroup

The name of the workgroup for which the metadata is being fetched. Required if requesting an IAM Identity Center enabled AWS Glue Data Catalog.

Type: String

Pattern: `[a-zA-Z0-9._-]{1,128}`

Required: No

Response Syntax

```
{
  "NextToken": "string",
  "TableMetadataList": [
    {
      "Columns": [
        {
          "Comment": "string",
          "Name": "string",
          "Type": "string"
        }
      ],
      "CreateTime": number,
      "LastAccessTime": number,
      "Name": "string",
      "Parameters": {
        "string" : "string"
      },
      "PartitionKeys": [
        {
          "Comment": "string",
          "Name": "string",
          "Type": "string"
        }
      ],
      "TableType": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

[TableMetadataList](#)

A list of table metadata.

Type: Array of [TableMetadata](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

MetadataException

An exception that Athena received when it called a custom metastore. Occurs if the error is not caused by user input (`InvalidRequestException`) or from the Athena platform (`InternalServerError`). For example, if a user-created Lambda function is missing permissions, the Lambda 4XX exception is returned in a `MetadataException`.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Lists the tags associated with an Athena resource.

Request Syntax

```
{
  "MaxResults": number,
  "NextToken": "string",
  "ResourceARN": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The maximum number of results to be returned per request that lists the tags for the resource.

Type: Integer

Valid Range: Minimum value of 75.

Required: No

NextToken

The token for the next set of results, or null if there are no additional results for this request, where the request lists the tags for the resource with the specified ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

ResourceARN

Lists the tags for the resource with the specified ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

Response Syntax

```
{
  "NextToken": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

A token to be used by the next request if this request is truncated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Tags

The list of tags associated with the specified resource.

Type: Array of [Tag](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

ResourceNotFoundException

A resource, such as a workgroup, was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListWorkGroups

Lists available workgroups for the account.

Request Syntax

```
{
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The maximum number of workgroups to return in this request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

Response Syntax

```
{
  "NextToken": "string",
}
```



```
"WorkGroups": [  
  {  
    "CreationTime": number,  
    "Description": "string",  
    "EngineVersion": {  
      "EffectiveEngineVersion": "string",  
      "SelectedEngineVersion": "string"  
    },  
    "IdentityCenterApplicationArn": "string",  
    "Name": "string",  
    "State": "string"  
  }  
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

WorkGroups

A list of [WorkGroupSummary](#) objects that include the names, descriptions, creation times, and states for each workgroup.

Type: Array of [WorkGroupSummary](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutCapacityAssignmentConfiguration

Puts a new capacity assignment configuration for a specified capacity reservation. If a capacity assignment configuration already exists for the capacity reservation, replaces the existing capacity assignment configuration.

Request Syntax

```
{
  "CapacityAssignments": [
    {
      "WorkGroupNames": [ "string" ]
    }
  ],
  "CapacityReservationName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[CapacityAssignments](#)

The list of assignments for the capacity assignment configuration.

Type: Array of [CapacityAssignment](#) objects

Required: Yes

[CapacityReservationName](#)

The name of the capacity reservation to put a capacity assignment configuration for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9._-]+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartCalculationExecution

Submits calculations for execution within a session. You can supply the code to run as an inline code block within the request.

Note

The request syntax requires the [StartCalculationExecution:CodeBlock](#) parameter or the [CalculationConfiguration:CodeBlock](#) parameter, but not both. Because [CalculationConfiguration:CodeBlock](#) is deprecated, use the [StartCalculationExecution:CodeBlock](#) parameter instead.

Request Syntax

```
{
  "CalculationConfiguration": {
    "CodeBlock": "string"
  },
  "ClientRequestToken": "string",
  "CodeBlock": "string",
  "Description": "string",
  "SessionId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[CalculationConfiguration](#)

This parameter has been deprecated.

Contains configuration information for the calculation.

Type: [CalculationConfiguration](#) object

Required: No

ClientRequestToken

A unique case-sensitive string used to ensure the request to create the calculation is idempotent (executes only once). If another `StartCalculationExecutionRequest` is received, the same response is returned and another calculation is not created. If a parameter has changed, an error is returned.

Important

This token is listed as not required because AWS SDKs (for example the AWS SDK for Java) auto-generate the token for users. If you are not using the AWS SDK or the AWS CLI, you must provide this token or the action will fail.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 128.

Required: No

CodeBlock

A string that contains the code of the calculation. Use this parameter instead of [CalculationConfiguration:CodeBlock](#), which is deprecated.

Type: String

Length Constraints: Maximum length of 68000.

Required: No

Description

A description of the calculation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

SessionId

The session ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

Response Syntax

```
{
  "CalculationExecutionId": "string",
  "State": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CalculationExecutionId

The calculation execution UUID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

State

CREATING - The calculation is in the process of being created.

CREATED - The calculation has been created and is ready to run.

QUEUED - The calculation has been queued for processing.

RUNNING - The calculation is running.

CANCELING - A request to cancel the calculation has been received and the system is working to stop it.

CANCELED - The calculation is no longer running as the result of a cancel request.

COMPLETED - The calculation has completed without error.

FAILED - The calculation failed and is no longer running.

Type: String

Valid Values: CREATING | CREATED | QUEUED | RUNNING | CANCELING | CANCELED | COMPLETED | FAILED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

ResourceNotFoundException

A resource, such as a workgroup, was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartQueryExecution

Runs the SQL query statements contained in the Query. Requires you to have access to the workgroup in which the query ran. Running queries against an external catalog requires [GetDataCatalog](#) permission to the catalog. For code samples using the AWS SDK for Java, see [Examples and Code Samples](#) in the *Amazon Athena User Guide*.

Request Syntax

```
{
  "ClientRequestToken": "string",
  "ExecutionParameters": [ "string" ],
  "QueryExecutionContext": {
    "Catalog": "string",
    "Database": "string"
  },
  "QueryString": "string",
  "ResultConfiguration": {
    "AclConfiguration": {
      "S3AclOption": "string"
    },
    "EncryptionConfiguration": {
      "EncryptionOption": "string",
      "KmsKey": "string"
    },
    "ExpectedBucketOwner": "string",
    "OutputLocation": "string"
  },
  "ResultReuseConfiguration": {
    "ResultReuseByAgeConfiguration": {
      "Enabled": boolean,
      "MaxAgeInMinutes": number
    }
  },
  "WorkGroup": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClientRequestToken

A unique case-sensitive string used to ensure the request to create the query is idempotent (executes only once). If another `StartQueryExecution` request is received, the same response is returned and another query is not created. An error is returned if a parameter, such as `QueryString`, has changed. A call to `StartQueryExecution` that uses a previous client request token returns the same `QueryExecutionId` even if the requester doesn't have permission on the tables specified in `QueryString`.

Important

This token is listed as not required because AWS SDKs (for example the AWS SDK for Java) auto-generate the token for users. If you are not using the AWS SDK or the AWS CLI, you must provide this token or the action will fail.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 128.

Required: No

ExecutionParameters

A list of values for the parameters in a query. The values are applied sequentially to the parameters in the query in the order in which the parameters occur.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

QueryExecutionContext

The database within which the query executes.

Type: [QueryExecutionContext](#) object

Required: No

QueryString

The SQL query statements to be executed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 262144.

Required: Yes

ResultConfiguration

Specifies information about where and how to save the results of the query execution. If the query runs in a workgroup, then workgroup's settings may override query settings. This affects the query results location. The workgroup settings override is specified in `EnforceWorkGroupConfiguration` (true/false) in the `WorkGroupConfiguration`. See [WorkGroupConfiguration:EnforceWorkGroupConfiguration](#).

Type: [ResultConfiguration](#) object

Required: No

ResultReuseConfiguration

Specifies the query result reuse behavior for the query.

Type: [ResultReuseConfiguration](#) object

Required: No

WorkGroup

The name of the workgroup in which the query is being started.

Type: String

Pattern: `[a-zA-Z0-9._-]{1,128}`

Required: No

Response Syntax

```
{
  "QueryExecutionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

QueryExecutionId

The unique ID of the query that ran as a result of this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: \S+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

TooManyRequestsException

Indicates that the request was throttled.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartSession

Creates a session for running calculations within a workgroup. The session is ready when it reaches an IDLE state.

Request Syntax

```
{
  "ClientRequestToken": "string",
  "Description": "string",
  "EngineConfiguration": {
    "AdditionalConfigs": {
      "string" : "string"
    },
    "CoordinatorDpuSize": number,
    "DefaultExecutorDpuSize": number,
    "MaxConcurrentDpus": number,
    "SparkProperties": {
      "string" : "string"
    }
  },
  "NotebookVersion": "string",
  "SessionIdleTimeoutInMinutes": number,
  "WorkGroup": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClientRequestToken

A unique case-sensitive string used to ensure the request to create the session is idempotent (executes only once). If another `StartSessionRequest` is received, the same response is returned and another session is not created. If a parameter has changed, an error is returned.

⚠ Important

This token is listed as not required because AWS SDKs (for example the AWS SDK for Java) auto-generate the token for users. If you are not using the AWS SDK or the AWS CLI, you must provide this token or the action will fail.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 128.

Required: No

Description

The session description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

EngineConfiguration

Contains engine data processing unit (DPU) configuration settings and parameter mappings.

Type: [EngineConfiguration](#) object

Required: Yes

NotebookVersion

The notebook version. This value is supplied automatically for notebook sessions in the Athena console and is not required for programmatic session access. The only valid notebook version is Athena notebook version 1. If you specify a value for NotebookVersion, you must also specify a value for NotebookId. See [EngineConfiguration:AdditionalConfigs](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

SessionIdleTimeoutInMinutes

The idle timeout in minutes for the session.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 480.

Required: No

WorkGroup

The workgroup to which the session belongs.

Type: String

Pattern: [a-zA-Z0-9._-]{1,128}

Required: Yes

Response Syntax

```
{
  "SessionId": "string",
  "State": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

SessionId

The session ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

State

The state of the session. A description of each state follows.

CREATING - The session is being started, including acquiring resources.

CREATED - The session has been started.

IDLE - The session is able to accept a calculation.

BUSY - The session is processing another task and is unable to accept a calculation.

TERMINATING - The session is in the process of shutting down.

TERMINATED - The session and its resources are no longer running.

DEGRADED - The session has no healthy coordinators.

FAILED - Due to a failure, the session and its resources are no longer running.

Type: String

Valid Values: CREATING | CREATED | IDLE | BUSY | TERMINATING | TERMINATED | DEGRADED | FAILED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

ResourceNotFoundException

A resource, such as a workgroup, was not found.

HTTP Status Code: 400

SessionAlreadyExistsException

The specified session already exists.

HTTP Status Code: 400

TooManyRequestsException

Indicates that the request was throttled.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StopCalculationExecution

Requests the cancellation of a calculation. A `StopCalculationExecution` call on a calculation that is already in a terminal state (for example, `STOPPED`, `FAILED`, or `COMPLETED`) succeeds but has no effect.

Note

Cancelling a calculation is done on a best effort basis. If a calculation cannot be cancelled, you can be charged for its completion. If you are concerned about being charged for a calculation that cannot be cancelled, consider terminating the session in which the calculation is running.

Request Syntax

```
{
  "CalculationExecutionId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

CalculationExecutionId

The calculation execution UUID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Required: Yes

Response Syntax

```
{
```

```
"State": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

State

CREATING - The calculation is in the process of being created.

CREATED - The calculation has been created and is ready to run.

QUEUED - The calculation has been queued for processing.

RUNNING - The calculation is running.

CANCELING - A request to cancel the calculation has been received and the system is working to stop it.

CANCELED - The calculation is no longer running as the result of a cancel request.

COMPLETED - The calculation has completed without error.

FAILED - The calculation failed and is no longer running.

Type: String

Valid Values: CREATING | CREATED | QUEUED | RUNNING | CANCELING | CANCELED | COMPLETED | FAILED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

ResourceNotFoundException

A resource, such as a workgroup, was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StopQueryExecution

Stops a query execution. Requires you to have access to the workgroup in which the query ran.

Request Syntax

```
{  
  "QueryExecutionId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[QueryExecutionId](#)

The unique ID of the query execution to stop.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: \S+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Adds one or more tags to an Athena resource. A tag is a label that you assign to a resource. Each tag consists of a key and an optional value, both of which you define. For example, you can use tags to categorize Athena workgroups, data catalogs, or capacity reservations by purpose, owner, or environment. Use a consistent set of tag keys to make it easier to search and filter the resources in your account. For best practices, see [Tagging Best Practices](#). Tag keys can be from 1 to 128 UTF-8 Unicode characters, and tag values can be from 0 to 256 UTF-8 Unicode characters. Tags can use letters and numbers representable in UTF-8, and the following characters: + - = . _ : / @. Tag keys and values are case-sensitive. Tag keys must be unique per resource. If you specify more than one tag, separate them by commas.

Request Syntax

```
{
  "ResourceARN": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ResourceARN

Specifies the ARN of the Athena resource to which tags are to be added.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

Tags

A collection of one or more tags, separated by commas, to be added to an Athena resource.

Type: Array of [Tag](#) objects

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

ResourceNotFoundException

A resource, such as a workgroup, was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TerminateSession

Terminates an active session. A `TerminateSession` call on a session that is already inactive (for example, in a `FAILED`, `TERMINATED` or `TERMINATING` state) succeeds but has no effect. Calculations running in the session when `TerminateSession` is called are forcefully stopped, but may display as `FAILED` instead of `STOPPED`.

Request Syntax

```
{  
  "SessionId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

SessionId

The session ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

Response Syntax

```
{  
  "State": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

State

The state of the session. A description of each state follows.

CREATING - The session is being started, including acquiring resources.

CREATED - The session has been started.

IDLE - The session is able to accept a calculation.

BUSY - The session is processing another task and is unable to accept a calculation.

TERMINATING - The session is in the process of shutting down.

TERMINATED - The session and its resources are no longer running.

DEGRADED - The session has no healthy coordinators.

FAILED - Due to a failure, the session and its resources are no longer running.

Type: String

Valid Values: CREATING | CREATED | IDLE | BUSY | TERMINATING | TERMINATED | DEGRADED | FAILED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

ResourceNotFoundException

A resource, such as a workgroup, was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Removes one or more tags from an Athena resource.

Request Syntax

```
{  
  "ResourceARN": "string",  
  "TagKeys": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ResourceARN

Specifies the ARN of the resource from which tags are to be removed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

TagKeys

A comma-separated list of one or more tag keys whose tags are to be removed from the specified resource.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

ResourceNotFoundException

A resource, such as a workgroup, was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateCapacityReservation

Updates the number of requested data processing units for the capacity reservation with the specified name.

Request Syntax

```
{  
  "Name": "string",  
  "TargetDpus": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

The name of the capacity reservation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9._-]+

Required: Yes

TargetDpus

The new number of requested data processing units.

Type: Integer

Valid Range: Minimum value of 24.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Required: Yes

Parameters

Specifies the Lambda function or functions to use for updating the data catalog. This is a mapping whose values depend on the catalog type.

- For the HIVE data catalog type, use the following syntax. The `metadata-function` parameter is required. The `sdk-version` parameter is optional and defaults to the currently supported version.

```
metadata-function=lambda_arn, sdk-version=version_number
```

- For the LAMBDA data catalog type, use one of the following sets of required parameters, but not both.
 - If you have one Lambda function that processes metadata and another for reading the actual data, use the following syntax. Both parameters are required.

```
metadata-function=lambda_arn, record-function=lambda_arn
```

- If you have a composite Lambda function that processes both metadata and data, use the following syntax to specify your Lambda function.

```
function=lambda_arn
```

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 255.

Key Pattern: `[\u0020-\uD7FF\uE000-\uFFFF\uD800\uDC00-\uDBFF\uDFFF\t]*`

Value Length Constraints: Maximum length of 51200.

Required: No

Type

Specifies the type of data catalog to update. Specify LAMBDA for a federated catalog, HIVE for an external hive metastore, or GLUE for an AWS Glue Data Catalog.

Type: String

Valid Values: LAMBDA | GLUE | HIVE

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateNamedQuery

Updates a [NamedQuery](#) object. The database or workgroup cannot be updated.

Request Syntax

```
{  
  "Description": "string",  
  "Name": "string",  
  "NamedQueryId": "string",  
  "QueryString": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Description

The query description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

Name

The name of the query.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

NamedQueryId

The unique identifier (UUID) of the query.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: \S+

Required: Yes

QueryString

The contents of the query with all query statements.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 262144.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateNotebook

Updates the contents of a Spark notebook.

Request Syntax

```
{
  "ClientRequestToken": "string",
  "NotebookId": "string",
  "Payload": "string",
  "SessionId": "string",
  "Type": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClientRequestToken

A unique case-sensitive string used to ensure the request to create the notebook is idempotent (executes only once).

Important

This token is listed as not required because AWS SDKs (for example the AWS SDK for Java) auto-generate the token for you. If you are not using the AWS SDK or the AWS CLI, you must provide this token or the action will fail.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Pattern: [a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}

Required: No

NotebookId

The ID of the notebook to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Pattern: `[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`

Required: Yes

Payload

The updated content for the notebook.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10485760.

Required: Yes

SessionId

The active notebook session ID. Required if the notebook has an active session.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

Type

The notebook content type. Currently, the only valid type is IPYNB.

Type: String

Valid Values: IPYNB

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

TooManyRequestsException

Indicates that the request was throttled.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateNotebookMetadata

Updates the metadata for a notebook.

Request Syntax

```
{
  "ClientRequestToken": "string",
  "Name": "string",
  "NotebookId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ClientRequestToken](#)

A unique case-sensitive string used to ensure the request to create the notebook is idempotent (executes only once).

Important

This token is listed as not required because AWS SDKs (for example the AWS SDK for Java) auto-generate the token for you. If you are not using the AWS SDK or the AWS CLI, you must provide this token or the action will fail.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Pattern: [a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}

Required: No

[Name](#)

The name to update the notebook to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: (?!.*/:\|)\[\u0020-\uD7FF\uE000-\uFFFF\uD800\uDC00-\uDBFF\uDFFF\t\]+

Required: Yes

NotebookId

The ID of the notebook to update the metadata for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Pattern: [a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

TooManyRequestsException

Indicates that the request was throttled.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdatePreparedStatement

Updates a prepared statement.

Request Syntax

```
{
  "Description": "string",
  "QueryStatement": "string",
  "StatementName": "string",
  "WorkGroup": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Description

The description of the prepared statement.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

QueryStatement

The query string for the prepared statement.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 262144.

Required: Yes

StatementName

The name of the prepared statement.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z_][a-zA-Z0-9_@:]{1,256}`

Required: Yes

WorkGroup

The workgroup for the prepared statement.

Type: String

Pattern: `[a-zA-Z0-9._-]{1,128}`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

ResourceNotFoundException

A resource, such as a workgroup, was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateWorkGroup

Updates the workgroup with the specified name. The workgroup's name cannot be changed. Only ConfigurationUpdates can be specified.

Request Syntax

```
{
  "ConfigurationUpdates": {
    "AdditionalConfiguration": "string",
    "BytesScannedCutoffPerQuery": number,
    "CustomerContentEncryptionConfiguration": {
      "KmsKey": "string"
    },
    "EnableMinimumEncryptionConfiguration": boolean,
    "EnforceWorkGroupConfiguration": boolean,
    "EngineVersion": {
      "EffectiveEngineVersion": "string",
      "SelectedEngineVersion": "string"
    },
    "ExecutionRole": "string",
    "PublishCloudWatchMetricsEnabled": boolean,
    "QueryResultsS3AccessGrantsConfiguration": {
      "AuthenticationType": "string",
      "CreateUserLevelPrefix": boolean,
      "EnableS3AccessGrants": boolean
    },
    "RemoveBytesScannedCutoffPerQuery": boolean,
    "RemoveCustomerContentEncryptionConfiguration": boolean,
    "RequesterPaysEnabled": boolean,
    "ResultConfigurationUpdates": {
      "AclConfiguration": {
        "S3AclOption": "string"
      },
      "EncryptionConfiguration": {
        "EncryptionOption": "string",
        "KmsKey": "string"
      },
      "ExpectedBucketOwner": "string",
      "OutputLocation": "string",
      "RemoveAclConfiguration": boolean,
      "RemoveEncryptionConfiguration": boolean,
      "RemoveExpectedBucketOwner": boolean,
```

```
    "RemoveOutputLocation": boolean
  }
},
"Description": "string",
"State": "string",
"WorkGroup": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ConfigurationUpdates

Contains configuration updates for an Athena SQL workgroup.

Type: [WorkGroupConfigurationUpdates](#) object

Required: No

Description

The workgroup description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

State

The workgroup state that will be updated for the given workgroup.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

WorkGroup

The specified workgroup that will be updated.

Type: String

Pattern: [a-zA-Z0-9._-]{1,128}

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Indicates a platform issue, which may be due to a transient condition or outage.

HTTP Status Code: 500

InvalidRequestException

Indicates that something is wrong with the input to the request. For example, a required parameter may be missing or out of range.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The Amazon Athena API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AclConfiguration](#)
- [ApplicationDPUSizes](#)
- [AthenaError](#)
- [BatchGetNamedQueryInput](#)
- [BatchGetQueryExecutionInput](#)
- [CalculationConfiguration](#)
- [CalculationResult](#)
- [CalculationStatistics](#)
- [CalculationStatus](#)
- [CalculationSummary](#)
- [CapacityAllocation](#)
- [CapacityAssignment](#)
- [CapacityAssignmentConfiguration](#)
- [CapacityReservation](#)
- [Column](#)
- [ColumnInfo](#)
- [CustomerContentEncryptionConfiguration](#)
- [Database](#)
- [DataCatalog](#)
- [DataCatalogSummary](#)

- [Datum](#)
- [EncryptionConfiguration](#)
- [EngineConfiguration](#)
- [EngineVersion](#)
- [ExecutorsSummary](#)
- [FilterDefinition](#)
- [IdentityCenterConfiguration](#)
- [ListNamedQueriesInput](#)
- [ListQueryExecutionsInput](#)
- [NamedQuery](#)
- [NotebookMetadata](#)
- [NotebookSessionSummary](#)
- [PreparedStatement](#)
- [PreparedStatementSummary](#)
- [QueryExecution](#)
- [QueryExecutionContext](#)
- [QueryExecutionStatistics](#)
- [QueryExecutionStatus](#)
- [QueryResultsS3AccessGrantsConfiguration](#)
- [QueryRuntimeStatistics](#)
- [QueryRuntimeStatisticsRows](#)
- [QueryRuntimeStatisticsTimeline](#)
- [QueryStage](#)
- [QueryStagePlanNode](#)
- [ResultConfiguration](#)
- [ResultConfigurationUpdates](#)
- [ResultReuseByAgeConfiguration](#)
- [ResultReuseConfiguration](#)
- [ResultReuseInformation](#)
- [ResultSet](#)

- [ResultSetMetadata](#)
- [Row](#)
- [SessionConfiguration](#)
- [SessionStatistics](#)
- [SessionStatus](#)
- [SessionSummary](#)
- [TableMetadata](#)
- [Tag](#)
- [UnprocessedNamedQueryId](#)
- [UnprocessedPreparedStatementName](#)
- [UnprocessedQueryExecutionId](#)
- [WorkGroup](#)
- [WorkGroupConfiguration](#)
- [WorkGroupConfigurationUpdates](#)
- [WorkGroupSummary](#)

AclConfiguration

Indicates that an Amazon S3 canned ACL should be set to control ownership of stored query results. When Athena stores query results in Amazon S3, the canned ACL is set with the `x-amz-ac1` request header. For more information about S3 Object Ownership, see [Object Ownership settings](#) in the *Amazon S3 User Guide*.

Contents

S3AclOption

The Amazon S3 canned ACL that Athena should specify when storing query results. Currently the only supported canned ACL is `BUCKET_OWNER_FULL_CONTROL`. If a query runs in a workgroup and the workgroup overrides client-side settings, then the Amazon S3 canned ACL specified in the workgroup's settings is used for all queries that run in the workgroup. For more information about Amazon S3 canned ACLs, see [Canned ACL](#) in the *Amazon S3 User Guide*.

Type: String

Valid Values: `BUCKET_OWNER_FULL_CONTROL`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ApplicationDPUSizes

Contains the application runtime IDs and their supported DPU sizes.

Contents

ApplicationRuntimeId

The name of the supported application runtime (for example, Athena notebook version 1).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

SupportedDPUSizes

A list of the supported DPU sizes that the application runtime supports.

Type: Array of integers

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AthenaError

Provides information about an Athena query error. The `AthenaError` feature provides standardized error information to help you understand failed queries and take steps after a query failure occurs. `AthenaError` includes an `ErrorCategory` field that specifies whether the cause of the failed query is due to system error, user error, or other error.

Contents

ErrorCategory

An integer value that specifies the category of a query failure error. The following list shows the category for each integer value.

1 - System

2 - User

3 - Other

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 3.

Required: No

ErrorMessage

Contains a short description of the error that occurred.

Type: String

Required: No

ErrorType

An integer value that provides specific information about an Athena query error. For the meaning of specific values, see the [Error Type Reference](#) in the *Amazon Athena User Guide*.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 9999.

Required: No

Retryable

True if the query might succeed if resubmitted.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchGetNamedQueryInput

Contains an array of named query IDs.

Contents

NamedQueryIds

An array of query IDs.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `\S+`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchGetQueryExecutionInput

Contains an array of query execution IDs.

Contents

QueryExecutionIds

An array of query execution IDs.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: \S+

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CalculationConfiguration

Contains configuration information for the calculation.

Contents

CodeBlock

A string that contains the code for the calculation.

Type: String

Length Constraints: Maximum length of 68000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CalculationResult

Contains information about an application-specific calculation result.

Contents

ResultS3Uri

The Amazon S3 location of the folder for the calculation results.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^(https|s3|S3)://([^\s]+)?(?:.*)$`

Required: No

ResultType

The data format of the calculation result.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `\w+\|[+-.\w]+\|`

Required: No

StdErrorS3Uri

The Amazon S3 location of the `stderr` error messages file for the calculation.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^(https|s3|S3)://([^\s]+)?(?:.*)$`

Required: No

StdOutS3Uri

The Amazon S3 location of the `stdout` file for the calculation.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^(https|s3|S3)://[^\s/]+/?(.*)$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CalculationStatistics

Contains statistics for a notebook calculation.

Contents

DpuExecutionInMillis

The data processing unit execution time in milliseconds for the calculation.

Type: Long

Required: No

Progress

The progress of the calculation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CalculationStatus

Contains information about the status of a notebook calculation.

Contents

CompletionDateTime

The date and time the calculation completed processing.

Type: Timestamp

Required: No

State

The state of the calculation execution. A description of each state follows.

CREATING - The calculation is in the process of being created.

CREATED - The calculation has been created and is ready to run.

QUEUED - The calculation has been queued for processing.

RUNNING - The calculation is running.

CANCELING - A request to cancel the calculation has been received and the system is working to stop it.

CANCELED - The calculation is no longer running as the result of a cancel request.

COMPLETED - The calculation has completed without error.

FAILED - The calculation failed and is no longer running.

Type: String

Valid Values: CREATING | CREATED | QUEUED | RUNNING | CANCELING | CANCELED | COMPLETED | FAILED

Required: No

StateChangeReason

The reason for the calculation state change (for example, the calculation was canceled because the session was terminated).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

SubmissionDateTime

The date and time the calculation was submitted for processing.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CalculationSummary

Summary information for a notebook calculation.

Contents

CalculationExecutionId

The calculation execution UUID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Required: No

Description

A description of the calculation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

Status

Contains information about the status of the calculation.

Type: [CalculationStatus](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CapacityAllocation

Contains the submission time of a single allocation request for a capacity reservation and the most recent status of the attempted allocation.

Contents

RequestTime

The time when the capacity allocation was requested.

Type: Timestamp

Required: Yes

Status

The status of the capacity allocation.

Type: String

Valid Values: PENDING | SUCCEEDED | FAILED

Required: Yes

RequestCompletionTime

The time when the capacity allocation request was completed.

Type: Timestamp

Required: No

StatusMessage

The status message of the capacity allocation.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CapacityAssignment

A mapping between one or more workgroups and a capacity reservation.

Contents

WorkGroupNames

The list of workgroup names for the capacity assignment.

Type: Array of strings

Pattern: `[a-zA-Z0-9._-]{1,128}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CapacityAssignmentConfiguration

Assigns Athena workgroups (and hence their queries) to capacity reservations. A capacity reservation can have only one capacity assignment configuration, but the capacity assignment configuration can be made up of multiple individual assignments. Each assignment specifies how Athena queries can consume capacity from the capacity reservation that their workgroup is mapped to.

Contents

CapacityAssignments

The list of assignments that make up the capacity assignment configuration.

Type: Array of [CapacityAssignment](#) objects

Required: No

CapacityReservationName

The name of the reservation that the capacity assignment configuration is for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9._-]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CapacityReservation

A reservation for a specified number of data processing units (DPUs). When a reservation is initially created, it has no DPUs. Athena allocates DPUs until the allocated amount equals the requested amount.

Contents

AllocatedDpus

The number of data processing units currently allocated.

Type: Integer

Valid Range: Minimum value of 0.

Required: Yes

CreationTime

The time in UTC epoch millis when the capacity reservation was created.

Type: Timestamp

Required: Yes

Name

The name of the capacity reservation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9._-]+

Required: Yes

Status

The status of the capacity reservation.

Type: String

Valid Values: PENDING | ACTIVE | CANCELLING | CANCELLED | FAILED | UPDATE_PENDING

Required: Yes

TargetDpus

The number of data processing units requested.

Type: Integer

Valid Range: Minimum value of 24.

Required: Yes

LastAllocation

Contains the submission time of a single allocation request for a capacity reservation and the most recent status of the attempted allocation.

Type: [CapacityAllocation](#) object

Required: No

LastSuccessfulAllocationTime

The time of the most recent capacity allocation that succeeded.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Column

Contains metadata for a column in a table.

Contents

Name

The name of the column.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Comment

Optional information about the column.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDC00-\uDBFF\uDFFF\t]*`

Required: No

Type

The data type of the column.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 4096.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDC00-\uDBFF\uDFFF\t]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ColumnInfo

Information about the columns in a query execution result.

Contents

Name

The name of the column.

Type: String

Required: Yes

Type

The data type of the column.

Type: String

Required: Yes

CaseSensitive

Indicates whether values in the column are case-sensitive.

Type: Boolean

Required: No

CatalogName

The catalog to which the query results belong.

Type: String

Required: No

Label

A column label.

Type: String

Required: No

Nullable

Unsupported constraint. This value always shows as UNKNOWN.

Type: String

Valid Values: NOT_NULL | NULLABLE | UNKNOWN

Required: No

Precision

For DECIMAL data types, specifies the total number of digits, up to 38. For performance reasons, we recommend up to 18 digits.

Type: Integer

Required: No

Scale

For DECIMAL data types, specifies the total number of digits in the fractional part of the value. Defaults to 0.

Type: Integer

Required: No

SchemaName

The schema name (database name) to which the query results belong.

Type: String

Required: No

TableName

The table name for the query results.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CustomerContentEncryptionConfiguration

Specifies the customer managed KMS key that is used to encrypt the user's data stores in Athena. When an AWS managed key is used, this value is null. This setting does not apply to Athena SQL workgroups.

Contents

KmsKey

The customer managed KMS key that is used to encrypt the user's data stores in Athena.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^arn:aws[a-z\-*]:kms:([a-z0-9\-*]+):\d{12}:key/?[a-zA-Z_0-9+=,.\@-_/_]+$|^arn:aws[a-z\-*]:kms:([a-z0-9\-*]+):\d{12}:alias/?[a-zA-Z_0-9+=,.\@-_/_]+$|^alias/[a-zA-Z0-9/_-]+$|[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Database

Contains metadata information for a database in a data catalog.

Contents

Name

The name of the database.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Description

An optional description of the database.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

Parameters

A set of custom key/value pairs.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 255.

Key Pattern: `[\u0020-\uD7FF\uE000-\uFFFF\uD800\uDC00-\uDBFF\uDFFF\t]*`

Value Length Constraints: Maximum length of 51200.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DataCatalog

Contains information about a data catalog in an AWS account.

Note

In the Athena console, data catalogs are listed as "data sources" on the **Data sources** page under the **Data source name** column.

Contents

Name

The name of the data catalog. The catalog name must be unique for the AWS account and can use a maximum of 127 alphanumeric, underscore, at sign, or hyphen characters. The remainder of the length constraint of 256 is reserved for use by Athena.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFF\uD800\uDC00-\uDBFF\uDFFF\t]*`

Required: Yes

Type

The type of data catalog to create: LAMBDA for a federated catalog, HIVE for an external hive metastore, or GLUE for an AWS Glue Data Catalog.

Type: String

Valid Values: LAMBDA | GLUE | HIVE

Required: Yes

Description

An optional description of the data catalog.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

Parameters

Specifies the Lambda function or functions to use for the data catalog. This is a mapping whose values depend on the catalog type.

- For the HIVE data catalog type, use the following syntax. The `metadata-function` parameter is required. The `sdk-version` parameter is optional and defaults to the currently supported version.

```
metadata-function=lambda_arn, sdk-version=version_number
```

- For the LAMBDA data catalog type, use one of the following sets of required parameters, but not both.
 - If you have one Lambda function that processes metadata and another for reading the actual data, use the following syntax. Both parameters are required.

```
metadata-function=lambda_arn, record-function=lambda_arn
```

- If you have a composite Lambda function that processes both metadata and data, use the following syntax to specify your Lambda function.

```
function=lambda_arn
```

- The GLUE type takes a catalog ID parameter and is required. The `catalog_id` is the account ID of the AWS account to which the AWS Glue catalog belongs.

```
catalog-id=catalog_id
```

- The GLUE data catalog type also applies to the default `AwsDataCatalog` that already exists in your account, of which you can have only one and cannot modify.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 255.

Key Pattern: `[\u0020-\uD7FF\uE000-\uFFFF\uD800\uDC00-\uDBFF\uDFFF\t]*`

Value Length Constraints: Maximum length of 51200.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DataCatalogSummary

The summary information for the data catalog, which includes its name and type.

Contents

CatalogName

The name of the data catalog. The catalog name is unique for the AWS account and can use a maximum of 127 alphanumeric, underscore, at sign, or hyphen characters. The remainder of the length constraint of 256 is reserved for use by Athena.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDC00-\uDBFF\uDFFF\t]*`

Required: No

Type

The data catalog type.

Type: String

Valid Values: LAMBDA | GLUE | HIVE

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Datum

A piece of data (a field in the table).

Contents

VarCharValue

The value of the datum.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EncryptionConfiguration

If query and calculation results are encrypted in Amazon S3, indicates the encryption option used (for example, SSE_S3 or SSE_KMS) and key information.

Contents

EncryptionOption

Indicates whether Amazon S3 server-side encryption with Amazon S3-managed keys (SSE_S3), server-side encryption with KMS-managed keys (SSE_KMS), or client-side encryption with KMS-managed keys (CSE_KMS) is used.

If a query runs in a workgroup and the workgroup overrides client-side settings, then the workgroup's setting for encryption is used. It specifies whether query results must be encrypted, for all queries that run in this workgroup.

Type: String

Valid Values: SSE_S3 | SSE_KMS | CSE_KMS

Required: Yes

KmsKey

For SSE_KMS and CSE_KMS, this is the KMS key ARN or ID.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EngineConfiguration

Contains data processing unit (DPU) configuration settings and parameter mappings for a notebook engine.

Contents

MaxConcurrentDpus

The maximum number of DPUs that can run concurrently.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 5000.

Required: Yes

AdditionalConfigs

Contains additional notebook engine MAP<string, string> parameter mappings in the form of key-value pairs. To specify an Athena notebook that the Jupyter server will download and serve, specify a value for the [StartSession:NotebookVersion](#) field, and then add a key named NotebookId to AdditionalConfigs that has the value of the Athena notebook ID.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 255.

Key Pattern: `[\u0020-\uD7FF\uE000-\uFFFF\uD800\uDC00-\uDBFF\uDFFF\t]*`

Value Length Constraints: Maximum length of 51200.

Required: No

CoordinatorDpuSize

The number of DPUs to use for the coordinator. A coordinator is a special executor that orchestrates processing work and manages other executors in a notebook session. The default is 1.

Type: Integer

Valid Range: Fixed value of 1.

Required: No

DefaultExecutorDpuSize

The default number of DPUs to use for executors. An executor is the smallest unit of compute that a notebook session can request from Athena. The default is 1.

Type: Integer

Valid Range: Fixed value of 1.

Required: No

SparkProperties

Specifies custom jar files and Spark properties for use cases like cluster encryption, table formats, and general Spark tuning.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 255.

Key Pattern: `[\u0020-\uD7FF\uE000-\uFFFF\uD800\uDC00-\uDBFF\uDFFF\t]*`

Value Length Constraints: Maximum length of 51200.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EngineVersion

The Athena engine version for running queries, or the PySpark engine version for running sessions.

Contents

EffectiveEngineVersion

Read only. The engine version on which the query runs. If the user requests a valid engine version other than Auto, the effective engine version is the same as the engine version that the user requested. If the user requests Auto, the effective engine version is chosen by Athena. When a request to update the engine version is made by a `CreateWorkGroup` or `UpdateWorkGroup` operation, the `EffectiveEngineVersion` field is ignored.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

SelectedEngineVersion

The engine version requested by the user. Possible values are determined by the output of `ListEngineVersions`, including AUTO. The default is AUTO.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ExecutorsSummary

Contains summary information about an executor.

Contents

ExecutorId

The UUID of the executor.

Type: String

Length Constraints: Maximum length of 100000.

Pattern: .*

Required: Yes

ExecutorSize

The smallest unit of compute that a session can request from Athena. Size is measured in data processing unit (DPU) values, a relative measure of processing power.

Type: Long

Required: No

ExecutorState

The processing state of the executor. A description of each state follows.

CREATING - The executor is being started, including acquiring resources.

CREATED - The executor has been started.

REGISTERED - The executor has been registered.

TERMINATING - The executor is in the process of shutting down.

TERMINATED - The executor is no longer running.

FAILED - Due to a failure, the executor is no longer running.

Type: String

Valid Values: CREATING | CREATED | REGISTERED | TERMINATING | TERMINATED | FAILED

Required: No

ExecutorType

The type of executor used for the application (COORDINATOR, GATEWAY, or WORKER).

Type: String

Valid Values: COORDINATOR | GATEWAY | WORKER

Required: No

StartDateTime

The date and time that the executor started.

Type: Long

Required: No

TerminationDateTime

The date and time that the executor was terminated.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FilterDefinition

A string for searching notebook names.

Contents

Name

The name of the notebook to search for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: (?!.*/:\.)*[\u0020-\uD7FF\uE000-\uFFFF\uD800\uDC00-\uDBFF\uDFFF\t]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IdentityCenterConfiguration

Specifies whether the workgroup is IAM Identity Center supported.

Contents

EnableIdentityCenter

Specifies whether the workgroup is IAM Identity Center supported.

Type: Boolean

Required: No

IdentityCenterInstanceArn

The IAM Identity Center instance ARN that the workgroup associates to.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `^arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-]{16}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListNamedQueriesInput

Contents

MaxResults

The maximum number of queries to return in this request.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 50.

Required: No

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

WorkGroup

The name of the workgroup from which the named queries are being returned. If a workgroup is not specified, the saved queries for the primary workgroup are returned.

Type: String

Pattern: [a-zA-Z0-9._-]{1,128}

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListQueryExecutionsInput

Contents

MaxResults

The maximum number of query executions to return in this request.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 50.

Required: No

NextToken

A token generated by the Athena service that specifies where to continue pagination if a previous request was truncated. To obtain the next set of pages, pass in the NextToken from the response object of the previous page call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

WorkGroup

The name of the workgroup from which queries are being returned. If a workgroup is not specified, a list of available query execution IDs for the queries in the primary workgroup is returned.

Type: String

Pattern: `[a-zA-Z0-9._-]{1,128}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NamedQuery

A query, where `QueryString` contains the SQL statements that make up the query.

Contents

Database

The database to which the query belongs.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Name

The query name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

QueryString

The SQL statements that make up the query.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 262144.

Required: Yes

Description

The query description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

NamedQueryId

The unique identifier of the query.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `\S+`

Required: No

WorkGroup

The name of the workgroup that contains the named query.

Type: String

Pattern: `[a-zA-Z0-9._-]{1,128}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NotebookMetadata

Contains metadata for notebook, including the notebook name, ID, workgroup, and time created.

Contents

CreationTime

The time when the notebook was created.

Type: Timestamp

Required: No

LastModifiedTime

The time when the notebook was last modified.

Type: Timestamp

Required: No

Name

The name of the notebook.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `(?!.*[/:\])[\u0020-\uD7FF\uE000-\uFFFF\uD800\uDC00-\uDBFF\uDFFF\t]+`

Required: No

NotebookId

The notebook ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Pattern: `[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`

Required: No

Type

The type of notebook. Currently, the only valid type is IPYNB.

Type: String

Valid Values: IPYNB

Required: No

WorkGroup

The name of the Spark enabled workgroup to which the notebook belongs.

Type: String

Pattern: [a-zA-Z0-9._-]{1,128}

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NotebookSessionSummary

Contains the notebook session ID and notebook session creation time.

Contents

CreationTime

The time when the notebook session was created.

Type: Timestamp

Required: No

SessionId

The notebook session ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PreparedStatement

A prepared SQL statement for use with Athena.

Contents

Description

The description of the prepared statement.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

LastModifiedTime

The last modified time of the prepared statement.

Type: Timestamp

Required: No

QueryString

The query string for the prepared statement.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 262144.

Required: No

StatementName

The name of the prepared statement.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z_][a-zA-Z0-9_@:]{1,256}`

Required: No

WorkGroupName

The name of the workgroup to which the prepared statement belongs.

Type: String

Pattern: [a-zA-Z0-9._-]{1,128}

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PreparedStatementSummary

The name and last modified time of the prepared statement.

Contents

LastModifiedTime

The last modified time of the prepared statement.

Type: Timestamp

Required: No

StatementName

The name of the prepared statement.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z_][a-zA-Z0-9_@:]{1,256}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

QueryExecution

Information about a single instance of a query execution.

Contents

EngineVersion

The engine version that executed the query.

Type: [EngineVersion](#) object

Required: No

ExecutionParameters

A list of values for the parameters in a query. The values are applied sequentially to the parameters in the query in the order in which the parameters occur. The list of parameters is not returned in the response.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

Query

The SQL query statements which the query execution ran.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 262144.

Required: No

QueryExecutionContext

The database in which the query execution occurred.

Type: [QueryExecutionContext](#) object

Required: No

QueryExecutionId

The unique identifier for each query execution.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: \S+

Required: No

QueryResultsS3AccessGrantsConfiguration

Specifies whether Amazon S3 access grants are enabled for query results.

Type: [QueryResultsS3AccessGrantsConfiguration](#) object

Required: No

ResultConfiguration

The location in Amazon S3 where query and calculation results are stored and the encryption option, if any, used for query results. These are known as "client-side settings". If workgroup settings override client-side settings, then the query uses the location for the query results and the encryption configuration that are specified for the workgroup.

Type: [ResultConfiguration](#) object

Required: No

ResultReuseConfiguration

Specifies the query result reuse behavior that was used for the query.

Type: [ResultReuseConfiguration](#) object

Required: No

StatementType

The type of query statement that was run. DDL indicates DDL query statements. DML indicates DML (Data Manipulation Language) query statements, such as CREATE TABLE AS SELECT. UTILITY indicates query statements other than DDL and DML, such as SHOW CREATE TABLE, or DESCRIBE TABLE.

Type: String

Valid Values: DDL | DML | UTILITY

Required: No

Statistics

Query execution statistics, such as the amount of data scanned, the amount of time that the query took to process, and the type of statement that was run.

Type: [QueryExecutionStatistics](#) object

Required: No

Status

The completion date, current state, submission time, and state change reason (if applicable) for the query execution.

Type: [QueryExecutionStatus](#) object

Required: No

SubstatementType

The kind of query statement that was run.

Type: String

Required: No

WorkGroup

The name of the workgroup in which the query ran.

Type: String

Pattern: [a-zA-Z0-9._-]{1,128}

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

QueryExecutionContext

The database and data catalog context in which the query execution occurs.

Contents

Catalog

The name of the data catalog used in the query execution.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDC00-\uDBFF\uDFFF\t]*`

Required: No

Database

The name of the database used in the query execution. The database must exist in the catalog.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

QueryExecutionStatistics

The amount of data scanned during the query execution and the amount of time that it took to execute, and the type of statement that was run.

Contents

DataManifestLocation

The location and file name of a data manifest file. The manifest file is saved to the Athena query results location in Amazon S3. The manifest file tracks files that the query wrote to Amazon S3. If the query fails, the manifest file also tracks files that the query intended to write. The manifest is useful for identifying orphaned files resulting from a failed query. For more information, see [Working with Query Results, Output Files, and Query History](#) in the *Amazon Athena User Guide*.

Type: String

Required: No

DataScannedInBytes

The number of bytes in the data that was queried.

Type: Long

Required: No

EngineExecutionTimeInMillis

The number of milliseconds that the query took to execute.

Type: Long

Required: No

QueryPlanningTimeInMillis

The number of milliseconds that Athena took to plan the query processing flow. This includes the time spent retrieving table partitions from the data source. Note that because the query engine performs the query planning, query planning time is a subset of engine processing time.

Type: Long

Required: No

QueryQueueTimeInMillis

The number of milliseconds that the query was in your query queue waiting for resources. Note that if transient errors occur, Athena might automatically add the query back to the queue.

Type: Long

Required: No

ResultReuseInformation

Contains information about whether previous query results were reused for the query.

Type: [ResultReuseInformation](#) object

Required: No

ServicePreProcessingTimeInMillis

The number of milliseconds that Athena took to preprocess the query before submitting the query to the query engine.

Type: Long

Required: No

ServiceProcessingTimeInMillis

The number of milliseconds that Athena took to finalize and publish the query results after the query engine finished running the query.

Type: Long

Required: No

TotalExecutionTimeInMillis

The number of milliseconds that Athena took to run the query.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

QueryExecutionStatus

The completion date, current state, submission time, and state change reason (if applicable) for the query execution.

Contents

AthenaError

Provides information about an Athena query error.

Type: [AthenaError](#) object

Required: No

CompletionDateTime

The date and time that the query completed.

Type: Timestamp

Required: No

State

The state of query execution. QUEUED indicates that the query has been submitted to the service, and Athena will execute the query as soon as resources are available. RUNNING indicates that the query is in execution phase. SUCCEEDED indicates that the query completed without errors. FAILED indicates that the query experienced an error and did not complete processing. CANCELLED indicates that a user input interrupted query execution.

Note

Athena automatically retries your queries in cases of certain transient errors. As a result, you may see the query state transition from RUNNING or FAILED to QUEUED.

Type: String

Valid Values: QUEUED | RUNNING | SUCCEEDED | FAILED | CANCELLED

Required: No

StateChangeReason

Further detail about the status of the query.

Type: String

Required: No

SubmissionDateTime

The date and time that the query was submitted.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

QueryResultsS3AccessGrantsConfiguration

Specifies whether Amazon S3 access grants are enabled for query results.

Contents

AuthenticationType

The authentication type used for Amazon S3 access grants. Currently, only `DIRECTORY_IDENTITY` is supported.

Type: String

Valid Values: `DIRECTORY_IDENTITY`

Required: Yes

EnableS3AccessGrants

Specifies whether Amazon S3 access grants are enabled for query results.

Type: Boolean

Required: Yes

CreateUserLevelPrefix

When enabled, appends the user ID as an Amazon S3 path prefix to the query result output location.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

QueryRuntimeStatistics

The query execution timeline, statistics on input and output rows and bytes, and the different query stages that form the query execution plan.

Contents

OutputStage

Stage statistics such as input and output rows and bytes, execution time, and stage state. This information also includes substages and the query stage plan.

Type: [QueryStage](#) object

Required: No

Rows

Statistics such as input rows and bytes read by the query, rows and bytes output by the query, and the number of rows written by the query.

Type: [QueryRuntimeStatisticsRows](#) object

Required: No

Timeline

Timeline statistics such as query queue time, planning time, execution time, service processing time, and total execution time.

Type: [QueryRuntimeStatisticsTimeline](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

QueryRuntimeStatisticsRows

Statistics such as input rows and bytes read by the query, rows and bytes output by the query, and the number of rows written by the query.

Contents

InputBytes

The number of bytes read to execute the query.

Type: Long

Required: No

InputRows

The number of rows read to execute the query.

Type: Long

Required: No

OutputBytes

The number of bytes returned by the query.

Type: Long

Required: No

OutputRows

The number of rows returned by the query.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

QueryRuntimeStatisticsTimeline

Timeline statistics such as query queue time, planning time, execution time, service processing time, and total execution time.

Contents

EngineExecutionTimeInMillis

The number of milliseconds that the query took to execute.

Type: Long

Required: No

QueryPlanningTimeInMillis

The number of milliseconds that Athena took to plan the query processing flow. This includes the time spent retrieving table partitions from the data source. Note that because the query engine performs the query planning, query planning time is a subset of engine processing time.

Type: Long

Required: No

QueryQueueTimeInMillis

The number of milliseconds that the query was in your query queue waiting for resources. Note that if transient errors occur, Athena might automatically add the query back to the queue.

Type: Long

Required: No

ServicePreProcessingTimeInMillis

The number of milliseconds that Athena spends on preprocessing before it submits the query to the engine.

Type: Long

Required: No

ServiceProcessingTimeInMillis

The number of milliseconds that Athena took to finalize and publish the query results after the query engine finished running the query.

Type: Long

Required: No

TotalExecutionTimeInMillis

The number of milliseconds that Athena took to run the query.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

QueryStage

Stage statistics such as input and output rows and bytes, execution time and stage state. This information also includes substages and the query stage plan.

Contents

ExecutionTime

Time taken to execute this stage.

Type: Long

Required: No

InputBytes

The number of bytes input into the stage for execution.

Type: Long

Required: No

InputRows

The number of rows input into the stage for execution.

Type: Long

Required: No

OutputBytes

The number of bytes output from the stage after execution.

Type: Long

Required: No

OutputRows

The number of rows output from the stage after execution.

Type: Long

Required: No

QueryStagePlan

Stage plan information such as name, identifier, sub plans, and source stages.

Type: [QueryStagePlanNode](#) object

Required: No

StageId

The identifier for a stage.

Type: Long

Required: No

State

State of the stage after query execution.

Type: String

Required: No

SubStages

List of sub query stages that form this stage execution plan.

Type: Array of [QueryStage](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

QueryStagePlanNode

Stage plan information such as name, identifier, sub plans, and remote sources.

Contents

Children

Stage plan information such as name, identifier, sub plans, and remote sources of child plan nodes/

Type: Array of [QueryStagePlanNode](#) objects

Required: No

Identifier

Information about the operation this query stage plan node is performing.

Type: String

Required: No

Name

Name of the query stage plan that describes the operation this stage is performing as part of query execution.

Type: String

Required: No

RemoteSources

Source plan node IDs.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResultConfiguration

The location in Amazon S3 where query and calculation results are stored and the encryption option, if any, used for query and calculation results. These are known as "client-side settings". If workgroup settings override client-side settings, then the query uses the workgroup settings.

Contents

AclConfiguration

Indicates that an Amazon S3 canned ACL should be set to control ownership of stored query results. Currently the only supported canned ACL is `BUCKET_OWNER_FULL_CONTROL`. This is a client-side setting. If workgroup settings override client-side settings, then the query uses the ACL configuration that is specified for the workgroup, and also uses the location for storing query results specified in the workgroup. For more information, see [WorkGroupConfiguration:EnforceWorkGroupConfiguration](#) and [Workgroup Settings Override Client-Side Settings](#).

Type: [AclConfiguration](#) object

Required: No

EncryptionConfiguration

If query and calculation results are encrypted in Amazon S3, indicates the encryption option used (for example, `SSE_KMS` or `CSE_KMS`) and key information. This is a client-side setting. If workgroup settings override client-side settings, then the query uses the encryption configuration that is specified for the workgroup, and also uses the location for storing query results specified in the workgroup. See [WorkGroupConfiguration:EnforceWorkGroupConfiguration](#) and [Workgroup Settings Override Client-Side Settings](#).

Type: [EncryptionConfiguration](#) object

Required: No

ExpectedBucketOwner

The AWS account ID that you expect to be the owner of the Amazon S3 bucket specified by [ResultConfiguration:OutputLocation](#). If set, Athena uses the value for `ExpectedBucketOwner` when it makes Amazon S3 calls to your specified output location. If

the `ExpectedBucketOwner` AWS account ID does not match the actual owner of the Amazon S3 bucket, the call fails with a permissions error.

This is a client-side setting. If workgroup settings override client-side settings, then the query uses the `ExpectedBucketOwner` setting that is specified for the workgroup, and also uses the location for storing query results specified in the workgroup. See [WorkGroupConfiguration:EnforceWorkGroupConfiguration](#) and [Workgroup Settings Override Client-Side Settings](#).

Type: String

Length Constraints: Fixed length of 12.

Pattern: `^[0-9]+$`

Required: No

OutputLocation

The location in Amazon S3 where your query and calculation results are stored, such as `s3://path/to/query/bucket/`. To run the query, you must specify the query results location using one of the ways: either for individual queries using either this setting (client-side), or in the workgroup, using [WorkGroupConfiguration](#). If none of them is set, Athena issues an error that no output location is provided. If workgroup settings override client-side settings, then the query uses the settings specified for the workgroup. See [WorkGroupConfiguration:EnforceWorkGroupConfiguration](#).

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResultConfigurationUpdates

The information about the updates in the query results, such as output location and encryption configuration for the query results.

Contents

AclConfiguration

The ACL configuration for the query results.

Type: [AclConfiguration](#) object

Required: No

EncryptionConfiguration

The encryption configuration for query and calculation results.

Type: [EncryptionConfiguration](#) object

Required: No

ExpectedBucketOwner

The AWS account ID that you expect to be the owner of the Amazon S3 bucket specified by [ResultConfiguration:OutputLocation](#). If set, Athena uses the value for `ExpectedBucketOwner` when it makes Amazon S3 calls to your specified output location. If the `ExpectedBucketOwner` AWS account ID does not match the actual owner of the Amazon S3 bucket, the call fails with a permissions error.

If workgroup settings override client-side settings, then the query uses the `ExpectedBucketOwner` setting that is specified for the workgroup, and also uses the location for storing query results specified in the workgroup. See [WorkGroupConfiguration:EnforceWorkGroupConfiguration](#) and [Workgroup Settings Override Client-Side Settings](#).

Type: String

Length Constraints: Fixed length of 12.

Pattern: `^[0-9]+$`

Required: No

OutputLocation

The location in Amazon S3 where your query and calculation results are stored, such as `s3://path/to/query/bucket/`. If workgroup settings override client-side settings, then the query uses the location for the query results and the encryption configuration that are specified for the workgroup. The "workgroup settings override" is specified in `EnforceWorkGroupConfiguration` (true/false) in the `WorkGroupConfiguration`. See [WorkGroupConfiguration:EnforceWorkGroupConfiguration](#).

Type: String

Required: No

RemoveAclConfiguration

If set to `true`, indicates that the previously-specified ACL configuration for queries in this workgroup should be ignored and set to null. If set to `false` or not set, and a value is present in the `AclConfiguration` of `ResultConfigurationUpdates`, the `AclConfiguration` in the workgroup's `ResultConfiguration` is updated with the new value. For more information, see [Workgroup Settings Override Client-Side Settings](#).

Type: Boolean

Required: No

RemoveEncryptionConfiguration

If set to `"true"`, indicates that the previously-specified encryption configuration (also known as the client-side setting) for queries in this workgroup should be ignored and set to null. If set to `"false"` or not set, and a value is present in the `EncryptionConfiguration` in `ResultConfigurationUpdates` (the client-side setting), the `EncryptionConfiguration` in the workgroup's `ResultConfiguration` will be updated with the new value. For more information, see [Workgroup Settings Override Client-Side Settings](#).

Type: Boolean

Required: No

RemoveExpectedBucketOwner

If set to `"true"`, removes the AWS account ID previously specified for [ResultConfiguration:ExpectedBucketOwner](#). If set to `"false"` or not set, and a value is present in

the `ExpectedBucketOwner` in `ResultConfigurationUpdates` (the client-side setting), the `ExpectedBucketOwner` in the workgroup's `ResultConfiguration` is updated with the new value. For more information, see [Workgroup Settings Override Client-Side Settings](#).

Type: Boolean

Required: No

RemoveOutputLocation

If set to "true", indicates that the previously-specified query results location (also known as a client-side setting) for queries in this workgroup should be ignored and set to null. If set to "false" or not set, and a value is present in the `OutputLocation` in `ResultConfigurationUpdates` (the client-side setting), the `OutputLocation` in the workgroup's `ResultConfiguration` will be updated with the new value. For more information, see [Workgroup Settings Override Client-Side Settings](#).

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResultReuseByAgeConfiguration

Specifies whether previous query results are reused, and if so, their maximum age.

Contents

Enabled

True if previous query results can be reused when the query is run; otherwise, false. The default is false.

Type: Boolean

Required: Yes

MaxAgeInMinutes

Specifies, in minutes, the maximum age of a previous query result that Athena should consider for reuse. The default is 60.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 10080.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResultReuseConfiguration

Specifies the query result reuse behavior for the query.

Contents

ResultReuseByAgeConfiguration

Specifies whether previous query results are reused, and if so, their maximum age.

Type: [ResultReuseByAgeConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResultReuseInformation

Contains information about whether the result of a previous query was reused.

Contents

ReusedPreviousResult

True if a previous query result was reused; false if the result was generated from a new run of the query.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResultSet

The metadata and rows that make up a query result set. The metadata describes the column structure and data types. To return a `ResultSet` object, use [GetQueryResults](#).

Contents

ResultSetMetadata

The metadata that describes the column structure and data types of a table of query results.

Type: [ResultSetMetadata](#) object

Required: No

Rows

The rows in the table.

Type: Array of [Row](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResultSetMetadata

The metadata that describes the column structure and data types of a table of query results. To return a `ResultSetMetadata` object, use [GetQueryResults](#).

Contents

ColumnInfo

Information about the columns returned in a query result metadata.

Type: Array of [ColumnInfo](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Row

The rows that make up a query result table.

Contents

Data

The data that populates a row in a query result table.

Type: Array of [Datum](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SessionConfiguration

Contains session configuration information.

Contents

EncryptionConfiguration

If query and calculation results are encrypted in Amazon S3, indicates the encryption option used (for example, SSE_KMS or CSE_KMS) and key information.

Type: [EncryptionConfiguration](#) object

Required: No

ExecutionRole

The ARN of the execution role used to access user resources for Spark sessions and Identity Center enabled workgroups. This property applies only to Spark enabled workgroups and Identity Center enabled workgroups.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `^arn:aws[a-z\-*:iam::\d{12}:role/?[a-zA-Z_0-9+=,.\@\-_/\]]+$`

Required: No

IdleTimeoutSeconds

The idle timeout in seconds for the session.

Type: Long

Required: No

WorkingDirectory

The Amazon S3 location that stores information for the notebook.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SessionStatistics

Contains statistics for a session.

Contents

DpuExecutionInMillis

The data processing unit execution time for a session in milliseconds.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SessionStatus

Contains information about the status of a session.

Contents

EndDateTime

The date and time that the session ended.

Type: Timestamp

Required: No

IdleSinceDateTime

The date and time starting at which the session became idle. Can be empty if the session is not currently idle.

Type: Timestamp

Required: No

LastModifiedDateTime

The most recent date and time that the session was modified.

Type: Timestamp

Required: No

StartDateTime

The date and time that the session started.

Type: Timestamp

Required: No

State

The state of the session. A description of each state follows.

CREATING - The session is being started, including acquiring resources.

CREATED - The session has been started.

IDLE - The session is able to accept a calculation.

BUSY - The session is processing another task and is unable to accept a calculation.

TERMINATING - The session is in the process of shutting down.

TERMINATED - The session and its resources are no longer running.

DEGRADED - The session has no healthy coordinators.

FAILED - Due to a failure, the session and its resources are no longer running.

Type: String

Valid Values: CREATING | CREATED | IDLE | BUSY | TERMINATING | TERMINATED | DEGRADED | FAILED

Required: No

StateChangeReason

The reason for the session state change (for example, canceled because the session was terminated).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SessionSummary

Contains summary information about a session.

Contents

Description

The session description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

EngineVersion

The engine version used by the session (for example, PySpark engine version 3).

Type: [EngineVersion](#) object

Required: No

NotebookVersion

The notebook version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

SessionId

The session ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

Status

Contains information about the session status.

Type: [SessionStatus](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TableMetadata

Contains metadata for a table.

Contents

Name

The name of the table.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Columns

A list of the columns in the table.

Type: Array of [Column](#) objects

Required: No

CreateTime

The time that the table was created.

Type: Timestamp

Required: No

LastAccessTime

The last time the table was accessed.

Type: Timestamp

Required: No

Parameters

A set of custom key/value pairs for table properties.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 255.

Key Pattern: `[\u0020-\uD7FF\uE000-\uFFFF\uD800\uDC00-\uDBFF\uDFFF\t]*`

Value Length Constraints: Maximum length of 51200.

Required: No

PartitionKeys

A list of the partition keys in the table.

Type: Array of [Column](#) objects

Required: No

TableType

The type of table. In Athena, only EXTERNAL_TABLE is supported.

Type: String

Length Constraints: Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

A label that you assign to a resource. Athena resources include workgroups, data catalogs, and capacity reservations. Each tag consists of a key and an optional value, both of which you define. For example, you can use tags to categorize Athena resources by purpose, owner, or environment. Use a consistent set of tag keys to make it easier to search and filter the resources in your account. For best practices, see [Tagging Best Practices](#). Tag keys can be from 1 to 128 UTF-8 Unicode characters, and tag values can be from 0 to 256 UTF-8 Unicode characters. Tags can use letters and numbers representable in UTF-8, and the following characters: + - = . _ : / @. Tag keys and values are case-sensitive. Tag keys must be unique per resource. If you specify more than one tag, separate them by commas.

Contents

Key

A tag key. The tag key length is from 1 to 128 Unicode characters in UTF-8. You can use letters and numbers representable in UTF-8, and the following characters: + - = . _ : / @. Tag keys are case-sensitive and must be unique per resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Value

A tag value. The tag value length is from 0 to 256 Unicode characters in UTF-8. You can use letters and numbers representable in UTF-8, and the following characters: + - = . _ : / @. Tag values are case-sensitive.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UnprocessedNamedQueryId

Information about a named query ID that could not be processed.

Contents

ErrorCode

The error code returned when the processing request for the named query failed, if applicable.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

ErrorMessage

The error message returned when the processing request for the named query failed, if applicable.

Type: String

Required: No

NamedQueryId

The unique identifier of the named query.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: \S+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UnprocessedPreparedStatementName

The name of a prepared statement that could not be returned.

Contents

ErrorCode

The error code returned when the request for the prepared statement failed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

ErrorMessage

The error message containing the reason why the prepared statement could not be returned.

The following error messages are possible:

- `INVALID_INPUT` - The name of the prepared statement that was provided is not valid (for example, the name is too long).
- `STATEMENT_NOT_FOUND` - A prepared statement with the name provided could not be found.
- `UNAUTHORIZED` - The requester does not have permission to access the workgroup that contains the prepared statement.

Type: String

Required: No

StatementName

The name of a prepared statement that could not be returned due to an error.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z_][a-zA-Z0-9_@:]{1,256}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UnprocessedQueryExecutionId

Describes a query execution that failed to process.

Contents

ErrorCode

The error code returned when the query execution failed to process, if applicable.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

ErrorMessage

The error message returned when the query execution failed to process, if applicable.

Type: String

Required: No

QueryExecutionId

The unique identifier of the query execution.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: \S+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

WorkGroup

A workgroup, which contains a name, description, creation time, state, and other configuration, listed under [WorkGroup:Configuration](#). Each workgroup enables you to isolate queries for you or your group of users from other queries in the same account, to configure the query results location and the encryption configuration (known as workgroup settings), to enable sending query metrics to Amazon CloudWatch, and to establish per-query data usage control limits for all queries in a workgroup. The workgroup settings override is specified in `EnforceWorkGroupConfiguration` (true/false) in the `WorkGroupConfiguration`. See [WorkGroupConfiguration:EnforceWorkGroupConfiguration](#).

Contents

Name

The workgroup name.

Type: String

Pattern: `[a-zA-Z0-9._-]{1,128}`

Required: Yes

Configuration

The configuration of the workgroup, which includes the location in Amazon S3 where query and calculation results are stored, the encryption configuration, if any, used for query and calculation results; whether the Amazon CloudWatch Metrics are enabled for the workgroup; whether workgroup settings override client-side settings; and the data usage limits for the amount of data scanned per query or per workgroup. The workgroup settings override is specified in `EnforceWorkGroupConfiguration` (true/false) in the `WorkGroupConfiguration`. See [WorkGroupConfiguration:EnforceWorkGroupConfiguration](#).

Type: [WorkGroupConfiguration](#) object

Required: No

CreationTime

The date and time the workgroup was created.

Type: Timestamp

Required: No

Description

The workgroup description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

IdentityCenterApplicationArn

The ARN of the IAM Identity Center enabled application associated with the workgroup.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `^arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-]{16}/apl-[a-zA-Z0-9]{16}$`

Required: No

State

The state of the workgroup: ENABLED or DISABLED.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

WorkGroupConfiguration

The configuration of the workgroup, which includes the location in Amazon S3 where query and calculation results are stored, the encryption option, if any, used for query and calculation results, whether the Amazon CloudWatch Metrics are enabled for the workgroup and whether workgroup settings override query settings, and the data usage limits for the amount of data scanned per query or per workgroup. The workgroup settings override is specified in `EnforceWorkGroupConfiguration` (true/false) in the `WorkGroupConfiguration`. See [WorkGroupConfiguration:EnforceWorkGroupConfiguration](#).

Contents

AdditionalConfiguration

Specifies a user defined JSON string that is passed to the notebook engine.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

BytesScannedCutoffPerQuery

The upper data usage limit (cutoff) for the amount of bytes a single query in a workgroup is allowed to scan.

Type: Long

Valid Range: Minimum value of 10000000.

Required: No

CustomerContentEncryptionConfiguration

Specifies the KMS key that is used to encrypt the user's data stores in Athena. This setting does not apply to Athena SQL workgroups.

Type: [CustomerContentEncryptionConfiguration](#) object

Required: No

EnableMinimumEncryptionConfiguration

Enforces a minimal level of encryption for the workgroup for query and calculation results that are written to Amazon S3. When enabled, workgroup users can set encryption only to the minimum level set by the administrator or higher when they submit queries.

The `EnforceWorkGroupConfiguration` setting takes precedence over the `EnableMinimumEncryptionConfiguration` flag. This means that if `EnforceWorkGroupConfiguration` is true, the `EnableMinimumEncryptionConfiguration` flag is ignored, and the workgroup configuration for encryption is used.

Type: Boolean

Required: No

EnforceWorkGroupConfiguration

If set to "true", the settings for the workgroup override client-side settings. If set to "false", client-side settings are used. For more information, see [Workgroup Settings Override Client-Side Settings](#).

Type: Boolean

Required: No

EngineVersion

The engine version that all queries running on the workgroup use. Queries on the `AmazonAthenaPreviewFunctionality` workgroup run on the preview engine regardless of this setting.

Type: [EngineVersion](#) object

Required: No

ExecutionRole

The ARN of the execution role used to access user resources for Spark sessions and IAM Identity Center enabled workgroups. This property applies only to Spark enabled workgroups and IAM Identity Center enabled workgroups. The property is required for IAM Identity Center enabled workgroups.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `^arn:aws[a-z\-*:iam::\d{12}:role/?[a-zA-Z_0-9+=,.\@-_/\]]+$`

Required: No

IdentityCenterConfiguration

Specifies whether the workgroup is IAM Identity Center supported.

Type: [IdentityCenterConfiguration](#) object

Required: No

PublishCloudWatchMetricsEnabled

Indicates that the Amazon CloudWatch metrics are enabled for the workgroup.

Type: Boolean

Required: No

QueryResultsS3AccessGrantsConfiguration

Specifies whether Amazon S3 access grants are enabled for query results.

Type: [QueryResultsS3AccessGrantsConfiguration](#) object

Required: No

RequesterPaysEnabled

If set to `true`, allows members assigned to a workgroup to reference Amazon S3 Requester Pays buckets in queries. If set to `false`, workgroup members cannot query data from Requester Pays buckets, and queries that retrieve data from Requester Pays buckets cause an error. The default is `false`. For more information about Requester Pays buckets, see [Requester Pays Buckets](#) in the *Amazon Simple Storage Service Developer Guide*.

Type: Boolean

Required: No

ResultConfiguration

The configuration for the workgroup, which includes the location in Amazon S3 where query and calculation results are stored and the encryption option, if any, used for query and

calculation results. To run the query, you must specify the query results location using one of the ways: either in the workgroup using this setting, or for individual queries (client-side), using [ResultConfiguration:OutputLocation](#). If none of them is set, Athena issues an error that no output location is provided.

Type: [ResultConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

WorkGroupConfigurationUpdates

The configuration information that will be updated for this workgroup, which includes the location in Amazon S3 where query and calculation results are stored, the encryption option, if any, used for query results, whether the Amazon CloudWatch Metrics are enabled for the workgroup, whether the workgroup settings override the client-side settings, and the data usage limit for the amount of bytes scanned per query, if it is specified.

Contents

AdditionalConfiguration

Contains a user defined string in JSON format for a Spark-enabled workgroup.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

BytesScannedCutoffPerQuery

The upper limit (cutoff) for the amount of bytes a single query in a workgroup is allowed to scan.

Type: Long

Valid Range: Minimum value of 10000000.

Required: No

CustomerContentEncryptionConfiguration

Specifies the customer managed KMS key that is used to encrypt the user's data stores in Athena. When an AWS managed key is used, this value is null. This setting does not apply to Athena SQL workgroups.

Type: [CustomerContentEncryptionConfiguration](#) object

Required: No

EnableMinimumEncryptionConfiguration

Enforces a minimal level of encryption for the workgroup for query and calculation results that are written to Amazon S3. When enabled, workgroup users can set encryption only to the

minimum level set by the administrator or higher when they submit queries. This setting does not apply to Spark-enabled workgroups.

The `EnforceWorkGroupConfiguration` setting takes precedence over the `EnableMinimumEncryptionConfiguration` flag. This means that if `EnforceWorkGroupConfiguration` is true, the `EnableMinimumEncryptionConfiguration` flag is ignored, and the workgroup configuration for encryption is used.

Type: Boolean

Required: No

EnforceWorkGroupConfiguration

If set to "true", the settings for the workgroup override client-side settings. If set to "false" client-side settings are used. For more information, see [Workgroup Settings Override Client-Side Settings](#).

Type: Boolean

Required: No

EngineVersion

The engine version requested when a workgroup is updated. After the update, all queries on the workgroup run on the requested engine version. If no value was previously set, the default is Auto. Queries on the `AmazonAthenaPreviewFunctionality` workgroup run on the preview engine regardless of this setting.

Type: [EngineVersion](#) object

Required: No

ExecutionRole

The ARN of the execution role used to access user resources for Spark sessions and Identity Center enabled workgroups. This property applies only to Spark enabled workgroups and Identity Center enabled workgroups.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `^arn:aws[a-z\-*]:iam:~d{12}:role/?[a-zA-Z_0-9+=,.\@-_/\]+$`

Required: No

PublishCloudWatchMetricsEnabled

Indicates whether this workgroup enables publishing metrics to Amazon CloudWatch.

Type: Boolean

Required: No

QueryResultsS3AccessGrantsConfiguration

Specifies whether Amazon S3 access grants are enabled for query results.

Type: [QueryResultsS3AccessGrantsConfiguration](#) object

Required: No

RemoveBytesScannedCutoffPerQuery

Indicates that the data usage control limit per query is removed.

[WorkGroupConfiguration:BytesScannedCutoffPerQuery](#)

Type: Boolean

Required: No

RemoveCustomerContentEncryptionConfiguration

Removes content encryption configuration from an Apache Spark-enabled Athena workgroup.

Type: Boolean

Required: No

RequesterPaysEnabled

If set to `true`, allows members assigned to a workgroup to specify Amazon S3 Requester Pays buckets in queries. If set to `false`, workgroup members cannot query data from Requester Pays buckets, and queries that retrieve data from Requester Pays buckets cause an error. The default is `false`. For more information about Requester Pays buckets, see [Requester Pays Buckets](#) in the *Amazon Simple Storage Service Developer Guide*.

Type: Boolean

Required: No

ResultConfigurationUpdates

The result configuration information about the queries in this workgroup that will be updated. Includes the updated results location and an updated option for encrypting query results.

Type: [ResultConfigurationUpdates](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

WorkGroupSummary

The summary information for the workgroup, which includes its name, state, description, and the date and time it was created.

Contents

CreationTime

The workgroup creation date and time.

Type: Timestamp

Required: No

Description

The workgroup description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

EngineVersion

The engine version setting for all queries on the workgroup. Queries on the AmazonAthenaPreviewFunctionality workgroup run on the preview engine regardless of this setting.

Type: [EngineVersion](#) object

Required: No

IdentityCenterApplicationArn

The ARN of the IAM Identity Center enabled application associated with the workgroup.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `^arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-]{16}/apl-[a-zA-Z0-9]{16}$`

Required: No

Name

The name of the workgroup.

Type: String

Pattern: [a-zA-Z0-9._-]{1,128}

Required: No

State

The state of the workgroup.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400