



API Reference

AWS CloudTrail



API Version 2013-11-01

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS CloudTrail: API Reference

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
AddTags	4
Request Syntax	4
Request Parameters	4
Response Elements	5
Errors	5
See Also	8
CancelQuery	9
Request Syntax	9
Request Parameters	9
Response Syntax	10
Response Elements	10
Errors	10
See Also	12
CreateChannel	13
Request Syntax	13
Request Parameters	13
Response Syntax	14
Response Elements	15
Errors	16
See Also	18
CreateEventDataStore	19
Request Syntax	19
Request Parameters	19
Response Syntax	23
Response Elements	24
Errors	27
See Also	30
CreateTrail	31
Request Syntax	31
Request Parameters	31
Response Syntax	35
Response Elements	35

Errors	37
See Also	42
DeleteChannel	43
Request Syntax	43
Request Parameters	43
Response Elements	43
Errors	43
See Also	44
DeleteEventDataStore	45
Request Syntax	45
Request Parameters	45
Response Elements	45
Errors	46
See Also	48
DeleteResourcePolicy	49
Request Syntax	49
Request Parameters	49
Response Elements	49
Errors	49
See Also	50
DeleteTrail	52
Request Syntax	52
Request Parameters	52
Response Elements	52
Errors	52
See Also	54
DeregisterOrganizationDelegatedAdmin	56
Request Syntax	56
Request Parameters	56
Response Elements	56
Errors	56
See Also	58
DescribeQuery	60
Request Syntax	60
Request Parameters	60
Response Syntax	61

Response Elements	61
Errors	63
See Also	64
DescribeTrails	65
Request Syntax	65
Request Parameters	65
Response Syntax	66
Response Elements	66
Errors	67
See Also	68
DisableFederation	69
Request Syntax	69
Request Parameters	69
Response Syntax	69
Response Elements	70
Errors	70
Examples	72
See Also	73
EnableFederation	74
Request Syntax	74
Request Parameters	74
Response Syntax	75
Response Elements	75
Errors	76
Examples	78
See Also	79
GetChannel	80
Request Syntax	80
Request Parameters	80
Response Syntax	80
Response Elements	81
Errors	83
See Also	83
GetEventDataStore	85
Request Syntax	85
Request Parameters	85

Response Syntax	85
Response Elements	86
Errors	89
See Also	90
GetEventSelectors	91
Request Syntax	91
Request Parameters	91
Response Syntax	92
Response Elements	93
Errors	93
See Also	94
GetImport	96
Request Syntax	96
Request Parameters	96
Response Syntax	96
Response Elements	97
Errors	99
See Also	99
GetInsightSelectors	101
Request Syntax	101
Request Parameters	101
Response Syntax	102
Response Elements	102
Errors	103
See Also	105
GetQueryResults	106
Request Syntax	106
Request Parameters	106
Response Syntax	107
Response Elements	108
Errors	109
See Also	110
GetResourcePolicy	111
Request Syntax	111
Request Parameters	111
Response Syntax	111

Response Elements	111
Errors	112
See Also	113
GetTrail	114
Request Syntax	114
Request Parameters	114
Response Syntax	114
Response Elements	115
Errors	115
See Also	116
GetTrailStatus	118
Request Syntax	118
Request Parameters	118
Response Syntax	118
Response Elements	119
Errors	122
See Also	123
ListChannels	124
Request Syntax	124
Request Parameters	124
Response Syntax	125
Response Elements	125
Errors	125
See Also	126
ListEventDataStores	127
Request Syntax	127
Request Parameters	127
Response Syntax	127
Response Elements	128
Errors	129
See Also	130
ListImportFailures	131
Request Syntax	131
Request Parameters	131
Response Syntax	132
Response Elements	132

Errors	133
See Also	133
ListImports	135
Request Syntax	135
Request Parameters	135
Response Syntax	136
Response Elements	136
Errors	137
See Also	138
ListInsightsMetricData	139
Request Syntax	139
Request Parameters	139
Response Syntax	142
Response Elements	143
Errors	144
Examples	145
See Also	145
ListPublicKeys	147
Request Syntax	147
Request Parameters	147
Response Syntax	148
Response Elements	148
Errors	149
See Also	149
ListQueries	151
Request Syntax	151
Request Parameters	151
Response Syntax	153
Response Elements	153
Errors	153
See Also	155
ListTags	156
Request Syntax	156
Request Parameters	156
Response Syntax	157
Response Elements	157

Errors	157
See Also	159
ListTrails	161
Request Syntax	161
Request Parameters	161
Response Syntax	161
Response Elements	162
Errors	162
See Also	162
LookupEvents	164
Request Syntax	165
Request Parameters	165
Response Syntax	167
Response Elements	167
Errors	168
See Also	169
PutEventSelectors	170
Request Syntax	171
Request Parameters	171
Response Syntax	173
Response Elements	173
Errors	174
Examples	177
See Also	178
PutInsightSelectors	180
Request Syntax	180
Request Parameters	181
Response Syntax	182
Response Elements	182
Errors	183
Examples	186
See Also	188
PutResourcePolicy	189
Request Syntax	189
Request Parameters	189
Response Syntax	190

Response Elements	190
Errors	191
See Also	192
RegisterOrganizationDelegatedAdmin	193
Request Syntax	193
Request Parameters	193
Response Elements	193
Errors	193
See Also	195
RemoveTags	197
Request Syntax	197
Request Parameters	197
Response Elements	198
Errors	198
See Also	200
RestoreEventDataStore	202
Request Syntax	202
Request Parameters	202
Response Syntax	202
Response Elements	203
Errors	205
See Also	207
StartEventDataStoreIngestion	209
Request Syntax	209
Request Parameters	209
Response Elements	209
Errors	209
See Also	211
StartImport	212
Request Syntax	212
Request Parameters	213
Response Syntax	214
Response Elements	214
Errors	216
See Also	218
StartLogging	219

Request Syntax	219
Request Parameters	219
Response Elements	219
Errors	219
See Also	222
StartQuery	223
Request Syntax	223
Request Parameters	223
Response Syntax	224
Response Elements	224
Errors	225
Examples	227
See Also	227
StopEventDataStoreIngestion	229
Request Syntax	229
Request Parameters	229
Response Elements	229
Errors	229
See Also	231
StopImport	232
Request Syntax	232
Request Parameters	232
Response Syntax	232
Response Elements	233
Errors	234
See Also	235
StopLogging	236
Request Syntax	236
Request Parameters	236
Response Elements	236
Errors	236
See Also	239
UpdateChannel	240
Request Syntax	240
Request Parameters	240
Response Syntax	241

Response Elements	241
Errors	242
See Also	244
UpdateEventDataStore	245
Request Syntax	245
Request Parameters	246
Response Syntax	249
Response Elements	250
Errors	253
See Also	257
UpdateTrail	258
Request Syntax	258
Request Parameters	258
Response Syntax	262
Response Elements	262
Errors	264
See Also	270
Data Types	271
AdvancedEventSelector	273
Contents	273
See Also	274
AdvancedFieldSelector	275
Contents	275
See Also	289
Channel	291
Contents	291
See Also	291
DataResource	293
Contents	294
See Also	296
Destination	297
Contents	297
See Also	297
Event	299
Contents	299
See Also	300

EventDataStore	301
Contents	301
See Also	303
EventSelector	304
Contents	304
See Also	305
ImportFailureListItem	306
Contents	306
See Also	307
ImportsListItem	308
Contents	308
See Also	309
ImportSource	310
Contents	310
See Also	310
ImportStatistics	311
Contents	311
See Also	312
IngestionStatus	313
Contents	313
See Also	314
InsightSelector	315
Contents	315
See Also	315
LookupAttribute	316
Contents	316
See Also	316
PartitionKey	317
Contents	317
See Also	317
PublicKey	318
Contents	318
See Also	318
Query	320
Contents	320
See Also	320

QueryStatistics	322
Contents	322
See Also	322
QueryStatisticsForDescribeQuery	323
Contents	323
See Also	324
Resource	325
Contents	325
See Also	325
ResourceTag	326
Contents	326
See Also	326
S3ImportSource	327
Contents	327
See Also	327
SourceConfig	328
Contents	328
See Also	328
Tag	329
Contents	329
See Also	329
Trail	330
Contents	330
See Also	333
TrailInfo	334
Contents	334
See Also	334
Common Parameters	335
Common Errors	338

Welcome

This is the CloudTrail API Reference. It provides descriptions of actions, data types, common parameters, and common errors for CloudTrail.

CloudTrail is a web service that records AWS API calls for your AWS account and delivers log files to an Amazon S3 bucket. The recorded information includes the identity of the user, the start time of the AWS API call, the source IP address, the request parameters, and the response elements returned by the service.

Note

As an alternative to the API, you can use one of the AWS SDKs, which consist of libraries and sample code for various programming languages and platforms (Java, Ruby, .NET, iOS, Android, etc.). The SDKs provide programmatic access to AWS CloudTrail. For example, the SDKs handle cryptographically signing requests, managing errors, and retrying requests automatically. For more information about the AWS SDKs, including how to download and install them, see [Tools to Build on AWS](#).

See the [AWS CloudTrail User Guide](#) for information about the data that is included with each AWS API call listed in the log files.

This document was last published on July 1, 2024.

Actions

The following actions are supported:

- [AddTags](#)
- [CancelQuery](#)
- [CreateChannel](#)
- [CreateEventDataStore](#)
- [CreateTrail](#)
- [DeleteChannel](#)
- [DeleteEventDataStore](#)
- [DeleteResourcePolicy](#)
- [DeleteTrail](#)
- [DeregisterOrganizationDelegatedAdmin](#)
- [DescribeQuery](#)
- [DescribeTrails](#)
- [DisableFederation](#)
- [EnableFederation](#)
- [GetChannel](#)
- [GetEventDataStore](#)
- [GetEventSelectors](#)
- [GetImport](#)
- [GetInsightSelectors](#)
- [GetQueryResults](#)
- [GetResourcePolicy](#)
- [GetTrail](#)
- [GetTrailStatus](#)
- [ListChannels](#)
- [ListEventDataStores](#)
- [ListImportFailures](#)
- [ListImports](#)

- [ListInsightsMetricData](#)
- [ListPublicKeys](#)
- [ListQueries](#)
- [ListTags](#)
- [ListTrails](#)
- [LookupEvents](#)
- [PutEventSelectors](#)
- [PutInsightSelectors](#)
- [PutResourcePolicy](#)
- [RegisterOrganizationDelegatedAdmin](#)
- [RemoveTags](#)
- [RestoreEventDataStore](#)
- [StartEventDataStoreIngestion](#)
- [StartImport](#)
- [StartLogging](#)
- [StartQuery](#)
- [StopEventDataStoreIngestion](#)
- [StopImport](#)
- [StopLogging](#)
- [UpdateChannel](#)
- [UpdateEventDataStore](#)
- [UpdateTrail](#)

AddTags

Adds one or more tags to a trail, event data store, or channel, up to a limit of 50. Overwrites an existing tag's value when a new value is specified for an existing tag key. Tag key names must be unique; you cannot have two keys with the same name but different values. If you specify a key without a value, the tag will be created with the specified key and a value of null. You can tag a trail or event data store that applies to all AWS Regions only from the Region in which the trail or event data store was created (also known as its home Region).

Request Syntax

```
{
  "ResourceId": "string",
  "TagsList": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ResourceId

Specifies the ARN of the trail, event data store, or channel to which one or more tags will be added.

The format of a trail ARN is: `arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail`

The format of an event data store ARN is: `arn:aws:cloudtrail:us-east-2:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE`

The format of a channel ARN is: `arn:aws:cloudtrail:us-east-2:123456789012:channel/01234567890`

Type: String

Required: Yes

TagsList

Contains a list of tags, up to a limit of 50

Type: Array of [Tag](#) objects

Array Members: Maximum number of 200 items.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ChannelARNInvalidException

This exception is thrown when the specified value of ChannelARN is not valid.

HTTP Status Code: 400

ChannelNotFoundException

This exception is thrown when CloudTrail cannot find the specified channel.

HTTP Status Code: 400

CloudTrailARNInvalidException

This exception is thrown when an operation is called with an ARN that is not valid.

The following is the format of a trail ARN: `arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail`

The following is the format of an event data store ARN: `arn:aws:cloudtrail:us-east-2:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE`

The following is the format of a channel ARN: `arn:aws:cloudtrail:us-east-2:123456789012:channel/01234567890`

HTTP Status Code: 400

ConflictException

This exception is thrown when the specified resource is not ready for an operation. This can occur when you try to run an operation on a resource before CloudTrail has time to fully load the resource, or because another operation is modifying the resource. If this exception occurs, wait a few minutes, and then try the operation again.

HTTP Status Code: 400

EventDataStoreARNInvalidException

The specified event data store ARN is not valid or does not map to an event data store in your account.

HTTP Status Code: 400

EventDataStoreNotFoundException

The specified event data store was not found.

HTTP Status Code: 400

InactiveEventDataStoreException

The event data store is inactive.

HTTP Status Code: 400

InvalidTagParameterException

This exception is thrown when the specified tag key or values are not valid. It can also occur if there are duplicate tags or too many tags on the resource.

HTTP Status Code: 400

InvalidTrailNameException

This exception is thrown when the provided trail name is not valid. Trail names must meet the following requirements:

- Contain only ASCII letters (a-z, A-Z), numbers (0-9), periods (.), underscores (_), or dashes (-)

- Start with a letter or number, and end with a letter or number
- Be between 3 and 128 characters
- Have no adjacent periods, underscores or dashes. Names like my-namespace and my--namespace are not valid.
- Not be in IP address format (for example, 192.168.5.4)

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

NotOrganizationMasterAccountException

This exception is thrown when the AWS account making the request to create or update an organization trail or event data store is not the management account for an organization in AWS Organizations. For more information, see [Prepare For Creating a Trail For Your Organization](#) or [Organization event data stores](#).

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

This exception is thrown when the specified resource is not found.

HTTP Status Code: 400

ResourceTypeNotSupportedException

This exception is thrown when the specified resource type is not supported by CloudTrail.

HTTP Status Code: 400

TagsLimitExceededException

The number of tags per trail, event data store, or channel has exceeded the permitted amount. Currently, the limit is 50.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CancelQuery

Cancels a query if the query is not in a terminated state, such as CANCELLED, FAILED, TIMED_OUT, or FINISHED. You must specify an ARN value for EventDataStore. The ID of the query that you want to cancel is also required. When you run CancelQuery, the query status might show as CANCELLED even if the operation is not yet finished.

Request Syntax

```
{
  "EventDataStore": "string",
  "QueryId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

EventDataStore

This parameter has been deprecated.

The ARN (or the ID suffix of the ARN) of an event data store on which the specified query is running.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: No

QueryId

The ID of the query that you want to cancel. The QueryId comes from the response of a StartQuery operation.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[a-f0-9\ -]+$`

Required: Yes

Response Syntax

```
{
  "QueryId": "string",
  "QueryStatus": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

QueryId

The ID of the canceled query.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[a-f0-9\ -]+$`

QueryStatus

Shows the status of a query after a `CancelQuery` request. Typically, the values shown are either `RUNNING` or `CANCELLED`.

Type: String

Valid Values: `QUEUED` | `RUNNING` | `FINISHED` | `FAILED` | `CANCELLED` | `TIMED_OUT`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

This exception is thrown when the specified resource is not ready for an operation. This can occur when you try to run an operation on a resource before CloudTrail has time to fully load the resource, or because another operation is modifying the resource. If this exception occurs, wait a few minutes, and then try the operation again.

HTTP Status Code: 400

EventDataStoreARNInvalidException

The specified event data store ARN is not valid or does not map to an event data store in your account.

HTTP Status Code: 400

EventDataStoreNotFoundException

The specified event data store was not found.

HTTP Status Code: 400

InactiveEventDataStoreException

The event data store is inactive.

HTTP Status Code: 400

InactiveQueryException

The specified query cannot be canceled because it is in the FINISHED, FAILED, TIMED_OUT, or CANCELLED state.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

QueryIdNotFoundException

The query ID does not exist or does not map to a query.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateChannel

Creates a channel for CloudTrail to ingest events from a partner or external source. After you create a channel, a CloudTrail Lake event data store can log events from the partner or source that you specify.

Request Syntax

```
{
  "Destinations": [
    {
      "Location": "string",
      "Type": "string"
    }
  ],
  "Name": "string",
  "Source": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Destinations

One or more event data stores to which events arriving through a channel will be logged.

Type: Array of [Destination](#) objects

Array Members: Minimum number of 1 item. Maximum number of 200 items.

Required: Yes

Name

The name of the channel.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9._\-\]+$`

Required: Yes

Source

The name of the partner or external event source. You cannot change this name after you create the channel. A maximum of one channel is allowed per source.

A source can be either Custom for all valid non-AWS events, or the name of a partner event source. For information about the source names for available partners, see [Additional information about integration partners](#) in the CloudTrail User Guide.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `.*`

Required: Yes

Tags

A list of tags.

Type: Array of [Tag](#) objects

Array Members: Maximum number of 200 items.

Required: No

Response Syntax

```
{
  "ChannelArn": "string",
```

```
"Destinations": [  
  {  
    "Location": "string",  
    "Type": "string"  
  }  
],  
"Name": "string",  
"Source": "string",  
"Tags": [  
  {  
    "Key": "string",  
    "Value": "string"  
  }  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ChannelArn

The Amazon Resource Name (ARN) of the new channel.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Destinations

The event data stores that log the events arriving through the channel.

Type: Array of [Destination](#) objects

Array Members: Minimum number of 1 item. Maximum number of 200 items.

Name

The name of the new channel.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9._\-\]+$`

Source

The partner or external event source name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `.*`

Tags

A list of tags.

Type: Array of [Tag](#) objects

Array Members: Maximum number of 200 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ChannelAlreadyExistsException

This exception is thrown when the provided channel already exists.

HTTP Status Code: 400

ChannelMaxLimitExceededException

This exception is thrown when the maximum number of channels limit is exceeded.

HTTP Status Code: 400

EventDataStoreARNInvalidException

The specified event data store ARN is not valid or does not map to an event data store in your account.

HTTP Status Code: 400

EventDataStoreNotFoundException

The specified event data store was not found.

HTTP Status Code: 400

InactiveEventDataStoreException

The event data store is inactive.

HTTP Status Code: 400

InvalidEventDataStoreCategoryException

This exception is thrown when event categories of specified event data stores are not valid.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

InvalidSourceException

This exception is thrown when the specified value of `Source` is not valid.

HTTP Status Code: 400

InvalidTagParameterException

This exception is thrown when the specified tag key or values are not valid. It can also occur if there are duplicate tags or too many tags on the resource.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

TagsLimitExceededException

The number of tags per trail, event data store, or channel has exceeded the permitted amount. Currently, the limit is 50.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateEventDataStore

Creates a new event data store.

Request Syntax

```
{
  "AdvancedEventSelectors": [
    {
      "FieldSelectors": [
        {
          "EndsWith": [ "string" ],
          "Equals": [ "string" ],
          "Field": "string",
          "NotEndsWith": [ "string" ],
          "NotEquals": [ "string" ],
          "NotStartsWith": [ "string" ],
          "StartsWith": [ "string" ]
        }
      ],
      "Name": "string"
    }
  ],
  "BillingMode": "string",
  "KmsKeyId": "string",
  "MultiRegionEnabled": boolean,
  "Name": "string",
  "OrganizationEnabled": boolean,
  "RetentionPeriod": number,
  "StartIngestion": boolean,
  "TagsList": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "TerminationProtectionEnabled": boolean
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AdvancedEventSelectors

The advanced event selectors to use to select the events for the data store. You can configure up to five advanced event selectors for each event data store.

For more information about how to use advanced event selectors to log CloudTrail events, see [Log events by using advanced event selectors](#) in the CloudTrail User Guide.

For more information about how to use advanced event selectors to include AWS Config configuration items in your event data store, see [Create an event data store for AWS Config configuration items](#) in the CloudTrail User Guide.

For more information about how to use advanced event selectors to include events outside of AWS events in your event data store, see [Create an integration to log events from outside AWS](#) in the CloudTrail User Guide.

Type: Array of [AdvancedEventSelector](#) objects

Required: No

BillingMode

The billing mode for the event data store determines the cost for ingesting events and the default and maximum retention period for the event data store.

The following are the possible values:

- `EXTENDABLE_RETENTION_PRICING` - This billing mode is generally recommended if you want a flexible retention period of up to 3653 days (about 10 years). The default retention period for this billing mode is 366 days.
- `FIXED_RETENTION_PRICING` - This billing mode is recommended if you expect to ingest more than 25 TB of event data per month and need a retention period of up to 2557 days (about 7 years). The default retention period for this billing mode is 2557 days.

The default value is `EXTENDABLE_RETENTION_PRICING`.

For more information about CloudTrail pricing, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail Lake costs](#).

Type: String

Valid Values: `EXTENDABLE_RETENTION_PRICING` | `FIXED_RETENTION_PRICING`

Required: No

KmsKeyId

Specifies the AWS KMS key ID to use to encrypt the events delivered by CloudTrail. The value can be an alias name prefixed by `alias/`, a fully specified ARN to an alias, a fully specified ARN to a key, or a globally unique identifier.

Important

Disabling or deleting the KMS key, or removing CloudTrail permissions on the key, prevents CloudTrail from logging events to the event data store, and prevents users from querying the data in the event data store that was encrypted with the key. After you associate an event data store with a KMS key, the KMS key cannot be removed or changed. Before you disable or delete a KMS key that you are using with an event data store, delete or back up your event data store.

CloudTrail also supports AWS KMS multi-Region keys. For more information about multi-Region keys, see [Using multi-Region keys](#) in the *AWS Key Management Service Developer Guide*.

Examples:

- `alias/MyAliasName`
- `arn:aws:kms:us-east-2:123456789012:alias/MyAliasName`
- `arn:aws:kms:us-east-2:123456789012:key/12345678-1234-1234-1234-123456789012`
- `12345678-1234-1234-1234-123456789012`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 350.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: No

MultiRegionEnabled

Specifies whether the event data store includes events from all Regions, or only from the Region in which the event data store is created.

Type: Boolean

Required: No

Name

The name of the event data store.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9._\-\]+$`

Required: Yes

OrganizationEnabled

Specifies whether an event data store collects events logged for an organization in AWS Organizations.

Type: Boolean

Required: No

RetentionPeriod

The retention period of the event data store, in days. If `BillingMode` is set to `EXTENDABLE_RETENTION_PRICING`, you can set a retention period of up to 3653 days, the equivalent of 10 years. If `BillingMode` is set to `FIXED_RETENTION_PRICING`, you can set a retention period of up to 2557 days, the equivalent of seven years.

CloudTrail Lake determines whether to retain an event by checking if the `eventTime` of the event is within the specified retention period. For example, if you set a retention period of 90 days, CloudTrail will remove events when the `eventTime` is older than 90 days.

Note

If you plan to copy trail events to this event data store, we recommend that you consider both the age of the events that you want to copy as well as how long you want to keep the copied events in your event data store. For example, if you copy trail events that are 5 years old and specify a retention period of 7 years, the event data store will retain those events for two years.

Type: Integer

Valid Range: Minimum value of 7. Maximum value of 3653.

Required: No

StartIngestion

Specifies whether the event data store should start ingesting live events. The default is true.

Type: Boolean

Required: No

TagsList

A list of tags.

Type: Array of [Tag](#) objects

Array Members: Maximum number of 200 items.

Required: No

TerminationProtectionEnabled

Specifies whether termination protection is enabled for the event data store. If termination protection is enabled, you cannot delete the event data store until termination protection is disabled.

Type: Boolean

Required: No

Response Syntax

```
{
  "AdvancedEventSelectors": [
    {
      "FieldSelectors": [
        {
          "EndsWith": [ "string" ],
          "Equals": [ "string" ],
          "Field": "string",
          "NotEndsWith": [ "string" ],
        }
      ]
    }
  ]
}
```

```
        "NotEquals": [ "string" ],
        "NotStartsWith": [ "string" ],
        "StartsWith": [ "string" ]
    }
],
    "Name": "string"
}
],
"BillingMode": "string",
"CreatedTimestamp": number,
"EventDataStoreArn": "string",
"KmsKeyId": "string",
"MultiRegionEnabled": boolean,
"Name": "string",
"OrganizationEnabled": boolean,
"RetentionPeriod": number,
"Status": "string",
"TagsList": [
    {
        "Key": "string",
        "Value": "string"
    }
],
"TerminationProtectionEnabled": boolean,
"UpdatedTimestamp": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AdvancedEventSelectors

The advanced event selectors that were used to select the events for the data store.

Type: Array of [AdvancedEventSelector](#) objects

BillingMode

The billing mode for the event data store.

Type: String

Valid Values: EXTENDABLE_RETENTION_PRICING | FIXED_RETENTION_PRICING

CreatedTimestamp

The timestamp that shows when the event data store was created.

Type: Timestamp

EventDataStoreArn

The ARN of the event data store.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

KmsKeyId

Specifies the AWS KMS key ID that encrypts the events delivered by CloudTrail. The value is a fully specified ARN to a AWS KMS key in the following format.

```
arn:aws:kms:us-east-2:123456789012:key/12345678-1234-1234-1234-123456789012
```

Type: String

Length Constraints: Minimum length of 1. Maximum length of 350.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

MultiRegionEnabled

Indicates whether the event data store collects events from all Regions, or only from the Region in which it was created.

Type: Boolean

Name

The name of the event data store.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9._\-]+$`

OrganizationEnabled

Indicates whether an event data store is collecting logged events for an organization in AWS Organizations.

Type: Boolean

RetentionPeriod

The retention period of an event data store, in days.

Type: Integer

Valid Range: Minimum value of 7. Maximum value of 3653.

Status

The status of event data store creation.

Type: String

Valid Values: CREATED | ENABLED | PENDING_DELETION | STARTING_INGESTION | STOPPING_INGESTION | STOPPED_INGESTION

TagsList

A list of tags.

Type: Array of [Tag](#) objects

Array Members: Maximum number of 200 items.

TerminationProtectionEnabled

Indicates whether termination protection is enabled for the event data store.

Type: Boolean

UpdatedTimestamp

The timestamp that shows when an event data store was updated, if applicable. UpdatedTimestamp is always either the same or newer than the time shown in CreatedTimestamp.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

CloudTrailAccessNotEnabledException

This exception is thrown when trusted access has not been enabled between AWS CloudTrail and AWS Organizations. For more information, see [How to enable or disable trusted access](#) in the *AWS Organizations User Guide* and [Prepare For Creating a Trail For Your Organization](#) in the *AWS CloudTrail User Guide*.

HTTP Status Code: 400

ConflictException

This exception is thrown when the specified resource is not ready for an operation. This can occur when you try to run an operation on a resource before CloudTrail has time to fully load the resource, or because another operation is modifying the resource. If this exception occurs, wait a few minutes, and then try the operation again.

HTTP Status Code: 400

EventDataStoreAlreadyExistsException

An event data store with that name already exists.

HTTP Status Code: 400

EventDataStoreMaxLimitExceededException

Your account has used the maximum number of event data stores.

HTTP Status Code: 400

InsufficientDependencyServiceAccessPermissionException

This exception is thrown when the IAM identity that is used to create the organization resource lacks one or more required permissions for creating an organization resource in a required service.

HTTP Status Code: 400

InsufficientEncryptionPolicyException

This exception is thrown when the policy on the S3 bucket or AWS KMS key does not have sufficient permissions for the operation.

HTTP Status Code: 400

InvalidEventSelectorsException

This exception is thrown when the `PutEventSelectors` operation is called with a number of event selectors, advanced event selectors, or data resources that is not valid. The combination of event selectors or advanced event selectors and data resources is not valid. A trail can have up to 5 event selectors. If a trail uses advanced event selectors, a maximum of 500 total values for all conditions in all advanced event selectors is allowed. A trail is limited to 250 data resources. These data resources can be distributed across event selectors, but the overall total cannot exceed 250.

You can:

- Specify a valid number of event selectors (1 to 5) for a trail.
- Specify a valid number of data resources (1 to 250) for an event selector. The limit of number of resources on an individual event selector is configurable up to 250. However, this upper limit is allowed only if the total number of data resources does not exceed 250 across all event selectors for a trail.
- Specify up to 500 values for all conditions in all advanced event selectors for a trail.
- Specify a valid value for a parameter. For example, specifying the `ReadWriteType` parameter with a value of `read-only` is not valid.

HTTP Status Code: 400

InvalidKmsKeyIdException

This exception is thrown when the AWS KMS key ARN is not valid.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

InvalidTagParameterException

This exception is thrown when the specified tag key or values are not valid. It can also occur if there are duplicate tags or too many tags on the resource.

HTTP Status Code: 400

KmsException

This exception is thrown when there is an issue with the specified AWS KMS key and the trail or event data store can't be updated.

HTTP Status Code: 400

KmsKeyNotFoundException

This exception is thrown when the AWS KMS key does not exist, when the S3 bucket and the AWS KMS key are not in the same Region, or when the AWS KMS key associated with the Amazon SNS topic either does not exist or is not in the same Region.

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

NotOrganizationMasterAccountException

This exception is thrown when the AWS account making the request to create or update an organization trail or event data store is not the management account for an organization in AWS Organizations. For more information, see [Prepare For Creating a Trail For Your Organization](#) or [Organization event data stores](#).

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

OrganizationNotInAllFeaturesModeException

This exception is thrown when AWS Organizations is not configured to support all features. All features must be enabled in Organizations to support creating an organization trail or event data store.

HTTP Status Code: 400

OrganizationsNotInUseException

This exception is thrown when the request is made from an AWS account that is not a member of an organization. To make this request, sign in using the credentials of an account that belongs to an organization.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateTrail

Creates a trail that specifies the settings for delivery of log data to an Amazon S3 bucket.

Request Syntax

```
{
  "CloudWatchLogsLogGroupArn": "string",
  "CloudWatchLogsRoleArn": "string",
  "EnableLogFileValidation": boolean,
  "IncludeGlobalServiceEvents": boolean,
  "IsMultiRegionTrail": boolean,
  "IsOrganizationTrail": boolean,
  "KmsKeyId": "string",
  "Name": "string",
  "S3BucketName": "string",
  "S3KeyPrefix": "string",
  "SnsTopicName": "string",
  "TagsList": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

CloudWatchLogsLogGroupArn

Specifies a log group name using an Amazon Resource Name (ARN), a unique identifier that represents the log group to which CloudTrail logs will be delivered. You must use a log group that exists in your account.

Not required unless you specify `CloudWatchLogsRoleArn`.

Type: String

Required: No

CloudWatchLogsRoleArn

Specifies the role for the CloudWatch Logs endpoint to assume to write to a user's log group. You must use a role that exists in your account.

Type: String

Required: No

EnableLogFileValidation

Specifies whether log file integrity validation is enabled. The default is false.

Note

When you disable log file integrity validation, the chain of digest files is broken after one hour. CloudTrail does not create digest files for log files that were delivered during a period in which log file integrity validation was disabled. For example, if you enable log file integrity validation at noon on January 1, disable it at noon on January 2, and re-enable it at noon on January 10, digest files will not be created for the log files delivered from noon on January 2 to noon on January 10. The same applies whenever you stop CloudTrail logging or delete a trail.

Type: Boolean

Required: No

IncludeGlobalServiceEvents

Specifies whether the trail is publishing events from global services such as IAM to the log files.

Type: Boolean

Required: No

IsMultiRegionTrail

Specifies whether the trail is created in the current Region or in all Regions. The default is false, which creates a trail only in the Region where you are signed in. As a best practice, consider creating trails that log events in all Regions.

Type: Boolean

Required: No

IsOrganizationTrail

Specifies whether the trail is created for all accounts in an organization in AWS Organizations, or only for the current AWS account. The default is false, and cannot be true unless the call is made on behalf of an AWS account that is the management account or delegated administrator account for an organization in AWS Organizations.

Type: Boolean

Required: No

KmsKeyId

Specifies the AWS KMS key ID to use to encrypt the logs delivered by CloudTrail. The value can be an alias name prefixed by `alias/`, a fully specified ARN to an alias, a fully specified ARN to a key, or a globally unique identifier.

CloudTrail also supports AWS KMS multi-Region keys. For more information about multi-Region keys, see [Using multi-Region keys](#) in the *AWS Key Management Service Developer Guide*.

Examples:

- `alias/MyAliasName`
- `arn:aws:kms:us-east-2:123456789012:alias/MyAliasName`
- `arn:aws:kms:us-east-2:123456789012:key/12345678-1234-1234-1234-123456789012`
- `12345678-1234-1234-1234-123456789012`

Type: String

Required: No

Name

Specifies the name of the trail. The name must meet the following requirements:

- Contain only ASCII letters (a-z, A-Z), numbers (0-9), periods (.), underscores (`_`), or dashes (`-`)
- Start with a letter or number, and end with a letter or number
- Be between 3 and 128 characters

- Have no adjacent periods, underscores or dashes. Names like my-__namespace and my--namespace are not valid.
- Not be in IP address format (for example, 192.168.5.4)

Type: String

Required: Yes

S3BucketName

Specifies the name of the Amazon S3 bucket designated for publishing log files. For information about bucket naming rules, see [Bucket naming rules](#) in the *Amazon Simple Storage Service User Guide*.

Type: String

Required: Yes

S3KeyPrefix

Specifies the Amazon S3 key prefix that comes after the name of the bucket you have designated for log file delivery. For more information, see [Finding Your CloudTrail Log Files](#). The maximum length is 200 characters.

Type: String

Required: No

SnsTopicName

Specifies the name of the Amazon SNS topic defined for notification of log file delivery. The maximum length is 256 characters.

Type: String

Required: No

TagsList

A list of tags.

Type: Array of [Tag](#) objects

Array Members: Maximum number of 200 items.

Required: No

Response Syntax

```
{
  "CloudWatchLogsLogGroupArn": "string",
  "CloudWatchLogsRoleArn": "string",
  "IncludeGlobalServiceEvents": boolean,
  "IsMultiRegionTrail": boolean,
  "IsOrganizationTrail": boolean,
  "KmsKeyId": "string",
  "LogFileValidationEnabled": boolean,
  "Name": "string",
  "S3BucketName": "string",
  "S3KeyPrefix": "string",
  "SnsTopicARN": "string",
  "SnsTopicName": "string",
  "TrailARN": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[CloudWatchLogsLogGroupArn](#)

Specifies the Amazon Resource Name (ARN) of the log group to which CloudTrail logs will be delivered.

Type: String

[CloudWatchLogsRoleArn](#)

Specifies the role for the CloudWatch Logs endpoint to assume to write to a user's log group.

Type: String

[IncludeGlobalServiceEvents](#)

Specifies whether the trail is publishing events from global services such as IAM to the log files.

Type: Boolean

IsMultiRegionTrail

Specifies whether the trail exists in one Region or in all Regions.

Type: Boolean

IsOrganizationTrail

Specifies whether the trail is an organization trail.

Type: Boolean

KmsKeyId

Specifies the AWS KMS key ID that encrypts the events delivered by CloudTrail. The value is a fully specified ARN to a AWS KMS key in the following format.

```
arn:aws:kms:us-  
east-2:123456789012:key/12345678-1234-1234-1234-123456789012
```

Type: String

LogFileValidationEnabled

Specifies whether log file integrity validation is enabled.

Type: Boolean

Name

Specifies the name of the trail.

Type: String

S3BucketName

Specifies the name of the Amazon S3 bucket designated for publishing log files.

Type: String

S3KeyPrefix

Specifies the Amazon S3 key prefix that comes after the name of the bucket you have designated for log file delivery. For more information, see [Finding Your CloudTrail Log Files](#).

Type: String

SnsTopicARN

Specifies the ARN of the Amazon SNS topic that CloudTrail uses to send notifications when log files are delivered. The format of a topic ARN is:

```
arn:aws:sns:us-east-2:123456789012:MyTopic
```

Type: String

SnsTopicName

This parameter has been deprecated.

This field is no longer in use. Use SnsTopicARN.

Type: String

TrailARN

Specifies the ARN of the trail that was created. The format of a trail ARN is:

```
arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail
```

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

CloudTrailAccessNotEnabledException

This exception is thrown when trusted access has not been enabled between AWS CloudTrail and AWS Organizations. For more information, see [How to enable or disable trusted access](#) in the *AWS Organizations User Guide* and [Prepare For Creating a Trail For Your Organization](#) in the *AWS CloudTrail User Guide*.

HTTP Status Code: 400

CloudTrailInvalidClientTokenIdException

This exception is thrown when a call results in the `InvalidClientTokenId` error code. This can occur when you are creating or updating a trail to send notifications to an Amazon SNS topic that is in a suspended AWS account.

HTTP Status Code: 400

CloudWatchLogsDeliveryUnavailableException

Cannot set a CloudWatch Logs delivery for this Region.

HTTP Status Code: 400

ConflictException

This exception is thrown when the specified resource is not ready for an operation. This can occur when you try to run an operation on a resource before CloudTrail has time to fully load the resource, or because another operation is modifying the resource. If this exception occurs, wait a few minutes, and then try the operation again.

HTTP Status Code: 400

InsufficientDependencyServiceAccessPermissionException

This exception is thrown when the IAM identity that is used to create the organization resource lacks one or more required permissions for creating an organization resource in a required service.

HTTP Status Code: 400

InsufficientEncryptionPolicyException

This exception is thrown when the policy on the S3 bucket or AWS KMS key does not have sufficient permissions for the operation.

HTTP Status Code: 400

InsufficientS3BucketPolicyException

This exception is thrown when the policy on the S3 bucket is not sufficient.

HTTP Status Code: 400

InsufficientSnsTopicPolicyException

This exception is thrown when the policy on the Amazon SNS topic is not sufficient.

HTTP Status Code: 400

InvalidCloudWatchLogsLogGroupArnException

This exception is thrown when the provided CloudWatch Logs log group is not valid.

HTTP Status Code: 400

InvalidCloudWatchLogsRoleArnException

This exception is thrown when the provided role is not valid.

HTTP Status Code: 400

InvalidKmsKeyIdException

This exception is thrown when the AWS KMS key ARN is not valid.

HTTP Status Code: 400

InvalidParameterCombinationException

This exception is thrown when the combination of parameters provided is not valid.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

InvalidS3BucketNameException

This exception is thrown when the provided S3 bucket name is not valid.

HTTP Status Code: 400

InvalidS3PrefixException

This exception is thrown when the provided S3 prefix is not valid.

HTTP Status Code: 400

InvalidSnsTopicNameException

This exception is thrown when the provided SNS topic name is not valid.

HTTP Status Code: 400

InvalidTagParameterException

This exception is thrown when the specified tag key or values are not valid. It can also occur if there are duplicate tags or too many tags on the resource.

HTTP Status Code: 400

InvalidTrailNameException

This exception is thrown when the provided trail name is not valid. Trail names must meet the following requirements:

- Contain only ASCII letters (a-z, A-Z), numbers (0-9), periods (.), underscores (_), or dashes (-)
- Start with a letter or number, and end with a letter or number
- Be between 3 and 128 characters
- Have no adjacent periods, underscores or dashes. Names like my-__namespace and my--namespace are not valid.
- Not be in IP address format (for example, 192.168.5.4)

HTTP Status Code: 400

KmsException

This exception is thrown when there is an issue with the specified AWS KMS key and the trail or event data store can't be updated.

HTTP Status Code: 400

KmsKeyDisabledException

This error has been deprecated.

This exception is no longer in use.

HTTP Status Code: 400

KmsKeyNotFoundException

This exception is thrown when the AWS KMS key does not exist, when the S3 bucket and the AWS KMS key are not in the same Region, or when the AWS KMS key associated with the Amazon SNS topic either does not exist or is not in the same Region.

HTTP Status Code: 400

MaximumNumberOfTrailsExceededException

This exception is thrown when the maximum number of trails is reached.

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

NotOrganizationMasterAccountException

This exception is thrown when the AWS account making the request to create or update an organization trail or event data store is not the management account for an organization in AWS Organizations. For more information, see [Prepare For Creating a Trail For Your Organization](#) or [Organization event data stores](#).

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

OrganizationNotInAllFeaturesModeException

This exception is thrown when AWS Organizations is not configured to support all features. All features must be enabled in Organizations to support creating an organization trail or event data store.

HTTP Status Code: 400

OrganizationsNotInUseException

This exception is thrown when the request is made from an AWS account that is not a member of an organization. To make this request, sign in using the credentials of an account that belongs to an organization.

HTTP Status Code: 400

S3BucketDoesNotExistException

This exception is thrown when the specified S3 bucket does not exist.

HTTP Status Code: 400

TagsLimitExceededException

The number of tags per trail, event data store, or channel has exceeded the permitted amount. Currently, the limit is 50.

HTTP Status Code: 400

ThrottlingException

This exception is thrown when the request rate exceeds the limit.

HTTP Status Code: 400

TrailAlreadyExistsException

This exception is thrown when the specified trail already exists.

HTTP Status Code: 400

TrailNotProvidedException

This exception is no longer in use.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteChannel

Deletes a channel.

Request Syntax

```
{  
  "Channel": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Channel

The ARN or the UUID value of the channel that you want to delete.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ChannelARNInvalidException

This exception is thrown when the specified value of ChannelARN is not valid.

HTTP Status Code: 400

ChannelNotFoundException

This exception is thrown when CloudTrail cannot find the specified channel.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteEventDataStore

Disables the event data store specified by `EventDataStore`, which accepts an event data store ARN. After you run `DeleteEventDataStore`, the event data store enters a `PENDING_DELETION` state, and is automatically deleted after a wait period of seven days. `TerminationProtectionEnabled` must be set to `False` on the event data store and the `FederationStatus` must be `DISABLED`. You cannot delete an event data store if `TerminationProtectionEnabled` is `True` or the `FederationStatus` is `ENABLED`.

After you run `DeleteEventDataStore` on an event data store, you cannot run `ListQueries`, `DescribeQuery`, or `GetQueryResults` on queries that are using an event data store in a `PENDING_DELETION` state. An event data store in the `PENDING_DELETION` state does not incur costs.

Request Syntax

```
{
  "EventDataStore": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

EventDataStore

The ARN (or the ID suffix of the ARN) of the event data store to delete.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ChannelExistsForEDSException

This exception is thrown when the specified event data store cannot yet be deleted because it is in use by a channel.

HTTP Status Code: 400

ConflictException

This exception is thrown when the specified resource is not ready for an operation. This can occur when you try to run an operation on a resource before CloudTrail has time to fully load the resource, or because another operation is modifying the resource. If this exception occurs, wait a few minutes, and then try the operation again.

HTTP Status Code: 400

EventDataStoreARNInvalidException

The specified event data store ARN is not valid or does not map to an event data store in your account.

HTTP Status Code: 400

EventDataStoreFederationEnabledException

You cannot delete the event data store because Lake query federation is enabled. To delete the event data store, run the `DisableFederation` operation to disable Lake query federation on the event data store.

HTTP Status Code: 400

EventDataStoreHasOngoingImportException

This exception is thrown when you try to update or delete an event data store that currently has an import in progress.

HTTP Status Code: 400

EventDataStoreNotFoundException

The specified event data store was not found.

HTTP Status Code: 400

EventDataStoreTerminationProtectedException

The event data store cannot be deleted because termination protection is enabled for it.

HTTP Status Code: 400

InactiveEventDataStoreException

The event data store is inactive.

HTTP Status Code: 400

InsufficientDependencyServiceAccessPermissionException

This exception is thrown when the IAM identity that is used to create the organization resource lacks one or more required permissions for creating an organization resource in a required service.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

NotOrganizationMasterAccountException

This exception is thrown when the AWS account making the request to create or update an organization trail or event data store is not the management account for an organization in AWS Organizations. For more information, see [Prepare For Creating a Trail For Your Organization](#) or [Organization event data stores](#).

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteResourcePolicy

Deletes the resource-based policy attached to the CloudTrail channel.

Request Syntax

```
{
  "ResourceArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ResourceArn

The Amazon Resource Name (ARN) of the CloudTrail channel you're deleting the resource-based policy from. The following is the format of a resource ARN: `arn:aws:cloudtrail:us-east-2:123456789012:channel/MyChannel`.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

ResourceARNNotValidException

This exception is thrown when the provided resource does not exist, or the ARN format of the resource is not valid. The following is the valid format for a resource ARN:
`arn:aws:cloudtrail:us-east-2:123456789012:channel/MyChannel.`

HTTP Status Code: 400

ResourceNotFoundException

This exception is thrown when the specified resource is not found.

HTTP Status Code: 400

ResourcePolicyNotFoundException

This exception is thrown when the specified resource policy is not found.

HTTP Status Code: 400

ResourceTypeNotSupportedException

This exception is thrown when the specified resource type is not supported by CloudTrail.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteTrail

Deletes a trail. This operation must be called from the Region in which the trail was created. `DeleteTrail` cannot be called on the shadow trails (replicated trails in other Regions) of a trail that is enabled in all Regions.

Request Syntax

```
{
  "Name": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

Specifies the name or the CloudTrail ARN of the trail to be deleted. The following is the format of a trail ARN: `arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail`

Type: String

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

CloudTrailARNInvalidException

This exception is thrown when an operation is called with an ARN that is not valid.

The following is the format of a trail ARN: `arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail`

The following is the format of an event data store ARN: `arn:aws:cloudtrail:us-east-2:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE`

The following is the format of a channel ARN: `arn:aws:cloudtrail:us-east-2:123456789012:channel/01234567890`

HTTP Status Code: 400

ConflictException

This exception is thrown when the specified resource is not ready for an operation. This can occur when you try to run an operation on a resource before CloudTrail has time to fully load the resource, or because another operation is modifying the resource. If this exception occurs, wait a few minutes, and then try the operation again.

HTTP Status Code: 400

InsufficientDependencyServiceAccessPermissionException

This exception is thrown when the IAM identity that is used to create the organization resource lacks one or more required permissions for creating an organization resource in a required service.

HTTP Status Code: 400

InvalidHomeRegionException

This exception is thrown when an operation is called on a trail from a Region other than the Region in which the trail was created.

HTTP Status Code: 400

InvalidTrailNameException

This exception is thrown when the provided trail name is not valid. Trail names must meet the following requirements:

- Contain only ASCII letters (a-z, A-Z), numbers (0-9), periods (.), underscores (_), or dashes (-)
- Start with a letter or number, and end with a letter or number
- Be between 3 and 128 characters
- Have no adjacent periods, underscores or dashes. Names like `my-__namespace` and `my--namespace` are not valid.
- Not be in IP address format (for example, 192.168.5.4)

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

NotOrganizationMasterAccountException

This exception is thrown when the AWS account making the request to create or update an organization trail or event data store is not the management account for an organization in AWS Organizations. For more information, see [Prepare For Creating a Trail For Your Organization](#) or [Organization event data stores](#).

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

ThrottlingException

This exception is thrown when the request rate exceeds the limit.

HTTP Status Code: 400

TrailNotFoundException

This exception is thrown when the trail with the given name is not found.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeregisterOrganizationDelegatedAdmin

Removes CloudTrail delegated administrator permissions from a member account in an organization.

Request Syntax

```
{  
  "DelegatedAdminAccountId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

DelegatedAdminAccountId

A delegated administrator account ID. This is a member account in an organization that is currently designated as a delegated administrator.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 16.

Pattern: `\d+`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccountNotFoundException

This exception is thrown when the specified account is not found or not part of an organization.

HTTP Status Code: 400

AccountNotRegisteredException

This exception is thrown when the specified account is not registered as the CloudTrail delegated administrator.

HTTP Status Code: 400

CloudTrailAccessNotEnabledException

This exception is thrown when trusted access has not been enabled between AWS CloudTrail and AWS Organizations. For more information, see [How to enable or disable trusted access](#) in the *AWS Organizations User Guide* and [Prepare For Creating a Trail For Your Organization](#) in the *AWS CloudTrail User Guide*.

HTTP Status Code: 400

ConflictException

This exception is thrown when the specified resource is not ready for an operation. This can occur when you try to run an operation on a resource before CloudTrail has time to fully load the resource, or because another operation is modifying the resource. If this exception occurs, wait a few minutes, and then try the operation again.

HTTP Status Code: 400

InsufficientDependencyServiceAccessPermissionException

This exception is thrown when the IAM identity that is used to create the organization resource lacks one or more required permissions for creating an organization resource in a required service.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

NotOrganizationManagementAccountException

This exception is thrown when the account making the request is not the organization's management account.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

OrganizationNotInAllFeaturesModeException

This exception is thrown when AWS Organizations is not configured to support all features. All features must be enabled in Organizations to support creating an organization trail or event data store.

HTTP Status Code: 400

OrganizationsNotInUseException

This exception is thrown when the request is made from an AWS account that is not a member of an organization. To make this request, sign in using the credentials of an account that belongs to an organization.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeQuery

Returns metadata about a query, including query run time in milliseconds, number of events scanned and matched, and query status. If the query results were delivered to an S3 bucket, the response also provides the S3 URI and the delivery status.

You must specify either a `QueryID` or a `QueryAlias`. Specifying the `QueryAlias` parameter returns information about the last query run for the alias.

Request Syntax

```
{
  "EventDataStore": "string",
  "QueryAlias": "string",
  "QueryId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

EventDataStore

This parameter has been deprecated.

The ARN (or the ID suffix of the ARN) of an event data store on which the specified query was run.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: No

QueryAlias

The alias that identifies a query template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^[a-zA-Z][a-zA-Z0-9._\-]*$`

Required: No

QueryId

The query ID.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[a-f0-9\-]+$`

Required: No

Response Syntax

```
{
  "DeliveryS3Uri": "string",
  "DeliveryStatus": "string",
  "ErrorMessage": "string",
  "QueryId": "string",
  "QueryStatistics": {
    "BytesScanned": number,
    "CreationTime": number,
    "EventsMatched": number,
    "EventsScanned": number,
    "ExecutionTimeInMillis": number
  },
  "QueryStatus": "string",
  "QueryString": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DeliveryS3Uri

The URI for the S3 bucket where CloudTrail delivered query results, if applicable.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `s3://[a-z0-9][\.\-a-z0-9]{1,61}[a-z0-9](/.*)?`

DeliveryStatus

The delivery status.

Type: String

Valid Values: SUCCESS | FAILED | FAILED_SIGNING_FILE | PENDING | RESOURCE_NOT_FOUND | ACCESS_DENIED | ACCESS_DENIED_SIGNING_FILE | CANCELLED | UNKNOWN

ErrorMessage

The error message returned if a query failed.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1000.

Pattern: `.*`

QueryId

The ID of the query.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[a-f0-9\-\-]+$`

QueryStatistics

Metadata about a query, including the number of events that were matched, the total number of events scanned, the query run time in milliseconds, and the query's creation time.

Type: [QueryStatisticsForDescribeQuery](#) object

QueryStatus

The status of a query. Values for QueryStatus include QUEUED, RUNNING, FINISHED, FAILED, TIMED_OUT, or CANCELLED

Type: String

Valid Values: QUEUED | RUNNING | FINISHED | FAILED | CANCELLED | TIMED_OUT

QueryString

The SQL code of a query.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10000.

Pattern: (?s).*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EventDataStoreARNInvalidException

The specified event data store ARN is not valid or does not map to an event data store in your account.

HTTP Status Code: 400

EventDataStoreNotFoundException

The specified event data store was not found.

HTTP Status Code: 400

InactiveEventDataStoreException

The event data store is inactive.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

QueryIdNotFoundException

The query ID does not exist or does not map to a query.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeTrails

Retrieves settings for one or more trails associated with the current Region for your account.

Request Syntax

```
{
  "includeShadowTrails": boolean,
  "trailNameList": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[includeShadowTrails](#)

Specifies whether to include shadow trails in the response. A shadow trail is the replication in a Region of a trail that was created in a different Region, or in the case of an organization trail, the replication of an organization trail in member accounts. If you do not include shadow trails, organization trails in a member account and Region replication trails will not be returned. The default is true.

Type: Boolean

Required: No

[trailNameList](#)

Specifies a list of trail names, trail ARNs, or both, of the trails to describe. The format of a trail ARN is:

```
arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail
```

If an empty list is specified, information for the trail in the current Region is returned.

- If an empty list is specified and `IncludeShadowTrails` is false, then information for all trails in the current Region is returned.
- If an empty list is specified and `IncludeShadowTrails` is null or true, then information for all trails in the current Region and any associated shadow trails in other Regions is returned.

Note

If one or more trail names are specified, information is returned only if the names match the names of trails belonging only to the current Region and current account. To return information about a trail in another Region, you must specify its trail ARN.

Type: Array of strings

Required: No

Response Syntax

```
{
  "trailList": [
    {
      "CloudWatchLogsLogGroupArn": "string",
      "CloudWatchLogsRoleArn": "string",
      "HasCustomEventSelectors": boolean,
      "HasInsightSelectors": boolean,
      "HomeRegion": "string",
      "IncludeGlobalServiceEvents": boolean,
      "IsMultiRegionTrail": boolean,
      "IsOrganizationTrail": boolean,
      "KmsKeyId": "string",
      "LogFileValidationEnabled": boolean,
      "Name": "string",
      "S3BucketName": "string",
      "S3KeyPrefix": "string",
      "SnsTopicARN": "string",
      "SnsTopicName": "string",
      "TrailARN": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[trailList](#)

The list of trail objects. Trail objects with string values are only returned if values for the objects exist in a trail's configuration. For example, `SNSTopicName` and `SNSTopicARN` are only returned in results if a trail is configured to send SNS notifications. Similarly, `KMSKeyId` only appears in results if a trail's log files are encrypted with AWS KMS customer managed keys.

Type: Array of [Trail](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

CloudTrailARNInvalidException

This exception is thrown when an operation is called with an ARN that is not valid.

The following is the format of a trail ARN: `arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail`

The following is the format of an event data store ARN: `arn:aws:cloudtrail:us-east-2:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE`

The following is the format of a channel ARN: `arn:aws:cloudtrail:us-east-2:123456789012:channel/01234567890`

HTTP Status Code: 400

InvalidTrailNameException

This exception is thrown when the provided trail name is not valid. Trail names must meet the following requirements:

- Contain only ASCII letters (a-z, A-Z), numbers (0-9), periods (.), underscores (_), or dashes (-)
- Start with a letter or number, and end with a letter or number
- Be between 3 and 128 characters
- Have no adjacent periods, underscores or dashes. Names like `my-__namespace` and `my--namespace` are not valid.
- Not be in IP address format (for example, 192.168.5.4)

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisableFederation

Disables Lake query federation on the specified event data store. When you disable federation, CloudTrail disables the integration with AWS Glue, AWS Lake Formation, and Amazon Athena. After disabling Lake query federation, you can no longer query your event data in Amazon Athena.

No CloudTrail Lake data is deleted when you disable federation and you can continue to run queries in CloudTrail Lake.

Request Syntax

```
{
  "EventDataStore": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[EventDataStore](#)

The ARN (or ID suffix of the ARN) of the event data store for which you want to disable Lake query federation.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: Yes

Response Syntax

```
{
  "EventDataStoreArn": "string",
  "FederationStatus": "string"
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

EventDataStoreArn

The ARN of the event data store for which you disabled Lake query federation.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

FederationStatus

The federation status.

Type: String

Valid Values: ENABLING | ENABLED | DISABLING | DISABLED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

CloudTrailAccessNotEnabledException

This exception is thrown when trusted access has not been enabled between AWS CloudTrail and AWS Organizations. For more information, see [How to enable or disable trusted access](#) in the *AWS Organizations User Guide* and [Prepare For Creating a Trail For Your Organization](#) in the *AWS CloudTrail User Guide*.

HTTP Status Code: 400

ConcurrentModificationException

You are trying to update a resource when another request is in progress. Allow sufficient wait time for the previous request to complete, then retry your request.

HTTP Status Code: 400

EventDataStoreARNInvalidException

The specified event data store ARN is not valid or does not map to an event data store in your account.

HTTP Status Code: 400

EventDataStoreNotFoundException

The specified event data store was not found.

HTTP Status Code: 400

InactiveEventDataStoreException

The event data store is inactive.

HTTP Status Code: 400

InsufficientDependencyServiceAccessPermissionException

This exception is thrown when the IAM identity that is used to create the organization resource lacks one or more required permissions for creating an organization resource in a required service.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

NotOrganizationMasterAccountException

This exception is thrown when the AWS account making the request to create or update an organization trail or event data store is not the management account for an organization in AWS Organizations. For more information, see [Prepare For Creating a Trail For Your Organization](#) or [Organization event data stores](#).

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

OrganizationNotInAllFeaturesModeException

This exception is thrown when AWS Organizations is not configured to support all features. All features must be enabled in Organizations to support creating an organization trail or event data store.

HTTP Status Code: 400

OrganizationsNotInUseException

This exception is thrown when the request is made from an AWS account that is not a member of an organization. To make this request, sign in using the credentials of an account that belongs to an organization.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

Examples

Example

The following example shows how to disable CloudTrail Lake federation on an event data store.

```
{
```

```
"EventDataStore": "arn:aws:cloudtrail:us-east-2:123456789012:eventdatastore/EXAMPLE-  
f852-4e8f-8bd1-bcf6cEXAMPLE"  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

EnableFederation

Enables Lake query federation on the specified event data store. Federating an event data store lets you view the metadata associated with the event data store in the AWS Glue [Data Catalog](#) and run SQL queries against your event data using Amazon Athena. The table metadata stored in the AWS Glue Data Catalog lets the Athena query engine know how to find, read, and process the data that you want to query.

When you enable Lake query federation, CloudTrail creates a managed database named `aws:cloudtrail` (if the database doesn't already exist) and a managed federated table in the AWS Glue Data Catalog. The event data store ID is used for the table name. CloudTrail registers the role ARN and event data store in [AWS Lake Formation](#), the service responsible for allowing fine-grained access control of the federated resources in the AWS Glue Data Catalog.

For more information about Lake query federation, see [Federate an event data store](#).

Request Syntax

```
{
  "EventDataStore": "string",
  "FederationRoleArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[EventDataStore](#)

The ARN (or ID suffix of the ARN) of the event data store for which you want to enable Lake query federation.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: Yes

FederationRoleArn

The ARN of the federation role to use for the event data store. AWS services like AWS Lake Formation use this federation role to access data for the federated event data store. The federation role must exist in your account and provide the [required minimum permissions](#).

Type: String

Length Constraints: Minimum length of 3. Maximum length of 125.

Pattern: `^[a-zA-Z0-9._/\-:@=\+,\.]+$`

Required: Yes

Response Syntax

```
{
  "EventDataStoreArn": "string",
  "FederationRoleArn": "string",
  "FederationStatus": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

EventDataStoreArn

The ARN of the event data store for which you enabled Lake query federation.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

FederationRoleArn

The ARN of the federation role.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 125.

Pattern: `^[a-zA-Z0-9._/\-:@=\+,\.]+$`

FederationStatus

The federation status.

Type: String

Valid Values: ENABLING | ENABLED | DISABLING | DISABLED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

CloudTrailAccessNotEnabledException

This exception is thrown when trusted access has not been enabled between AWS CloudTrail and AWS Organizations. For more information, see [How to enable or disable trusted access](#) in the *AWS Organizations User Guide* and [Prepare For Creating a Trail For Your Organization](#) in the *AWS CloudTrail User Guide*.

HTTP Status Code: 400

ConcurrentModificationException

You are trying to update a resource when another request is in progress. Allow sufficient wait time for the previous request to complete, then retry your request.

HTTP Status Code: 400

EventDataStoreARNInvalidException

The specified event data store ARN is not valid or does not map to an event data store in your account.

HTTP Status Code: 400

EventDataStoreFederationEnabledException

You cannot delete the event data store because Lake query federation is enabled. To delete the event data store, run the `DisableFederation` operation to disable Lake query federation on the event data store.

HTTP Status Code: 400

EventDataStoreNotFoundException

The specified event data store was not found.

HTTP Status Code: 400

InactiveEventDataStoreException

The event data store is inactive.

HTTP Status Code: 400

InsufficientDependencyServiceAccessPermissionException

This exception is thrown when the IAM identity that is used to create the organization resource lacks one or more required permissions for creating an organization resource in a required service.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

NotOrganizationMasterAccountException

This exception is thrown when the AWS account making the request to create or update an organization trail or event data store is not the management account for an organization

in AWS Organizations. For more information, see [Prepare For Creating a Trail For Your Organization](#) or [Organization event data stores](#).

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

OrganizationNotInAllFeaturesModeException

This exception is thrown when AWS Organizations is not configured to support all features. All features must be enabled in Organizations to support creating an organization trail or event data store.

HTTP Status Code: 400

OrganizationsNotInUseException

This exception is thrown when the request is made from an AWS account that is not a member of an organization. To make this request, sign in using the credentials of an account that belongs to an organization.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

Examples

Example

The following example shows how to enable CloudTrail Lake federation on an event data store.

```
{
  "EventDataStore": "arn:aws:cloudtrail:us-east-2:123456789012:eventdatastore/EXAMPLE-
f852-4e8f-8bd1-bcf6cEXAMPLE",
  "FederationRoleArn": "arn:aws:iam::123456789012:role/FederationRole"
```

```
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetChannel

Returns information about a specific channel.

Request Syntax

```
{
  "Channel": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Channel

The ARN or UUID of a channel.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: Yes

Response Syntax

```
{
  "ChannelArn": "string",
  "Destinations": [
    {
      "Location": "string",
      "Type": "string"
    }
  ],
  "IngestionStatus": {
    "LatestIngestionAttemptEventID": "string",
```

```

    "LatestIngestionAttemptTime": number,
    "LatestIngestionErrorCode": "string",
    "LatestIngestionSuccessEventID": "string",
    "LatestIngestionSuccessTime": number
  },
  "Name": "string",
  "Source": "string",
  "SourceConfig": {
    "AdvancedEventSelectors": [
      {
        "FieldSelectors": [
          {
            "EndsWith": [ "string " ],
            "Equals": [ "string " ],
            "Field": "string",
            "NotEndsWith": [ "string " ],
            "NotEquals": [ "string " ],
            "NotStartsWith": [ "string " ],
            "StartsWith": [ "string " ]
          }
        ],
        "Name": "string"
      }
    ],
    "ApplyToAllRegions": boolean
  }
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ChannelArn

The ARN of an channel returned by a `GetChannel` request.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Destinations

The destinations for the channel. For channels created for integrations, the destinations are the event data stores that log events arriving through the channel. For service-linked channels, the destination is the AWS service that created the service-linked channel to receive events.

Type: Array of [Destination](#) objects

Array Members: Minimum number of 1 item. Maximum number of 200 items.

IngestionStatus

A table showing information about the most recent successful and failed attempts to ingest events.

Type: [IngestionStatus](#) object

Name

The name of the CloudTrail channel. For service-linked channels, the name is `aws-service-channel/service-name/custom-suffix` where `service-name` represents the name of the AWS service that created the channel and `custom-suffix` represents the suffix generated by the AWS service.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9._\ -]+$`

Source

The source for the CloudTrail channel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `.*`

SourceConfig

Provides information about the advanced event selectors configured for the channel, and whether the channel applies to all Regions or a single Region.

Type: [SourceConfig](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ChannelARNInvalidException

This exception is thrown when the specified value of ChannelARN is not valid.

HTTP Status Code: 400

ChannelNotFoundException

This exception is thrown when CloudTrail cannot find the specified channel.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetEventDataStore

Returns information about an event data store specified as either an ARN or the ID portion of the ARN.

Request Syntax

```
{
  "EventDataStore": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

EventDataStore

The ARN (or ID suffix of the ARN) of the event data store about which you want information.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: Yes

Response Syntax

```
{
  "AdvancedEventSelectors": [
    {
      "FieldSelectors": [
        {
          "EndsWith": [ "string" ],
          "Equals": [ "string" ],
          "Field": "string",
          "NotEndsWith": [ "string" ],
        }
      ]
    }
  ]
}
```

```

        "NotEquals": [ "string" ],
        "NotStartsWith": [ "string" ],
        "StartsWith": [ "string" ]
    }
],
    "Name": "string"
}
],
"BillingMode": "string",
"CreatedTimestamp": number,
"EventDataStoreArn": "string",
"FederationRoleArn": "string",
"FederationStatus": "string",
"KmsKeyId": "string",
"MultiRegionEnabled": boolean,
"Name": "string",
"OrganizationEnabled": boolean,
"PartitionKeys": [
    {
        "Name": "string",
        "Type": "string"
    }
],
"RetentionPeriod": number,
"Status": "string",
"TerminationProtectionEnabled": boolean,
"UpdatedTimestamp": number
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AdvancedEventSelectors

The advanced event selectors used to select events for the data store.

Type: Array of [AdvancedEventSelector](#) objects

BillingMode

The billing mode for the event data store.

Type: String

Valid Values: EXTENDABLE_RETENTION_PRICING | FIXED_RETENTION_PRICING

CreatedTimestamp

The timestamp of the event data store's creation.

Type: Timestamp

EventDataStoreArn

The event data store Amazon Resource Number (ARN).

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

FederationRoleArn

If Lake query federation is enabled, provides the ARN of the federation role used to access the resources for the federated event data store.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 125.

Pattern: `^[a-zA-Z0-9._/\-:@=\+,\.]+$`

FederationStatus

Indicates the [Lake query federation](#) status. The status is ENABLED if Lake query federation is enabled, or DISABLED if Lake query federation is disabled. You cannot delete an event data store if the FederationStatus is ENABLED.

Type: String

Valid Values: ENABLING | ENABLED | DISABLING | DISABLED

KmsKeyId

Specifies the AWS KMS key ID that encrypts the events delivered by CloudTrail. The value is a fully specified ARN to a AWS KMS key in the following format.

```
arn:aws:kms:us-east-2:123456789012:key/12345678-1234-1234-1234-123456789012
```

Type: String

Length Constraints: Minimum length of 1. Maximum length of 350.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

MultiRegionEnabled

Indicates whether the event data store includes events from all Regions, or only from the Region in which it was created.

Type: Boolean

Name

The name of the event data store.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9._\-]+$`

OrganizationEnabled

Indicates whether an event data store is collecting logged events for an organization in AWS Organizations.

Type: Boolean

PartitionKeys

The partition keys for the event data store. To improve query performance and efficiency, CloudTrail Lake organizes event data into partitions based on values derived from partition keys.

Type: Array of [PartitionKey](#) objects

Array Members: Maximum number of 2 items.

RetentionPeriod

The retention period of the event data store, in days.

Type: Integer

Valid Range: Minimum value of 7. Maximum value of 3653.

Status

The status of an event data store.

Type: String

Valid Values: CREATED | ENABLED | PENDING_DELETION | STARTING_INGESTION | STOPPING_INGESTION | STOPPED_INGESTION

TerminationProtectionEnabled

Indicates that termination protection is enabled.

Type: Boolean

UpdatedTimestamp

Shows the time that an event data store was updated, if applicable. UpdatedTimestamp is always either the same or newer than the time shown in CreatedTimestamp.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EventDataStoreARNInvalidException

The specified event data store ARN is not valid or does not map to an event data store in your account.

HTTP Status Code: 400

EventDataStoreNotFoundException

The specified event data store was not found.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetEventSelectors

Describes the settings for the event selectors that you configured for your trail. The information returned for your event selectors includes the following:

- If your event selector includes read-only events, write-only events, or all events. This applies to both management events and data events.
- If your event selector includes management events.
- If your event selector includes data events, the resources on which you are logging data events.

For more information about logging management and data events, see the following topics in the *AWS CloudTrail User Guide*:

- [Logging management events](#)
- [Logging data events](#)

Request Syntax

```
{  
  "TrailName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[TrailName](#)

Specifies the name of the trail or trail ARN. If you specify a trail name, the string must meet the following requirements:

- Contain only ASCII letters (a-z, A-Z), numbers (0-9), periods (.), underscores (_), or dashes (-)
- Start with a letter or number, and end with a letter or number
- Be between 3 and 128 characters
- Have no adjacent periods, underscores or dashes. Names like my-__namespace and my--namespace are not valid.

- Not be in IP address format (for example, 192.168.5.4)

If you specify a trail ARN, it must be in the format:

```
arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail
```

Type: String

Required: Yes

Response Syntax

```
{
  "AdvancedEventSelectors": [
    {
      "FieldSelectors": [
        {
          "EndsWith": [ "string" ],
          "Equals": [ "string" ],
          "Field": "string",
          "NotEndsWith": [ "string" ],
          "NotEquals": [ "string" ],
          "NotStartsWith": [ "string" ],
          "StartsWith": [ "string" ]
        }
      ],
      "Name": "string"
    }
  ],
  "EventSelectors": [
    {
      "DataResources": [
        {
          "Type": "string",
          "Values": [ "string" ]
        }
      ],
      "ExcludeManagementEventSources": [ "string" ],
      "IncludeManagementEvents": boolean,
      "ReadWriteType": "string"
    }
  ],
  "TrailARN": "string"
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AdvancedEventSelectors

The advanced event selectors that are configured for the trail.

Type: Array of [AdvancedEventSelector](#) objects

EventSelectors

The event selectors that are configured for the trail.

Type: Array of [EventSelector](#) objects

TrailARN

The specified trail ARN that has the event selectors.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

CloudTrailARNInvalidException

This exception is thrown when an operation is called with an ARN that is not valid.

The following is the format of a trail ARN: `arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail`

The following is the format of an event data store ARN: `arn:aws:cloudtrail:us-east-2:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE`

The following is the format of a channel ARN: `arn:aws:cloudtrail:us-east-2:123456789012:channel/01234567890`

HTTP Status Code: 400

InvalidTrailNameException

This exception is thrown when the provided trail name is not valid. Trail names must meet the following requirements:

- Contain only ASCII letters (a-z, A-Z), numbers (0-9), periods (.), underscores (_), or dashes (-)
- Start with a letter or number, and end with a letter or number
- Be between 3 and 128 characters
- Have no adjacent periods, underscores or dashes. Names like my-__namespace and my--namespace are not valid.
- Not be in IP address format (for example, 192.168.5.4)

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

TrailNotFoundException

This exception is thrown when the trail with the given name is not found.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetImport

Returns information about a specific import.

Request Syntax

```
{  
  "ImportId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ImportId

The ID for the import.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[a-f0-9\ -]+$`

Required: Yes

Response Syntax

```
{  
  "CreatedTimestamp": number,  
  "Destinations": [ "string" ],  
  "EndEventTime": number,  
  "ImportId": "string",  
  "ImportSource": {  
    "S3": {  
      "S3BucketAccessRoleArn": "string",  
      "S3BucketRegion": "string",  
      "S3LocationUri": "string"  
    }  
  }  
}
```

```
    }  
  },  
  "ImportStatistics": {  
    "EventsCompleted": number,  
    "FailedEntries": number,  
    "FilesCompleted": number,  
    "PrefixesCompleted": number,  
    "PrefixesFound": number  
  },  
  "ImportStatus": "string",  
  "StartEventTime": number,  
  "UpdatedTimestamp": number  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CreatedTimestamp

The timestamp of the import's creation.

Type: Timestamp

Destinations

The ARN of the destination event data store.

Type: Array of strings

Array Members: Fixed number of 1 item.

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

EndEventTime

Used with `StartEventTime` to bound a `StartImport` request, and limit imported trail events to only those events logged within a specified time period.

Type: Timestamp

ImportId

The ID of the import.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[a-f0-9\-\-]+$`

ImportSource

The source S3 bucket.

Type: [ImportSource](#) object

ImportStatistics

Provides statistics for the import. CloudTrail does not update import statistics in real-time. Returned values for parameters such as `EventsCompleted` may be lower than the actual value, because CloudTrail updates statistics incrementally over the course of the import.

Type: [ImportStatistics](#) object

ImportStatus

The status of the import.

Type: String

Valid Values: `INITIALIZING | IN_PROGRESS | FAILED | STOPPED | COMPLETED`

StartEventTime

Used with `EndEventTime` to bound a `StartImport` request, and limit imported trail events to only those events logged within a specified time period.

Type: Timestamp

UpdatedTimestamp

The timestamp of when the import was updated.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ImportNotFoundException

The specified import was not found.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

GetInsightSelectors

Describes the settings for the Insights event selectors that you configured for your trail or event data store. `GetInsightSelectors` shows if CloudTrail Insights event logging is enabled on the trail or event data store, and if it is, which Insights types are enabled. If you run `GetInsightSelectors` on a trail or event data store that does not have Insights events enabled, the operation throws the exception `InsightNotEnabledException`.

Specify either the `EventDataStore` parameter to get Insights event selectors for an event data store, or the `TrailName` parameter to get Insights event selectors for a trail. You cannot specify these parameters together.

For more information, see [Logging CloudTrail Insights events](#) in the *AWS CloudTrail User Guide*.

Request Syntax

```
{
  "EventDataStore": "string",
  "TrailName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[EventDataStore](#)

Specifies the ARN (or ID suffix of the ARN) of the event data store for which you want to get Insights selectors.

You cannot use this parameter with the `TrailName` parameter.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: No

TrailName

Specifies the name of the trail or trail ARN. If you specify a trail name, the string must meet the following requirements:

- Contain only ASCII letters (a-z, A-Z), numbers (0-9), periods (.), underscores (_), or dashes (-)
- Start with a letter or number, and end with a letter or number
- Be between 3 and 128 characters
- Have no adjacent periods, underscores or dashes. Names like my-__namespace and my--namespace are not valid.
- Not be in IP address format (for example, 192.168.5.4)

If you specify a trail ARN, it must be in the format:

```
arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail
```

You cannot use this parameter with the `EventDataStore` parameter.

Type: String

Required: No

Response Syntax

```
{
  "EventDataStoreArn": "string",
  "InsightsDestination": "string",
  "InsightSelectors": [
    {
      "InsightType": "string"
    }
  ],
  "TrailARN": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

EventDataStoreArn

The ARN of the source event data store that enabled Insights events.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

InsightsDestination

The ARN of the destination event data store that logs Insights events.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

InsightSelectors

A JSON string that contains the Insight types you want to log on a trail or event data store. `ApiErrorRateInsight` and `ApiCallRateInsight` are supported as Insights types.

Type: Array of [InsightSelector](#) objects

TrailARN

The Amazon Resource Name (ARN) of a trail for which you want to get Insights selectors.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

CloudTrailARNInvalidException

This exception is thrown when an operation is called with an ARN that is not valid.

The following is the format of a trail ARN: `arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail`

The following is the format of an event data store ARN: `arn:aws:cloudtrail:us-east-2:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE`

The following is the format of a channel ARN: `arn:aws:cloudtrail:us-east-2:123456789012:channel/01234567890`

HTTP Status Code: 400

InsightNotEnabledException

If you run `GetInsightSelectors` on a trail or event data store that does not have Insights events enabled, the operation throws the exception `InsightNotEnabledException`.

HTTP Status Code: 400

InvalidParameterCombinationException

This exception is thrown when the combination of parameters provided is not valid.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

InvalidTrailNameException

This exception is thrown when the provided trail name is not valid. Trail names must meet the following requirements:

- Contain only ASCII letters (a-z, A-Z), numbers (0-9), periods (.), underscores (_), or dashes (-)
- Start with a letter or number, and end with a letter or number
- Be between 3 and 128 characters
- Have no adjacent periods, underscores or dashes. Names like `my-__namespace` and `my--namespace` are not valid.
- Not be in IP address format (for example, 192.168.5.4)

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

ThrottlingException

This exception is thrown when the request rate exceeds the limit.

HTTP Status Code: 400

TrailNotFoundException

This exception is thrown when the trail with the given name is not found.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetQueryResults

Gets event data results of a query. You must specify the QueryID value returned by the StartQuery operation.

Request Syntax

```
{
  "EventDataStore": "string",
  "MaxQueryResults": number,
  "NextToken": "string",
  "QueryId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

EventDataStore

This parameter has been deprecated.

The ARN (or ID suffix of the ARN) of the event data store against which the query was run.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: No

MaxQueryResults

The maximum number of query results to display on a single page.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

NextToken

A token you can use to get the next page of query results.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1000.

Pattern: .*

Required: No

QueryId

The ID of the query for which you want to get results.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[a-f0-9\-]+\$

Required: Yes

Response Syntax

```
{
  "ErrorMessage": "string",
  "NextToken": "string",
  "QueryResultRows": [
    [
      {
        "string" : "string"
      }
    ]
  ],
  "QueryStatistics": {
    "BytesScanned": number,
    "ResultsCount": number,
    "TotalResultsCount": number
  },
  "QueryStatus": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ErrorMessage

The error message returned if a query failed.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1000.

Pattern: .*

NextToken

A token you can use to get the next page of query results.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1000.

Pattern: .*

QueryResultRows

Contains the individual event results of the query.

Type: Array of arrays of string to string maps

QueryStatistics

Shows the count of query results.

Type: [QueryStatistics](#) object

QueryStatus

The status of the query. Values include QUEUED, RUNNING, FINISHED, FAILED, TIMED_OUT, or CANCELLED.

Type: String

Valid Values: QUEUED | RUNNING | FINISHED | FAILED | CANCELLED | TIMED_OUT

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EventDataStoreARNInvalidException

The specified event data store ARN is not valid or does not map to an event data store in your account.

HTTP Status Code: 400

EventDataStoreNotFoundException

The specified event data store was not found.

HTTP Status Code: 400

InactiveEventDataStoreException

The event data store is inactive.

HTTP Status Code: 400

InsufficientEncryptionPolicyException

This exception is thrown when the policy on the S3 bucket or AWS KMS key does not have sufficient permissions for the operation.

HTTP Status Code: 400

InvalidMaxResultsException

This exception is thrown if the limit specified is not valid.

HTTP Status Code: 400

InvalidNextTokenException

A token that is not valid, or a token that was previously used in a request with different parameters. This exception is thrown if the token is not valid.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

QueryIdNotFoundException

The query ID does not exist or does not map to a query.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetResourcePolicy

Retrieves the JSON text of the resource-based policy document attached to the CloudTrail channel.

Request Syntax

```
{  
  "ResourceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ResourceArn

The Amazon Resource Name (ARN) of the CloudTrail channel attached to the resource-based policy. The following is the format of a resource ARN: `arn:aws:cloudtrail:us-east-2:123456789012:channel/MyChannel`.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: Yes

Response Syntax

```
{  
  "ResourceArn": "string",  
  "ResourcePolicy": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ResourceArn

The Amazon Resource Name (ARN) of the CloudTrail channel attached to resource-based policy.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

ResourcePolicy

A JSON-formatted string that contains the resource-based policy attached to the CloudTrail channel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8192.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

ResourceARNNotValidException

This exception is thrown when the provided resource does not exist, or the ARN format of the resource is not valid. The following is the valid format for a resource ARN:
`arn:aws:cloudtrail:us-east-2:123456789012:channel/MyChannel.`

HTTP Status Code: 400

ResourceNotFoundException

This exception is thrown when the specified resource is not found.

HTTP Status Code: 400

ResourcePolicyNotFoundException

This exception is thrown when the specified resource policy is not found.

HTTP Status Code: 400

ResourceTypeNotSupportedException

This exception is thrown when the specified resource type is not supported by CloudTrail.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTrail

Returns settings information for a specified trail.

Request Syntax

```
{
  "Name": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

The name or the Amazon Resource Name (ARN) of the trail for which you want to retrieve settings information.

Type: String

Required: Yes

Response Syntax

```
{
  "Trail": {
    "CloudWatchLogsLogGroupArn": "string",
    "CloudWatchLogsRoleArn": "string",
    "HasCustomEventSelectors": boolean,
    "HasInsightSelectors": boolean,
    "HomeRegion": "string",
    "IncludeGlobalServiceEvents": boolean,
    "IsMultiRegionTrail": boolean,
    "IsOrganizationTrail": boolean,
    "KmsKeyId": "string",
    "LogFileValidationEnabled": boolean,
    "Name": "string",
    "S3BucketName": "string",
  }
}
```



```
"S3KeyPrefix": "string",  
"SnsTopicARN": "string",  
"SnsTopicName": "string",  
"TrailARN": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Trail

The settings for a trail.

Type: [Trail](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

CloudTrailARNInvalidException

This exception is thrown when an operation is called with an ARN that is not valid.

The following is the format of a trail ARN: `arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail`

The following is the format of an event data store ARN: `arn:aws:cloudtrail:us-east-2:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE`

The following is the format of a channel ARN: `arn:aws:cloudtrail:us-east-2:123456789012:channel/01234567890`

HTTP Status Code: 400

InvalidTrailNameException

This exception is thrown when the provided trail name is not valid. Trail names must meet the following requirements:

- Contain only ASCII letters (a-z, A-Z), numbers (0-9), periods (.), underscores (_), or dashes (-)
- Start with a letter or number, and end with a letter or number
- Be between 3 and 128 characters
- Have no adjacent periods, underscores or dashes. Names like my-namespace and my--namespace are not valid.
- Not be in IP address format (for example, 192.168.5.4)

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

TrailNotFoundException

This exception is thrown when the trail with the given name is not found.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTrailStatus

Returns a JSON-formatted list of information about the specified trail. Fields include information on delivery errors, Amazon SNS and Amazon S3 errors, and start and stop logging times for each trail. This operation returns trail status from a single Region. To return trail status from all Regions, you must call the operation on each Region.

Request Syntax

```
{  
  "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

Specifies the name or the CloudTrail ARN of the trail for which you are requesting status. To get the status of a shadow trail (a replication of the trail in another Region), you must specify its ARN. The following is the format of a trail ARN.

```
arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail
```

Type: String

Required: Yes

Response Syntax

```
{  
  "IsLogging": boolean,  
  "LatestCloudWatchLogsDeliveryError": "string",  
  "LatestCloudWatchLogsDeliveryTime": number,  
  "LatestDeliveryAttemptSucceeded": "string",  
  "LatestDeliveryAttemptTime": "string",
```

```
"LatestDeliveryError": "string",
"LatestDeliveryTime": number,
"LatestDigestDeliveryError": "string",
"LatestDigestDeliveryTime": number,
"LatestNotificationAttemptSucceeded": "string",
"LatestNotificationAttemptTime": "string",
"LatestNotificationError": "string",
"LatestNotificationTime": number,
"StartLoggingTime": number,
"StopLoggingTime": number,
"TimeLoggingStarted": "string",
"TimeLoggingStopped": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

IsLogging

Whether the CloudTrail trail is currently logging AWS API calls.

Type: Boolean

LatestCloudWatchLogsDeliveryError

Displays any CloudWatch Logs error that CloudTrail encountered when attempting to deliver logs to CloudWatch Logs.

Type: String

LatestCloudWatchLogsDeliveryTime

Displays the most recent date and time when CloudTrail delivered logs to CloudWatch Logs.

Type: Timestamp

LatestDeliveryAttemptSucceeded

This field is no longer in use.

Type: String

LatestDeliveryAttemptTime

This field is no longer in use.

Type: String

LatestDeliveryError

Displays any Amazon S3 error that CloudTrail encountered when attempting to deliver log files to the designated bucket. For more information, see [Error Responses](#) in the Amazon S3 API Reference.

Note

This error occurs only when there is a problem with the destination S3 bucket, and does not occur for requests that time out. To resolve the issue, fix the [bucket policy](#) so that CloudTrail can write to the bucket; or create a new bucket and call `UpdateTrail` to specify the new bucket.

Type: String

LatestDeliveryTime

Specifies the date and time that CloudTrail last delivered log files to an account's Amazon S3 bucket.

Type: Timestamp

LatestDigestDeliveryError

Displays any Amazon S3 error that CloudTrail encountered when attempting to deliver a digest file to the designated bucket. For more information, see [Error Responses](#) in the Amazon S3 API Reference.

Note

This error occurs only when there is a problem with the destination S3 bucket, and does not occur for requests that time out. To resolve the issue, fix the [bucket policy](#) so that CloudTrail can write to the bucket; or create a new bucket and call `UpdateTrail` to specify the new bucket.

Type: String

LatestDigestDeliveryTime

Specifies the date and time that CloudTrail last delivered a digest file to an account's Amazon S3 bucket.

Type: Timestamp

LatestNotificationAttemptSucceeded

This field is no longer in use.

Type: String

LatestNotificationAttemptTime

This field is no longer in use.

Type: String

LatestNotificationError

Displays any Amazon SNS error that CloudTrail encountered when attempting to send a notification. For more information about Amazon SNS errors, see the [Amazon SNS Developer Guide](#).

Type: String

LatestNotificationTime

Specifies the date and time of the most recent Amazon SNS notification that CloudTrail has written a new log file to an account's Amazon S3 bucket.

Type: Timestamp

StartLoggingTime

Specifies the most recent date and time when CloudTrail started recording API calls for an AWS account.

Type: Timestamp

StopLoggingTime

Specifies the most recent date and time when CloudTrail stopped recording API calls for an AWS account.

Type: Timestamp

TimeLoggingStarted

This field is no longer in use.

Type: String

TimeLoggingStopped

This field is no longer in use.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

CloudTrailARNInvalidException

This exception is thrown when an operation is called with an ARN that is not valid.

The following is the format of a trail ARN: `arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail`

The following is the format of an event data store ARN: `arn:aws:cloudtrail:us-east-2:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE`

The following is the format of a channel ARN: `arn:aws:cloudtrail:us-east-2:123456789012:channel/01234567890`

HTTP Status Code: 400

InvalidTrailNameException

This exception is thrown when the provided trail name is not valid. Trail names must meet the following requirements:

- Contain only ASCII letters (a-z, A-Z), numbers (0-9), periods (.), underscores (_), or dashes (-)
- Start with a letter or number, and end with a letter or number
- Be between 3 and 128 characters
- Have no adjacent periods, underscores or dashes. Names like `my-__namespace` and `my--namespace` are not valid.

- Not be in IP address format (for example, 192.168.5.4)

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

TrailNotFoundException

This exception is thrown when the trail with the given name is not found.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListChannels

Lists the channels in the current account, and their source names.

Request Syntax

```
{  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[MaxResults](#)

The maximum number of CloudTrail channels to display on a single page.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

[NextToken](#)

The token to use to get the next page of results after a previous API call. This token must be passed in with the same parameters that were specified in the original call. For example, if the original call specified an AttributeKey of 'Username' with a value of 'root', the call with NextToken should include those same parameters.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1000.

Pattern: .*

Required: No

Response Syntax

```
{
  "Channels": [
    {
      "ChannelArn": "string",
      "Name": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Channels

The list of channels in the account.

Type: Array of [Channel](#) objects

NextToken

The token to use to get the next page of results after a previous API call.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1000.

Pattern: .*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidNextTokenException

A token that is not valid, or a token that was previously used in a request with different parameters. This exception is thrown if the token is not valid.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListEventDataStores

Returns information about all event data stores in the account, in the current Region.

Request Syntax

```
{  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The maximum number of event data stores to display on a single page.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

NextToken

A token you can use to get the next page of event data store results.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1000.

Pattern: .*

Required: No

Response Syntax

```
{
```

```

"EventDataStores": [
  {
    "AdvancedEventSelectors": [
      {
        "FieldSelectors": [
          {
            "EndsWith": [ "string" ],
            "Equals": [ "string" ],
            "Field": "string",
            "NotEndsWith": [ "string" ],
            "NotEquals": [ "string" ],
            "NotStartsWith": [ "string" ],
            "StartsWith": [ "string" ]
          }
        ],
        "Name": "string"
      }
    ],
    "CreatedTimestamp": number,
    "EventDataStoreArn": "string",
    "MultiRegionEnabled": boolean,
    "Name": "string",
    "OrganizationEnabled": boolean,
    "RetentionPeriod": number,
    "Status": "string",
    "TerminationProtectionEnabled": boolean,
    "UpdatedTimestamp": number
  }
],
"NextToken": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

EventDataStores

Contains information about event data stores in the account, in the current Region.

Type: Array of [EventDataStore](#) objects

NextToken

A token you can use to get the next page of results.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1000.

Pattern: .*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidMaxResultsException

This exception is thrown if the limit specified is not valid.

HTTP Status Code: 400

InvalidNextTokenException

A token that is not valid, or a token that was previously used in a request with different parameters. This exception is thrown if the token is not valid.

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListImportFailures

Returns a list of failures for the specified import.

Request Syntax

```
{
  "ImportId": "string",
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ImportId

The ID of the import.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[a-f0-9\-\-]+$`

Required: Yes

MaxResults

The maximum number of failures to display on a single page.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

NextToken

A token you can use to get the next page of import failures.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1000.

Pattern: .*

Required: No

Response Syntax

```
{
  "Failures": [
    {
      "ErrorMessage": "string",
      "ErrorType": "string",
      "LastUpdatedTime": number,
      "Location": "string",
      "Status": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Failures

Contains information about the import failures.

Type: Array of [ImportFailureListItem](#) objects

NextToken

A token you can use to get the next page of results.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1000.

Pattern: .*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidNextTokenException

A token that is not valid, or a token that was previously used in a request with different parameters. This exception is thrown if the token is not valid.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListImports

Returns information on all imports, or a select set of imports by `ImportStatus` or `Destination`.

Request Syntax

```
{
  "Destination": "string",
  "ImportStatus": "string",
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Destination

The ARN of the destination event data store.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: No

ImportStatus

The status of the import.

Type: String

Valid Values: `INITIALIZING` | `IN_PROGRESS` | `FAILED` | `STOPPED` | `COMPLETED`

Required: No

MaxResults

The maximum number of imports to display on a single page.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

NextToken

A token you can use to get the next page of import results.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1000.

Pattern: .*

Required: No

Response Syntax

```
{
  "Imports": [
    {
      "CreatedTimestamp": number,
      "Destinations": [ string ],
      "ImportId": string,
      "ImportStatus": string,
      "UpdatedTimestamp": number
    }
  ],
  "NextToken": string
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Imports

The list of returned imports.

Type: Array of [ImportsListItem](#) objects

NextToken

A token you can use to get the next page of import results.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1000.

Pattern: .*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EventDataStoreARNInvalidException

The specified event data store ARN is not valid or does not map to an event data store in your account.

HTTP Status Code: 400

InvalidNextTokenException

A token that is not valid, or a token that was previously used in a request with different parameters. This exception is thrown if the token is not valid.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListInsightsMetricData

Returns Insights metrics data for trails that have enabled Insights. The request must include the `EventSource`, `EventName`, and `InsightType` parameters.

If the `InsightType` is set to `ApiErrorRateInsight`, the request must also include the `ErrorCode` parameter.

The following are the available time periods for `ListInsightsMetricData`. Each cutoff is inclusive.

- Data points with a period of 60 seconds (1-minute) are available for 15 days.
- Data points with a period of 300 seconds (5-minute) are available for 63 days.
- Data points with a period of 3600 seconds (1 hour) are available for 90 days.

Access to the `ListInsightsMetricData` API operation is linked to the `cloudtrail:LookupEvents` action. To use this operation, you must have permissions to perform the `cloudtrail:LookupEvents` action.

Request Syntax

```
{
  "DataType": "string",
  "EndTime": number,
  "ErrorCode": "string",
  "EventName": "string",
  "EventSource": "string",
  "InsightType": "string",
  "MaxResults": number,
  "NextToken": "string",
  "Period": number,
  "StartTime": number
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Data Type

Type of datapoints to return. Valid values are `NonZeroData` and `FillWithZeros`. The default is `NonZeroData`.

Type: String

Valid Values: `FillWithZeros` | `NonZeroData`

Required: No

EndTime

Specifies, in UTC, the end time for time-series data. The value specified is exclusive; results include data points up to the specified time stamp.

The default is the time of request.

Type: Timestamp

Required: No

ErrorCode

Conditionally required if the `InsightType` parameter is set to `ApiErrorRateInsight`.

If returning metrics for the `ApiErrorRateInsight` Insights type, this is the error to retrieve data for. For example, `AccessDenied`.

Type: String

Length Constraints: Maximum length of 128.

Pattern: `^[\\w\\d\\s_.,\\-:\\[\\]]+\\$`

Required: No

EventName

The name of the event, typically the AWS API on which unusual levels of activity were recorded.

Type: String

Length Constraints: Maximum length of 128.

Pattern: `^[A-Za-z0-9_]+\\$`

Required: Yes

EventSource

The AWS service to which the request was made, such as `iam.amazonaws.com` or `s3.amazonaws.com`.

Type: String

Length Constraints: Maximum length of 256.

Pattern: `^[a-z0-9_-]+\.amazonaws.com$`

Required: Yes

InsightType

The type of CloudTrail Insights event, which is either `ApiCallRateInsight` or `ApiErrorRateInsight`. The `ApiCallRateInsight` Insights type analyzes write-only management API calls that are aggregated per minute against a baseline API call volume. The `ApiErrorRateInsight` Insights type analyzes management API calls that result in error codes.

Type: String

Valid Values: `ApiCallRateInsight` | `ApiErrorRateInsight`

Required: Yes

MaxResults

The maximum number of datapoints to return. Valid values are integers from 1 to 21600. The default value is 21600.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 21600.

Required: No

NextToken

Returned if all datapoints can't be returned in a single call. For example, due to reaching `MaxResults`.

Add this parameter to the request to continue retrieving results starting from the last evaluated point.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 5000.

Required: No

Period

Granularity of data to retrieve, in seconds. Valid values are 60, 300, and 3600. If you specify any other value, you will get an error. The default is 3600 seconds.

Type: Integer

Valid Range: Minimum value of 60. Maximum value of 3600.

Required: No

StartTime

Specifies, in UTC, the start time for time-series data. The value specified is inclusive; results include data points with the specified time stamp.

The default is 90 days before the time of request.

Type: Timestamp

Required: No

Response Syntax

```
{
  "ErrorCode": "string",
  "EventName": "string",
  "EventSource": "string",
  "InsightType": "string",
  "NextToken": "string",
  "Timestamps": [ number ],
  "Values": [ number ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ErrorCode

Only returned if `InsightType` parameter was set to `ApiErrorRateInsight`.

If returning metrics for the `ApiErrorRateInsight` Insights type, this is the error to retrieve data for. For example, `AccessDenied`.

Type: String

Length Constraints: Maximum length of 128.

Pattern: `^[\w\d\s_.,\-\: \[\]]+$`

EventName

The name of the event, typically the AWS API on which unusual levels of activity were recorded.

Type: String

Length Constraints: Maximum length of 128.

Pattern: `^[A-Za-z0-9_]+$`

EventSource

The AWS service to which the request was made, such as `iam.amazonaws.com` or `s3.amazonaws.com`.

Type: String

Length Constraints: Maximum length of 256.

Pattern: `^[a-z0-9_-]+\.amazonaws\.com$`

InsightType

The type of CloudTrail Insights event, which is either `ApiCallRateInsight` or `ApiErrorRateInsight`. The `ApiCallRateInsight` Insights type analyzes write-only management API calls that are aggregated per minute against a baseline API call volume. The

`ApiErrorRateInsight` Insights type analyzes management API calls that result in error codes.

Type: String

Valid Values: `ApiCallRateInsight` | `ApiErrorRateInsight`

NextToken

Only returned if the full results could not be returned in a single query. You can set the `NextToken` parameter in the next request to this value to continue retrieval.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 5000.

Timestamps

List of timestamps at intervals corresponding to the specified time period.

Type: Array of timestamps

Values

List of values representing the API call rate or error rate at each timestamp. The number of values is equal to the number of timestamps.

Type: Array of doubles

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

Examples

Example

The following example shows how to retrieve API call rate metric data for the CloudTrail `CreateTrail` API.

```
{
  "EventSource": "cloudtrail.amazonaws.com",
  "EventName": "CreateTrail",
  "InsightType": "ApiCallRateInsight"
}
```

Example

The following example shows how to retrieve API error rate metric data for receiving the error `TrailNotFoundException` when calling the CloudTrail `UpdateTrail` API.

```
{
  "EventSource": "cloudtrail.amazonaws.com",
  "EventName": "UpdateTrail",
  "InsightType": "ApiErrorRateInsight",
  "ErrorCode": "TrailNotFoundException"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPublicKeys

Returns all public keys whose private keys were used to sign the digest files within the specified time range. The public key is needed to validate digest files that were signed with its corresponding private key.

Note

CloudTrail uses different private and public key pairs per Region. Each digest file is signed with a private key unique to its Region. When you validate a digest file from a specific Region, you must look in the same Region for its corresponding public key.

Request Syntax

```
{
  "EndTime": number,
  "NextToken": "string",
  "StartTime": number
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

EndTime

Optionally specifies, in UTC, the end of the time range to look up public keys for CloudTrail digest files. If not specified, the current time is used.

Type: Timestamp

Required: No

NextToken

Reserved for future use.

Type: String

Required: No

StartTime

Optionally specifies, in UTC, the start of the time range to look up public keys for CloudTrail digest files. If not specified, the current time is used, and the current public key is returned.

Type: Timestamp

Required: No

Response Syntax

```
{
  "NextToken": "string",
  "PublicKeyList": [
    {
      "Fingerprint": "string",
      "ValidityEndTime": number,
      "ValidityStartTime": number,
      "Value": blob
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

Reserved for future use.

Type: String

PublicKeyList

Contains an array of PublicKey objects.

Note

The returned public keys may have validity time ranges that overlap.

Type: Array of [PublicKey](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidTimeRangeException

Occurs if the timestamp values are not valid. Either the start time occurs after the end time, or the time range is outside the range of possible values.

HTTP Status Code: 400

InvalidTokenException

Reserved for future use.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListQueries

Returns a list of queries and query statuses for the past seven days. You must specify an ARN value for `EventDataStore`. Optionally, to shorten the list of results, you can specify a time range, formatted as timestamps, by adding `StartTime` and `EndTime` parameters, and a `QueryStatus` value. Valid values for `QueryStatus` include `QUEUED`, `RUNNING`, `FINISHED`, `FAILED`, `TIMED_OUT`, or `CANCELLED`.

Request Syntax

```
{
  "EndTime": number,
  "EventDataStore": "string",
  "MaxResults": number,
  "NextToken": "string",
  "QueryStatus": "string",
  "StartTime": number
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

EndTime

Use with `StartTime` to bound a `ListQueries` request, and limit its results to only those queries run within a specified time period.

Type: Timestamp

Required: No

EventDataStore

The ARN (or the ID suffix of the ARN) of an event data store on which queries were run.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: Yes

MaxResults

The maximum number of queries to show on a page.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

NextToken

A token you can use to get the next page of results.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1000.

Pattern: `.*`

Required: No

QueryStatus

The status of queries that you want to return in results. Valid values for QueryStatus include QUEUED, RUNNING, FINISHED, FAILED, TIMED_OUT, or CANCELLED.

Type: String

Valid Values: QUEUED | RUNNING | FINISHED | FAILED | CANCELLED | TIMED_OUT

Required: No

StartTime

Use with EndTime to bound a ListQueries request, and limit its results to only those queries run within a specified time period.

Type: Timestamp

Required: No

Response Syntax

```
{
  "NextToken": "string",
  "Queries": [
    {
      "CreationTime": number,
      "QueryId": "string",
      "QueryStatus": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

A token you can use to get the next page of results.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1000.

Pattern: .*

Queries

Lists matching query results, and shows query ID, status, and creation time of each query.

Type: Array of [Query](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EventDataStoreARNInvalidException

The specified event data store ARN is not valid or does not map to an event data store in your account.

HTTP Status Code: 400

EventDataStoreNotFoundException

The specified event data store was not found.

HTTP Status Code: 400

InactiveEventDataStoreException

The event data store is inactive.

HTTP Status Code: 400

InvalidDateRangeException

A date range for the query was specified that is not valid. Be sure that the start time is chronologically before the end time. For more information about writing a query, see [Create or edit a query](#) in the *AWS CloudTrail User Guide*.

HTTP Status Code: 400

InvalidMaxResultsException

This exception is thrown if the limit specified is not valid.

HTTP Status Code: 400

InvalidNextTokenException

A token that is not valid, or a token that was previously used in a request with different parameters. This exception is thrown if the token is not valid.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

InvalidQueryStatusException

The query status is not valid for the operation.

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTags

Lists the tags for the specified trails, event data stores, or channels in the current Region.

Request Syntax

```
{  
  "NextToken": "string",  
  "ResourceIdList": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

NextToken

Reserved for future use.

Type: String

Required: No

ResourceIdList

Specifies a list of trail, event data store, or channel ARNs whose tags will be listed. The list has a limit of 20 ARNs.

Example trail ARN format: `arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail`

Example event data store ARN format: `arn:aws:cloudtrail:us-east-2:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE`

Example channel ARN format: `arn:aws:cloudtrail:us-east-2:123456789012:channel/01234567890`

Type: Array of strings

Required: Yes

Response Syntax

```
{
  "NextToken": "string",
  "ResourceTagList": [
    {
      "ResourceId": "string",
      "TagsList": [
        {
          "Key": "string",
          "Value": "string"
        }
      ]
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

Reserved for future use.

Type: String

ResourceTagList

A list of resource tags.

Type: Array of [ResourceTag](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ChannelARNInvalidException

This exception is thrown when the specified value of ChannelARN is not valid.

HTTP Status Code: 400

CloudTrailARNInvalidException

This exception is thrown when an operation is called with an ARN that is not valid.

The following is the format of a trail ARN: `arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail`

The following is the format of an event data store ARN: `arn:aws:cloudtrail:us-east-2:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE`

The following is the format of a channel ARN: `arn:aws:cloudtrail:us-east-2:123456789012:channel/01234567890`

HTTP Status Code: 400

EventDataStoreARNInvalidException

The specified event data store ARN is not valid or does not map to an event data store in your account.

HTTP Status Code: 400

EventDataStoreNotFoundException

The specified event data store was not found.

HTTP Status Code: 400

InactiveEventDataStoreException

The event data store is inactive.

HTTP Status Code: 400

InvalidTokenException

Reserved for future use.

HTTP Status Code: 400

InvalidTrailNameException

This exception is thrown when the provided trail name is not valid. Trail names must meet the following requirements:

- Contain only ASCII letters (a-z, A-Z), numbers (0-9), periods (.), underscores (_), or dashes (-)
- Start with a letter or number, and end with a letter or number
- Be between 3 and 128 characters
- Have no adjacent periods, underscores or dashes. Names like my-__namespace and my--namespace are not valid.
- Not be in IP address format (for example, 192.168.5.4)

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

This exception is thrown when the specified resource is not found.

HTTP Status Code: 400

ResourceTypeNotSupportedException

This exception is thrown when the specified resource type is not supported by CloudTrail.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTrails

Lists trails that are in the current account.

Request Syntax

```
{  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

NextToken

The token to use to get the next page of results after a previous API call. This token must be passed in with the same parameters that were specified in the original call. For example, if the original call specified an `AttributeKey` of 'Username' with a value of 'root', the call with `NextToken` should include those same parameters.

Type: String

Required: No

Response Syntax

```
{  
  "NextToken": "string",  
  "Trails": [  
    {  
      "HomeRegion": "string",  
      "Name": "string",  
      "TrailARN": "string"  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to use to get the next page of results after a previous API call. If the token does not appear, there are no more results to return. The token must be passed in with the same parameters as the previous call. For example, if the original call specified an `AttributeKey` of 'Username' with a value of 'root', the call with `NextToken` should include those same parameters.

Type: String

Trails

Returns the name, ARN, and home Region of trails in the current account.

Type: Array of [TrailInfo](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

LookupEvents

Looks up [management events](#) or [CloudTrail Insights events](#) that are captured by CloudTrail. You can look up events that occurred in a Region within the last 90 days.

Note

LookupEvents returns recent Insights events for trails that enable Insights. To view Insights events for an event data store, you can run queries on your Insights event data store, and you can also view the Lake dashboard for Insights.

Lookup supports the following attributes for management events:

- AWS access key
- Event ID
- Event name
- Event source
- Read only
- Resource name
- Resource type
- User name

Lookup supports the following attributes for Insights events:

- Event ID
- Event name
- Event source

All attributes are optional. The default number of results returned is 50, with a maximum of 50 possible. The response includes a token that you can use to get the next page of results.

Important

The rate of lookup requests is limited to two per second, per account, per Region. If this limit is exceeded, a throttling error occurs.

Request Syntax

```
{
  "EndTime": number,
  "EventCategory": "string",
  "LookupAttributes": [
    {
      "AttributeKey": "string",
      "AttributeValue": "string"
    }
  ],
  "MaxResults": number,
  "NextToken": "string",
  "StartTime": number
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

EndTime

Specifies that only events that occur before or at the specified time are returned. If the specified end time is before the specified start time, an error is returned.

Type: Timestamp

Required: No

EventCategory

Specifies the event category. If you do not specify an event category, events of the category are not returned in the response. For example, if you do not specify `insight` as the value of `EventCategory`, no Insights events are returned.

Type: String

Valid Values: insight

Required: No

LookupAttributes

Contains a list of lookup attributes. Currently the list can contain only one item.

Type: Array of [LookupAttribute](#) objects

Required: No

MaxResults

The number of events to return. Possible values are 1 through 50. The default is 50.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

The token to use to get the next page of results after a previous API call. This token must be passed in with the same parameters that were specified in the original call. For example, if the original call specified an AttributeKey of 'Username' with a value of 'root', the call with NextToken should include those same parameters.

Type: String

Required: No

StartTime

Specifies that only events that occur after or at the specified time are returned. If the specified start time is after the specified end time, an error is returned.

Type: Timestamp

Required: No

Response Syntax

```
{
  "Events": [
    {
      "AccessKeyId": "string",
      "CloudTrailEvent": "string",
      "EventId": "string",
      "EventName": "string",
      "EventSource": "string",
      "EventTime": number,
      "ReadOnly": "string",
      "Resources": [
        {
          "ResourceName": "string",
          "ResourceType": "string"
        }
      ],
      "Username": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Events

A list of events returned based on the lookup attributes specified and the CloudTrail event. The events list is sorted by time. The most recent event is listed first.

Type: Array of [Event](#) objects

NextToken

The token to use to get the next page of results after a previous API call. If the token does not appear, there are no more results to return. The token must be passed in with the same parameters as the previous call. For example, if the original call specified an AttributeKey

of 'Username' with a value of 'root', the call with NextToken should include those same parameters.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidEventCategoryException

Occurs if an event category that is not valid is specified as a value of EventCategory.

HTTP Status Code: 400

InvalidLookupAttributesException

Occurs when a lookup attribute is specified that is not valid.

HTTP Status Code: 400

InvalidMaxResultsException

This exception is thrown if the limit specified is not valid.

HTTP Status Code: 400

InvalidNextTokenException

A token that is not valid, or a token that was previously used in a request with different parameters. This exception is thrown if the token is not valid.

HTTP Status Code: 400

InvalidTimeRangeException

Occurs if the timestamp values are not valid. Either the start time occurs after the end time, or the time range is outside the range of possible values.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutEventSelectors

Configures an event selector or advanced event selectors for your trail. Use event selectors or advanced event selectors to specify management and data event settings for your trail. If you want your trail to log Insights events, be sure the event selector enables logging of the Insights event types you want configured for your trail. For more information about logging Insights events, see [Logging Insights events](#) in the *CloudTrail User Guide*. By default, trails created without specific event selectors are configured to log all read and write management events, and no data events.

When an event occurs in your account, CloudTrail evaluates the event selectors or advanced event selectors in all trails. For each trail, if the event matches any event selector, the trail processes and logs the event. If the event doesn't match any event selector, the trail doesn't log the event.

Example

1. You create an event selector for a trail and specify that you want write-only events.
2. The EC2 `GetConsoleOutput` and `RunInstances` API operations occur in your account.
3. CloudTrail evaluates whether the events match your event selectors.
4. The `RunInstances` is a write-only event and it matches your event selector. The trail logs the event.
5. The `GetConsoleOutput` is a read-only event that doesn't match your event selector. The trail doesn't log the event.

The `PutEventSelectors` operation must be called from the Region in which the trail was created; otherwise, an `InvalidHomeRegionException` exception is thrown.

You can configure up to five event selectors for each trail. For more information, see [Logging management events](#), [Logging data events](#), and [Quotas in AWS CloudTrail](#) in the *AWS CloudTrail User Guide*.

You can add advanced event selectors, and conditions for your advanced event selectors, up to a maximum of 500 values for all conditions and selectors on a trail. You can use either `AdvancedEventSelectors` or `EventSelectors`, but not both. If you apply `AdvancedEventSelectors` to a trail, any existing `EventSelectors` are overwritten. For more information about advanced event selectors, see [Logging data events](#) in the *AWS CloudTrail User Guide*.

Request Syntax

```
{
  "AdvancedEventSelectors": [
    {
      "FieldSelectors": [
        {
          "EndsWith": [ "string" ],
          "Equals": [ "string" ],
          "Field": "string",
          "NotEndsWith": [ "string" ],
          "NotEquals": [ "string" ],
          "NotStartsWith": [ "string" ],
          "StartsWith": [ "string" ]
        }
      ],
      "Name": "string"
    }
  ],
  "EventSelectors": [
    {
      "DataResources": [
        {
          "Type": "string",
          "Values": [ "string" ]
        }
      ],
      "ExcludeManagementEventSources": [ "string" ],
      "IncludeManagementEvents": boolean,
      "ReadWriteType": "string"
    }
  ],
  "TrailName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AdvancedEventSelectors

Specifies the settings for advanced event selectors. You can add advanced event selectors, and conditions for your advanced event selectors, up to a maximum of 500 values for all conditions and selectors on a trail. You can use either `AdvancedEventSelectors` or `EventSelectors`, but not both. If you apply `AdvancedEventSelectors` to a trail, any existing `EventSelectors` are overwritten. For more information about advanced event selectors, see [Logging data events](#) in the *AWS CloudTrail User Guide*.

Type: Array of [AdvancedEventSelector](#) objects

Required: No

EventSelectors

Specifies the settings for your event selectors. You can configure up to five event selectors for a trail. You can use either `EventSelectors` or `AdvancedEventSelectors` in a `PutEventSelectors` request, but not both. If you apply `EventSelectors` to a trail, any existing `AdvancedEventSelectors` are overwritten.

Type: Array of [EventSelector](#) objects

Required: No

TrailName

Specifies the name of the trail or trail ARN. If you specify a trail name, the string must meet the following requirements:

- Contain only ASCII letters (a-z, A-Z), numbers (0-9), periods (.), underscores (_), or dashes (-)
- Start with a letter or number, and end with a letter or number
- Be between 3 and 128 characters
- Have no adjacent periods, underscores or dashes. Names like `my-__namespace` and `my--namespace` are not valid.
- Not be in IP address format (for example, 192.168.5.4)

If you specify a trail ARN, it must be in the following format.

```
arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail
```

Type: String

Required: Yes

Response Syntax

```
{
  "AdvancedEventSelectors": [
    {
      "FieldSelectors": [
        {
          "EndsWith": [ "string" ],
          "Equals": [ "string" ],
          "Field": "string",
          "NotEndsWith": [ "string" ],
          "NotEquals": [ "string" ],
          "NotStartsWith": [ "string" ],
          "StartsWith": [ "string" ]
        }
      ],
      "Name": "string"
    }
  ],
  "EventSelectors": [
    {
      "DataResources": [
        {
          "Type": "string",
          "Values": [ "string" ]
        }
      ],
      "ExcludeManagementEventSources": [ "string" ],
      "IncludeManagementEvents": boolean,
      "ReadWriteType": "string"
    }
  ],
  "TrailARN": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AdvancedEventSelectors

Specifies the advanced event selectors configured for your trail.

Type: Array of [AdvancedEventSelector](#) objects

EventSelectors

Specifies the event selectors configured for your trail.

Type: Array of [EventSelector](#) objects

TrailARN

Specifies the ARN of the trail that was updated with event selectors. The following is the format of a trail ARN.

```
arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail
```

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

CloudTrailARNInvalidException

This exception is thrown when an operation is called with an ARN that is not valid.

The following is the format of a trail ARN: `arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail`

The following is the format of an event data store ARN: `arn:aws:cloudtrail:us-east-2:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE`

The following is the format of a channel ARN: `arn:aws:cloudtrail:us-east-2:123456789012:channel/01234567890`

HTTP Status Code: 400

ConflictException

This exception is thrown when the specified resource is not ready for an operation. This can occur when you try to run an operation on a resource before CloudTrail has time to fully load

the resource, or because another operation is modifying the resource. If this exception occurs, wait a few minutes, and then try the operation again.

HTTP Status Code: 400

InsufficientDependencyServiceAccessPermissionException

This exception is thrown when the IAM identity that is used to create the organization resource lacks one or more required permissions for creating an organization resource in a required service.

HTTP Status Code: 400

InvalidEventSelectorsException

This exception is thrown when the `PutEventSelectors` operation is called with a number of event selectors, advanced event selectors, or data resources that is not valid. The combination of event selectors or advanced event selectors and data resources is not valid. A trail can have up to 5 event selectors. If a trail uses advanced event selectors, a maximum of 500 total values for all conditions in all advanced event selectors is allowed. A trail is limited to 250 data resources. These data resources can be distributed across event selectors, but the overall total cannot exceed 250.

You can:

- Specify a valid number of event selectors (1 to 5) for a trail.
- Specify a valid number of data resources (1 to 250) for an event selector. The limit of number of resources on an individual event selector is configurable up to 250. However, this upper limit is allowed only if the total number of data resources does not exceed 250 across all event selectors for a trail.
- Specify up to 500 values for all conditions in all advanced event selectors for a trail.
- Specify a valid value for a parameter. For example, specifying the `ReadWriteType` parameter with a value of `read-only` is not valid.

HTTP Status Code: 400

InvalidHomeRegionException

This exception is thrown when an operation is called on a trail from a Region other than the Region in which the trail was created.

HTTP Status Code: 400

InvalidTrailNameException

This exception is thrown when the provided trail name is not valid. Trail names must meet the following requirements:

- Contain only ASCII letters (a-z, A-Z), numbers (0-9), periods (.), underscores (_), or dashes (-)
- Start with a letter or number, and end with a letter or number
- Be between 3 and 128 characters
- Have no adjacent periods, underscores or dashes. Names like my-__namespace and my--namespace are not valid.
- Not be in IP address format (for example, 192.168.5.4)

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

NotOrganizationMasterAccountException

This exception is thrown when the AWS account making the request to create or update an organization trail or event data store is not the management account for an organization in AWS Organizations. For more information, see [Prepare For Creating a Trail For Your Organization](#) or [Organization event data stores](#).

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

ThrottlingException

This exception is thrown when the request rate exceeds the limit.

HTTP Status Code: 400

TrailNotFoundException

This exception is thrown when the trail with the given name is not found.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

Examples

Example

The following example shows how to use advanced event selectors to log all management events (both `readOnly` and `writeOnly`), and include `PutObject` and `DeleteObject` data events for the S3 objects in two S3 bucket prefixes. As shown here, you can use advanced event selectors to select not only the S3 prefix names by ARN, but the names of the specific events that you want to log.

```
{
  "AdvancedEventSelectors": [
    {
      "FieldSelectors": [
        { "Field": "eventCategory", "Equals": ["Management"] }
      ],
      "Name": "Log all management events"
    },
    {
      "FieldSelectors": [
        { "Field": "eventCategory", "Equals": ["Data"] },
        { "Field": "resources.type", "Equals": ["AWS::S3::Object"] },
        { "Field": "eventName", "Equals": ["PutObject", "DeleteObject"] },
        { "Field": "resources.ARN", "StartsWith": ["arn:aws:s3:::DOC-EXAMPLE-
BUCKET/prefix", "arn:aws:s3:::DOC-EXAMPLE-BUCKET2/prefix2"] }
      ],
      "Name": "Log PutObject and DeleteObject events for two S3 prefixes"
    }
  ],
  "TrailName": "myTrail"
}
```

Example

The following example shows how to use advanced event selectors to log all data events for Amazon SNS topics and platform endpoints, and to log only SendMessage data events for Amazon SQS.

```
{
  "AdvancedEventSelectors": [
    {
      "FieldSelectors": [
        { "Field": "eventCategory", "Equals": ["Data"] },
        { "Field": "resources.type", "Equals": ["AWS::SNS::Topic"] }
      ],
      "Name": "Log all data events for Amazon SNS topics"
    },
    {
      "FieldSelectors": [
        { "Field": "eventCategory", "Equals": ["Data"] },
        { "Field": "resources.type", "Equals": ["AWS::SNS::PlatformEndpoint"] }
      ],
      "Name": "Log all data events for Amazon SNS platform endpoints"
    },
    {
      "FieldSelectors": [
        { "Field": "eventCategory", "Equals": ["Data"] },
        { "Field": "resources.type", "Equals": ["AWS::SQS::Queue"] },
        { "Field": "eventName", "Equals": ["SendMessage"] }
      ],
      "Name": "Log SendMessage data events for SQS"
    }
  ],
  "TrailName": "myTrail"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutInsightSelectors

Lets you enable Insights event logging by specifying the Insights selectors that you want to enable on an existing trail or event data store. You also use `PutInsightSelectors` to turn off Insights event logging, by passing an empty list of Insights types. The valid Insights event types are `ApiErrorRateInsight` and `ApiCallRateInsight`.

To enable Insights on an event data store, you must specify the ARNs (or ID suffix of the ARNs) for the source event data store (`EventDataStore`) and the destination event data store (`InsightsDestination`). The source event data store logs management events and enables Insights. The destination event data store logs Insights events based upon the management event activity of the source event data store. The source and destination event data stores must belong to the same AWS account.

To log Insights events for a trail, you must specify the name (`TrailName`) of the CloudTrail trail for which you want to change or add Insights selectors.

To log CloudTrail Insights events on API call volume, the trail or event data store must log write management events. To log CloudTrail Insights events on API error rate, the trail or event data store must log read or write management events. You can call `GetEventSelectors` on a trail to check whether the trail logs management events. You can call `GetEventDataStore` on an event data store to check whether the event data store logs management events.

For more information, see [Logging CloudTrail Insights events](#) in the *AWS CloudTrail User Guide*.

Request Syntax

```
{
  "EventDataStore": "string",
  "InsightsDestination": "string",
  "InsightSelectors": [
    {
      "InsightType": "string"
    }
  ],
  "TrailName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

EventDataStore

The ARN (or ID suffix of the ARN) of the source event data store for which you want to change or add Insights selectors. To enable Insights on an event data store, you must provide both the `EventDataStore` and `InsightsDestination` parameters.

You cannot use this parameter with the `TrailName` parameter.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: No

InsightsDestination

The ARN (or ID suffix of the ARN) of the destination event data store that logs Insights events. To enable Insights on an event data store, you must provide both the `EventDataStore` and `InsightsDestination` parameters.

You cannot use this parameter with the `TrailName` parameter.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: No

InsightSelectors

A JSON string that contains the Insights types you want to log on a trail or event data store. `ApiCallRateInsight` and `ApiErrorRateInsight` are valid Insight types.

The `ApiCallRateInsight` Insights type analyzes write-only management API calls that are aggregated per minute against a baseline API call volume.

The `ApiErrorRateInsight` Insights type analyzes management API calls that result in error codes. The error is shown if the API call is unsuccessful.

Type: Array of [InsightSelector](#) objects

Required: Yes

TrailName

The name of the CloudTrail trail for which you want to change or add Insights selectors.

You cannot use this parameter with the `EventDataStore` and `InsightsDestination` parameters.

Type: String

Required: No

Response Syntax

```
{
  "EventDataStoreArn": "string",
  "InsightsDestination": "string",
  "InsightSelectors": [
    {
      "InsightType": "string"
    }
  ],
  "TrailARN": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

EventDataStoreArn

The Amazon Resource Name (ARN) of the source event data store for which you want to change or add Insights selectors.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

InsightsDestination

The ARN of the destination event data store that logs Insights events.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

InsightSelectors

A JSON string that contains the Insights event types that you want to log on a trail or event data store. The valid Insights types are `ApiErrorRateInsight` and `ApiCallRateInsight`.

Type: Array of [InsightSelector](#) objects

TrailARN

The Amazon Resource Name (ARN) of a trail for which you want to change or add Insights selectors.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

CloudTrailARNInvalidException

This exception is thrown when an operation is called with an ARN that is not valid.

The following is the format of a trail ARN: `arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail`

The following is the format of an event data store ARN: `arn:aws:cloudtrail:us-east-2:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE`

The following is the format of a channel ARN: `arn:aws:cloudtrail:us-east-2:123456789012:channel/01234567890`

HTTP Status Code: 400

InsufficientEncryptionPolicyException

This exception is thrown when the policy on the S3 bucket or AWS KMS key does not have sufficient permissions for the operation.

HTTP Status Code: 400

InsufficientS3BucketPolicyException

This exception is thrown when the policy on the S3 bucket is not sufficient.

HTTP Status Code: 400

InvalidHomeRegionException

This exception is thrown when an operation is called on a trail from a Region other than the Region in which the trail was created.

HTTP Status Code: 400

InvalidInsightSelectorsException

For `PutInsightSelectors`, this exception is thrown when the formatting or syntax of the `InsightSelectors` JSON statement is not valid, or the specified `InsightType` in the `InsightSelectors` statement is not valid. Valid values for `InsightType` are `ApiCallRateInsight` and `ApiErrorRateInsight`. To enable Insights on an event data store, the destination event data store specified by the `InsightsDestination` parameter must log Insights events and the source event data store specified by the `EventDataStore` parameter must log management events.

For `UpdateEventDataStore`, this exception is thrown if Insights are enabled on the event data store and the updated advanced event selectors are not compatible with the configured `InsightSelectors`. If the `InsightSelectors` includes an `InsightType` of `ApiCallRateInsight`, the source event data store must log write management events. If the `InsightSelectors` includes an `InsightType` of `ApiErrorRateInsight`, the source event data store must log management events.

HTTP Status Code: 400

InvalidParameterCombinationException

This exception is thrown when the combination of parameters provided is not valid.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

InvalidTrailNameException

This exception is thrown when the provided trail name is not valid. Trail names must meet the following requirements:

- Contain only ASCII letters (a-z, A-Z), numbers (0-9), periods (.), underscores (_), or dashes (-)
- Start with a letter or number, and end with a letter or number
- Be between 3 and 128 characters
- Have no adjacent periods, underscores or dashes. Names like my-_
namespace and my--
namespace are not valid.
- Not be in IP address format (for example, 192.168.5.4)

HTTP Status Code: 400

KmsException

This exception is thrown when there is an issue with the specified AWS KMS key and the trail or event data store can't be updated.

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

NotOrganizationMasterAccountException

This exception is thrown when the AWS account making the request to create or update an organization trail or event data store is not the management account for an organization

in AWS Organizations. For more information, see [Prepare For Creating a Trail For Your Organization](#) or [Organization event data stores](#).

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

S3BucketDoesNotExistException

This exception is thrown when the specified S3 bucket does not exist.

HTTP Status Code: 400

ThrottlingException

This exception is thrown when the request rate exceeds the limit.

HTTP Status Code: 400

TrailNotFoundException

This exception is thrown when the trail with the given name is not found.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

Examples

Example

The following example shows how to use Insight selectors to enable CloudTrail Insights on a trail named *SampleTrail*.

```
{
  "InsightSelectors": '[{"InsightType": "ApiCallRateInsight"}, {"InsightType":
"ApiErrorRateInsight"}]',
```



```
"TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/SampleTrail"
}
```

Example

The following example shows how to disable CloudTrail Insights on a trail named SampleTrail. Disable Insights event collection by passing an empty string of insight types ([]).

```
{
  "InsightSelectors": [ ],
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/SampleTrail"
}
```

Example

The following example shows how to use Insight selectors to enable CloudTrail Insights on an event data store.

```
{
  "EventDataStore": "arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE",
  "InsightsDestination": "arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE-d483-5c7d-4ac2-adb5dEXAMPLE",
  "InsightSelectors": [
    {
      "InsightType": "ApiCallRateInsight"
    },
    {
      "InsightType": "ApiErrorRateInsight"
    }
  ]
}
```

Example

The following example shows how to disable CloudTrail Insights on an event data store.

```
{
  "EventDataStore": "arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE",
  "InsightSelectors": [ ]
}
```

```
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutResourcePolicy

Attaches a resource-based permission policy to a CloudTrail channel that is used for an integration with an event source outside of AWS. For more information about resource-based policies, see [CloudTrail resource-based policy examples](#) in the *CloudTrail User Guide*.

Request Syntax

```
{
  "ResourceArn": "string",
  "ResourcePolicy": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ResourceArn](#)

The Amazon Resource Name (ARN) of the CloudTrail channel attached to the resource-based policy. The following is the format of a resource ARN: `arn:aws:cloudtrail:us-east-2:123456789012:channel/MyChannel`.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: Yes

[ResourcePolicy](#)

A JSON-formatted string for an AWS resource-based policy.

The following are requirements for the resource policy:

- Contains only one action: `cloudtrail-data:PutAuditEvents`
- Contains at least one statement. The policy can have a maximum of 20 statements.

- Each statement contains at least one principal. A statement can have a maximum of 50 principals.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8192.

Required: Yes

Response Syntax

```
{  
  "ResourceArn": "string",  
  "ResourcePolicy": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ResourceArn](#)

The Amazon Resource Name (ARN) of the CloudTrail channel attached to the resource-based policy.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

[ResourcePolicy](#)

The JSON-formatted string of the AWS resource-based policy attached to the CloudTrail channel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8192.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

ResourceARNNotValidException

This exception is thrown when the provided resource does not exist, or the ARN format of the resource is not valid. The following is the valid format for a resource ARN:
`arn:aws:cloudtrail:us-east-2:123456789012:channel/MyChannel.`

HTTP Status Code: 400

ResourceNotFoundException

This exception is thrown when the specified resource is not found.

HTTP Status Code: 400

ResourcePolicyNotValidException

This exception is thrown when the resource-based policy has syntax errors, or contains a principal that is not valid.

The following are requirements for the resource policy:

- Contains only one action: `cloudtrail-data:PutAuditEvents`
- Contains at least one statement. The policy can have a maximum of 20 statements.
- Each statement contains at least one principal. A statement can have a maximum of 50 principals.

HTTP Status Code: 400

ResourceTypeNotSupportedException

This exception is thrown when the specified resource type is not supported by CloudTrail.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RegisterOrganizationDelegatedAdmin

Registers an organization's member account as the CloudTrail [delegated administrator](#).

Request Syntax

```
{  
  "MemberAccountId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[MemberAccountId](#)

An organization member account ID that you want to designate as a delegated administrator.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 16.

Pattern: \d+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccountNotFoundException

This exception is thrown when the specified account is not found or not part of an organization.

HTTP Status Code: 400

AccountRegisteredException

This exception is thrown when the account is already registered as the CloudTrail delegated administrator.

HTTP Status Code: 400

CannotDelegateManagementAccountException

This exception is thrown when the management account of an organization is registered as the CloudTrail delegated administrator.

HTTP Status Code: 400

CloudTrailAccessNotEnabledException

This exception is thrown when trusted access has not been enabled between AWS CloudTrail and AWS Organizations. For more information, see [How to enable or disable trusted access](#) in the *AWS Organizations User Guide* and [Prepare For Creating a Trail For Your Organization](#) in the *AWS CloudTrail User Guide*.

HTTP Status Code: 400

ConflictException

This exception is thrown when the specified resource is not ready for an operation. This can occur when you try to run an operation on a resource before CloudTrail has time to fully load the resource, or because another operation is modifying the resource. If this exception occurs, wait a few minutes, and then try the operation again.

HTTP Status Code: 400

DelegatedAdminAccountLimitExceededException

This exception is thrown when the maximum number of CloudTrail delegated administrators is reached.

HTTP Status Code: 400

InsufficientDependencyServiceAccessPermissionException

This exception is thrown when the IAM identity that is used to create the organization resource lacks one or more required permissions for creating an organization resource in a required service.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

NotOrganizationManagementAccountException

This exception is thrown when the account making the request is not the organization's management account.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

OrganizationNotInAllFeaturesModeException

This exception is thrown when AWS Organizations is not configured to support all features. All features must be enabled in Organizations to support creating an organization trail or event data store.

HTTP Status Code: 400

OrganizationsNotInUseException

This exception is thrown when the request is made from an AWS account that is not a member of an organization. To make this request, sign in using the credentials of an account that belongs to an organization.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RemoveTags

Removes the specified tags from a trail, event data store, or channel.

Request Syntax

```
{
  "ResourceId": "string",
  "TagsList": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ResourceId

Specifies the ARN of the trail, event data store, or channel from which tags should be removed.

Example trail ARN format: `arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail`

Example event data store ARN format: `arn:aws:cloudtrail:us-east-2:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE`

Example channel ARN format: `arn:aws:cloudtrail:us-east-2:123456789012:channel/01234567890`

Type: String

Required: Yes

TagsList

Specifies a list of tags to be removed.

Type: Array of [Tag](#) objects

Array Members: Maximum number of 200 items.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ChannelARNInvalidException

This exception is thrown when the specified value of ChannelARN is not valid.

HTTP Status Code: 400

ChannelNotFoundException

This exception is thrown when CloudTrail cannot find the specified channel.

HTTP Status Code: 400

CloudTrailARNInvalidException

This exception is thrown when an operation is called with an ARN that is not valid.

The following is the format of a trail ARN: `arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail`

The following is the format of an event data store ARN: `arn:aws:cloudtrail:us-east-2:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE`

The following is the format of a channel ARN: `arn:aws:cloudtrail:us-east-2:123456789012:channel/01234567890`

HTTP Status Code: 400

EventDataStoreARNInvalidException

The specified event data store ARN is not valid or does not map to an event data store in your account.

HTTP Status Code: 400

EventDataStoreNotFoundException

The specified event data store was not found.

HTTP Status Code: 400

InactiveEventDataStoreException

The event data store is inactive.

HTTP Status Code: 400

InvalidTagParameterException

This exception is thrown when the specified tag key or values are not valid. It can also occur if there are duplicate tags or too many tags on the resource.

HTTP Status Code: 400

InvalidTrailNameException

This exception is thrown when the provided trail name is not valid. Trail names must meet the following requirements:

- Contain only ASCII letters (a-z, A-Z), numbers (0-9), periods (.), underscores (_), or dashes (-)
- Start with a letter or number, and end with a letter or number
- Be between 3 and 128 characters
- Have no adjacent periods, underscores or dashes. Names like my-__namespace and my--namespace are not valid.
- Not be in IP address format (for example, 192.168.5.4)

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

NotOrganizationMasterAccountException

This exception is thrown when the AWS account making the request to create or update an organization trail or event data store is not the management account for an organization

in AWS Organizations. For more information, see [Prepare For Creating a Trail For Your Organization](#) or [Organization event data stores](#).

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

This exception is thrown when the specified resource is not found.

HTTP Status Code: 400

ResourceTypeNotSupportedException

This exception is thrown when the specified resource type is not supported by CloudTrail.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

RestoreEventDataStore

Restores a deleted event data store specified by `EventDataStore`, which accepts an event data store ARN. You can only restore a deleted event data store within the seven-day wait period after deletion. Restoring an event data store can take several minutes, depending on the size of the event data store.

Request Syntax

```
{
  "EventDataStore": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

EventDataStore

The ARN (or the ID suffix of the ARN) of the event data store that you want to restore.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: Yes

Response Syntax

```
{
  "AdvancedEventSelectors": [
    {
      "FieldSelectors": [
        {
          "EndsWith": [ "string" ],
          "Equals": [ "string" ],
          "Field": "string",

```



```

        "NotEndsWith": [ "string" ],
        "NotEquals": [ "string" ],
        "NotStartsWith": [ "string" ],
        "StartsWith": [ "string" ]
    }
],
    "Name": "string"
}
],
"BillingMode": "string",
"CreatedTimestamp": number,
"EventDataStoreArn": "string",
"KmsKeyId": "string",
"MultiRegionEnabled": boolean,
"Name": "string",
"OrganizationEnabled": boolean,
"RetentionPeriod": number,
"Status": "string",
"TerminationProtectionEnabled": boolean,
"UpdatedTimestamp": number
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AdvancedEventSelectors

The advanced event selectors that were used to select events.

Type: Array of [AdvancedEventSelector](#) objects

BillingMode

The billing mode for the event data store.

Type: String

Valid Values: EXTENDABLE_RETENTION_PRICING | FIXED_RETENTION_PRICING

CreatedTimestamp

The timestamp of an event data store's creation.

Type: Timestamp

EventDataStoreArn

The event data store ARN.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

KmsKeyId

Specifies the AWS KMS key ID that encrypts the events delivered by CloudTrail. The value is a fully specified ARN to a AWS KMS key in the following format.

```
arn:aws:kms:us-east-2:123456789012:key/12345678-1234-1234-1234-123456789012
```

Type: String

Length Constraints: Minimum length of 1. Maximum length of 350.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

MultiRegionEnabled

Indicates whether the event data store is collecting events from all Regions, or only from the Region in which the event data store was created.

Type: Boolean

Name

The name of the event data store.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9._\-]+$`

OrganizationEnabled

Indicates whether an event data store is collecting logged events for an organization in AWS Organizations.

Type: Boolean

RetentionPeriod

The retention period, in days.

Type: Integer

Valid Range: Minimum value of 7. Maximum value of 3653.

Status

The status of the event data store.

Type: String

Valid Values: CREATED | ENABLED | PENDING_DELETION | STARTING_INGESTION | STOPPING_INGESTION | STOPPED_INGESTION

TerminationProtectionEnabled

Indicates that termination protection is enabled and the event data store cannot be automatically deleted.

Type: Boolean

UpdatedTimestamp

The timestamp that shows when an event data store was updated, if applicable. UpdatedTimestamp is always either the same or newer than the time shown in CreatedTimestamp.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

CloudTrailAccessNotEnabledException

This exception is thrown when trusted access has not been enabled between AWS CloudTrail and AWS Organizations. For more information, see [How to enable or disable trusted access](#) in the *AWS Organizations User Guide* and [Prepare For Creating a Trail For Your Organization](#) in the *AWS CloudTrail User Guide*.

HTTP Status Code: 400

EventDataStoreARNInvalidException

The specified event data store ARN is not valid or does not map to an event data store in your account.

HTTP Status Code: 400

EventDataStoreMaxLimitExceededException

Your account has used the maximum number of event data stores.

HTTP Status Code: 400

EventDataStoreNotFoundException

The specified event data store was not found.

HTTP Status Code: 400

InsufficientDependencyServiceAccessPermissionException

This exception is thrown when the IAM identity that is used to create the organization resource lacks one or more required permissions for creating an organization resource in a required service.

HTTP Status Code: 400

InvalidEventDataStoreStatusException

The event data store is not in a status that supports the operation.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

NotOrganizationMasterAccountException

This exception is thrown when the AWS account making the request to create or update an organization trail or event data store is not the management account for an organization in AWS Organizations. For more information, see [Prepare For Creating a Trail For Your Organization](#) or [Organization event data stores](#).

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

OrganizationNotInAllFeaturesModeException

This exception is thrown when AWS Organizations is not configured to support all features. All features must be enabled in Organizations to support creating an organization trail or event data store.

HTTP Status Code: 400

OrganizationsNotInUseException

This exception is thrown when the request is made from an AWS account that is not a member of an organization. To make this request, sign in using the credentials of an account that belongs to an organization.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartEventDataStoreIngestion

Starts the ingestion of live events on an event data store specified as either an ARN or the ID portion of the ARN. To start ingestion, the event data store Status must be STOPPED_INGESTION and the eventCategory must be Management, Data, or ConfigurationItem.

Request Syntax

```
{
  "EventDataStore": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

EventDataStore

The ARN (or ID suffix of the ARN) of the event data store for which you want to start ingestion.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EventDataStoreARNInvalidException

The specified event data store ARN is not valid or does not map to an event data store in your account.

HTTP Status Code: 400

EventDataStoreNotFoundException

The specified event data store was not found.

HTTP Status Code: 400

InsufficientDependencyServiceAccessPermissionException

This exception is thrown when the IAM identity that is used to create the organization resource lacks one or more required permissions for creating an organization resource in a required service.

HTTP Status Code: 400

InvalidEventDataStoreCategoryException

This exception is thrown when event categories of specified event data stores are not valid.

HTTP Status Code: 400

InvalidEventDataStoreStatusException

The event data store is not in a status that supports the operation.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

NotOrganizationMasterAccountException

This exception is thrown when the AWS account making the request to create or update an organization trail or event data store is not the management account for an organization in AWS Organizations. For more information, see [Prepare For Creating a Trail For Your Organization](#) or [Organization event data stores](#).

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartImport

Starts an import of logged trail events from a source S3 bucket to a destination event data store. By default, CloudTrail only imports events contained in the S3 bucket's `CloudTrail` prefix and the prefixes inside the `CloudTrail` prefix, and does not check prefixes for other AWS services. If you want to import CloudTrail events contained in another prefix, you must include the prefix in the `S3LocationUri`. For more considerations about importing trail events, see [Considerations for copying trail events](#) in the *CloudTrail User Guide*.

When you start a new import, the `Destinations` and `ImportSource` parameters are required. Before starting a new import, disable any access control lists (ACLs) attached to the source S3 bucket. For more information about disabling ACLs, see [Controlling ownership of objects and disabling ACLs for your bucket](#).

When you retry an import, the `ImportID` parameter is required.

Note

If the destination event data store is for an organization, you must use the management account to import trail events. You cannot use the delegated administrator account for the organization.

Request Syntax

```
{
  "Destinations": [ "string" ],
  "EndEventTime": number,
  "ImportId": "string",
  "ImportSource": {
    "S3": {
      "S3BucketAccessRoleArn": "string",
      "S3BucketRegion": "string",
      "S3LocationUri": "string"
    }
  },
  "StartEventTime": number
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Destinations

The ARN of the destination event data store. Use this parameter for a new import.

Type: Array of strings

Array Members: Fixed number of 1 item.

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: No

EndEventTime

Use with `StartEventTime` to bound a `StartImport` request, and limit imported trail events to only those events logged within a specified time period. When you specify a time range, CloudTrail checks the prefix and log file names to verify the names contain a date between the specified `StartEventTime` and `EndEventTime` before attempting to import events.

Type: Timestamp

Required: No

ImportId

The ID of the import. Use this parameter when you are retrying an import.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[a-f0-9\ -]+$`

Required: No

ImportSource

The source S3 bucket for the import. Use this parameter for a new import.

Type: [ImportSource](#) object

Required: No

StartEventTime

Use with `EndEventTime` to bound a `StartImport` request, and limit imported trail events to only those events logged within a specified time period. When you specify a time range, CloudTrail checks the prefix and log file names to verify the names contain a date between the specified `StartEventTime` and `EndEventTime` before attempting to import events.

Type: Timestamp

Required: No

Response Syntax

```
{
  "CreatedTimestamp": number,
  "Destinations": [ string ],
  "EndEventTime": number,
  "ImportId": string,
  "ImportSource": {
    "S3": {
      "S3BucketAccessRoleArn": string,
      "S3BucketRegion": string,
      "S3LocationUri": string
    }
  },
  "ImportStatus": string,
  "StartEventTime": number,
  "UpdatedTimestamp": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CreatedTimestamp

The timestamp for the import's creation.

Type: Timestamp

Destinations

The ARN of the destination event data store.

Type: Array of strings

Array Members: Fixed number of 1 item.

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

EndEventTime

Used with `StartEventTime` to bound a `StartImport` request, and limit imported trail events to only those events logged within a specified time period.

Type: Timestamp

ImportId

The ID of the import.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[a-f0-9\ -]+$`

ImportSource

The source S3 bucket for the import.

Type: [ImportSource](#) object

ImportStatus

Shows the status of the import after a `StartImport` request. An import finishes with a status of `COMPLETED` if there were no failures, or `FAILED` if there were failures.

Type: String

Valid Values: INITIALIZING | IN_PROGRESS | FAILED | STOPPED | COMPLETED

StartEventTime

Used with EndEventTime to bound a StartImport request, and limit imported trail events to only those events logged within a specified time period.

Type: Timestamp

UpdatedTimestamp

The timestamp of the import's last update, if applicable.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccountHasOngoingImportException

This exception is thrown when you start a new import and a previous import is still in progress.

HTTP Status Code: 400

EventDataStoreARNInvalidException

The specified event data store ARN is not valid or does not map to an event data store in your account.

HTTP Status Code: 400

EventDataStoreNotFoundException

The specified event data store was not found.

HTTP Status Code: 400

ImportNotFoundException

The specified import was not found.

HTTP Status Code: 400

InactiveEventDataStoreException

The event data store is inactive.

HTTP Status Code: 400

InsufficientEncryptionPolicyException

This exception is thrown when the policy on the S3 bucket or AWS KMS key does not have sufficient permissions for the operation.

HTTP Status Code: 400

InvalidEventDataStoreCategoryException

This exception is thrown when event categories of specified event data stores are not valid.

HTTP Status Code: 400

InvalidEventDataStoreStatusException

The event data store is not in a status that supports the operation.

HTTP Status Code: 400

InvalidImportSourceException

This exception is thrown when the provided source S3 bucket is not valid for import.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartLogging

Starts the recording of AWS API calls and log file delivery for a trail. For a trail that is enabled in all Regions, this operation must be called from the Region in which the trail was created. This operation cannot be called on the shadow trails (replicated trails in other Regions) of a trail that is enabled in all Regions.

Request Syntax

```
{  
  "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

Specifies the name or the CloudTrail ARN of the trail for which CloudTrail logs AWS API calls. The following is the format of a trail ARN.

```
arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail
```

Type: String

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

CloudTrailARNInvalidException

This exception is thrown when an operation is called with an ARN that is not valid.

The following is the format of a trail ARN: `arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail`

The following is the format of an event data store ARN: `arn:aws:cloudtrail:us-east-2:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE`

The following is the format of a channel ARN: `arn:aws:cloudtrail:us-east-2:123456789012:channel/01234567890`

HTTP Status Code: 400

ConflictException

This exception is thrown when the specified resource is not ready for an operation. This can occur when you try to run an operation on a resource before CloudTrail has time to fully load the resource, or because another operation is modifying the resource. If this exception occurs, wait a few minutes, and then try the operation again.

HTTP Status Code: 400

InsufficientDependencyServiceAccessPermissionException

This exception is thrown when the IAM identity that is used to create the organization resource lacks one or more required permissions for creating an organization resource in a required service.

HTTP Status Code: 400

InvalidHomeRegionException

This exception is thrown when an operation is called on a trail from a Region other than the Region in which the trail was created.

HTTP Status Code: 400

InvalidTrailNameException

This exception is thrown when the provided trail name is not valid. Trail names must meet the following requirements:

- Contain only ASCII letters (a-z, A-Z), numbers (0-9), periods (.), underscores (_), or dashes (-)
- Start with a letter or number, and end with a letter or number
- Be between 3 and 128 characters

- Have no adjacent periods, underscores or dashes. Names like my-__namespace and my--namespace are not valid.
- Not be in IP address format (for example, 192.168.5.4)

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

NotOrganizationMasterAccountException

This exception is thrown when the AWS account making the request to create or update an organization trail or event data store is not the management account for an organization in AWS Organizations. For more information, see [Prepare For Creating a Trail For Your Organization](#) or [Organization event data stores](#).

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

ThrottlingException

This exception is thrown when the request rate exceeds the limit.

HTTP Status Code: 400

TrailNotFoundException

This exception is thrown when the trail with the given name is not found.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartQuery

Starts a CloudTrail Lake query. Use the `QueryStatement` parameter to provide your SQL query, enclosed in single quotation marks. Use the optional `DeliveryS3Uri` parameter to deliver the query results to an S3 bucket.

`StartQuery` requires you specify either the `QueryStatement` parameter, or a `QueryAlias` and any `QueryParameters`. In the current release, the `QueryAlias` and `QueryParameters` parameters are used only for the queries that populate the CloudTrail Lake dashboards.

Request Syntax

```
{
  "DeliveryS3Uri": "string",
  "QueryAlias": "string",
  "QueryParameters": [ "string" ],
  "QueryStatement": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[DeliveryS3Uri](#)

The URI for the S3 bucket where CloudTrail delivers the query results.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `s3://[a-z0-9][\.\-a-z0-9]{1,61}[a-z0-9](/.*)?`

Required: No

[QueryAlias](#)

The alias that identifies a query template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^[a-zA-Z][a-zA-Z0-9._\-]*$`

Required: No

QueryParameters

The query parameters for the specified `QueryAlias`.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `.*`

Required: No

QueryStatement

The SQL code of your query.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10000.

Pattern: `(?s).*`

Required: No

Response Syntax

```
{
  "QueryId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

QueryId

The ID of the started query.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[a-f0-9\-]+$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EventDataStoreARNInvalidException

The specified event data store ARN is not valid or does not map to an event data store in your account.

HTTP Status Code: 400

EventDataStoreNotFoundException

The specified event data store was not found.

HTTP Status Code: 400

InactiveEventDataStoreException

The event data store is inactive.

HTTP Status Code: 400

InsufficientEncryptionPolicyException

This exception is thrown when the policy on the S3 bucket or AWS KMS key does not have sufficient permissions for the operation.

HTTP Status Code: 400

InsufficientS3BucketPolicyException

This exception is thrown when the policy on the S3 bucket is not sufficient.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

InvalidQueryStatementException

The query that was submitted has validation errors, or uses incorrect syntax or unsupported keywords. For more information about writing a query, see [Create or edit a query](#) in the *AWS CloudTrail User Guide*.

HTTP Status Code: 400

InvalidS3BucketNameException

This exception is thrown when the provided S3 bucket name is not valid.

HTTP Status Code: 400

InvalidS3PrefixException

This exception is thrown when the provided S3 prefix is not valid.

HTTP Status Code: 400

MaxConcurrentQueriesException

You are already running the maximum number of concurrent queries. The maximum number of concurrent queries is 10. Wait a minute for some queries to finish, and then run the query again.

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

S3BucketDoesNotExistException

This exception is thrown when the specified S3 bucket does not exist.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

Examples

Example

The following example uses the `QueryStatement` parameter with the optional `DeliveryS3Uri` parameter to deliver the query results to an S3 bucket.

```
{
  "DeliveryS3Uri": "s3://aws-cloudtrail-lake-query-results-123456789012-us-east-1",
  "QueryStatement": "SELECT eventID, eventTime FROM EXAMPLE-f852-4e8f-8bd1-
bcf6cEXAMPLE LIMIT 10"
}
```

Example

The following example uses the `QueryAlias` and `QueryParameters` parameters.

```
{
  "QueryAlias": "query-alias",
  "QueryParameters": [ "EXAMPLE-
b8e1-4e93-848f-573b9bfEXAMPLE", "2023-05-26T17:47:22.541Z", "2023-05-27T17:47:22.541Z" ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StopEventDataStoreIngestion

Stops the ingestion of live events on an event data store specified as either an ARN or the ID portion of the ARN. To stop ingestion, the event data store Status must be ENABLED and the eventCategory must be Management, Data, or ConfigurationItem.

Request Syntax

```
{
  "EventDataStore": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

EventDataStore

The ARN (or ID suffix of the ARN) of the event data store for which you want to stop ingestion.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EventDataStoreARNInvalidException

The specified event data store ARN is not valid or does not map to an event data store in your account.

HTTP Status Code: 400

EventDataStoreNotFoundException

The specified event data store was not found.

HTTP Status Code: 400

InsufficientDependencyServiceAccessPermissionException

This exception is thrown when the IAM identity that is used to create the organization resource lacks one or more required permissions for creating an organization resource in a required service.

HTTP Status Code: 400

InvalidEventDataStoreCategoryException

This exception is thrown when event categories of specified event data stores are not valid.

HTTP Status Code: 400

InvalidEventDataStoreStatusException

The event data store is not in a status that supports the operation.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

NotOrganizationMasterAccountException

This exception is thrown when the AWS account making the request to create or update an organization trail or event data store is not the management account for an organization in AWS Organizations. For more information, see [Prepare For Creating a Trail For Your Organization](#) or [Organization event data stores](#).

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StopImport

Stops a specified import.

Request Syntax

```
{
  "ImportId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ImportId

The ID of the import.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[a-f0-9\-\-]+$`

Required: Yes

Response Syntax

```
{
  "CreatedTimestamp": number,
  "Destinations": [ "string" ],
  "EndEventTime": number,
  "ImportId": "string",
  "ImportSource": {
    "S3": {
      "S3BucketAccessRoleArn": "string",
      "S3BucketRegion": "string",
      "S3LocationUri": "string"
    }
  }
}
```

```
    }
  },
  "ImportStatistics": {
    "EventsCompleted": number,
    "FailedEntries": number,
    "FilesCompleted": number,
    "PrefixesCompleted": number,
    "PrefixesFound": number
  },
  "ImportStatus": "string",
  "StartEventTime": number,
  "UpdatedTimestamp": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CreatedTimestamp

The timestamp of the import's creation.

Type: Timestamp

Destinations

The ARN of the destination event data store.

Type: Array of strings

Array Members: Fixed number of 1 item.

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

EndEventTime

Used with `StartEventTime` to bound a `StartImport` request, and limit imported trail events to only those events logged within a specified time period.

Type: Timestamp

ImportId

The ID for the import.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[a-f0-9\-]+\`

ImportSource

The source S3 bucket for the import.

Type: [ImportSource](#) object

ImportStatistics

Returns information on the stopped import.

Type: [ImportStatistics](#) object

ImportStatus

The status of the import.

Type: String

Valid Values: INITIALIZING | IN_PROGRESS | FAILED | STOPPED | COMPLETED

StartEventTime

Used with `EndEventTime` to bound a `StartImport` request, and limit imported trail events to only those events logged within a specified time period.

Type: Timestamp

UpdatedTimestamp

The timestamp of the import's last update.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ImportNotFoundException

The specified import was not found.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StopLogging

Suspends the recording of AWS API calls and log file delivery for the specified trail. Under most circumstances, there is no need to use this action. You can update a trail without stopping it first. This action is the only way to stop recording. For a trail enabled in all Regions, this operation must be called from the Region in which the trail was created, or an `InvalidHomeRegionException` will occur. This operation cannot be called on the shadow trails (replicated trails in other Regions) of a trail enabled in all Regions.

Request Syntax

```
{
  "Name": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

Specifies the name or the CloudTrail ARN of the trail for which CloudTrail will stop logging AWS API calls. The following is the format of a trail ARN.

```
arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail
```

Type: String

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

CloudTrailARNInvalidException

This exception is thrown when an operation is called with an ARN that is not valid.

The following is the format of a trail ARN: `arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail`

The following is the format of an event data store ARN: `arn:aws:cloudtrail:us-east-2:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE`

The following is the format of a channel ARN: `arn:aws:cloudtrail:us-east-2:123456789012:channel/01234567890`

HTTP Status Code: 400

ConflictException

This exception is thrown when the specified resource is not ready for an operation. This can occur when you try to run an operation on a resource before CloudTrail has time to fully load the resource, or because another operation is modifying the resource. If this exception occurs, wait a few minutes, and then try the operation again.

HTTP Status Code: 400

InsufficientDependencyServiceAccessPermissionException

This exception is thrown when the IAM identity that is used to create the organization resource lacks one or more required permissions for creating an organization resource in a required service.

HTTP Status Code: 400

InvalidHomeRegionException

This exception is thrown when an operation is called on a trail from a Region other than the Region in which the trail was created.

HTTP Status Code: 400

InvalidTrailNameException

This exception is thrown when the provided trail name is not valid. Trail names must meet the following requirements:

- Contain only ASCII letters (a-z, A-Z), numbers (0-9), periods (.), underscores (_), or dashes (-)

- Start with a letter or number, and end with a letter or number
- Be between 3 and 128 characters
- Have no adjacent periods, underscores or dashes. Names like my-_namespace and my--namespace are not valid.
- Not be in IP address format (for example, 192.168.5.4)

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

NotOrganizationMasterAccountException

This exception is thrown when the AWS account making the request to create or update an organization trail or event data store is not the management account for an organization in AWS Organizations. For more information, see [Prepare For Creating a Trail For Your Organization](#) or [Organization event data stores](#).

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

ThrottlingException

This exception is thrown when the request rate exceeds the limit.

HTTP Status Code: 400

TrailNotFoundException

This exception is thrown when the trail with the given name is not found.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateChannel

Updates a channel specified by a required channel ARN or UUID.

Request Syntax

```
{
  "Channel": "string",
  "Destinations": [
    {
      "Location": "string",
      "Type": "string"
    }
  ],
  "Name": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Channel

The ARN or ID (the ARN suffix) of the channel that you want to update.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: Yes

Destinations

The ARNs of event data stores that you want to log events arriving through the channel.

Type: Array of [Destination](#) objects

Array Members: Minimum number of 1 item. Maximum number of 200 items.

Required: No

Name

Changes the name of the channel.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9._\-\-]+$`

Required: No

Response Syntax

```
{
  "ChannelArn": "string",
  "Destinations": [
    {
      "Location": "string",
      "Type": "string"
    }
  ],
  "Name": "string",
  "Source": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ChannelArn

The ARN of the channel that was updated.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-\-:]+$`

Destinations

The event data stores that log events arriving through the channel.

Type: Array of [Destination](#) objects

Array Members: Minimum number of 1 item. Maximum number of 200 items.

Name

The name of the channel that was updated.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9._\-\]+$`

Source

The event source of the channel that was updated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `.*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ChannelAlreadyExistsException

This exception is thrown when the provided channel already exists.

HTTP Status Code: 400

ChannelARNInvalidException

This exception is thrown when the specified value of ChannelARN is not valid.

HTTP Status Code: 400

ChannelNotFoundException

This exception is thrown when CloudTrail cannot find the specified channel.

HTTP Status Code: 400

EventDataStoreARNInvalidException

The specified event data store ARN is not valid or does not map to an event data store in your account.

HTTP Status Code: 400

EventDataStoreNotFoundException

The specified event data store was not found.

HTTP Status Code: 400

InactiveEventDataStoreException

The event data store is inactive.

HTTP Status Code: 400

InvalidEventDataStoreCategoryException

This exception is thrown when event categories of specified event data stores are not valid.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateEventDataStore

Updates an event data store. The required `EventDataStore` value is an ARN or the ID portion of the ARN. Other parameters are optional, but at least one optional parameter must be specified, or CloudTrail throws an error. `RetentionPeriod` is in days, and valid values are integers between 7 and 3653 if the `BillingMode` is set to `EXTENDABLE_RETENTION_PRICING`, or between 7 and 2557 if `BillingMode` is set to `FIXED_RETENTION_PRICING`. By default, `TerminationProtection` is enabled.

For event data stores for CloudTrail events, `AdvancedEventSelectors` includes or excludes management or data events in your event data store. For more information about `AdvancedEventSelectors`, see [AdvancedEventSelectors](#).

For event data stores for CloudTrail Insights events, AWS Config configuration items, Audit Manager evidence, or non-AWS events, `AdvancedEventSelectors` includes events of that type in your event data store.

Request Syntax

```
{
  "AdvancedEventSelectors": [
    {
      "FieldSelectors": [
        {
          "EndsWith": [ "string" ],
          "Equals": [ "string" ],
          "Field": "string",
          "NotEndsWith": [ "string" ],
          "NotEquals": [ "string" ],
          "NotStartsWith": [ "string" ],
          "StartsWith": [ "string" ]
        }
      ],
      "Name": "string"
    }
  ],
  "BillingMode": "string",
  "EventDataStore": "string",
  "KmsKeyId": "string",
  "MultiRegionEnabled": boolean,
  "Name": "string",
```

```
"OrganizationEnabled": boolean,  
"RetentionPeriod": number,  
"TerminationProtectionEnabled": boolean  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[AdvancedEventSelectors](#)

The advanced event selectors used to select events for the event data store. You can configure up to five advanced event selectors for each event data store.

Type: Array of [AdvancedEventSelector](#) objects

Required: No

[BillingMode](#)

Note

You can't change the billing mode from `EXTENDABLE_RETENTION_PRICING` to `FIXED_RETENTION_PRICING`. If `BillingMode` is set to `EXTENDABLE_RETENTION_PRICING` and you want to use `FIXED_RETENTION_PRICING` instead, you'll need to stop ingestion on the event data store and create a new event data store that uses `FIXED_RETENTION_PRICING`.

The billing mode for the event data store determines the cost for ingesting events and the default and maximum retention period for the event data store.

The following are the possible values:

- `EXTENDABLE_RETENTION_PRICING` - This billing mode is generally recommended if you want a flexible retention period of up to 3653 days (about 10 years). The default retention period for this billing mode is 366 days.
- `FIXED_RETENTION_PRICING` - This billing mode is recommended if you expect to ingest more than 25 TB of event data per month and need a retention period of up to 2557 days (about 7 years). The default retention period for this billing mode is 2557 days.

For more information about CloudTrail pricing, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail Lake costs](#).

Type: String

Valid Values: EXTENDABLE_RETENTION_PRICING | FIXED_RETENTION_PRICING

Required: No

[EventDataStore](#)

The ARN (or the ID suffix of the ARN) of the event data store that you want to update.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: Yes

[KmsKeyId](#)

Specifies the AWS KMS key ID to use to encrypt the events delivered by CloudTrail. The value can be an alias name prefixed by `alias/`, a fully specified ARN to an alias, a fully specified ARN to a key, or a globally unique identifier.

Important

Disabling or deleting the KMS key, or removing CloudTrail permissions on the key, prevents CloudTrail from logging events to the event data store, and prevents users from querying the data in the event data store that was encrypted with the key. After you associate an event data store with a KMS key, the KMS key cannot be removed or changed. Before you disable or delete a KMS key that you are using with an event data store, delete or back up your event data store.

CloudTrail also supports AWS KMS multi-Region keys. For more information about multi-Region keys, see [Using multi-Region keys](#) in the *AWS Key Management Service Developer Guide*.

Examples:

- `alias/MyAliasName`

- `arn:aws:kms:us-east-2:123456789012:alias/MyAliasName`
- `arn:aws:kms:us-east-2:123456789012:key/12345678-1234-1234-1234-123456789012`
- `12345678-1234-1234-1234-123456789012`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 350.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: No

MultiRegionEnabled

Specifies whether an event data store collects events from all Regions, or only from the Region in which it was created.

Type: Boolean

Required: No

Name

The event data store name.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9._\-]+$`

Required: No

OrganizationEnabled

Specifies whether an event data store collects events logged for an organization in AWS Organizations.

Note

Only the management account for the organization can convert an organization event data store to a non-organization event data store, or convert a non-organization event data store to an organization event data store.

Type: Boolean

Required: No

RetentionPeriod

The retention period of the event data store, in days. If `BillingMode` is set to `EXTENDABLE_RETENTION_PRICING`, you can set a retention period of up to 3653 days, the equivalent of 10 years. If `BillingMode` is set to `FIXED_RETENTION_PRICING`, you can set a retention period of up to 2557 days, the equivalent of seven years.

CloudTrail Lake determines whether to retain an event by checking if the `eventTime` of the event is within the specified retention period. For example, if you set a retention period of 90 days, CloudTrail will remove events when the `eventTime` is older than 90 days.

Note

If you decrease the retention period of an event data store, CloudTrail will remove any events with an `eventTime` older than the new retention period. For example, if the previous retention period was 365 days and you decrease it to 100 days, CloudTrail will remove events with an `eventTime` older than 100 days.

Type: Integer

Valid Range: Minimum value of 7. Maximum value of 3653.

Required: No

TerminationProtectionEnabled

Indicates that termination protection is enabled and the event data store cannot be automatically deleted.

Type: Boolean

Required: No

Response Syntax

```
{
```

```
"AdvancedEventSelectors": [
  {
    "FieldSelectors": [
      {
        "EndsWith": [ "string" ],
        "Equals": [ "string" ],
        "Field": "string",
        "NotEndsWith": [ "string" ],
        "NotEquals": [ "string" ],
        "NotStartsWith": [ "string" ],
        "StartsWith": [ "string" ]
      }
    ],
    "Name": "string"
  }
],
"BillingMode": "string",
"CreatedTimestamp": number,
"EventDataStoreArn": "string",
"FederationRoleArn": "string",
"FederationStatus": "string",
"KmsKeyId": "string",
"MultiRegionEnabled": boolean,
"Name": "string",
"OrganizationEnabled": boolean,
"RetentionPeriod": number,
"Status": "string",
"TerminationProtectionEnabled": boolean,
"UpdatedTimestamp": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AdvancedEventSelectors](#)

The advanced event selectors that are applied to the event data store.

Type: Array of [AdvancedEventSelector](#) objects

BillingMode

The billing mode for the event data store.

Type: String

Valid Values: EXTENDABLE_RETENTION_PRICING | FIXED_RETENTION_PRICING

CreatedTimestamp

The timestamp that shows when an event data store was first created.

Type: Timestamp

EventDataStoreArn

The ARN of the event data store.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

FederationRoleArn

If Lake query federation is enabled, provides the ARN of the federation role used to access the resources for the federated event data store.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 125.

Pattern: `^[a-zA-Z0-9._/\-:@=\+,\.]+$`

FederationStatus

Indicates the [Lake query federation](#) status. The status is ENABLED if Lake query federation is enabled, or DISABLED if Lake query federation is disabled. You cannot delete an event data store if the FederationStatus is ENABLED.

Type: String

Valid Values: ENABLING | ENABLED | DISABLING | DISABLED

KmsKeyId

Specifies the AWS KMS key ID that encrypts the events delivered by CloudTrail. The value is a fully specified ARN to a AWS KMS key in the following format.

```
arn:aws:kms:us-east-2:123456789012:key/12345678-1234-1234-1234-123456789012
```

Type: String

Length Constraints: Minimum length of 1. Maximum length of 350.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

MultiRegionEnabled

Indicates whether the event data store includes events from all Regions, or only from the Region in which it was created.

Type: Boolean

Name

The name of the event data store.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9._\-]+$`

OrganizationEnabled

Indicates whether an event data store is collecting logged events for an organization in AWS Organizations.

Type: Boolean

RetentionPeriod

The retention period, in days.

Type: Integer

Valid Range: Minimum value of 7. Maximum value of 3653.

Status

The status of an event data store.

Type: String

Valid Values: CREATED | ENABLED | PENDING_DELETION | STARTING_INGESTION | STOPPING_INGESTION | STOPPED_INGESTION

TerminationProtectionEnabled

Indicates whether termination protection is enabled for the event data store.

Type: Boolean

UpdatedTimestamp

The timestamp that shows when the event data store was last updated. UpdatedTimestamp is always either the same or newer than the time shown in CreatedTimestamp.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

CloudTrailAccessNotEnabledException

This exception is thrown when trusted access has not been enabled between AWS CloudTrail and AWS Organizations. For more information, see [How to enable or disable trusted access](#) in the *AWS Organizations User Guide* and [Prepare For Creating a Trail For Your Organization](#) in the *AWS CloudTrail User Guide*.

HTTP Status Code: 400

EventDataStoreAlreadyExistsException

An event data store with that name already exists.

HTTP Status Code: 400

EventDataStoreARNInvalidException

The specified event data store ARN is not valid or does not map to an event data store in your account.

HTTP Status Code: 400

EventDataStoreHasOngoingImportException

This exception is thrown when you try to update or delete an event data store that currently has an import in progress.

HTTP Status Code: 400

EventDataStoreNotFoundException

The specified event data store was not found.

HTTP Status Code: 400

InactiveEventDataStoreException

The event data store is inactive.

HTTP Status Code: 400

InsufficientDependencyServiceAccessPermissionException

This exception is thrown when the IAM identity that is used to create the organization resource lacks one or more required permissions for creating an organization resource in a required service.

HTTP Status Code: 400

InsufficientEncryptionPolicyException

This exception is thrown when the policy on the S3 bucket or AWS KMS key does not have sufficient permissions for the operation.

HTTP Status Code: 400

InvalidEventSelectorsException

This exception is thrown when the `PutEventSelectors` operation is called with a number of event selectors, advanced event selectors, or data resources that is not valid. The combination of event selectors or advanced event selectors and data resources is not valid. A trail can have up to 5 event selectors. If a trail uses advanced event selectors, a maximum of 500 total values for all conditions in all advanced event selectors is allowed. A trail is limited to 250 data resources. These data resources can be distributed across event selectors, but the overall total cannot exceed 250.

You can:

- Specify a valid number of event selectors (1 to 5) for a trail.
- Specify a valid number of data resources (1 to 250) for an event selector. The limit of number of resources on an individual event selector is configurable up to 250. However, this upper limit is allowed only if the total number of data resources does not exceed 250 across all event selectors for a trail.
- Specify up to 500 values for all conditions in all advanced event selectors for a trail.
- Specify a valid value for a parameter. For example, specifying the `ReadWriteType` parameter with a value of `read-only` is not valid.

HTTP Status Code: 400

InvalidInsightSelectorsException

For `PutInsightSelectors`, this exception is thrown when the formatting or syntax of the `InsightSelectors` JSON statement is not valid, or the specified `InsightType` in the `InsightSelectors` statement is not valid. Valid values for `InsightType` are `ApiCallRateInsight` and `ApiErrorRateInsight`. To enable Insights on an event data store, the destination event data store specified by the `InsightsDestination` parameter must log Insights events and the source event data store specified by the `EventDataStore` parameter must log management events.

For `UpdateEventDataStore`, this exception is thrown if Insights are enabled on the event data store and the updated advanced event selectors are not compatible with the configured `InsightSelectors`. If the `InsightSelectors` includes an `InsightType` of `ApiCallRateInsight`, the source event data store must log `write` management events. If the `InsightSelectors` includes an `InsightType` of `ApiErrorRateInsight`, the source event data store must log management events.

HTTP Status Code: 400

InvalidKmsKeyIdException

This exception is thrown when the AWS KMS key ARN is not valid.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

KmsException

This exception is thrown when there is an issue with the specified AWS KMS key and the trail or event data store can't be updated.

HTTP Status Code: 400

KmsKeyNotFoundException

This exception is thrown when the AWS KMS key does not exist, when the S3 bucket and the AWS KMS key are not in the same Region, or when the AWS KMS key associated with the Amazon SNS topic either does not exist or is not in the same Region.

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

NotOrganizationMasterAccountException

This exception is thrown when the AWS account making the request to create or update an organization trail or event data store is not the management account for an organization in AWS Organizations. For more information, see [Prepare For Creating a Trail For Your Organization](#) or [Organization event data stores](#).

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

OrganizationNotInAllFeaturesModeException

This exception is thrown when AWS Organizations is not configured to support all features. All features must be enabled in Organizations to support creating an organization trail or event data store.

HTTP Status Code: 400

OrganizationsNotInUseException

This exception is thrown when the request is made from an AWS account that is not a member of an organization. To make this request, sign in using the credentials of an account that belongs to an organization.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateTrail

Updates trail settings that control what events you are logging, and how to handle log files. Changes to a trail do not require stopping the CloudTrail service. Use this action to designate an existing bucket for log delivery. If the existing bucket has previously been a target for CloudTrail log files, an IAM policy exists for the bucket. UpdateTrail must be called from the Region in which the trail was created; otherwise, an `InvalidHomeRegionException` is thrown.

Request Syntax

```
{
  "CloudWatchLogsLogGroupArn": "string",
  "CloudWatchLogsRoleArn": "string",
  "EnableLogFileValidation": boolean,
  "IncludeGlobalServiceEvents": boolean,
  "IsMultiRegionTrail": boolean,
  "IsOrganizationTrail": boolean,
  "KmsKeyId": "string",
  "Name": "string",
  "S3BucketName": "string",
  "S3KeyPrefix": "string",
  "SnsTopicName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

CloudWatchLogsLogGroupArn

Specifies a log group name using an Amazon Resource Name (ARN), a unique identifier that represents the log group to which CloudTrail logs are delivered. You must use a log group that exists in your account.

Not required unless you specify `CloudWatchLogsRoleArn`.

Type: String

Required: No

CloudWatchLogsRoleArn

Specifies the role for the CloudWatch Logs endpoint to assume to write to a user's log group. You must use a role that exists in your account.

Type: String

Required: No

EnableLogFileValidation

Specifies whether log file validation is enabled. The default is false.

Note

When you disable log file integrity validation, the chain of digest files is broken after one hour. CloudTrail does not create digest files for log files that were delivered during a period in which log file integrity validation was disabled. For example, if you enable log file integrity validation at noon on January 1, disable it at noon on January 2, and re-enable it at noon on January 10, digest files will not be created for the log files delivered from noon on January 2 to noon on January 10. The same applies whenever you stop CloudTrail logging or delete a trail.

Type: Boolean

Required: No

IncludeGlobalServiceEvents

Specifies whether the trail is publishing events from global services such as IAM to the log files.

Type: Boolean

Required: No

IsMultiRegionTrail

Specifies whether the trail applies only to the current Region or to all Regions. The default is false. If the trail exists only in the current Region and this value is set to true, shadow trails (replications of the trail) will be created in the other Regions. If the trail exists in all Regions and this value is set to false, the trail will remain in the Region where it was created, and its shadow

trails in other Regions will be deleted. As a best practice, consider using trails that log events in all Regions.

Type: Boolean

Required: No

IsOrganizationTrail

Specifies whether the trail is applied to all accounts in an organization in AWS Organizations, or only for the current AWS account. The default is `false`, and cannot be `true` unless the call is made on behalf of an AWS account that is the management account for an organization in AWS Organizations. If the trail is not an organization trail and this is set to `true`, the trail will be created in all AWS accounts that belong to the organization. If the trail is an organization trail and this is set to `false`, the trail will remain in the current AWS account but be deleted from all member accounts in the organization.

Note

Only the management account for the organization can convert an organization trail to a non-organization trail, or convert a non-organization trail to an organization trail.

Type: Boolean

Required: No

KmsKeyId

Specifies the AWS KMS key ID to use to encrypt the logs delivered by CloudTrail. The value can be an alias name prefixed by "alias/", a fully specified ARN to an alias, a fully specified ARN to a key, or a globally unique identifier.

CloudTrail also supports AWS KMS multi-Region keys. For more information about multi-Region keys, see [Using multi-Region keys](#) in the *AWS Key Management Service Developer Guide*.

Examples:

- `alias/MyAliasName`
- `arn:aws:kms:us-east-2:123456789012:alias/MyAliasName`
- `arn:aws:kms:us-east-2:123456789012:key/12345678-1234-1234-1234-123456789012`

- 12345678-1234-1234-1234-123456789012

Type: String

Required: No

Name

Specifies the name of the trail or trail ARN. If Name is a trail name, the string must meet the following requirements:

- Contain only ASCII letters (a-z, A-Z), numbers (0-9), periods (.), underscores (_), or dashes (-)
- Start with a letter or number, and end with a letter or number
- Be between 3 and 128 characters
- Have no adjacent periods, underscores or dashes. Names like my-__namespace and my--namespace are not valid.
- Not be in IP address format (for example, 192.168.5.4)

If Name is a trail ARN, it must be in the following format.

```
arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail
```

Type: String

Required: Yes

S3BucketName

Specifies the name of the Amazon S3 bucket designated for publishing log files. See [Amazon S3 Bucket naming rules](#).

Type: String

Required: No

S3KeyPrefix

Specifies the Amazon S3 key prefix that comes after the name of the bucket you have designated for log file delivery. For more information, see [Finding Your CloudTrail Log Files](#). The maximum length is 200 characters.

Type: String

Required: No

SnsTopicName

Specifies the name of the Amazon SNS topic defined for notification of log file delivery. The maximum length is 256 characters.

Type: String

Required: No

Response Syntax

```
{
  "CloudWatchLogsLogGroupArn": "string",
  "CloudWatchLogsRoleArn": "string",
  "IncludeGlobalServiceEvents": boolean,
  "IsMultiRegionTrail": boolean,
  "IsOrganizationTrail": boolean,
  "KmsKeyId": "string",
  "LogFileValidationEnabled": boolean,
  "Name": "string",
  "S3BucketName": "string",
  "S3KeyPrefix": "string",
  "SnsTopicARN": "string",
  "SnsTopicName": "string",
  "TrailARN": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CloudWatchLogsLogGroupArn

Specifies the Amazon Resource Name (ARN) of the log group to which CloudTrail logs are delivered.

Type: String

CloudWatchLogsRoleArn

Specifies the role for the CloudWatch Logs endpoint to assume to write to a user's log group.

Type: String

IncludeGlobalServiceEvents

Specifies whether the trail is publishing events from global services such as IAM to the log files.

Type: Boolean

IsMultiRegionTrail

Specifies whether the trail exists in one Region or in all Regions.

Type: Boolean

IsOrganizationTrail

Specifies whether the trail is an organization trail.

Type: Boolean

KmsKeyId

Specifies the AWS KMS key ID that encrypts the logs delivered by CloudTrail. The value is a fully specified ARN to a AWS KMS key in the following format.

```
arn:aws:kms:us-east-2:123456789012:key/12345678-1234-1234-1234-123456789012
```

Type: String

LogFileValidationEnabled

Specifies whether log file integrity validation is enabled.

Type: Boolean

Name

Specifies the name of the trail.

Type: String

S3BucketName

Specifies the name of the Amazon S3 bucket designated for publishing log files.

Type: String

S3KeyPrefix

Specifies the Amazon S3 key prefix that comes after the name of the bucket you have designated for log file delivery. For more information, see [Finding Your IAM Log Files](#).

Type: String

SnsTopicARN

Specifies the ARN of the Amazon SNS topic that CloudTrail uses to send notifications when log files are delivered. The following is the format of a topic ARN.

```
arn:aws:sns:us-east-2:123456789012:MyTopic
```

Type: String

SnsTopicName

This parameter has been deprecated.

This field is no longer in use. Use SnsTopicARN.

Type: String

TrailARN

Specifies the ARN of the trail that was updated. The following is the format of a trail ARN.

```
arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail
```

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

CloudTrailAccessNotEnabledException

This exception is thrown when trusted access has not been enabled between AWS CloudTrail and AWS Organizations. For more information, see [How to enable or disable trusted access](#) in the *AWS Organizations User Guide* and [Prepare For Creating a Trail For Your Organization](#) in the *AWS CloudTrail User Guide*.

HTTP Status Code: 400

CloudTrailARNInvalidException

This exception is thrown when an operation is called with an ARN that is not valid.

The following is the format of a trail ARN: `arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail`

The following is the format of an event data store ARN: `arn:aws:cloudtrail:us-east-2:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE`

The following is the format of a channel ARN: `arn:aws:cloudtrail:us-east-2:123456789012:channel/01234567890`

HTTP Status Code: 400

CloudTrailInvalidClientTokenIdException

This exception is thrown when a call results in the `InvalidClientTokenId` error code. This can occur when you are creating or updating a trail to send notifications to an Amazon SNS topic that is in a suspended AWS account.

HTTP Status Code: 400

CloudWatchLogsDeliveryUnavailableException

Cannot set a CloudWatch Logs delivery for this Region.

HTTP Status Code: 400

ConflictException

This exception is thrown when the specified resource is not ready for an operation. This can occur when you try to run an operation on a resource before CloudTrail has time to fully load the resource, or because another operation is modifying the resource. If this exception occurs, wait a few minutes, and then try the operation again.

HTTP Status Code: 400

InsufficientDependencyServiceAccessPermissionException

This exception is thrown when the IAM identity that is used to create the organization resource lacks one or more required permissions for creating an organization resource in a required service.

HTTP Status Code: 400

InsufficientEncryptionPolicyException

This exception is thrown when the policy on the S3 bucket or AWS KMS key does not have sufficient permissions for the operation.

HTTP Status Code: 400

InsufficientS3BucketPolicyException

This exception is thrown when the policy on the S3 bucket is not sufficient.

HTTP Status Code: 400

InsufficientSnsTopicPolicyException

This exception is thrown when the policy on the Amazon SNS topic is not sufficient.

HTTP Status Code: 400

InvalidCloudWatchLogsLogGroupArnException

This exception is thrown when the provided CloudWatch Logs log group is not valid.

HTTP Status Code: 400

InvalidCloudWatchLogsRoleArnException

This exception is thrown when the provided role is not valid.

HTTP Status Code: 400

InvalidEventSelectorsException

This exception is thrown when the `PutEventSelectors` operation is called with a number of event selectors, advanced event selectors, or data resources that is not valid. The combination of event selectors or advanced event selectors and data resources is not valid. A trail can have up to 5 event selectors. If a trail uses advanced event selectors, a maximum of 500 total values for all conditions in all advanced event selectors is allowed. A trail is limited to 250 data resources. These data resources can be distributed across event selectors, but the overall total cannot exceed 250.

You can:

- Specify a valid number of event selectors (1 to 5) for a trail.

- Specify a valid number of data resources (1 to 250) for an event selector. The limit of number of resources on an individual event selector is configurable up to 250. However, this upper limit is allowed only if the total number of data resources does not exceed 250 across all event selectors for a trail.
- Specify up to 500 values for all conditions in all advanced event selectors for a trail.
- Specify a valid value for a parameter. For example, specifying the `ReadWriteType` parameter with a value of `read-only` is not valid.

HTTP Status Code: 400

InvalidHomeRegionException

This exception is thrown when an operation is called on a trail from a Region other than the Region in which the trail was created.

HTTP Status Code: 400

InvalidKmsKeyIdException

This exception is thrown when the AWS KMS key ARN is not valid.

HTTP Status Code: 400

InvalidParameterCombinationException

This exception is thrown when the combination of parameters provided is not valid.

HTTP Status Code: 400

InvalidParameterException

The request includes a parameter that is not valid.

HTTP Status Code: 400

InvalidS3BucketNameException

This exception is thrown when the provided S3 bucket name is not valid.

HTTP Status Code: 400

InvalidS3PrefixException

This exception is thrown when the provided S3 prefix is not valid.

HTTP Status Code: 400

InvalidSnsTopicNameException

This exception is thrown when the provided SNS topic name is not valid.

HTTP Status Code: 400

InvalidTrailNameException

This exception is thrown when the provided trail name is not valid. Trail names must meet the following requirements:

- Contain only ASCII letters (a-z, A-Z), numbers (0-9), periods (.), underscores (_), or dashes (-)
- Start with a letter or number, and end with a letter or number
- Be between 3 and 128 characters
- Have no adjacent periods, underscores or dashes. Names like my- _namespace and my- - namespace are not valid.
- Not be in IP address format (for example, 192.168.5.4)

HTTP Status Code: 400

KmsException

This exception is thrown when there is an issue with the specified AWS KMS key and the trail or event data store can't be updated.

HTTP Status Code: 400

KmsKeyDisabledException

This error has been deprecated.

This exception is no longer in use.

HTTP Status Code: 400

KmsKeyNotFoundException

This exception is thrown when the AWS KMS key does not exist, when the S3 bucket and the AWS KMS key are not in the same Region, or when the AWS KMS key associated with the Amazon SNS topic either does not exist or is not in the same Region.

HTTP Status Code: 400

NoManagementAccountSLRExistsException

This exception is thrown when the management account does not have a service-linked role.

HTTP Status Code: 400

NotOrganizationMasterAccountException

This exception is thrown when the AWS account making the request to create or update an organization trail or event data store is not the management account for an organization in AWS Organizations. For more information, see [Prepare For Creating a Trail For Your Organization](#) or [Organization event data stores](#).

HTTP Status Code: 400

OperationNotPermittedException

This exception is thrown when the requested operation is not permitted.

HTTP Status Code: 400

OrganizationNotInAllFeaturesModeException

This exception is thrown when AWS Organizations is not configured to support all features. All features must be enabled in Organizations to support creating an organization trail or event data store.

HTTP Status Code: 400

OrganizationsNotInUseException

This exception is thrown when the request is made from an AWS account that is not a member of an organization. To make this request, sign in using the credentials of an account that belongs to an organization.

HTTP Status Code: 400

S3BucketDoesNotExistException

This exception is thrown when the specified S3 bucket does not exist.

HTTP Status Code: 400

ThrottlingException

This exception is thrown when the request rate exceeds the limit.

HTTP Status Code: 400

TrailNotFoundException

This exception is thrown when the trail with the given name is not found.

HTTP Status Code: 400

TrailNotProvidedException

This exception is no longer in use.

HTTP Status Code: 400

UnsupportedOperationException

This exception is thrown when the requested operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS CloudTrail API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AdvancedEventSelector](#)
- [AdvancedFieldSelector](#)
- [Channel](#)
- [DataResource](#)
- [Destination](#)
- [Event](#)
- [EventDataStore](#)
- [EventSelector](#)
- [ImportFailureListItem](#)
- [ImportsListItem](#)
- [ImportSource](#)
- [ImportStatistics](#)
- [IngestionStatus](#)
- [InsightSelector](#)
- [LookupAttribute](#)
- [PartitionKey](#)
- [PublicKey](#)
- [Query](#)
- [QueryStatistics](#)
- [QueryStatisticsForDescribeQuery](#)

- [Resource](#)
- [ResourceTag](#)
- [S3ImportSource](#)
- [SourceConfig](#)
- [Tag](#)
- [Trail](#)
- [TrailInfo](#)

AdvancedEventSelector

Advanced event selectors let you create fine-grained selectors for CloudTrail management and data events. They help you control costs by logging only those events that are important to you. For more information about advanced event selectors, see [Logging management events](#) and [Logging data events](#) in the *AWS CloudTrail User Guide*.

You cannot apply both event selectors and advanced event selectors to a trail.

Supported CloudTrail event record fields for management events

- `eventCategory` (required)
- `eventSource`
- `readOnly`

Supported CloudTrail event record fields for data events

- `eventCategory` (required)
- `resources.type` (required)
- `readOnly`
- `eventName`
- `resources.ARN`

Note

For event data stores for CloudTrail Insights events, AWS Config configuration items, Audit Manager evidence, or events outside of AWS, the only supported field is `eventCategory`.

Contents

FieldSelectors

Contains all selector statements in an advanced event selector.

Type: Array of [AdvancedFieldSelector](#) objects

Array Members: Minimum number of 1 item.

Required: Yes

Name

An optional, descriptive name for an advanced event selector, such as "Log data events for only two S3 buckets".

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Pattern: .*

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AdvancedFieldSelector

A single selector statement in an advanced event selector.

Contents

Field

A field in a CloudTrail event record on which to filter events to be logged. For event data stores for CloudTrail Insights events, AWS Config configuration items, Audit Manager evidence, or events outside of AWS, the field is used only for selecting events as filtering is not supported.

For CloudTrail management events, supported fields include `readOnly`, `eventCategory`, and `eventSource`.

For CloudTrail data events, supported fields include `readOnly`, `eventCategory`, `eventName`, `resources.type`, and `resources.ARN`.

For event data stores for CloudTrail Insights events, AWS Config configuration items, Audit Manager evidence, or events outside of AWS, the only supported field is `eventCategory`.

- **readOnly** - Optional. Can be set to `Equals` a value of `true` or `false`. If you do not add this field, CloudTrail logs both `read` and `write` events. A value of `true` logs only `read` events. A value of `false` logs only `write` events.
- **eventSource** - For filtering management events only. This can be set to `NotEquals kms.amazonaws.com` or `NotEquals rdsdata.amazonaws.com`.
- **eventName** - Can use any operator. You can use it to filter in or filter out any data event logged to CloudTrail, such as `PutBucket` or `GetSnapshotBlock`. You can have multiple values for this field, separated by commas.
- **eventCategory** - This is required and must be set to `Equals`.
 - For CloudTrail management events, the value must be `Management`.
 - For CloudTrail data events, the value must be `Data`.

The following are used only for event data stores:

- For CloudTrail Insights events, the value must be `Insight`.
- For AWS Config configuration items, the value must be `ConfigurationItem`.
- For Audit Manager evidence, the value must be `Evidence`.

- For non-AWS events, the value must be `ActivityAuditLog`.
- **resources.type** - This field is required for CloudTrail data events. `resources.type` can only use the `Equals` operator, and the value can be one of the following:
 - `AWS::DynamoDB::Table`
 - `AWS::Lambda::Function`
 - `AWS::S3::Object`
 - `AWS::AppConfig::Configuration`
 - `AWS::B2BI::Transformer`
 - `AWS::Bedrock::AgentAlias`
 - `AWS::Bedrock::KnowledgeBase`
 - `AWS::Cassandra::Table`
 - `AWS::CloudFront::KeyValueStore`
 - `AWS::CloudTrail::Channel`
 - `AWS::CloudWatch::Metric`
 - `AWS::CodeWhisperer::Customization`
 - `AWS::CodeWhisperer::Profile`
 - `AWS::Cognito::IdentityPool`
 - `AWS::DynamoDB::Stream`
 - `AWS::EC2::Snapshot`
 - `AWS::EMRWAL::Workspace`
 - `AWS::FinSpace::Environment`
 - `AWS::Glue::Table`
 - `AWS::GreengrassV2::ComponentVersion`
 - `AWS::GreengrassV2::Deployment`
 - `AWS::GuardDuty::Detector`
 - `AWS::IoT::Certificate`
 - `AWS::IoT::Thing`
 - `AWS::IoTSiteWise::Asset`
 - `AWS::IoTSiteWise::TimeSeries`
 - `AWS::IoT TwinMaker::Entity`


- `AWS::IoT::IoTTwinMaker::Workspace`
- `AWS::KendraRanking::ExecutionPlan`
- `AWS::Kinesis::Stream`
- `AWS::Kinesis::StreamConsumer`
- `AWS::KinesisVideo::Stream`
- `AWS::MachineLearning::MLModel`
- `AWS::ManagedBlockchain::Network`
- `AWS::ManagedBlockchain::Node`
- `AWS::MedicalImaging::Datastore`
- `AWS::NeptuneGraph::Graph`
- `AWS::PCAConectorAD::Connector`
- `AWS::PCAConectorSCEP::Connector`
- `AWS::QApps::QApp`
- `AWS::QBusiness::Application`
- `AWS::QBusiness::DataSource`
- `AWS::QBusiness::Index`
- `AWS::QBusiness::WebExperience`
- `AWS::RDS::DBCluster`
- `AWS::S3::AccessPoint`
- `AWS::S3ObjectLambda::AccessPoint`
- `AWS::S3Outposts::Object`
- `AWS::SageMaker::Endpoint`
- `AWS::SageMaker::ExperimentTrialComponent`
- `AWS::SageMaker::FeatureGroup`
- `AWS::ServiceDiscovery::Namespace`
- `AWS::ServiceDiscovery::Service`
- `AWS::SCN::Instance`
- `AWS::SNS::PlatformEndpoint`

- `AWS::SQS::Queue`

- `AWS::SSM::ManagedNode`
- `AWS::SSMMessages::ControlChannel`
- `AWS::StepFunctions::StateMachine`
- `AWS::SWF::Domain`
- `AWS::ThinClient::Device`
- `AWS::ThinClient::Environment`
- `AWS::Timestream::Database`
- `AWS::Timestream::Table`
- `AWS::VerifiedPermissions::PolicyStore`
- `AWS::XRay::Trace`

You can have only one `resources.type` field per selector. To log data events on more than one resource type, add another selector.

- **resources.ARN** - You can use any operator with `resources.ARN`, but if you use `Equals` or `NotEquals`, the value must exactly match the ARN of a valid resource of the type you've specified in the template as the value of `resources.type`.

 **Note**

You can't use the `resources.ARN` field to filter resource types that do not have ARNs.

The `resources.ARN` field can be set one of the following.

If `resources.type` equals `AWS::S3::Object`, the ARN must be in one of the following formats. To log all data events for all objects in a specific S3 bucket, use the `StartsWith` operator, and include only the bucket ARN as the matching value.

The trailing slash is intentional; do not exclude it. Replace the text between less than and greater than symbols (<>) with resource-specific information.

- `arn:<partition>:s3:::<bucket_name>/`
- `arn:<partition>:s3:::<bucket_name>/<object_path>/`

When `resources.type` equals `AWS::DynamoDB::Table`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:dynamodb:<region>:<account_ID>:table/<table_name>`

When `resources.type` equals `AWS::Lambda::Function`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:lambda:<region>:<account_ID>:function:<function_name>`

When `resources.type` equals `AWS::AppConfig::Configuration`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:appconfig:<region>:<account_ID>:application/
<application_ID>/environment/<environment_ID>/configuration/
<configuration_profile_ID>`

When `resources.type` equals `AWS::B2BI::Transformer`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:b2bi:<region>:<account_ID>:transformer/
<transformer_ID>`

When `resources.type` equals `AWS::Bedrock::AgentAlias`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:bedrock:<region>:<account_ID>:agent-alias/<agent_ID>/
<alias_ID>`

When `resources.type` equals `AWS::Bedrock::KnowledgeBase`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:bedrock:<region>:<account_ID>:knowledge-base/
<knowledge_base_ID>`

When `resources.type` equals `AWS::Cassandra::Table`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:cassandra:<region>:<account_ID>:/keyspace/
<keyspace_name>/table/<table_name>`

When `resources.type` equals `AWS::CloudFront::KeyValueStore`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:cloudfront:<region>:<account_ID>:key-value-store/<KVS_name>`

When `resources.type` equals `AWS::CloudTrail::Channel`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:cloudtrail:<region>:<account_ID>:channel/<channel_UUID>`

When `resources.type` equals `AWS::CodeWhisperer::Customization`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:codewhisperer:<region>:<account_ID>:customization/<customization_ID>`

When `resources.type` equals `AWS::CodeWhisperer::Profile`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:codewhisperer:<region>:<account_ID>:profile/<profile_ID>`

When `resources.type` equals `AWS::Cognito::IdentityPool`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:cognito-identity:<region>:<account_ID>:identitypool/<identity_pool_ID>`

When `resources.type` equals `AWS::DynamoDB::Stream`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:dynamodb:<region>:<account_ID>:table/<table_name>/stream/<date_time>`

When `resources.type` equals `AWS::EC2::Snapshot`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:ec2:<region>::snapshot/<snapshot_ID>`

When `resources.type` equals `AWS::EMRWAL::Workspace`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:emrwal:<region>:<account_ID>:workspace/<workspace_name>`

When `resources.type` equals `AWS::FinSpace::Environment`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:finspace:<region>:<account_ID>:environment/<environment_ID>`

When `resources.type` equals `AWS::Glue::Table`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:glue:<region>:<account_ID>:table/<database_name>/<table_name>`

When `resources.type` equals `AWS::GreengrassV2::ComponentVersion`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:greengrass:<region>:<account_ID>:components/<component_name>`

When `resources.type` equals `AWS::GreengrassV2::Deployment`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:greengrass:<region>:<account_ID>:deployments/<deployment_ID>`

When `resources.type` equals `AWS::GuardDuty::Detector`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:guardduty:<region>:<account_ID>:detector/<detector_ID>`

When `resources.type` equals `AWS::IoT::Certificate`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:iot:<region>:<account_ID>:cert/<certificate_ID>`

When `resources.type` equals `AWS::IoT::Thing`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:iot:<region>:<account_ID>:thing/<thing_ID>`

When `resources.type` equals `AWS::IoTSiteWise::Asset`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:iotsitewise:<region>:<account_ID>:asset/<asset_ID>`

When `resources.type` equals `AWS::IoTSiteWise::TimeSeries`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:iotsitewise:<region>:<account_ID>:timeseries/<timeseries_ID>`

When `resources.type` equals `AWS::IoTtwinMaker::Entity`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:iottwinmaker:<region>:<account_ID>:workspace/<workspace_ID>/entity/<entity_ID>`

When `resources.type` equals `AWS::IoTtwinMaker::Workspace`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:iottwinmaker:<region>:<account_ID>:workspace/<workspace_ID>`

When `resources.type` equals `AWS::KendraRanking::ExecutionPlan`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:kendra-ranking:<region>:<account_ID>:rescore-execution-plan/<rescore_execution_plan_ID>`

When `resources.type` equals `AWS::Kinesis::Stream`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:kinesis:<region>:<account_ID>:stream/<stream_name>`

When `resources.type` equals `AWS::Kinesis::Stream`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:kinesis:<region>:<account_ID>:<stream_type>/<stream_name>/consumer/<consumer_name>:<consumer_creation_timestamp>`

When `resources.type` equals `AWS::KinesisVideo::Stream`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:kinesisvideo:<region>:<account_ID>:stream/<stream_name>/<creation_time>`

When `resources.type` equals `AWS::MachineLearning::MLModel`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:machinelearning:<region>:<account_ID>:mlmodel/
<model_ID>`

When `resources.type` equals `AWS::ManagedBlockchain::Network`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:managedblockchain:::networks/<network_name>`

When `resources.type` equals `AWS::ManagedBlockchain::Node`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:managedblockchain:<region>:<account_ID>:nodes/
<node_ID>`

When `resources.type` equals `AWS::MedicalImaging::Datastore`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:medical-imaging:<region>:<account_ID>:datastore/
<data_store_ID>`

When `resources.type` equals `AWS::NeptuneGraph::Graph`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:neptune-graph:<region>:<account_ID>:graph/<graph_ID>`

When `resources.type` equals `AWS::PCAConnectorAD::Connector`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:pca-connector-ad:<region>:<account_ID>:connector/
<connector_ID>`

When `resources.type` equals `AWS::PCAConnectorSCEP::Connector`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:pca-connector-scep:<region>:<account_ID>:connector/
<connector_ID>`

When `resources.type` equals `AWS::QApps::QApp`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:qapps:<region>:<account_ID>:application/
<application_UUID>/qapp/<qapp_UUID>`

When `resources.type` equals `AWS::QBusiness::Application`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:qbusiness:<region>:<account_ID>:application/<application_ID>`

When `resources.type` equals `AWS::QBusiness::DataSource`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:qbusiness:<region>:<account_ID>:application/<application_ID>/index/<index_ID>/data-source/<datasource_ID>`

When `resources.type` equals `AWS::QBusiness::Index`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:qbusiness:<region>:<account_ID>:application/<application_ID>/index/<index_ID>`

When `resources.type` equals `AWS::QBusiness::WebExperience`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:qbusiness:<region>:<account_ID>:application/<application_ID>/web-experience/<web_experience_ID>`

When `resources.type` equals `AWS::RDS::DBCluster`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:rds:<region>:<account_ID>:cluster/<cluster_name>`

When `resources.type` equals `AWS::S3::AccessPoint`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in one of the following formats. To log events on all objects in an S3 access point, we recommend that you use only the access point ARN, don't include the object path, and use the `StartsWith` or `NotStartsWith` operators.

- `arn:<partition>:s3:<region>:<account_ID>:accesspoint/<access_point_name>`
- `arn:<partition>:s3:<region>:<account_ID>:accesspoint/<access_point_name>/object/<object_path>`

When `resources.type` equals `AWS::S3ObjectLambda::AccessPoint`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:s3-object-lambda:<region>:<account_ID>:accesspoint/<access_point_name>`

When `resources.type` equals `AWS::S3Outposts::Object`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:s3-outposts:<region>:<account_ID>:<object_path>`

When `resources.type` equals `AWS::SageMaker::Endpoint`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:sagemaker:<region>:<account_ID>:endpoint/<endpoint_name>`

When `resources.type` equals `AWS::SageMaker::ExperimentTrialComponent`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:sagemaker:<region>:<account_ID>:experiment-trial-component/<experiment_trial_component_name>`

When `resources.type` equals `AWS::SageMaker::FeatureGroup`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:sagemaker:<region>:<account_ID>:feature-group/<feature_group_name>`

When `resources.type` equals `AWS::SCN::Instance`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:scn:<region>:<account_ID>:instance/<instance_ID>`

When `resources.type` equals `AWS::ServiceDiscovery::Namespace`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:servicediscovery:<region>:<account_ID>:namespace/<namespace_ID>`

When `resources.type` equals `AWS::ServiceDiscovery::Service`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:servicediscovery:<region>:<account_ID>:service/<service_ID>`

When `resources.type` equals `AWS::SNS::PlatformEndpoint`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:sns:<region>:<account_ID>:endpoint/<endpoint_type>/<endpoint_name>/<endpoint_ID>`

When `resources.type` equals `AWS::SNS::Topic`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:sns:<region>:<account_ID>:<topic_name>`

When `resources.type` equals `AWS::SQS::Queue`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:sqs:<region>:<account_ID>:<queue_name>`

When `resources.type` equals `AWS::SSM::ManagedNode`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in one of the following formats:

- `arn:<partition>:ssm:<region>:<account_ID>:managed-instance/<instance_ID>`
- `arn:<partition>:ec2:<region>:<account_ID>:instance/<instance_ID>`

When `resources.type` equals `AWS::SSMMessages::ControlChannel`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:ssmmessages:<region>:<account_ID>:control-channel/<channel_ID>`

When `resources.type` equals `AWS::StepFunctions::StateMachine`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in one of the following formats:

- `arn:<partition>:states:<region>:<account_ID>:stateMachine:<stateMachine_name>`
- `arn:<partition>:states:<region>:<account_ID>:stateMachine:<stateMachine_name>:<label_name>`

When `resources.type` equals `AWS::SWF::Domain`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:swf:<region>:<account_ID>:domain/<domain_name>`

When `resources.type` equals `AWS::ThinClient::Device`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:thinclient:<region>:<account_ID>:device/<device_ID>`

When `resources.type` equals `AWS::ThinClient::Environment`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:thinclient:<region>:<account_ID>:environment/<environment_ID>`

When `resources.type` equals `AWS::Timestream::Database`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:timestream:<region>:<account_ID>:database/<database_name>`

When `resources.type` equals `AWS::Timestream::Table`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:timestream:<region>:<account_ID>:database/<database_name>/table/<table_name>`

When `resources.type` equals `AWS::VerifiedPermissions::PolicyStore`, and the operator is set to `Equals` or `NotEquals`, the ARN must be in the following format:

- `arn:<partition>:verifiedpermissions:<region>:<account_ID>:policy-store/<policy_store_UUID>`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `[\w|\d|\.|_]+`

Required: Yes

EndsWith

An operator that includes events that match the last few characters of the event record field specified as the value of `Field`.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: . +

Required: No

Equals

An operator that includes events that match the exact value of the event record field specified as the value of `Field`. This is the only valid operator that you can use with the `readOnly`, `eventCategory`, and `resources.type` fields.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: . +

Required: No

NotEndsWith

An operator that excludes events that match the last few characters of the event record field specified as the value of `Field`.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: . +

Required: No

NotEquals

An operator that excludes events that match the exact value of the event record field specified as the value of `Field`.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: . +

Required: No

NotStartsWith

An operator that excludes events that match the first few characters of the event record field specified as the value of `Field`.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: . +

Required: No

StartsWith

An operator that includes events that match the first few characters of the event record field specified as the value of `Field`.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: . +

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Channel

Contains information about a returned CloudTrail channel.

Contents

ChannelArn

The Amazon Resource Name (ARN) of a channel.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: No

Name

The name of the CloudTrail channel. For service-linked channels, the name is `aws-service-channel/service-name/custom-suffix` where `service-name` represents the name of the AWS service that created the channel and `custom-suffix` represents the suffix created by the AWS service.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9._\-]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DataResource

Data events provide information about the resource operations performed on or within a resource itself. These are also known as data plane operations. You can specify up to 250 data resources for a trail.

Configure the `DataResource` to specify the resource type and resource ARNs for which you want to log data events.

You can specify the following resource types in your event selectors for your trail:

- `AWS::DynamoDB::Table`
- `AWS::Lambda::Function`
- `AWS::S3::Object`

Note

The total number of allowed data resources is 250. This number can be distributed between 1 and 5 event selectors, but the total cannot exceed 250 across all selectors for the trail.

If you are using advanced event selectors, the maximum total number of values for all conditions, across all advanced event selectors for the trail, is 500.

The following example demonstrates how logging works when you configure logging of all data events for an S3 bucket named `DOC-EXAMPLE-BUCKET1`. In this example, the CloudTrail user specified an empty prefix, and the option to log both `Read` and `Write` data events.

1. A user uploads an image file to `DOC-EXAMPLE-BUCKET1`.
2. The `PutObject` API operation is an Amazon S3 object-level API. It is recorded as a data event in CloudTrail. Because the CloudTrail user specified an S3 bucket with an empty prefix, events that occur on any object in that bucket are logged. The trail processes and logs the event.
3. A user uploads an object to an Amazon S3 bucket named `arn:aws:s3:::DOC-EXAMPLE-BUCKET1`.
4. The `PutObject` API operation occurred for an object in an S3 bucket that the CloudTrail user didn't specify for the trail. The trail doesn't log the event.

The following example demonstrates how logging works when you configure logging of AWS Lambda data events for a Lambda function named *MyLambdaFunction*, but not for all Lambda functions.

1. A user runs a script that includes a call to the *MyLambdaFunction* function and the *MyOtherLambdaFunction* function.
2. The Invoke API operation on *MyLambdaFunction* is an Lambda API. It is recorded as a data event in CloudTrail. Because the CloudTrail user specified logging data events for *MyLambdaFunction*, any invocations of that function are logged. The trail processes and logs the event.
3. The Invoke API operation on *MyOtherLambdaFunction* is an Lambda API. Because the CloudTrail user did not specify logging data events for all Lambda functions, the Invoke operation for *MyOtherLambdaFunction* does not match the function specified for the trail. The trail doesn't log the event.

Contents

Type

The resource type in which you want to log data events. You can specify the following *basic* event selector resource types:

- `AWS::DynamoDB::Table`
- `AWS::Lambda::Function`
- `AWS::S3::Object`

Additional resource types are available through *advanced* event selectors. For more information about these additional resource types, see [AdvancedFieldSelector](#).

Type: String

Required: No

Values

An array of Amazon Resource Name (ARN) strings or partial ARN strings for the specified resource type.

- To log data events for all objects in all S3 buckets in your AWS account, specify the prefix as `arn:aws:s3`.

Note

This also enables logging of data event activity performed by any user or role in your AWS account, even if that activity is performed on a bucket that belongs to another AWS account.

- To log data events for all objects in an S3 bucket, specify the bucket and an empty object prefix such as `arn:aws:s3:::DOC-EXAMPLE-BUCKET1/`. The trail logs data events for all objects in this S3 bucket.
- To log data events for specific objects, specify the S3 bucket and object prefix such as `arn:aws:s3:::DOC-EXAMPLE-BUCKET1/example-images`. The trail logs data events for objects in this S3 bucket that match the prefix.
- To log data events for all Lambda functions in your AWS account, specify the prefix as `arn:aws:lambda`.

Note

This also enables logging of Invoke activity performed by any user or role in your AWS account, even if that activity is performed on a function that belongs to another AWS account.

- To log data events for a specific Lambda function, specify the function ARN.

Note

Lambda function ARNs are exact. For example, if you specify a function ARN `arn:aws:lambda:us-west-2:111111111111:function:helloworld`, data events will only be logged for `arn:aws:lambda:us-west-2:111111111111:function:helloworld`. They will not be logged for `arn:aws:lambda:us-west-2:111111111111:function:helloworld2`.

- To log data events for all DynamoDB tables in your AWS account, specify the prefix as `arn:aws:dynamodb`.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Destination

Contains information about the destination receiving events.

Contents

Location

For channels used for a CloudTrail Lake integration, the location is the ARN of an event data store that receives events from a channel. For service-linked channels, the location is the name of the AWS service.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 1024.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: Yes

Type

The type of destination for events arriving from a channel. For channels used for a CloudTrail Lake integration, the value is `EVENT_DATA_STORE`. For service-linked channels, the value is `AWS_SERVICE`.

Type: String

Valid Values: `EVENT_DATA_STORE` | `AWS_SERVICE`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Event

Contains information about an event that was returned by a lookup request. The result includes a representation of a CloudTrail event.

Contents

AccessKeyId

The AWS access key ID that was used to sign the request. If the request was made with temporary security credentials, this is the access key ID of the temporary credentials.

Type: String

Required: No

CloudTrailEvent

A JSON string that contains a representation of the event returned.

Type: String

Required: No

EventId

The CloudTrail ID of the event returned.

Type: String

Required: No

EventName

The name of the event returned.

Type: String

Required: No

EventSource

The AWS service to which the request was made.

Type: String

Required: No

EventTime

The date and time of the event returned.

Type: Timestamp

Required: No

ReadOnly

Information about whether the event is a write event or a read event.

Type: String

Required: No

Resources

A list of resources referenced by the event returned.

Type: Array of [Resource](#) objects

Required: No

Username

A user name or role name of the requester that called the API in the event returned.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EventDataStore

A storage lake of event data against which you can run complex SQL-based queries. An event data store can include events that you have logged on your account. To select events for an event data store, use [advanced event selectors](#).

Contents

AdvancedEventSelectors

This member has been deprecated.

The advanced event selectors that were used to select events for the data store.

Type: Array of [AdvancedEventSelector](#) objects

Required: No

CreatedTimestamp

This member has been deprecated.

The timestamp of the event data store's creation.

Type: Timestamp

Required: No

EventDataStoreArn

The ARN of the event data store.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: No

MultiRegionEnabled

This member has been deprecated.

Indicates whether the event data store includes events from all Regions, or only from the Region in which it was created.

Type: Boolean

Required: No

Name

The name of the event data store.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9._\ -]+$`

Required: No

OrganizationEnabled

This member has been deprecated.

Indicates that an event data store is collecting logged events for an organization.

Type: Boolean

Required: No

RetentionPeriod

This member has been deprecated.

The retention period, in days.

Type: Integer

Valid Range: Minimum value of 7. Maximum value of 3653.

Required: No

Status

This member has been deprecated.

The status of an event data store.

Type: String

Valid Values: CREATED | ENABLED | PENDING_DELETION | STARTING_INGESTION | STOPPING_INGESTION | STOPPED_INGESTION

Required: No

TerminationProtectionEnabled

This member has been deprecated.

Indicates whether the event data store is protected from termination.

Type: Boolean

Required: No

UpdatedTimestamp

This member has been deprecated.

The timestamp showing when an event data store was updated, if applicable.

UpdatedTimestamp is always either the same or newer than the time shown in CreatedTimestamp.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EventSelector

Use event selectors to further specify the management and data event settings for your trail. By default, trails created without specific event selectors will be configured to log all read and write management events, and no data events. When an event occurs in your account, CloudTrail evaluates the event selector for all trails. For each trail, if the event matches any event selector, the trail processes and logs the event. If the event doesn't match any event selector, the trail doesn't log the event.

You can configure up to five event selectors for a trail.

You cannot apply both event selectors and advanced event selectors to a trail.

Contents

DataResources

CloudTrail supports data event logging for Amazon S3 objects, AWS Lambda functions, and Amazon DynamoDB tables with basic event selectors. You can specify up to 250 resources for an individual event selector, but the total number of data resources cannot exceed 250 across all event selectors in a trail. This limit does not apply if you configure resource logging for all data events.

For more information, see [Data Events](#) and [Limits in AWS CloudTrail](#) in the *AWS CloudTrail User Guide*.

Type: Array of [DataResource](#) objects

Required: No

ExcludeManagementEventSources

An optional list of service event sources from which you do not want management events to be logged on your trail. In this release, the list can be empty (disables the filter), or it can filter out AWS Key Management Service or Amazon RDS Data API events by containing `kms.amazonaws.com` or `rdsdata.amazonaws.com`. By default, `ExcludeManagementEventSources` is empty, and AWS KMS and Amazon RDS Data API events are logged to your trail. You can exclude management event sources only in Regions that support the event source.

Type: Array of strings

Required: No

IncludeManagementEvents

Specify if you want your event selector to include management events for your trail.

For more information, see [Management Events](#) in the *AWS CloudTrail User Guide*.

By default, the value is `true`.

The first copy of management events is free. You are charged for additional copies of management events that you are logging on any subsequent trail in the same Region. For more information about CloudTrail pricing, see [AWS CloudTrail Pricing](#).

Type: Boolean

Required: No

ReadWriteType

Specify if you want your trail to log read-only events, write-only events, or all. For example, the EC2 `GetConsoleOutput` is a read-only API operation and `RunInstances` is a write-only API operation.

By default, the value is `All`.

Type: String

Valid Values: `ReadOnly` | `WriteOnly` | `All`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImportFailureListItem

Provides information about an import failure.

Contents

ErrorMessage

Provides the reason the import failed.

Type: String

Required: No

ErrorType

The type of import error.

Type: String

Required: No

LastUpdatedTime

When the import was last updated.

Type: Timestamp

Required: No

Location

The location of the failure in the S3 bucket.

Type: String

Required: No

Status

The status of the import.

Type: String

Valid Values: FAILED | RETRY | SUCCEEDED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImportsListItem

Contains information about an import that was returned by a lookup request.

Contents

CreatedTimestamp

The timestamp of the import's creation.

Type: Timestamp

Required: No

Destinations

The ARN of the destination event data store.

Type: Array of strings

Array Members: Fixed number of 1 item.

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `^[a-zA-Z0-9._/\-:]+$`

Required: No

ImportId

The ID of the import.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[a-f0-9\ -]+$`

Required: No

ImportStatus

The status of the import.

Type: String

Valid Values: INITIALIZING | IN_PROGRESS | FAILED | STOPPED | COMPLETED

Required: No

UpdatedTimestamp

The timestamp of the import's last update.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImportSource

The import source.

Contents

S3

The source S3 bucket.

Type: [S3ImportSource](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImportStatistics

Provides statistics for the specified ImportID. CloudTrail does not update import statistics in real-time. Returned values for parameters such as EventsCompleted may be lower than the actual value, because CloudTrail updates statistics incrementally over the course of the import.

Contents

EventsCompleted

The number of trail events imported into the event data store.

Type: Long

Required: No

FailedEntries

The number of failed entries.

Type: Long

Required: No

FilesCompleted

The number of log files that completed import.

Type: Long

Required: No

PrefixesCompleted

The number of S3 prefixes that completed import.

Type: Long

Required: No

PrefixesFound

The number of S3 prefixes found for the import.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IngestionStatus

A table showing information about the most recent successful and failed attempts to ingest events.

Contents

LatestIngestionAttemptEventID

The event ID of the most recent attempt to ingest events.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[a-f0-9\ -]+$`

Required: No

LatestIngestionAttemptTime

The time stamp of the most recent attempt to ingest events on the channel.

Type: Timestamp

Required: No

LatestIngestionErrorCode

The error code for the most recent failure to ingest events.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1000.

Pattern: `.*`

Required: No

LatestIngestionSuccessEventID

The event ID of the most recent successful ingestion of events.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[a-f0-9\-]+`

Required: No

LatestIngestionSuccessTime

The time stamp of the most recent successful ingestion of events for the channel.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InsightSelector

A JSON string that contains a list of Insights types that are logged on a trail or event data store.

Contents

InsightType

The type of Insights events to log on a trail or event data store. `ApiCallRateInsight` and `ApiErrorRateInsight` are valid Insight types.

The `ApiCallRateInsight` Insights type analyzes write-only management API calls that are aggregated per minute against a baseline API call volume.

The `ApiErrorRateInsight` Insights type analyzes management API calls that result in error codes. The error is shown if the API call is unsuccessful.

Type: String

Valid Values: `ApiCallRateInsight` | `ApiErrorRateInsight`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LookupAttribute

Specifies an attribute and value that filter the events returned.

Contents

AttributeKey

Specifies an attribute on which to filter the events returned.

Type: String

Valid Values: EventId | EventName | ReadOnly | Username | ResourceType | ResourceName | EventSource | AccessKeyId

Required: Yes

AttributeValue

Specifies a value for the specified `AttributeKey`.

The maximum length for the `AttributeValue` is 2000 characters. The following characters ('_', ' ', ',', '\n') count as two characters towards the 2000 character limit.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PartitionKey

Contains information about a partition key for an event data store.

Contents

Name

The name of the partition key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDC00-\uDBFF\uDFFF\t]*`

Required: Yes

Type

The data type of the partition key. For example, `bigint` or `string`.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDC00-\uDBFF\uDFFF\t]*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PublicKey

Contains information about a returned public key.

Contents

Fingerprint

The fingerprint of the public key.

Type: String

Required: No

ValidityEndTime

The ending time of validity of the public key.

Type: Timestamp

Required: No

ValidityStartTime

The starting time of validity of the public key.

Type: Timestamp

Required: No

Value

The DER encoded public key value in PKCS#1 format.

Type: Base64-encoded binary data object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Query

A SQL string of criteria about events that you want to collect in an event data store.

Contents

CreationTime

The creation time of a query.

Type: Timestamp

Required: No

QueryId

The ID of a query.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[a-f0-9\ -]+$`

Required: No

QueryStatus

The status of the query. This can be QUEUED, RUNNING, FINISHED, FAILED, TIMED_OUT, or CANCELLED.

Type: String

Valid Values: QUEUED | RUNNING | FINISHED | FAILED | CANCELLED | TIMED_OUT

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

QueryStatistics

Metadata about a query, such as the number of results.

Contents

BytesScanned

The total bytes that the query scanned in the event data store. This value matches the number of bytes for which your account is billed for the query, unless the query is still running.

Type: Long

Required: No

ResultsCount

The number of results returned.

Type: Integer

Required: No

TotalResultsCount

The total number of results returned by a query.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

QueryStatisticsForDescribeQuery

Gets metadata about a query, including the number of events that were matched, the total number of events scanned, the query run time in milliseconds, and the query's creation time.

Contents

BytesScanned

The total bytes that the query scanned in the event data store. This value matches the number of bytes for which your account is billed for the query, unless the query is still running.

Type: Long

Required: No

CreationTime

The creation time of the query.

Type: Timestamp

Required: No

EventsMatched

The number of events that matched a query.

Type: Long

Required: No

EventsScanned

The number of events that the query scanned in the event data store.

Type: Long

Required: No

ExecutionTimeInMillis

The query's run time, in milliseconds.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Resource

Specifies the type and name of a resource referenced by an event.

Contents

ResourceName

The name of the resource referenced by the event returned. These are user-created names whose values will depend on the environment. For example, the resource name might be "auto-scaling-test-group" for an Auto Scaling Group or "i-1234567" for an EC2 Instance.

Type: String

Required: No

ResourceType

The type of a resource referenced by the event returned. When the resource type cannot be determined, null is returned. Some examples of resource types are: **Instance** for EC2, **Trail** for CloudTrail, **DBInstance** for Amazon RDS, and **AccessKey** for IAM. To learn more about how to look up and filter events by the resource types supported for a service, see [Filtering CloudTrail Events](#).

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceTag

A resource tag.

Contents

ResourceId

Specifies the ARN of the resource.

Type: String

Required: No

TagsList

A list of tags.

Type: Array of [Tag](#) objects

Array Members: Maximum number of 200 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3ImportSource

The settings for the source S3 bucket.

Contents

S3BucketAccessRoleArn

The IAM ARN role used to access the source S3 bucket.

Type: String

Required: Yes

S3BucketRegion

The Region associated with the source S3 bucket.

Type: String

Required: Yes

S3LocationUri

The URI for the source S3 bucket.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SourceConfig

Contains configuration information about the channel.

Contents

AdvancedEventSelectors

The advanced event selectors that are configured for the channel.

Type: Array of [AdvancedEventSelector](#) objects

Required: No

ApplyToAllRegions

Specifies whether the channel applies to a single Region or to all Regions.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

A custom key-value pair associated with a resource such as a CloudTrail trail, event data store, or channel.

Contents

Key

The key in a key-value pair. The key must be no longer than 128 Unicode characters. The key must be unique for the resource to which it applies.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Value

The value in a key-value pair of a tag. The value must be no longer than 256 Unicode characters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Trail

The settings for a trail.

Contents

CloudWatchLogsLogGroupArn

Specifies an Amazon Resource Name (ARN), a unique identifier that represents the log group to which CloudTrail logs will be delivered.

Type: String

Required: No

CloudWatchLogsRoleArn

Specifies the role for the CloudWatch Logs endpoint to assume to write to a user's log group.

Type: String

Required: No

HasCustomEventSelectors

Specifies if the trail has custom event selectors.

Type: Boolean

Required: No

HasInsightSelectors

Specifies whether a trail has insight types specified in an `InsightSelector` list.

Type: Boolean

Required: No

HomeRegion

The Region in which the trail was created.

Type: String

Required: No

IncludeGlobalServiceEvents

Set to **True** to include AWS API calls from AWS global services such as IAM. Otherwise, **False**.

Type: Boolean

Required: No

IsMultiRegionTrail

Specifies whether the trail exists only in one Region or exists in all Regions.

Type: Boolean

Required: No

IsOrganizationTrail

Specifies whether the trail is an organization trail.

Type: Boolean

Required: No

KmsKeyId

Specifies the AWS KMS key ID that encrypts the logs delivered by CloudTrail. The value is a fully specified ARN to a AWS KMS key in the following format.

```
arn:aws:kms:us-east-2:123456789012:key/12345678-1234-1234-1234-123456789012
```

Type: String

Required: No

LogFileValidationEnabled

Specifies whether log file validation is enabled.

Type: Boolean

Required: No

Name

Name of the trail set by calling [CreateTrail](#). The maximum length is 128 characters.

Type: String

Required: No

S3BucketName

Name of the Amazon S3 bucket into which CloudTrail delivers your trail files. See [Amazon S3 Bucket naming rules](#).

Type: String

Required: No

S3KeyPrefix

Specifies the Amazon S3 key prefix that comes after the name of the bucket you have designated for log file delivery. For more information, see [Finding Your CloudTrail Log Files](#). The maximum length is 200 characters.

Type: String

Required: No

SnsTopicARN

Specifies the ARN of the Amazon SNS topic that CloudTrail uses to send notifications when log files are delivered. The following is the format of a topic ARN.

```
arn:aws:sns:us-east-2:123456789012:MyTopic
```

Type: String

Required: No

SnsTopicName

This member has been deprecated.

This field is no longer in use. Use SnsTopicARN.

Type: String

Required: No

TrailARN

Specifies the ARN of the trail. The following is the format of a trail ARN.

```
arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail
```

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrailInfo

Information about a CloudTrail trail, including the trail's name, home Region, and Amazon Resource Name (ARN).

Contents

HomeRegion

The AWS Region in which a trail was created.

Type: String

Required: No

Name

The name of a trail.

Type: String

Required: No

TrailARN

The ARN of a trail.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400