



API Reference

# AWS Directory Service



# AWS Directory Service: API Reference

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

---

# Table of Contents

<b>Welcome</b> .....	<b>1</b>
<b>Actions</b> .....	<b>2</b>
AcceptSharedDirectory .....	5
Request Syntax .....	5
Request Parameters .....	5
Response Syntax .....	5
Response Elements .....	6
Errors .....	6
See Also .....	7
AddIpRoutes .....	8
Request Syntax .....	8
Request Parameters .....	8
Response Elements .....	10
Errors .....	10
Examples .....	11
See Also .....	12
AddRegion .....	13
Request Syntax .....	13
Request Parameters .....	13
Response Elements .....	14
Errors .....	14
See Also .....	15
AddTagsToResource .....	17
Request Syntax .....	17
Request Parameters .....	17
Response Elements .....	18
Errors .....	18
Examples .....	18
See Also .....	19
CancelSchemaExtension .....	21
Request Syntax .....	21
Request Parameters .....	21
Response Elements .....	21
Errors .....	22

---

Examples .....	22
See Also .....	23
ConnectDirectory .....	24
Request Syntax .....	24
Request Parameters .....	24
Response Syntax .....	26
Response Elements .....	26
Errors .....	26
Examples .....	27
See Also .....	28
CreateAlias .....	30
Request Syntax .....	30
Request Parameters .....	30
Response Syntax .....	31
Response Elements .....	31
Errors .....	31
Examples .....	32
See Also .....	33
CreateComputer .....	35
Request Syntax .....	35
Request Parameters .....	35
Response Syntax .....	36
Response Elements .....	37
Errors .....	37
Examples .....	38
See Also .....	40
CreateConditionalForwarder .....	41
Request Syntax .....	41
Request Parameters .....	41
Response Elements .....	42
Errors .....	42
Examples .....	43
See Also .....	44
CreateDirectory .....	45
Request Syntax .....	45
Request Parameters .....	45

---

Response Syntax .....	47
Response Elements .....	47
Errors .....	48
Examples .....	48
See Also .....	50
CreateLogSubscription .....	51
Request Syntax .....	51
Request Parameters .....	51
Response Elements .....	51
Errors .....	52
See Also .....	52
CreateMicrosoftAD .....	54
Request Syntax .....	54
Request Parameters .....	54
Response Syntax .....	56
Response Elements .....	56
Errors .....	57
Examples .....	57
See Also .....	59
CreateSnapshot .....	60
Request Syntax .....	60
Request Parameters .....	60
Response Syntax .....	61
Response Elements .....	61
Errors .....	61
Examples .....	62
See Also .....	63
CreateTrust .....	64
Request Syntax .....	64
Request Parameters .....	64
Response Syntax .....	66
Response Elements .....	66
Errors .....	66
Examples .....	67
See Also .....	68
DeleteConditionalForwarder .....	70

---

Request Syntax .....	70
Request Parameters .....	70
Response Elements .....	70
Errors .....	71
Examples .....	71
See Also .....	72
DeleteDirectory .....	74
Request Syntax .....	74
Request Parameters .....	74
Response Syntax .....	74
Response Elements .....	74
Errors .....	75
Examples .....	75
See Also .....	76
DeleteLogSubscription .....	78
Request Syntax .....	78
Request Parameters .....	78
Response Elements .....	78
Errors .....	78
See Also .....	79
DeleteSnapshot .....	80
Request Syntax .....	80
Request Parameters .....	80
Response Syntax .....	80
Response Elements .....	80
Errors .....	81
Examples .....	81
See Also .....	82
DeleteTrust .....	84
Request Syntax .....	84
Request Parameters .....	84
Response Syntax .....	84
Response Elements .....	85
Errors .....	85
Examples .....	86
See Also .....	87

DeregisterCertificate .....	88
Request Syntax .....	88
Request Parameters .....	88
Response Elements .....	88
Errors .....	89
See Also .....	90
DeregisterEventTopic .....	91
Request Syntax .....	91
Request Parameters .....	91
Response Elements .....	91
Errors .....	92
Examples .....	92
See Also .....	93
DescribeCertificate .....	95
Request Syntax .....	95
Request Parameters .....	95
Response Syntax .....	95
Response Elements .....	96
Errors .....	96
See Also .....	97
DescribeClientAuthenticationSettings .....	98
Request Syntax .....	98
Request Parameters .....	98
Response Syntax .....	99
Response Elements .....	99
Errors .....	100
See Also .....	101
DescribeConditionalForwarders .....	102
Request Syntax .....	102
Request Parameters .....	102
Response Syntax .....	103
Response Elements .....	103
Errors .....	103
Examples .....	104
See Also .....	105
DescribeDirectories .....	107

Request Syntax .....	107
Request Parameters .....	107
Response Syntax .....	108
Response Elements .....	110
Errors .....	110
Examples .....	111
See Also .....	113
<b>DescribeDomainControllers .....</b>	<b>114</b>
Request Syntax .....	114
Request Parameters .....	114
Response Syntax .....	115
Response Elements .....	115
Errors .....	116
See Also .....	117
<b>DescribeEventTopics .....</b>	<b>118</b>
Request Syntax .....	118
Request Parameters .....	118
Response Syntax .....	119
Response Elements .....	119
Errors .....	119
Examples .....	120
See Also .....	121
<b>DescribeLDAPSSettings .....</b>	<b>122</b>
Request Syntax .....	122
Request Parameters .....	122
Response Syntax .....	123
Response Elements .....	123
Errors .....	124
See Also .....	124
<b>DescribeRegions .....</b>	<b>126</b>
Request Syntax .....	126
Request Parameters .....	126
Response Syntax .....	127
Response Elements .....	127
Errors .....	128
See Also .....	129



---

DescribeSettings .....	130
Request Syntax .....	130
Request Parameters .....	130
Response Syntax .....	131
Response Elements .....	131
Errors .....	132
See Also .....	133
DescribeSharedDirectories .....	134
Request Syntax .....	134
Request Parameters .....	134
Response Syntax .....	135
Response Elements .....	135
Errors .....	136
See Also .....	137
DescribeSnapshots .....	138
Request Syntax .....	138
Request Parameters .....	138
Response Syntax .....	139
Response Elements .....	139
Errors .....	140
Examples .....	141
See Also .....	142
DescribeTrusts .....	143
Request Syntax .....	143
Request Parameters .....	143
Response Syntax .....	144
Response Elements .....	144
Errors .....	145
Examples .....	146
See Also .....	147
DescribeUpdateDirectory .....	148
Request Syntax .....	148
Request Parameters .....	148
Response Syntax .....	149
Response Elements .....	149
Errors .....	150

---

See Also .....	151
DisableClientAuthentication .....	152
Request Syntax .....	152
Request Parameters .....	152
Response Elements .....	152
Errors .....	153
See Also .....	153
DisableLDAPS .....	155
Request Syntax .....	155
Request Parameters .....	155
Response Elements .....	155
Errors .....	155
See Also .....	156
DisableRadius .....	158
Request Syntax .....	158
Request Parameters .....	158
Response Elements .....	158
Errors .....	158
Examples .....	159
See Also .....	160
DisableSso .....	161
Request Syntax .....	161
Request Parameters .....	161
Response Elements .....	162
Errors .....	162
Examples .....	163
See Also .....	164
EnableClientAuthentication .....	165
Request Syntax .....	165
Request Parameters .....	165
Response Elements .....	165
Errors .....	166
See Also .....	167
EnableLDAPS .....	168
Request Syntax .....	168
Request Parameters .....	168

Response Elements .....	168
Errors .....	168
See Also .....	170
EnableRadius .....	171
Request Syntax .....	171
Request Parameters .....	171
Response Elements .....	172
Errors .....	172
Examples .....	172
See Also .....	174
EnableSso .....	175
Request Syntax .....	175
Request Parameters .....	175
Response Elements .....	176
Errors .....	176
Examples .....	177
See Also .....	178
GetDirectoryLimits .....	179
Response Syntax .....	179
Response Elements .....	179
Errors .....	179
Examples .....	180
See Also .....	181
GetSnapshotLimits .....	182
Request Syntax .....	182
Request Parameters .....	182
Response Syntax .....	182
Response Elements .....	182
Errors .....	183
Examples .....	183
See Also .....	184
ListCertificates .....	186
Request Syntax .....	186
Request Parameters .....	186
Response Syntax .....	187
Response Elements .....	187

Errors .....	187
See Also .....	188
ListIpRoutes .....	190
Request Syntax .....	190
Request Parameters .....	190
Response Syntax .....	191
Response Elements .....	191
Errors .....	191
Examples .....	192
See Also .....	193
ListLogSubscriptions .....	195
Request Syntax .....	195
Request Parameters .....	195
Response Syntax .....	196
Response Elements .....	196
Errors .....	196
See Also .....	197
ListSchemaExtensions .....	198
Request Syntax .....	198
Request Parameters .....	198
Response Syntax .....	199
Response Elements .....	199
Errors .....	199
Examples .....	200
See Also .....	201
ListTagsForResource .....	203
Request Syntax .....	203
Request Parameters .....	203
Response Syntax .....	204
Response Elements .....	204
Errors .....	204
Examples .....	205
See Also .....	206
RegisterCertificate .....	207
Request Syntax .....	207
Request Parameters .....	207

---

Response Syntax .....	208
Response Elements .....	208
Errors .....	208
See Also .....	210
RegisterEventTopic .....	211
Request Syntax .....	211
Request Parameters .....	211
Response Elements .....	212
Errors .....	212
Examples .....	212
See Also .....	213
RejectSharedDirectory .....	215
Request Syntax .....	215
Request Parameters .....	215
Response Syntax .....	215
Response Elements .....	215
Errors .....	216
See Also .....	216
RemoveIpRoutes .....	218
Request Syntax .....	218
Request Parameters .....	218
Response Elements .....	218
Errors .....	219
Examples .....	219
See Also .....	220
RemoveRegion .....	222
Request Syntax .....	222
Request Parameters .....	222
Response Elements .....	222
Errors .....	222
See Also .....	223
RemoveTagsFromResource .....	224
Request Syntax .....	224
Request Parameters .....	224
Response Elements .....	224
Errors .....	225

---

Examples .....	225
See Also .....	226
ResetUserPassword .....	228
Request Syntax .....	228
Request Parameters .....	228
Response Elements .....	229
Errors .....	229
See Also .....	230
RestoreFromSnapshot .....	231
Request Syntax .....	231
Request Parameters .....	231
Response Elements .....	231
Errors .....	231
Examples .....	232
See Also .....	233
ShareDirectory .....	234
Request Syntax .....	234
Request Parameters .....	234
Response Syntax .....	235
Response Elements .....	236
Errors .....	236
See Also .....	237
StartSchemaExtension .....	239
Request Syntax .....	239
Request Parameters .....	239
Response Syntax .....	240
Response Elements .....	240
Errors .....	240
Examples .....	241
See Also .....	243
UnshareDirectory .....	244
Request Syntax .....	244
Request Parameters .....	244
Response Syntax .....	244
Response Elements .....	245
Errors .....	245

---

See Also .....	246
UpdateConditionalForwarder .....	247
Request Syntax .....	247
Request Parameters .....	247
Response Elements .....	248
Errors .....	248
Examples .....	249
See Also .....	250
UpdateDirectorySetup .....	251
Request Syntax .....	251
Request Parameters .....	251
Response Elements .....	252
Errors .....	252
See Also .....	253
UpdateNumberOfDomainControllers .....	255
Request Syntax .....	255
Request Parameters .....	255
Response Elements .....	255
Errors .....	256
See Also .....	257
UpdateRadius .....	258
Request Syntax .....	258
Request Parameters .....	258
Response Elements .....	259
Errors .....	259
Examples .....	259
See Also .....	260
UpdateSettings .....	262
Request Syntax .....	262
Request Parameters .....	262
Response Syntax .....	262
Response Elements .....	263
Errors .....	263
See Also .....	264
UpdateTrust .....	265
Request Syntax .....	265

---

Request Parameters .....	265
Response Syntax .....	265
Response Elements .....	266
Errors .....	266
See Also .....	267
VerifyTrust .....	268
Request Syntax .....	268
Request Parameters .....	268
Response Syntax .....	268
Response Elements .....	268
Errors .....	269
Examples .....	269
See Also .....	270
<b>Data Types .....</b>	<b>272</b>
Attribute .....	274
Contents .....	274
See Also .....	274
Certificate .....	275
Contents .....	275
See Also .....	276
CertificateInfo .....	277
Contents .....	277
See Also .....	278
ClientAuthenticationSettingInfo .....	279
Contents .....	279
See Also .....	279
ClientCertAuthSettings .....	281
Contents .....	281
See Also .....	281
Computer .....	282
Contents .....	282
See Also .....	282
ConditionalForwarder .....	284
Contents .....	284
See Also .....	285
DirectoryConnectSettings .....	286



Contents .....	286
See Also .....	287
DirectoryConnectSettingsDescription .....	288
Contents .....	288
See Also .....	289
DirectoryDescription .....	290
Contents .....	290
See Also .....	295
DirectoryLimits .....	297
Contents .....	297
See Also .....	298
DirectoryVpcSettings .....	300
Contents .....	300
See Also .....	300
DirectoryVpcSettingsDescription .....	301
Contents .....	301
See Also .....	302
DomainController .....	303
Contents .....	303
See Also .....	305
EventTopic .....	306
Contents .....	306
See Also .....	307
IpRoute .....	308
Contents .....	308
See Also .....	308
IpRouteInfo .....	310
Contents .....	310
See Also .....	311
LDAPSSettingInfo .....	312
Contents .....	312
See Also .....	312
LogSubscription .....	313
Contents .....	313
See Also .....	313
OSUpdateSettings .....	315

---

Contents .....	315
See Also .....	315
OwnerDirectoryDescription .....	316
Contents .....	316
See Also .....	317
RadiusSettings .....	318
Contents .....	318
See Also .....	320
RegionDescription .....	321
Contents .....	321
See Also .....	322
RegionsInfo .....	324
Contents .....	324
See Also .....	324
SchemaExtensionInfo .....	325
Contents .....	325
See Also .....	326
Setting .....	327
Contents .....	327
See Also .....	327
SettingEntry .....	329
Contents .....	329
See Also .....	331
SharedDirectory .....	332
Contents .....	332
See Also .....	334
ShareTarget .....	335
Contents .....	335
See Also .....	335
Snapshot .....	336
Contents .....	336
See Also .....	337
SnapshotLimits .....	338
Contents .....	338
See Also .....	338
Tag .....	340

---

Contents .....	340
See Also .....	340
Trust .....	342
Contents .....	342
See Also .....	344
UnshareTarget .....	345
Contents .....	345
See Also .....	345
UpdateInfoEntry .....	346
Contents .....	346
See Also .....	347
UpdateValue .....	348
Contents .....	348
See Also .....	348
<b>CloudTrail Logging .....</b>	<b>349</b>
AWS Directory Service Information in CloudTrail .....	349
Understanding AWS Directory Service Log File Entries .....	350
<b>Common Errors .....</b>	<b>352</b>
<b>Document History .....</b>	<b>354</b>

# Welcome to the AWS Directory Service API Reference

AWS Directory Service is a web service that makes it easy for you to setup and run directories in the AWS cloud, or connect your AWS resources with an existing self-managed Microsoft Active Directory (located in the cloud or on-premises). This guide provides detailed information about AWS Directory Service operations, data types, parameters, and errors. For information about AWS Directory Service features, see [AWS Directory Service](#) and the [AWS Directory Service Administration Guide](#).

## Note

AWS provides SDKs that consist of libraries and sample code for various programming languages and platforms (Java, Ruby, .Net, iOS, Android, etc.). The SDKs provide a convenient way to create programmatic access to AWS Directory Service and other AWS services. For more information about the AWS SDKs, including how to download and install them, see [Tools for Amazon Web Services](#).

# Actions

The following actions are supported:

- [AcceptSharedDirectory](#)
- [AddIpRoutes](#)
- [AddRegion](#)
- [AddTagsToResource](#)
- [CancelSchemaExtension](#)
- [ConnectDirectory](#)
- [CreateAlias](#)
- [CreateComputer](#)
- [CreateConditionalForwarder](#)
- [CreateDirectory](#)
- [CreateLogSubscription](#)
- [CreateMicrosoftAD](#)
- [CreateSnapshot](#)
- [CreateTrust](#)
- [DeleteConditionalForwarder](#)
- [DeleteDirectory](#)
- [DeleteLogSubscription](#)
- [DeleteSnapshot](#)
- [DeleteTrust](#)
- [DeregisterCertificate](#)
- [DeregisterEventTopic](#)
- [DescribeCertificate](#)
- [DescribeClientAuthenticationSettings](#)
- [DescribeConditionalForwarders](#)
- [DescribeDirectories](#)
- [DescribeDomainControllers](#)
- [DescribeEventTopics](#)

- [DescribeLDAPSSettings](#)
- [DescribeRegions](#)
- [DescribeSettings](#)
- [DescribeSharedDirectories](#)
- [DescribeSnapshots](#)
- [DescribeTrusts](#)
- [DescribeUpdateDirectory](#)
- [DisableClientAuthentication](#)
- [DisableLDAPS](#)
- [DisableRadius](#)
- [DisableSso](#)
- [EnableClientAuthentication](#)
- [EnableLDAPS](#)
- [EnableRadius](#)
- [EnableSso](#)
- [GetDirectoryLimits](#)
- [GetSnapshotLimits](#)
- [ListCertificates](#)
- [ListIpRoutes](#)
- [ListLogSubscriptions](#)
- [ListSchemaExtensions](#)
- [ListTagsForResource](#)
- [RegisterCertificate](#)
- [RegisterEventTopic](#)
- [RejectSharedDirectory](#)
- [RemoveIpRoutes](#)
- [RemoveRegion](#)
- [RemoveTagsFromResource](#)
- [ResetUserPassword](#)
- [RestoreFromSnapshot](#)

- [ShareDirectory](#)
- [StartSchemaExtension](#)
- [UnshareDirectory](#)
- [UpdateConditionalForwarder](#)
- [UpdateDirectorySetup](#)
- [UpdateNumberOfDomainControllers](#)
- [UpdateRadius](#)
- [UpdateSettings](#)
- [UpdateTrust](#)
- [VerifyTrust](#)

# AcceptSharedDirectory

Accepts a directory sharing request that was sent from the directory owner account.

## Request Syntax

```
{  
  "SharedDirectoryId": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### SharedDirectoryId

Identifier of the shared directory in the directory consumer account. This identifier is different for each directory owner account.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

## Response Syntax

```
{  
  "SharedDirectory": {  
    "CreatedDateTime": number,  
    "LastUpdatedDateTime": number,  
    "OwnerAccountId": "string",  
    "OwnerDirectoryId": "string",  
    "SharedAccountId": "string",  
    "SharedDirectoryId": "string",  
    "ShareMethod": "string",  
    "ShareNotes": "string",  
    "ShareStatus": "string"  
  }  
}
```



## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### SharedDirectory

The shared directory in the directory consumer account.

Type: [SharedDirectory](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **DirectoryAlreadySharedException**

The specified directory has already been shared with this AWS account.

HTTP Status Code: 400

### **EntityDoesNotExistException**

The specified entity could not be found.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# AddIpRoutes

If the DNS server for your self-managed domain uses a publicly addressable IP address, you must add a CIDR address block to correctly route traffic to and from your Microsoft AD on Amazon Web Services. *AddIpRoutes* adds this address block. You can also use *AddIpRoutes* to facilitate routing traffic that uses public IP ranges from your Microsoft AD on AWS to a peer VPC.

Before you call *AddIpRoutes*, ensure that all of the required permissions have been explicitly granted through a policy. For details about what permissions are required to run the *AddIpRoutes* operation, see [AWS Directory Service API Permissions: Actions, Resources, and Conditions Reference](#).

## Request Syntax

```
{
  "DirectoryId": "string",
  "IpRoutes": [
    {
      "CidrIp": "string",
      "Description": "string"
    }
  ],
  "UpdateSecurityGroupForDirectoryControllers": boolean
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

Identifier (ID) of the directory to which to add the address block.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

## IpRoutes

IP address blocks, using CIDR format, of the traffic to route. This is often the IP address block of the DNS server used for your self-managed domain.

Type: Array of [IpRoute](#) objects

Required: Yes

## UpdateSecurityGroupForDirectoryControllers

If set to true, updates the inbound and outbound rules of the security group that has the description: "AWS created security group for *directory ID* directory controllers." Following are the new rules:

Inbound:

- Type: Custom UDP Rule, Protocol: UDP, Range: 88, Source: 0.0.0.0/0
- Type: Custom UDP Rule, Protocol: UDP, Range: 123, Source: 0.0.0.0/0
- Type: Custom UDP Rule, Protocol: UDP, Range: 138, Source: 0.0.0.0/0
- Type: Custom UDP Rule, Protocol: UDP, Range: 389, Source: 0.0.0.0/0
- Type: Custom UDP Rule, Protocol: UDP, Range: 464, Source: 0.0.0.0/0
- Type: Custom UDP Rule, Protocol: UDP, Range: 445, Source: 0.0.0.0/0
- Type: Custom TCP Rule, Protocol: TCP, Range: 88, Source: 0.0.0.0/0
- Type: Custom TCP Rule, Protocol: TCP, Range: 135, Source: 0.0.0.0/0
- Type: Custom TCP Rule, Protocol: TCP, Range: 445, Source: 0.0.0.0/0
- Type: Custom TCP Rule, Protocol: TCP, Range: 464, Source: 0.0.0.0/0
- Type: Custom TCP Rule, Protocol: TCP, Range: 636, Source: 0.0.0.0/0
- Type: Custom TCP Rule, Protocol: TCP, Range: 1024-65535, Source: 0.0.0.0/0
- Type: Custom TCP Rule, Protocol: TCP, Range: 3268-33269, Source: 0.0.0.0/0
- Type: DNS (UDP), Protocol: UDP, Range: 53, Source: 0.0.0.0/0
- Type: DNS (TCP), Protocol: TCP, Range: 53, Source: 0.0.0.0/0
- Type: LDAP, Protocol: TCP, Range: 389, Source: 0.0.0.0/0
- Type: All ICMP, Protocol: All, Range: N/A, Source: 0.0.0.0/0

Outbound:

- Type: All traffic, Protocol: All, Range: All, Destination: 0.0.0.0/0

These security rules impact an internal network interface that is not exposed publicly.

Type: Boolean

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ClientException

A client exception has occurred.

HTTP Status Code: 400

### DirectoryUnavailableException

The specified directory is unavailable or could not be found.

HTTP Status Code: 400

### EntityAlreadyExistsException

The specified entity already exists.

HTTP Status Code: 400

### EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

### InvalidParameterException

One or more parameters are not valid.

HTTP Status Code: 400

## IpRouteLimitExceededException

The maximum allowed number of IP addresses was exceeded. The default limit is 100 IP address blocks.

HTTP Status Code: 400

## ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of `AddIpRoutes`.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 98
X-Amz-Target: DirectoryService_20150416.AddIpRoutes
X-Amz-Date: 20161212T212029Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161212/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=477f3a2802dcc303f69499723eb2e29a455fe3d1b646df0dacfd7c005a3a9509

{
  "DirectoryId": "d-926example",
  "IpRoutes": [
    {
      "Description": "my IpRoute",
      "CidrIp": "12.12.12.12/32"
    }
  ]
}
```

## Example Response

This example illustrates one usage of AddIpRoutes.

```
HTTP/1.1 200 OK
x-amzn-RequestId: cfc1cbc8-c0b0-11e6-aa44-41d91ee57463
Content-Type: application/x-amz-json-1.1
Content-Length: 2
Date: Mon, 12 Dec 2016 21:20:31 GMT

{
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# AddRegion

Adds two domain controllers in the specified Region for the specified directory.

## Request Syntax

```
{
  "DirectoryId": "string",
  "RegionName": "string",
  "VPCSettings": {
    "SubnetIds": [ "string" ],
    "VpcId": "string"
  }
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The identifier of the directory to which you want to add Region replication.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### RegionName

The name of the Region where you want to add domain controllers for replication. For example, `us-east-1`.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 32.

Required: Yes

### VPCSettings

Contains VPC information for the [CreateDirectory](#) or [CreateMicrosoftAD](#) operation.



Type: [DirectoryVpcSettings](#) object

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

Client authentication is not available in this region at this time.

HTTP Status Code: 400

### ClientException

A client exception has occurred.

HTTP Status Code: 400

### DirectoryAlreadyInRegionException

The Region you specified is the same Region where the AWS Managed Microsoft AD directory was created. Specify a different Region and try again.

HTTP Status Code: 400

### DirectoryDoesNotExistException

The specified directory does not exist in the system.

HTTP Status Code: 400

### DirectoryUnavailableException

The specified directory is unavailable or could not be found.

HTTP Status Code: 400

### EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

### **RegionLimitExceededException**

You have reached the limit for maximum number of simultaneous Region replications per directory.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

### **UnsupportedOperationException**

The operation is not supported.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# AddTagsToResource

Adds or overwrites one or more tags for the specified directory. Each directory can have a maximum of 50 tags. Each tag consists of a key and optional value. Tag keys must be unique to each resource.

## Request Syntax

```
{
  "ResourceId": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

## Request Parameters

The request accepts the following data in JSON format.

### ResourceId

Identifier (ID) for the directory to which to add the tag.

Type: String

Pattern: `^[d]-[0-9a-f]{10}$`

Required: Yes

### Tags

The tags to be assigned to the directory.

Type: Array of [Tag](#) objects

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ClientException

A client exception has occurred.

HTTP Status Code: 400

### EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

### InvalidParameterException

One or more parameters are not valid.

HTTP Status Code: 400

### ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

### TagLimitExceededException

The maximum allowed number of tags was exceeded.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of `AddTagsToResource`.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 87
X-Amz-Target: DirectoryService_20150416.AddTagsToResource
X-Amz-Date: 20161212T222805Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 boto-core/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161212/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=2756d8b256b5e6b3d74879557e4f421d21111510a78c6c3650a7a93809d533c4

{
  "ResourceId": "d-926example",
  "Tags": [
    {
      "Key": "environment",
      "Value": "production"
    }
  ]
}
```

## Example Response

This example illustrates one usage of `AddTagsToResource`.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 419ff1d5-c0ba-11e6-9ed0-172b3469d361
Content-Type: application/x-amz-json-1.1
Content-Length: 2
Date: Mon, 12 Dec 2016 22:28:07 GMT

{
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CancelSchemaExtension

Cancels an in-progress schema extension to a Microsoft AD directory. Once a schema extension has started replicating to all domain controllers, the task can no longer be canceled. A schema extension can be canceled during any of the following states; `Initializing`, `CreatingSnapshot`, and `UpdatingSchema`.

## Request Syntax

```
{
  "DirectoryId": "string",
  "SchemaExtensionId": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The identifier of the directory whose schema extension will be canceled.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### SchemaExtensionId

The identifier of the schema extension that will be canceled.

Type: String

Pattern: `^e-[0-9a-f]{10}$`

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.



## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ClientException

A client exception has occurred.

HTTP Status Code: 400

### EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

### ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of CancelSchemaExtension.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 68
X-Amz-Target: DirectoryService_20150416.CancelSchemaExtension
X-Amz-Date: 20161212T231630Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161212/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=14da7b7426d03c907c02a3e29f96158b8c1cd2be2e0f323a86b338a1614848f1
```

```
{
  "DirectoryId": "d-926example",
  "SchemaExtensionId": "e-926731d2a0"
}
```

## Example Response

This example illustrates one usage of `CancelSchemaExtension`.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 04eada50-c0c1-11e6-887b-29887bf36843
Content-Type: application/x-amz-json-1.1
Content-Length: 2
Date: Mon, 12 Dec 2016 23:16:32 GMT
```

```
{
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ConnectDirectory

Creates an AD Connector to connect to a self-managed directory.

Before you call `ConnectDirectory`, ensure that all of the required permissions have been explicitly granted through a policy. For details about what permissions are required to run the `ConnectDirectory` operation, see [AWS Directory Service API Permissions: Actions, Resources, and Conditions Reference](#).

## Request Syntax

```
{
  "ConnectSettings": {
    "CustomerDnsIps": [ "string" ],
    "CustomerUserName": "string",
    "SubnetIds": [ "string" ],
    "VpcId": "string"
  },
  "Description": "string",
  "Name": "string",
  "Password": "string",
  "ShortName": "string",
  "Size": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

## Request Parameters

The request accepts the following data in JSON format.

### ConnectSettings

A [DirectoryConnectSettings](#) object that contains additional information for the operation.

Type: [DirectoryConnectSettings](#) object

Required: Yes

## Description

A description for the directory.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `^([a-zA-Z0-9_])[\a-zA-Z0-9_@#%*+=:?./!\s-]*$`

Required: No

## Name

The fully qualified name of your self-managed directory, such as `corp.example.com`.

Type: String

Pattern: `^([a-zA-Z0-9]+[\.\-])+( [a-zA-Z0-9] )+$`

Required: Yes

## Password

The password for your self-managed user account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

## ShortName

The NetBIOS name of your self-managed directory, such as `CORP`.

Type: String

Pattern: `^[^\\\/:*?"<>|.]+[^\\/:*?"<>|]*$`

Required: No

## Size

The size of the directory.

Type: String

Valid Values: Small | Large

Required: Yes

### Tags

The tags to be assigned to AD Connector.

Type: Array of [Tag](#) objects

Required: No

## Response Syntax

```
{  
  "DirectoryId": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### DirectoryId

The identifier of the new directory.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

## DirectoryLimitExceededException

The maximum number of directories in the region has been reached. You can use the [GetDirectoryLimits](#) operation to determine your directory limits in the region.

HTTP Status Code: 400

## InvalidParameterException

One or more parameters are not valid.

HTTP Status Code: 400

## ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of ConnectDirectory.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 295
X-Amz-Target: DirectoryService_20150416.ConnectDirectory
X-Amz-Date: 20161212T233740Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161212/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=60ddfa4a90d91327ef8cb510563d6f031eab1b092d5b1034fab7b157733bf86b

{
  "Name": "corp.example.com",
  "ConnectSettings": {
    "CustomerUserName": "Administrator",
```

```
    "VpcId": "vpc-45025421",
    "SubnetIds": [
      "subnet-ba0146de",
      "subnet-bef46bc8"
    ],
    "CustomerDnsIps": [
      "172.30.21.228"
    ]
  },
  "Description": "Connector to corp",
  "ShortName": "corp",
  "Password": "Str0ngP@ssw0rd",
  "Size": "Small"
}
```

## Example Response

This example illustrates one usage of ConnectDirectory.

```
HTTP/1.1 200 OK
x-amzn-RequestId: fa22d0f1-c0c3-11e6-9ed0-172b3469d361
Content-Type: application/x-amz-json-1.1
Content-Length: 30
Date: Mon, 12 Dec 2016 23:37:43 GMT

{
  "DirectoryId": "d-926example"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# CreateAlias

Creates an alias for a directory and assigns the alias to the directory. The alias is used to construct the access URL for the directory, such as `http://<alias>.awsapps.com`.

## Important

After an alias has been created, it cannot be deleted or reused, so this operation should only be used when absolutely necessary.

## Request Syntax

```
{
  "Alias": "string",
  "DirectoryId": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### Alias

The requested alias.

The alias must be unique amongst all aliases in AWS. This operation throws an `EntityAlreadyExistsException` error if the alias already exists.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 62.

Pattern: `^(?!D-|d-)([\da-zA-Z]+)([-]*[\da-zA-Z])*`

Required: Yes

### DirectoryId

The identifier of the directory for which to create the alias.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

## Response Syntax

```
{  
  "Alias": "string",  
  "DirectoryId": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [Alias](#)

The alias for the directory.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 62.

Pattern: `^(?!D-|d-)([\da-zA-Z]+)([-]*[\da-zA-Z])*`

### [DirectoryId](#)

The identifier of the directory.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## ClientException

A client exception has occurred.

HTTP Status Code: 400

## EntityAlreadyExistsException

The specified entity already exists.

HTTP Status Code: 400

## EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

## InvalidParameterException

One or more parameters are not valid.

HTTP Status Code: 400

## ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of `CreateAlias`.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 52X-Amz-Target:DirectoryService_20150416.CreateAlias
X-Amz-Date: 20161209T175951Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
```

```
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161209/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=673029721752b71c1ff4752d0e42e6a05283c305238538d746c2b42d7864ec11

{
  "DirectoryId": "d-926example",
  "Alias": "myaccess"
}
```

## Example Response

This example illustrates one usage of `CreateAlias`.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 49abfbf6-be39-11e6-9458-41d91ee57463
Content-Type: application/x-amz-json-1.1
Content-Length: 49
Date: Fri, 09 Dec 2016 17:59:57 GMT

{
  "Alias": "myaccess",
  "DirectoryId": "d-926example"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# CreateComputer

Creates an Active Directory computer object in the specified directory.

## Request Syntax

```
{
  "ComputerAttributes": [
    {
      "Name": "string",
      "Value": "string"
    }
  ],
  "ComputerName": "string",
  "DirectoryId": "string",
  "OrganizationalUnitDistinguishedName": "string",
  "Password": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### ComputerAttributes

An array of [Attribute](#) objects that contain any LDAP attributes to apply to the computer account.

Type: Array of [Attribute](#) objects

Required: No

### ComputerName

The name of the computer account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 15.

Required: Yes

## DirectoryId

The identifier of the directory in which to create the computer account.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

## OrganizationalUnitDistinguishedName

The fully-qualified distinguished name of the organizational unit to place the computer account in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Required: No

## Password

A one-time password that is used to join the computer to the directory. You should generate a random, strong password to use for this parameter.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 64.

Pattern: `[\u0020-\u00FF]+`

Required: Yes

## Response Syntax

```
{
  "Computer": {
    "ComputerAttributes": [
      {
        "Name": "string",
        "Value": "string"
      }
    ]
  }
}
```

```
    ],  
    "ComputerId": "string",  
    "ComputerName": "string"  
  }  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Computer

A [Computer](#) object that represents the computer account.

Type: [Computer](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AuthenticationFailedException**

An authentication error occurred.

HTTP Status Code: 400

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **DirectoryUnavailableException**

The specified directory is unavailable or could not be found.

HTTP Status Code: 400

### **EntityAlreadyExistsException**

The specified entity already exists.



HTTP Status Code: 400

### **EntityDoesNotExistException**

The specified entity could not be found.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

### **UnsupportedOperationException**

The operation is not supported.

HTTP Status Code: 400

## **Examples**

The following examples are formatted for legibility.

### **Example Request**

This example illustrates one usage of CreateComputer.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 245
X-Amz-Target: DirectoryService_20150416.CreateComputer
X-Amz-Date: 20161213T163452Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161213/us-west-2/ds/aws4_request,
```

```
SignedHeaders=content-type;host;x-amz-date;x-amz-target,
Signature=5fa12f147bce3620568504361b860de07868da3b1c27d5f0bde6e5ffa51bf6ef

{
  "DirectoryId":"d-926example",
  "ComputerName":"labcomputer",
  "Password":"Str0ngP@ssw0rd",
  "ComputerAttributes":[
    {
      "Name":"ip",
      "Value":"192.168.101.100"
    }
  ],
  "OrganizationalUnitDistinguishedName":"OU=Computers,OU=example,DC=corp,DC=example,DC=com"
}
```

## Example Response

This example illustrates one usage of CreateComputer.

```
HTTP/1.1 200 OK
x-amzn-RequestId: afcea813-c196-11e6-a6a8-5110402a26c3
Content-Type: application/x-amz-json-1.1
Content-Length: 286
Date: Wed, 14 Dec 2016 00:46:03 GMT

{
  "Computer":{
    "ComputerAttributes":[
      {
        "Name":"DistinguishedName",
        "Value":"CN=labcomputer,OU=Computers,OU=example,DC=corp,DC=example,DC=com"
      },
      {
        "Name":"WindowsSamName",
        "Value":"labcomputer$"
      }
    ],
    "ComputerId":"S-1-5-21-1932691875-1648176379-1176097576-1124",
    "ComputerName":"labcomputer"
  }
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateConditionalForwarder

Creates a conditional forwarder associated with your AWS directory. Conditional forwarders are required in order to set up a trust relationship with another domain. The conditional forwarder points to the trusted domain.

## Request Syntax

```
{
  "DirectoryId": "string",
  "DnsIpAddr": [ "string" ],
  "RemoteDomainName": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The directory ID of the AWS directory for which you are creating the conditional forwarder.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### DnsIpAddr

The IP addresses of the remote DNS server associated with RemoteDomainName.

Type: Array of strings

Pattern: `^(?:(:25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)\.){3}(?:25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)$`

Required: Yes

### RemoteDomainName

The fully qualified domain name (FQDN) of the remote domain with which you will set up a trust relationship.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^([a-zA-Z0-9]+[\\.\-])+([a-zA-Z0-9])+[.]?$`

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ClientException

A client exception has occurred.

HTTP Status Code: 400

### DirectoryUnavailableException

The specified directory is unavailable or could not be found.

HTTP Status Code: 400

### EntityAlreadyExistsException

The specified entity already exists.

HTTP Status Code: 400

### EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

### InvalidParameterException

One or more parameters are not valid.

HTTP Status Code: 400

### ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

### UnsupportedOperationException

The operation is not supported.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of `CreateConditionalForwarder`.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 105
X-Amz-Target: DirectoryService_20150416.CreateConditionalForwarder
X-Amz-Date: 20161213T215543Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161213/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=717e381f0258731fe0197c68d1f5d2a0e96825119c15a6e0dcfa2d07063c6af6

{
  "DirectoryId": "d-926example",
  "RemoteDomainName": "sales.example.com",
  "DnsIpAddrs": [
    "172.30.21.228"
  ]
}
```

## Example Response

This example illustrates one usage of `CreateConditionalForwarder`.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 68e74443-c180-11e6-91f4-6dbff6648f8a
Content-Type: application/x-amz-json-1.1
Content-Length: 2
Date: Tue, 13 Dec 2016 22:06:34 GMT

{

}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateDirectory

Creates a Simple AD directory. For more information, see [Simple Active Directory](#) in the *AWS Directory Service Admin Guide*.

Before you call `CreateDirectory`, ensure that all of the required permissions have been explicitly granted through a policy. For details about what permissions are required to run the `CreateDirectory` operation, see [AWS Directory Service API Permissions: Actions, Resources, and Conditions Reference](#).

## Request Syntax

```
{
  "Description": "string",
  "Name": "string",
  "Password": "string",
  "ShortName": "string",
  "Size": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "VpcSettings": {
    "SubnetIds": [ "string" ],
    "VpcId": "string"
  }
}
```

## Request Parameters

The request accepts the following data in JSON format.

### Description

A description for the directory.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.



Pattern: `^[a-zA-Z0-9_][\\a-zA-Z0-9_@#%*+=:?./!\s-]*$`

Required: No

### Name

The fully qualified name for the directory, such as `corp.example.com`.

Type: String

Pattern: `^[a-zA-Z0-9]+[\\.-]+([a-zA-Z0-9])+$`

Required: Yes

### Password

The password for the directory administrator. The directory creation process creates a directory administrator account with the user name `Administrator` and this password.

If you need to change the password for the administrator account, you can use the [ResetUserPassword](#) API call.

The regex pattern for this string is made up of the following conditions:

- Length `(?=^.{8,64}$)` – Must be between 8 and 64 characters

AND any 3 of the following password complexity rules required by Active Directory:

- Numbers and upper case and lowercase `(?=.*\d)(?=.*[A-Z])(?=.*[a-z])`
- Numbers and special characters and lower case `(?=.*\d)(?=.*[^A-Za-z0-9\s])(?=.*[a-z])`
- Special characters and upper case and lower case `(?=.*[^A-Za-z0-9\s])(?=.*[A-Z])(?=.*[a-z])`
- Numbers and upper case and special characters `(?=.*\d)(?=.*[A-Z])(?=.*[^A-Za-z0-9\s])`

For additional information about how Active Directory passwords are enforced, see [Password must meet complexity requirements](#) on the Microsoft website.

Type: String

Pattern: `(?=^.{8,64}$)((?=.*\d)(?=.*[A-Z])(?=.*[a-z])|(?=.*\d)(?=.*[^A-Za-z0-9\s])(?=.*[a-z])|(?=.*[^A-Za-z0-9\s])(?=.*[A-Z])(?=.*[a-z])|(?=.*\d)(?=.*[A-Z])(?=.*[^A-Za-z0-9\s]))^.*`

Required: Yes

## ShortName

The NetBIOS name of the directory, such as CORP.

Type: String

Pattern: `^[^\\\/:*?"<>|.]+[^\\/:*?"<>|]*$`

Required: No

## Size

The size of the directory.

Type: String

Valid Values: `Small` | `Large`

Required: Yes

## Tags

The tags to be assigned to the Simple AD directory.

Type: Array of [Tag](#) objects

Required: No

## VpcSettings

A [DirectoryVpcSettings](#) object that contains additional information for the operation.

Type: [DirectoryVpcSettings](#) object

Required: No

## Response Syntax

```
{
  "DirectoryId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **DirectoryId**

The identifier of the directory that was created.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

## **Errors**

For information about the errors that are common to all actions, see [Common Errors](#).

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **DirectoryLimitExceededException**

The maximum number of directories in the region has been reached. You can use the [GetDirectoryLimits](#) operation to determine your directory limits in the region.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## **Examples**

The following examples are formatted for legibility.

## Example Request

This example illustrates one usage of CreateDirectory.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 245
X-Amz-Target: DirectoryService_20150416.CreateDirectory
X-Amz-Date: 20161213T222613Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 boto/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161213/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=e0bf599277231d294b0ebb1c7ad7a68aafdfc49db016adbee32a167954c53d54

{
  "Description": "Regional directory for example.com",
  "VpcSettings": {
    "SubnetIds": [
      "subnet-ba0146de",
      "subnet-bef46bc8"
    ],
    "VpcId": "vpc-45025421"
  },
  "Name": "seattle.example.com",
  "ShortName": "seattle",
  "Password": "Str0ngP@ssw0rd",
  "Size": "Small"
}
```

## Example Response

This example illustrates one usage of CreateDirectory.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 298112b6-c183-11e6-9b49-eff49203d13b
Content-Type: application/x-amz-json-1.1
Content-Length: 30
Date: Tue, 13 Dec 2016 22:26:17 GMT

{
```

```
"DirectoryId": "d-926example"  
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateLogSubscription

Creates a subscription to forward real-time Directory Service domain controller security logs to the specified Amazon CloudWatch log group in your AWS account.

## Request Syntax

```
{  
  "DirectoryId": "string",  
  "LogGroupName": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

Identifier of the directory to which you want to subscribe and receive real-time logs to your specified CloudWatch log group.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### LogGroupName

The name of the CloudWatch log group where the real-time domain controller logs are forwarded.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `[-. _/#A-Za-z0-9]+`

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **EntityAlreadyExistsException**

The specified entity already exists.

HTTP Status Code: 400

### **EntityDoesNotExistException**

The specified entity could not be found.

HTTP Status Code: 400

### **InsufficientPermissionsException**

The account does not have sufficient permission to perform the operation.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

### **UnsupportedOperationException**

The operation is not supported.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# CreateMicrosoftAD

Creates a Microsoft AD directory in the AWS Cloud. For more information, see [AWS Managed Microsoft AD](#) in the *AWS Directory Service Admin Guide*.

Before you call `CreateMicrosoftAD`, ensure that all of the required permissions have been explicitly granted through a policy. For details about what permissions are required to run the `CreateMicrosoftAD` operation, see [AWS Directory Service API Permissions: Actions, Resources, and Conditions Reference](#).

## Request Syntax

```
{
  "Description": "string",
  "Edition": "string",
  "Name": "string",
  "Password": "string",
  "ShortName": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "VpcSettings": {
    "SubnetIds": [ "string" ],
    "VpcId": "string"
  }
}
```

## Request Parameters

The request accepts the following data in JSON format.

### Description

A description for the directory. This label will appear on the AWS console Directory Details page after the directory is created.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `^([a-zA-Z0-9_])[\a-zA-Z0-9_@#%*+=:?./!\s-]*$`

Required: No

### Edition

AWS Managed Microsoft AD is available in two editions: Standard and Enterprise. Enterprise is the default.

Type: String

Valid Values: Enterprise | Standard

Required: No

### Name

The fully qualified domain name for the AWS Managed Microsoft AD directory, such as `corp.example.com`. This name will resolve inside your VPC only. It does not need to be publicly resolvable.

Type: String

Pattern: `^([a-zA-Z0-9]+[\.\-])+( [a-zA-Z0-9] )+$`

Required: Yes

### Password

The password for the default administrative user named Admin.

If you need to change the password for the administrator account, you can use the [ResetUserPassword](#) API call.

Type: String

Pattern: `(?=^.{8,64}$)((?=\d)(?=[A-Z])(?=[a-z])|(?=\d)(?=[^A-Za-z0-9\s])(?=[a-z])|(?=[^A-Za-z0-9\s])(?=[A-Z])(?=[a-z])|(?=\d)(?=[A-Z])(?=[^A-Za-z0-9\s]))^.*`

Required: Yes

## ShortName

The NetBIOS name for your domain, such as CORP. If you don't specify a NetBIOS name, it will default to the first part of your directory DNS. For example, CORP for the directory DNS corp.example.com.

Type: String

Pattern: `^[^\\\/:*?"<>|.]+[^\\/:*?"<>|]*$`

Required: No

## Tags

The tags to be assigned to the AWS Managed Microsoft AD directory.

Type: Array of [Tag](#) objects

Required: No

## VpcSettings

Contains VPC information for the [CreateDirectory](#) or [CreateMicrosoftAD](#) operation.

Type: [DirectoryVpcSettings](#) object

Required: Yes

## Response Syntax

```
{
  "DirectoryId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### DirectoryId

The identifier of the directory that was created.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ClientException

A client exception has occurred.

HTTP Status Code: 400

### DirectoryLimitExceededException

The maximum number of directories in the region has been reached. You can use the [GetDirectoryLimits](#) operation to determine your directory limits in the region.

HTTP Status Code: 400

### InvalidParameterException

One or more parameters are not valid.

HTTP Status Code: 400

### ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

### UnsupportedOperationException

The operation is not supported.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

## Example Request

This example illustrates one usage of CreateMicrosoftAD.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 207
X-Amz-Target: DirectoryService_20150416.CreateMicrosoftAD
X-Amz-Date: 20161213T231510Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 boto-core/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161213/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=5a73aaebf6dd7db4a17ffa5a0a5af7f8e134ad03034cb0b3e05e4f1a999d9e0a

{
  "ShortName": "ad",
  "Password": "Str0ngP@ssw0rd",
  "Name": "ad.example.com",
  "Description": "Corporate AD directory",
  "VpcSettings": {
    "SubnetIds": [
      "subnet-ba0146de",
      "subnet-bef46bc8"
    ],
    "VpcId": "vpc-45025421"
  }
}
```

## Example Response

This example illustrates one usage of CreateMicrosoftAD.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 00019586-c18a-11e6-870b-c3330207df37
Content-Type: application/x-amz-json-1.1
Content-Length: 30
Date: Tue, 13 Dec 2016 23:15:12 GMT

{
  "DirectoryId": "d-926example"
```

```
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateSnapshot

Creates a snapshot of a Simple AD or Microsoft AD directory in the AWS cloud.

## Note

You cannot take snapshots of AD Connector directories.

## Request Syntax

```
{
  "DirectoryId": "string",
  "Name": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The identifier of the directory of which to take a snapshot.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### Name

The descriptive name to apply to the snapshot.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `^([a-zA-Z0-9_])[\a-zA-Z0-9_@#%*+=:?./!\s-]*$`

Required: No

## Response Syntax

```
{  
  "SnapshotId": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### SnapshotId

The identifier of the snapshot that was created.

Type: String

Pattern: `^s-[0-9a-f]{10}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **EntityDoesNotExistException**

The specified entity could not be found.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400



## ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## SnapshotLimitExceededException

The maximum number of manual snapshots for the directory has been reached. You can use the [GetSnapshotLimits](#) operation to determine the snapshot limits for a directory.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of CreateSnapshot.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 58
X-Amz-Target: DirectoryService_20150416.CreateSnapshot
X-Amz-Date: 20161213T233356Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161213/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=8789d87320d00e26fec4d745a34b3c5d898e4e89bf96b5f9c744ca612bed3d6d

{
  "DirectoryId":"d-926example",
  "Name":"ad.example.com"
}
```

### Example Response

This example illustrates one usage of CreateSnapshot.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 9eedb7ba-c18c-11e6-a099-03078e35561b
Content-Type: application/x-amz-json-1.1
Content-Length: 29
Date: Tue, 13 Dec 2016 23:33:58 GMT

{
  "SnapshotId": "s-9267f8d3f0"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateTrust

AWS Directory Service for Microsoft Active Directory allows you to configure trust relationships. For example, you can establish a trust between your AWS Managed Microsoft AD directory, and your existing self-managed Microsoft Active Directory. This would allow you to provide users and groups access to resources in either domain, with a single set of credentials.

This action initiates the creation of the AWS side of a trust relationship between an AWS Managed Microsoft AD directory and an external domain. You can create either a forest trust or an external trust.

## Request Syntax

```
{
  "ConditionalForwarderIpAddr": [ "string" ],
  "DirectoryId": "string",
  "RemoteDomainName": "string",
  "SelectiveAuth": "string",
  "TrustDirection": "string",
  "TrustPassword": "string",
  "TrustType": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### ConditionalForwarderIpAddr

The IP addresses of the remote DNS server associated with RemoteDomainName.

Type: Array of strings

Pattern: `^(?:(:25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)\.)\{3\}(?:25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)$`

Required: No

### DirectoryId

The Directory ID of the AWS Managed Microsoft AD directory for which to establish the trust relationship.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### RemoteDomainName

The Fully Qualified Domain Name (FQDN) of the external domain for which to create the trust relationship.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^([a-zA-Z0-9]+[\\.\-])+( [a-zA-Z0-9] )+[\.]?$`

Required: Yes

### SelectiveAuth

Optional parameter to enable selective authentication for the trust.

Type: String

Valid Values: Enabled | Disabled

Required: No

### TrustDirection

The direction of the trust relationship.

Type: String

Valid Values: One-Way: Outgoing | One-Way: Incoming | Two-Way

Required: Yes

### TrustPassword

The trust password. The must be the same password that was used when creating the trust relationship on the external domain.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^(\\p{LD}|\\p{Punct}| )+$`

Required: Yes

### TrustType

The trust relationship type. Forest is the default.

Type: String

Valid Values: Forest | External

Required: No

## Response Syntax

```
{
  "TrustId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### TrustId

A unique identifier for the trust relationship that was created.

Type: String

Pattern: `^t-[0-9a-f]{10}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **EntityAlreadyExistsException**

The specified entity already exists.

HTTP Status Code: 400

### **EntityDoesNotExistException**

The specified entity could not be found.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

### **UnsupportedOperationException**

The operation is not supported.

HTTP Status Code: 400

## **Examples**

The following examples are formatted for legibility.

### **Example Request**

This example illustrates one usage of CreateTrust.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 222
X-Amz-Target: DirectoryService_20150416.CreateTrust
X-Amz-Date: 20161213T235223Z
```

```
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 boto-core/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161213/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=1f0cff7825d20bab2a0dab1e0b8bedbed72f0c22175c7d9ed0e63598ae99cae5

{
  "TrustPassword": "Str0ngP@ssw0rd",
  "DirectoryId": "d-926example",
  "RemoteDomainName": "europa.example.com",
  "ConditionalForwarderIpAddrs": [
    "172.30.21.228"
  ],
  "TrustType": "Forest",
  "TrustDirection": "One-Way: Outgoing"
}
```

## Example Response

This example illustrates one usage of CreateTrust.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 3343bc79-c18f-11e6-ba7f-e33ae22bc363
Content-Type: application/x-amz-json-1.1
Content-Length: 26
Date: Tue, 13 Dec 2016 23:52:26 GMT

{
  "TrustId": "t-9267353743"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# DeleteConditionalForwarder

Deletes a conditional forwarder that has been set up for your AWS directory.

## Request Syntax

```
{  
  "DirectoryId": "string",  
  "RemoteDomainName": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The directory ID for which you are deleting the conditional forwarder.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### RemoteDomainName

The fully qualified domain name (FQDN) of the remote domain with which you are deleting the conditional forwarder.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^([a-zA-Z0-9]+[\\.\-])+([a-zA-Z0-9])+[.]?$`

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **DirectoryUnavailableException**

The specified directory is unavailable or could not be found.

HTTP Status Code: 400

### **EntityDoesNotExistException**

The specified entity could not be found.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

### **UnsupportedOperationException**

The operation is not supported.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### **Example Request**

This example illustrates one usage of DeleteConditionalForwarder.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 76
X-Amz-Target: DirectoryService_20150416.DeleteConditionalForwarder
X-Amz-Date: 20161214T001055Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 boto3/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161214/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=ffc3c3d6feac461a9b093cab94dd8957b252f2936b51f14a1ad8499a8b401d4a

{
  "DirectoryId":"d-926example",
  "RemoteDomainName":"sales.example.com"
}
```

## Example Response

This example illustrates one usage of DeleteConditionalForwarder.

```
HTTP/1.1 200 OK
x-amzn-RequestId: ca119fd0-c191-11e6-8f8e-ed61d076c15a
Content-Type: application/x-amz-json-1.1
Content-Length: 2
Date: Wed, 14 Dec 2016 00:11:00 GMT

{
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteDirectory

Deletes an AWS Directory Service directory.

Before you call `DeleteDirectory`, ensure that all of the required permissions have been explicitly granted through a policy. For details about what permissions are required to run the `DeleteDirectory` operation, see [AWS Directory Service API Permissions: Actions, Resources, and Conditions Reference](#).

## Request Syntax

```
{
  "DirectoryId": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The identifier of the directory to delete.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

## Response Syntax

```
{
  "DirectoryId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## DirectoryId

The directory identifier.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ClientException

A client exception has occurred.

HTTP Status Code: 400

### EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

### ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of `DeleteDirectory`.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 31
X-Amz-Target: DirectoryService_20150416.DeleteDirectory
```

```
X-Amz-Date: 20161214T002424Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161214/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=b542aa77381528e27afc08b229252606fa79723695fb2d19b81b51d66d7f92d

{
  "DirectoryId": "d-926example"
}
```

## Example Response

This example illustrates one usage of DeleteDirectory.

```
HTTP/1.1 200 OK
x-amzn-RequestId: abcbeb82-c193-11e6-bf9e-272b6602bf9f
Content-Type: application/x-amz-json-1.1
Content-Length: 30
Date: Wed, 14 Dec 2016 00:24:26 GMT

{
  "DirectoryId": "d-926example"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)



# DeleteLogSubscription

Deletes the specified log subscription.

## Request Syntax

```
{  
  "DirectoryId": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

Identifier of the directory whose log subscription you want to delete.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ClientException

A client exception has occurred.

HTTP Status Code: 400

### EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

### **UnsupportedOperationException**

The operation is not supported.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteSnapshot

Deletes a directory snapshot.

## Request Syntax

```
{  
  "SnapshotId": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### SnapshotId

The identifier of the directory snapshot to be deleted.

Type: String

Pattern: `^s-[0-9a-f]{10}$`

Required: Yes

## Response Syntax

```
{  
  "SnapshotId": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### SnapshotId

The identifier of the directory snapshot that was deleted.

Type: String

Pattern: `^s-[0-9a-f]{10}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ClientException

A client exception has occurred.

HTTP Status Code: 400

### EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

### InvalidParameterException

One or more parameters are not valid.

HTTP Status Code: 400

### ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of DeleteSnapshot.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
```

```
Accept-Encoding: identity
Content-Length: 30
X-Amz-Target: DirectoryService_20150416.DeleteSnapshot
X-Amz-Date: 20161214T012131Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161214/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=685c5716e7e11b8d5b2ed5f413d6ff47fe179a1f215b83aa89d00d3b28827c1c

{
  "SnapshotId": "s-9267f8d3f0"
}
```

## Example Response

This example illustrates one usage of DeleteSnapshot.

```
HTTP/1.1 200 OK
x-amzn-RequestId: a68a1e79-c19b-11e6-870b-c3330207df37
Content-Type: application/x-amz-json-1.1
Content-Length: 29
Date: Wed, 14 Dec 2016 01:21:34 GMT

{
  "SnapshotId": "s-9267f8d3f0"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteTrust

Deletes an existing trust relationship between your AWS Managed Microsoft AD directory and an external domain.

## Request Syntax

```
{  
  "DeleteAssociatedConditionalForwarder": boolean,  
  "TrustId": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### [DeleteAssociatedConditionalForwarder](#)

Delete a conditional forwarder as part of a DeleteTrustRequest.

Type: Boolean

Required: No

### [TrustId](#)

The Trust ID of the trust relationship to be deleted.

Type: String

Pattern: `^t-[0-9a-f]{10}$`

Required: Yes

## Response Syntax

```
{  
  "TrustId": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### TrustId

The Trust ID of the trust relationship that was deleted.

Type: String

Pattern: `^t-[0-9a-f]{10}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **EntityDoesNotExistException**

The specified entity could not be found.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

### **UnsupportedOperationException**

The operation is not supported.



HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of DeleteTrust.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 73
X-Amz-Target: DirectoryService_20150416.DeleteTrust
X-Amz-Date: 20161214T013332Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 boto3/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161214/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=ced49ef4329d015ebde09b7bc586eee4455b0b1e6608ade2fd6cd123440bbd6d

{
  "TrustId": "t-9267353743",
  "DeleteAssociatedConditionalForwarder": true
}
```

### Example Response

This example illustrates one usage of DeleteTrust.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 54425c2e-c19d-11e6-b0d6-83af322c90cd
Content-Type: application/x-amz-json-1.1
Content-Length: 26
Date: Wed, 14 Dec 2016 01:33:37 GMT

{
  "TrustId": "t-9267353743"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeregisterCertificate

Deletes from the system the certificate that was registered for secure LDAP or client certificate authentication.

## Request Syntax

```
{  
  "CertificateId": "string",  
  "DirectoryId": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### CertificateId

The identifier of the certificate.

Type: String

Pattern: `^c-[0-9a-f]{10}$`

Required: Yes

### DirectoryId

The identifier of the directory.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **CertificateDoesNotExistException**

The certificate is not present in the system for describe or deregister activities.

HTTP Status Code: 400

### **CertificateInUseException**

The certificate is being used for the LDAP security connection and cannot be removed without disabling LDAP security.

HTTP Status Code: 400

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **DirectoryDoesNotExistException**

The specified directory does not exist in the system.

HTTP Status Code: 400

### **DirectoryUnavailableException**

The specified directory is unavailable or could not be found.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## UnsupportedOperationException

The operation is not supported.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeregisterEventTopic

Removes the specified directory as a publisher to the specified Amazon SNS topic.

## Request Syntax

```
{  
  "DirectoryId": "string",  
  "TopicName": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The Directory ID to remove as a publisher. This directory will no longer send messages to the specified Amazon SNS topic.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### TopicName

The name of the Amazon SNS topic from which to remove the directory as a publisher.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9_-]+`

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ClientException

A client exception has occurred.

HTTP Status Code: 400

### EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

### InvalidParameterException

One or more parameters are not valid.

HTTP Status Code: 400

### ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of `DeregisterEventTopic`.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 52
X-Amz-Target: DirectoryService_20150416.DeregisterEventTopic
X-Amz-Date: 20161214T014408Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
```

```
Authorization: AWS4-HMAC-SHA256
Credential=AKIAI7E3BYXS3example/20161214/us-west-2/ds/aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target,
Signature=e3b8ad858165a3dd7d4fb35b0adf17bee8d71aed26b0f49e6db792ed8b10f8b1

{
  "DirectoryId": "d-926example",
  "TopicName": "snstopicexample"
}
```

## Example Response

This example illustrates one usage of DeregisterEventTopic.

```
HTTP/1.1 200 OK
x-amzn-RequestId: a68a1e79-c19b-11e6-870b-c3330207df37
Content-Type: application/x-amz-json-1.1
Content-Length: 29
Date: Wed, 14 Dec 2016 01:44:10 GMT

{
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)





# DescribeCertificate

Displays information about the certificate registered for secure LDAP or client certificate authentication.

## Request Syntax

```
{
  "CertificateId": "string",
  "DirectoryId": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### CertificateId

The identifier of the certificate.

Type: String

Pattern: `^c-[0-9a-f]{10}$`

Required: Yes

### DirectoryId

The identifier of the directory.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

## Response Syntax

```
{
  "Certificate": {
    "CertificateId": "string",
```

```
    "ClientCertAuthSettings": {
      "OCSPUrl": "string"
    },
    "CommonName": "string",
    "ExpiryDateTime": number,
    "RegisteredDateTime": number,
    "State": "string",
    "StateReason": "string",
    "Type": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Certificate

Information about the certificate, including registered date time, certificate state, the reason for the state, expiration date time, and certificate common name.

Type: [Certificate](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **CertificateDoesNotExistException**

The certificate is not present in the system for describe or deregister activities.

HTTP Status Code: 400

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **DirectoryDoesNotExistException**

The specified directory does not exist in the system.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

### **UnsupportedOperationException**

The operation is not supported.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DescribeClientAuthenticationSettings

Retrieves information about the type of client authentication for the specified directory, if the type is specified. If no type is specified, information about all client authentication types that are supported for the specified directory is retrieved. Currently, only SmartCard is supported.

## Request Syntax

```
{
  "DirectoryId": "string",
  "Limit": number,
  "NextToken": "string",
  "Type": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The identifier of the directory for which to retrieve information.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### Limit

The maximum number of items to return. If this value is zero, the maximum number of items is specified by the limitations of the operation.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

### NextToken

The *DescribeClientAuthenticationSettingsResult.NextToken* value from a previous call to [DescribeClientAuthenticationSettings](#). Pass null if this is the first call.

Type: String

Required: No

## Type

The type of client authentication for which to retrieve information. If no type is specified, a list of all client authentication types that are supported for the specified directory is retrieved.

Type: String

Valid Values: SmartCard | SmartCardOrPassword

Required: No

## Response Syntax

```
{
  "ClientAuthenticationSettingsInfo": [
    {
      "LastUpdatedDateTime": number,
      "Status": "string",
      "Type": "string"
    }
  ],
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [ClientAuthenticationSettingsInfo](#)

Information about the type of client authentication for the specified directory. The following information is retrieved: The date and time when the status of the client authentication type was last updated, whether the client authentication type is enabled or disabled, and the type of client authentication.

Type: Array of [ClientAuthenticationSettingInfo](#) objects

## **NextToken**

The next token used to retrieve the client authentication settings if the number of setting types exceeds page limit and there is another page.

Type: String

## **Errors**

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

Client authentication is not available in this region at this time.

HTTP Status Code: 400

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **DirectoryDoesNotExistException**

The specified directory does not exist in the system.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

### **UnsupportedOperationException**

The operation is not supported.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# DescribeConditionalForwarders

Obtains information about the conditional forwarders for this account.

If no input parameters are provided for `RemoteDomainNames`, this request describes all conditional forwarders for the specified directory ID.

## Request Syntax

```
{
  "DirectoryId": "string",
  "RemoteDomainNames": [ "string" ]
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The directory ID for which to get the list of associated conditional forwarders.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### RemoteDomainNames

The fully qualified domain names (FQDN) of the remote domains for which to get the list of associated conditional forwarders. If this member is null, all conditional forwarders are returned.

Type: Array of strings

Length Constraints: Maximum length of 1024.

Pattern: `^([a-zA-Z0-9]+[\.\-])+( [a-zA-Z0-9] )+[\.]?$`

Required: No

## Response Syntax

```
{
  "ConditionalForwarders": [
    {
      "DnsIpAddr": [ "string" ],
      "RemoteDomainName": "string",
      "ReplicationScope": "string"
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### ConditionalForwarders

The list of conditional forwarders that have been created.

Type: Array of [ConditionalForwarder](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **DirectoryUnavailableException**

The specified directory is unavailable or could not be found.

HTTP Status Code: 400

### **EntityDoesNotExistException**

The specified entity could not be found.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

### **UnsupportedOperationException**

The operation is not supported.

HTTP Status Code: 400

## **Examples**

The following examples are formatted for legibility.

### **Example Request**

This example illustrates one usage of `DescribeConditionalForwarders`.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 79
X-Amz-Target: DirectoryService_20150416.DescribeConditionalForwarders
X-Amz-Date: 20161214T020215Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161214/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=d8f7ff4237b393b4734bbf5d96713dff3deff651b4ab348f64bd776606147f9d

{
  "DirectoryId": "d-926example",
  "RemoteDomainNames": ["sales.example.com"]
}
```

```
}
```

## Example Response

This example illustrates one usage of DescribeConditionalForwarders.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 56d08425-c1a1-11e6-a132-e5016ac609f4
Content-Type: application/x-amz-json-1.1
Content-Length: 28
Date: Wed, 14 Dec 2016 02:02:18 GMT

{
  "ConditionalForwarders": [
    {
      "RemoteDomainName": "sales.example.com",
      "DnsIpAddrs": [
        "172.30.21.228"
      ],
      "ReplicationScope": "Domain"
    }
  ]
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# DescribeDirectories

Obtains information about the directories that belong to this account.

You can retrieve information about specific directories by passing the directory identifiers in the `DirectoryIds` parameter. Otherwise, all directories that belong to the current account are returned.

This operation supports pagination with the use of the `NextToken` request and response parameters. If more results are available, the `DescribeDirectoriesResult.NextToken` member contains a token that you pass in the next call to [DescribeDirectories](#) to retrieve the next set of items.

You can also specify a maximum number of return results with the `Limit` parameter.

## Request Syntax

```
{
  "DirectoryIds": [ "string" ],
  "Limit": number,
  "NextToken": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryIds

A list of identifiers of the directories for which to obtain the information. If this member is null, all directories that belong to the current account are returned.

An empty list results in an `InvalidParameterException` being thrown.

Type: Array of strings

Pattern: `^d-[0-9a-f]{10}$`

Required: No

## Limit

The maximum number of items to return. If this value is zero, the maximum number of items is specified by the limitations of the operation.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

## NextToken

The `DescribeDirectoriesResult.NextToken` value from a previous call to [DescribeDirectories](#). Pass null if this is the first call.

Type: String

Required: No

## Response Syntax

```
{
  "DirectoryDescriptions": [
    {
      "AccessUrl": "string",
      "Alias": "string",
      "ConnectSettings": {
        "AvailabilityZones": [ "string" ],
        "ConnectIps": [ "string" ],
        "CustomerUserName": "string",
        "SecurityGroupId": "string",
        "SubnetIds": [ "string" ],
        "VpcId": "string"
      },
      "Description": "string",
      "DesiredNumberOfDomainControllers": number,
      "DirectoryId": "string",
      "DnsIpAddr": [ "string" ],
      "Edition": "string",
      "LaunchTime": number,
      "Name": "string",
      "OsVersion": "string",
      "OwnerDirectoryDescription": {
```

```
"AccountId": "string",
"DirectoryId": "string",
"DnsIpAddrs": [ "string" ],
"RadiusSettings": {
  "AuthenticationProtocol": "string",
  "DisplayLabel": "string",
  "RadiusPort": number,
  "RadiusRetries": number,
  "RadiusServers": [ "string" ],
  "RadiusTimeout": number,
  "SharedSecret": "string",
  "UseSameUsername": boolean
},
"RadiusStatus": "string",
"VpcSettings": {
  "AvailabilityZones": [ "string" ],
  "SecurityGroupId": "string",
  "SubnetIds": [ "string" ],
  "VpcId": "string"
}
},
"RadiusSettings": {
  "AuthenticationProtocol": "string",
  "DisplayLabel": "string",
  "RadiusPort": number,
  "RadiusRetries": number,
  "RadiusServers": [ "string" ],
  "RadiusTimeout": number,
  "SharedSecret": "string",
  "UseSameUsername": boolean
},
"RadiusStatus": "string",
"RegionsInfo": {
  "AdditionalRegions": [ "string" ],
  "PrimaryRegion": "string"
},
"ShareMethod": "string",
"ShareNotes": "string",
"ShareStatus": "string",
"ShortName": "string",
"Size": "string",
"SsoEnabled": boolean,
"Stage": "string",
"StageLastUpdatedDateTime": number,
```



```
    "StageReason": "string",
    "Type": "string",
    "VpcSettings": {
      "AvailabilityZones": [ "string" ],
      "SecurityGroupId": "string",
      "SubnetIds": [ "string" ],
      "VpcId": "string"
    }
  },
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### DirectoryDescriptions

The list of [DirectoryDescription](#) objects that were retrieved.

It is possible that this list contains less than the number of items specified in the `Limit` member of the request. This occurs if there are less than the requested number of items left to retrieve, or if the limitations of the operation have been exceeded.

Type: Array of [DirectoryDescription](#) objects

### NextToken

If not null, more results are available. Pass this value for the `NextToken` parameter in a subsequent call to [DescribeDirectories](#) to retrieve the next set of items.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ClientException

A client exception has occurred.

HTTP Status Code: 400

### **EntityDoesNotExistException**

The specified entity could not be found.

HTTP Status Code: 400

### **InvalidNextTokenException**

The NextToken value is not valid.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## **Examples**

The following examples are formatted for legibility.

### **Example Request**

This example illustrates one usage of DescribeDirectories.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 46
X-Amz-Target: DirectoryService_20150416.DescribeDirectories
X-Amz-Date: 20161214T022424Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 boto-core/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161214/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
```

```
Signature=4e138f2c34fe61b203c621e69264a9347db842b944df2eb88fce7e2c337eab8c
```

```
{  
  "DirectoryIds": "d-926example",  
  "Limit": 0  
}
```

## Example Response

This example illustrates one usage of DescribeDirectories.

```
HTTP/1.1 200 OK  
x-amzn-RequestId: 6f884e4a-c1a4-11e6-a099-03078e35561b  
Content-Type: application/x-amz-json-1.1  
Content-Length: 470  
Date: Wed, 14 Dec 2016 02:24:27 GMT
```

```
{  
  "DirectoryDescriptions": [  
    {  
      "AccessUrl": "myaccess.awsapps.com",  
      "Alias": "myaccess",  
      "DirectoryId": "d-926example",  
      "DnsIpAddrs": [  
        "172.30.21.228",  
        "172.30.9.82"  
      ],  
      "LaunchTime": 1.469737584772E9,  
      "Name": "corp.example.com",  
      "ShortName": "example",  
      "SsoEnabled": true,  
      "Stage": "Active",  
      "StageLastUpdatedDateTime": 1.46973913171E9,  
      "Type": "MicrosoftAD",  
      "VpcSettings": {  
        "AvailabilityZones": [  
          "us-west-2a",  
          "us-west-2b"  
        ],  
        "SubnetIds": [  
          "subnet-ba0146de",  
          "subnet-bef46bc8"  
        ],  
      }  
    ],  
  ]  
}
```

```
        "VpcId": "vpc-45025421"  
      }  
    }  
  ]  
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DescribeDomainControllers

Provides information about any domain controllers in your directory.

## Request Syntax

```
{
  "DirectoryId": "string",
  "DomainControllerIds": [ "string" ],
  "Limit": number,
  "NextToken": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

Identifier of the directory for which to retrieve the domain controller information.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### DomainControllerIds

A list of identifiers for the domain controllers whose information will be provided.

Type: Array of strings

Pattern: `^dc-[0-9a-f]{10}$`

Required: No

### Limit

The maximum number of items to return.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

### NextToken

The *DescribeDomainControllers.NextToken* value from a previous call to [DescribeDomainControllers](#). Pass null if this is the first call.

Type: String

Required: No

## Response Syntax

```
{
  "DomainControllers": [
    {
      "AvailabilityZone": "string",
      "DirectoryId": "string",
      "DnsIpAddress": "string",
      "DomainControllerId": "string",
      "LaunchTime": number,
      "Status": "string",
      "StatusLastUpdatedDateTime": number,
      "StatusReason": "string",
      "SubnetId": "string",
      "VpcId": "string"
    }
  ],
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### DomainControllers

List of the [DomainController](#) objects that were retrieved.

Type: Array of [DomainController](#) objects

## **NextToken**

If not null, more results are available. Pass this value for the `NextToken` parameter in a subsequent call to [DescribeDomainControllers](#) retrieve the next set of items.

Type: String

## **Errors**

For information about the errors that are common to all actions, see [Common Errors](#).

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **EntityDoesNotExistException**

The specified entity could not be found.

HTTP Status Code: 400

### **InvalidNextTokenException**

The `NextToken` value is not valid.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

### **UnsupportedOperationException**

The operation is not supported.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# DescribeEventTopics

Obtains information about which Amazon SNS topics receive status messages from the specified directory.

If no input parameters are provided, such as `DirectoryId` or `TopicName`, this request describes all of the associations in the account.

## Request Syntax

```
{
  "DirectoryId": "string",
  "TopicNames": [ "string" ]
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The Directory ID for which to get the list of associated Amazon SNS topics. If this member is null, associations for all Directory IDs are returned.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: No

### TopicNames

A list of Amazon SNS topic names for which to obtain the information. If this member is null, all associations for the specified Directory ID are returned.

An empty list results in an `InvalidParameterException` being thrown.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9_-]+`

Required: No

## Response Syntax

```
{
  "EventTopics": [
    {
      "CreatedDateTime": number,
      "DirectoryId": "string",
      "Status": "string",
      "TopicArn": "string",
      "TopicName": "string"
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### EventTopics

A list of Amazon SNS topic names that receive status messages from the specified Directory ID.

Type: Array of [EventTopic](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **EntityDoesNotExistException**

The specified entity could not be found.

HTTP Status Code: 400

### InvalidParameterException

One or more parameters are not valid.

HTTP Status Code: 400

### ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of DescribeEventTopics.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 66
X-Amz-Target: DirectoryService_20150416.DescribeEventTopics
X-Amz-Date: 20161214T025225Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161214/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=d04fcf5cf8439dd8d0503933cab61c2bad6d6b29b9e1e5dca25f6d6de1704e17

{
  "DirectoryId": "d-926example",
  "TopicNames": "snstopicexample"
}
```

### Example Response

This example illustrates one usage of DescribeEventTopics.

```
HTTP/1.1 200 OK
x-amzn-RequestId: a68a1e79-c19b-11e6-870b-c3330207df37
Content-Type: application/x-amz-json-1.1
Content-Length: 29
Date: Wed, 14 Dec 2016 02:52:27 GMT

{
  "EventTopics": ["eventtopicexample"]
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DescribeLDAPSSettings

Describes the status of LDAP security for the specified directory.

## Request Syntax

```
{
  "DirectoryId": "string",
  "Limit": number,
  "NextToken": "string",
  "Type": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The identifier of the directory.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### Limit

Specifies the number of items that should be displayed on one page.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

### NextToken

The type of next token used for pagination.

Type: String

Required: No

## Type

The type of LDAP security to enable. Currently only the value `Client` is supported.

Type: String

Valid Values: `Client`

Required: No

## Response Syntax

```
{
  "LDAPSSettingsInfo": [
    {
      "LastUpdatedDateTime": number,
      "LDAPSStatus": "string",
      "LDAPSStatusReason": "string"
    }
  ],
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### LDAPSSettingsInfo

Information about LDAP security for the specified directory, including status of enablement, state last updated date time, and the reason for the state.

Type: Array of [LDAPSSettingInfo](#) objects

### NextToken

The next token used to retrieve the LDAPS settings if the number of setting types exceeds page limit and there is another page.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **DirectoryDoesNotExistException**

The specified directory does not exist in the system.

HTTP Status Code: 400

### **InvalidNextTokenException**

The NextToken value is not valid.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

### **UnsupportedOperationException**

The operation is not supported.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# DescribeRegions

Provides information about the Regions that are configured for multi-Region replication.

## Request Syntax

```
{
  "DirectoryId": "string",
  "NextToken": "string",
  "RegionName": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The identifier of the directory.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### NextToken

The `DescribeRegionsResult.NextToken` value from a previous call to [DescribeRegions](#). Pass null if this is the first call.

Type: String

Required: No

### RegionName

The name of the Region. For example, `us-east-1`.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 32.

Required: No

## Response Syntax

```
{
  "NextToken": "string",
  "RegionsDescription": [
    {
      "DesiredNumberOfDomainControllers": number,
      "DirectoryId": "string",
      "LastUpdatedDateTime": number,
      "LaunchTime": number,
      "RegionName": "string",
      "RegionType": "string",
      "Status": "string",
      "StatusLastUpdatedDateTime": number,
      "VpcSettings": {
        "SubnetIds": [ "string" ],
        "VpcId": "string"
      }
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### NextToken

If not null, more results are available. Pass this value for the NextToken parameter in a subsequent call to [DescribeRegions](#) to retrieve the next set of items.

Type: String

### RegionsDescription

List of Region information related to the directory for each replicated Region.

Type: Array of [RegionDescription](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

Client authentication is not available in this region at this time.

HTTP Status Code: 400

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **DirectoryDoesNotExistException**

The specified directory does not exist in the system.

HTTP Status Code: 400

### **InvalidNextTokenException**

The NextToken value is not valid.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

### **UnsupportedOperationException**

The operation is not supported.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DescribeSettings

Retrieves information about the configurable settings for the specified directory.

## Request Syntax

```
{
  "DirectoryId": "string",
  "NextToken": "string",
  "Status": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The identifier of the directory for which to retrieve information.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### NextToken

The `DescribeSettingsResult.NextToken` value from a previous call to [DescribeSettings](#). Pass null if this is the first call.

Type: String

Required: No

### Status

The status of the directory settings for which to retrieve information.

Type: String

Valid Values: Requested | Updating | Updated | Failed | Default

Required: No

## Response Syntax

```
{
  "DirectoryId": "string",
  "NextToken": "string",
  "SettingEntries": [
    {
      "AllowedValues": "string",
      "AppliedValue": "string",
      "DataType": "string",
      "LastRequestedDateTime": number,
      "LastUpdatedDateTime": number,
      "Name": "string",
      "RequestDetailedStatus": {
        "string" : "string"
      },
      "RequestedValue": "string",
      "RequestStatus": "string",
      "RequestStatusMessage": "string",
      "Type": "string"
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### DirectoryId

The identifier of the directory.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

### NextToken

If not null, token that indicates that more results are available. Pass this value for the `NextToken` parameter in a subsequent call to `DescribeSettings` to retrieve the next set of items.

Type: String

### **SettingEntries**

The list of [SettingEntry](#) objects that were retrieved.

It is possible that this list contains less than the number of items specified in the `Limit` member of the request. This occurs if there are less than the requested number of items left to retrieve, or if the limitations of the operation have been exceeded.

Type: Array of [SettingEntry](#) objects

## **Errors**

For information about the errors that are common to all actions, see [Common Errors](#).

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **DirectoryDoesNotExistException**

The specified directory does not exist in the system.

HTTP Status Code: 400

### **InvalidNextTokenException**

The `NextToken` value is not valid.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## UnsupportedOperationException

The operation is not supported.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# DescribeSharedDirectories

Returns the shared directories in your account.

## Request Syntax

```
{
  "Limit": number,
  "NextToken": "string",
  "OwnerDirectoryId": "string",
  "SharedDirectoryIds": [ "string" ]
}
```

## Request Parameters

The request accepts the following data in JSON format.

### Limit

The number of shared directories to return in the response object.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

### NextToken

The `DescribeSharedDirectoriesResult.NextToken` value from a previous call to [DescribeSharedDirectories](#). Pass null if this is the first call.

Type: String

Required: No

### OwnerDirectoryId

Returns the identifier of the directory in the directory owner account.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### SharedDirectoryIds

A list of identifiers of all shared directories in your account.

Type: Array of strings

Pattern: `^d-[0-9a-f]{10}$`

Required: No

## Response Syntax

```
{
  "NextToken": "string",
  "SharedDirectories": [
    {
      "CreatedDateTime": number,
      "LastUpdatedDateTime": number,
      "OwnerAccountId": "string",
      "OwnerDirectoryId": "string",
      "SharedAccountId": "string",
      "SharedDirectoryId": "string",
      "ShareMethod": "string",
      "ShareNotes": "string",
      "ShareStatus": "string"
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### NextToken

If not null, token that indicates that more results are available. Pass this value for the NextToken parameter in a subsequent call to [DescribeSharedDirectories](#) to retrieve the next set of items.

Type: String

## **SharedDirectories**

A list of all shared directories in your account.

Type: Array of [SharedDirectory](#) objects

## **Errors**

For information about the errors that are common to all actions, see [Common Errors](#).

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **EntityDoesNotExistException**

The specified entity could not be found.

HTTP Status Code: 400

### **InvalidNextTokenException**

The NextToken value is not valid.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

### **UnsupportedOperationException**

The operation is not supported.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DescribeSnapshots

Obtains information about the directory snapshots that belong to this account.

This operation supports pagination with the use of the *NextToken* request and response parameters. If more results are available, the *DescribeSnapshots.NextToken* member contains a token that you pass in the next call to [DescribeSnapshots](#) to retrieve the next set of items.

You can also specify a maximum number of return results with the *Limit* parameter.

## Request Syntax

```
{
  "DirectoryId": "string",
  "Limit": number,
  "NextToken": "string",
  "SnapshotIds": [ "string" ]
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The identifier of the directory for which to retrieve snapshot information.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: No

### Limit

The maximum number of objects to return.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

## NextToken

The *DescribeSnapshotsResult.NextToken* value from a previous call to [DescribeSnapshots](#). Pass null if this is the first call.

Type: String

Required: No

## SnapshotIds

A list of identifiers of the snapshots to obtain the information for. If this member is null or empty, all snapshots are returned using the *Limit* and *NextToken* members.

Type: Array of strings

Pattern: `^s-[0-9a-f]{10}$`

Required: No

## Response Syntax

```
{
  "NextToken": "string",
  "Snapshots": [
    {
      "DirectoryId": "string",
      "Name": "string",
      "SnapshotId": "string",
      "StartTime": number,
      "Status": "string",
      "Type": "string"
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## **NextToken**

If not null, more results are available. Pass this value in the *NextToken* member of a subsequent call to [DescribeSnapshots](#).

Type: String

## **Snapshots**

The list of [Snapshot](#) objects that were retrieved.

It is possible that this list contains less than the number of items specified in the *Limit* member of the request. This occurs if there are less than the requested number of items left to retrieve, or if the limitations of the operation have been exceeded.

Type: Array of [Snapshot](#) objects

## **Errors**

For information about the errors that are common to all actions, see [Common Errors](#).

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **EntityDoesNotExistException**

The specified entity could not be found.

HTTP Status Code: 400

### **InvalidNextTokenException**

The NextToken value is not valid.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

## ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of DescribeSnapshots.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 76
X-Amz-Target: DirectoryService_20150416.DescribeSnapshots
X-Amz-Date: 20161214T164618Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161214/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=602552c456c471537cbafaec3b7712674bdc20574c076dace469f3848fa8ab7a

{
  "DirectoryId": "d-926example",
  "Limit": 0,
  "SnapshotIds": ["s-9267f6da4e"]
}
```

### Example Response

This example illustrates one usage of DescribeSnapshots.

```
HTTP/1.1 200 OK
x-amzn-RequestId: d7b33e7e-c21c-11e6-91f4-6dbff6648f8a
Content-Type: application/x-amz-json-1.1
Content-Length: 138
Date: Wed, 14 Dec 2016 16:46:21 GMT
```



```
{
  "Snapshots": [
    {
      "DirectoryId": "d-926example",
      "SnapshotId": "s-9267f6da4e",
      "StartTime": 1.481289211615E9,
      "Status": "Completed",
      "Type": "Auto"
    }
  ]
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DescribeTrusts

Obtains information about the trust relationships for this account.

If no input parameters are provided, such as `DirectoryId` or `TrustIds`, this request describes all the trust relationships belonging to the account.

## Request Syntax

```
{
  "DirectoryId": "string",
  "Limit": number,
  "NextToken": "string",
  "TrustIds": [ "string" ]
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The Directory ID of the AWS directory that is a part of the requested trust relationship.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: No

### Limit

The maximum number of objects to return.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

### NextToken

The `DescribeTrustsResult.NextToken` value from a previous call to [DescribeTrusts](#). Pass null if this is the first call.

Type: String

Required: No

### TrustIds

A list of identifiers of the trust relationships for which to obtain the information. If this member is null, all trust relationships that belong to the current account are returned.

An empty list results in an `InvalidParameterException` being thrown.

Type: Array of strings

Pattern: `^t-[0-9a-f]{10}$`

Required: No

## Response Syntax

```
{
  "NextToken": "string",
  "Trusts": [
    {
      "CreatedDateTime": number,
      "DirectoryId": "string",
      "LastUpdatedDateTime": number,
      "RemoteDomainName": "string",
      "SelectiveAuth": "string",
      "StateLastUpdatedDateTime": number,
      "TrustDirection": "string",
      "TrustId": "string",
      "TrustState": "string",
      "TrustStateReason": "string",
      "TrustType": "string"
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## NextToken

If not null, more results are available. Pass this value for the *NextToken* parameter in a subsequent call to [DescribeTrusts](#) to retrieve the next set of items.

Type: String

## Trusts

The list of Trust objects that were retrieved.

It is possible that this list contains less than the number of items specified in the *Limit* member of the request. This occurs if there are less than the requested number of items left to retrieve, or if the limitations of the operation have been exceeded.

Type: Array of [Trust](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **EntityDoesNotExistException**

The specified entity could not be found.

HTTP Status Code: 400

### **InvalidNextTokenException**

The NextToken value is not valid.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

## ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## UnsupportedOperationException

The operation is not supported.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of DescribeTrusts.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 61
X-Amz-Target: DirectoryService_20150416.DescribeTrusts
X-Amz-Date: 20161214T210907Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161214/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=fc201f050b631958cf6c5e186c5c897e82a974dad41b0e3c141a811003fa3c9b

{
  "DirectoryId": "d-926example",
  "TrustIds": ["t-9267353df0"]
}
```

### Example Response

This example illustrates one usage of DescribeTrusts.

```
HTTP/1.1 200 OK
```

```
x-amzn-RequestId: 8e6560bd-c241-11e6-a4dc-e5519684970a
Content-Type: application/x-amz-json-1.1
Content-Length: 406
Date: Wed, 14 Dec 2016 21:09:09 GMT
```

```
{
  "Trusts": [
    {
      "CreatedDateTime": 1481749250.657,
      "DirectoryId": "d-926example",
      "LastUpdatedDateTime": 1481749260.156,
      "RemoteDomainName": "sales.example.com",
      "StateLastUpdatedDateTime": 1481749260.156,
      "TrustDirection": "One-Way: Outgoing",
      "TrustId": "t-9267353df0",
      "TrustState": "Failed",
      "TrustStateReason": "The specified domain either does not exist or could not be
contacted. Name: sales.example.com",
      "TrustType": "Forest"
    }
  ]
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DescribeUpdateDirectory

Describes the updates of a directory for a particular update type.

## Request Syntax

```
{  
  "DirectoryId": "string",  
  "NextToken": "string",  
  "RegionName": "string",  
  "UpdateType": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The unique identifier of the directory.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### NextToken

The `DescribeUpdateDirectoryResult.NextToken` value from a previous call to [DescribeUpdateDirectory](#). Pass null if this is the first call.

Type: String

Required: No

### RegionName

The name of the Region.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 32.

Required: No

## UpdateType

The type of updates you want to describe for the directory.

Type: String

Valid Values: OS

Required: Yes

## Response Syntax

```
{
  "NextToken": "string",
  "UpdateActivities": [
    {
      "InitiatedBy": "string",
      "LastUpdatedDateTime": number,
      "NewValue": {
        "OSUpdateSettings": {
          "OSVersion": "string"
        }
      },
      "PreviousValue": {
        "OSUpdateSettings": {
          "OSVersion": "string"
        }
      },
      "Region": "string",
      "StartTime": number,
      "Status": "string",
      "StatusReason": "string"
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.



## **NextToken**

If not null, more results are available. Pass this value for the `NextToken` parameter.

Type: String

## **UpdateActivities**

The list of update activities on a directory for the requested update type.

Type: Array of [UpdateInfoEntry](#) objects

## **Errors**

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

Client authentication is not available in this region at this time.

HTTP Status Code: 400

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **DirectoryDoesNotExistException**

The specified directory does not exist in the system.

HTTP Status Code: 400

### **InvalidNextTokenException**

The `NextToken` value is not valid.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

## ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DisableClientAuthentication

Disables alternative client authentication methods for the specified directory.

## Request Syntax

```
{
  "DirectoryId": "string",
  "Type": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The identifier of the directory

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### Type

The type of client authentication to disable. Currently the only parameter "SmartCard" is supported.

Type: String

Valid Values: SmartCard | SmartCardOrPassword

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

Client authentication is not available in this region at this time.

HTTP Status Code: 400

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **DirectoryDoesNotExistException**

The specified directory does not exist in the system.

HTTP Status Code: 400

### **InvalidClientAuthStatusException**

Client authentication is already enabled.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

### **UnsupportedOperationException**

The operation is not supported.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DisableLDAPS

Deactivates LDAP secure calls for the specified directory.

## Request Syntax

```
{
  "DirectoryId": "string",
  "Type": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The identifier of the directory.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### Type

The type of LDAP security to enable. Currently only the value `Client` is supported.

Type: String

Valid Values: `Client`

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## **ClientException**

A client exception has occurred.

HTTP Status Code: 400

## **DirectoryDoesNotExistException**

The specified directory does not exist in the system.

HTTP Status Code: 400

## **DirectoryUnavailableException**

The specified directory is unavailable or could not be found.

HTTP Status Code: 400

## **InvalidLDAPStatusException**

The LDAP activities could not be performed because they are limited by the LDAPS status.

HTTP Status Code: 400

## **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

## **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## **UnsupportedOperationException**

The operation is not supported.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# DisableRadius

Disables multi-factor authentication (MFA) with the Remote Authentication Dial In User Service (RADIUS) server for an AD Connector or Microsoft AD directory.

## Request Syntax

```
{  
  "DirectoryId": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The identifier of the directory for which to disable MFA.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **EntityDoesNotExistException**

The specified entity could not be found.

HTTP Status Code: 400

## ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of DisableRadius.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 31
X-Amz-Target: DirectoryService_20150416.DisableRadius
X-Amz-Date: 20161214T215510Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 boto-core/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161214/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=c7ae53fed950cedb5cc393489a79a60b9c548ee85c9c2339f8a75108a2d18525

{
  "DirectoryId": "d-926example"
}
```

### Example Response

This example illustrates one usage of DisableRadius.

```
HTTP/1.1 200 OK
x-amzn-RequestId: fcd40ac9-c247-11e6-a7ca-f9a52a6a0390
Content-Type: application/x-amz-json-1.1
Content-Length: 2
Date: Wed, 14 Dec 2016 21:55:12 GMT
```

```
{  
  
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DisableSso

Disables single-sign on for a directory.

## Request Syntax

```
{
  "DirectoryId": "string",
  "Password": "string",
  "UserName": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The identifier of the directory for which to disable single-sign on.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### Password

The password of an alternate account to use to disable single-sign on. This is only used for AD Connector directories. For more information, see the *UserName* parameter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### UserName

The username of an alternate account to use to disable single-sign on. This is only used for AD Connector directories. This account must have privileges to remove a service principal name.

If the AD Connector service account does not have privileges to remove a service principal name, you can specify an alternate account with the *UserName* and *Password* parameters. These credentials are only used to disable single sign-on and are not stored by the service. The AD Connector service account is not changed.

Type: String

Length Constraints: Minimum length of 1.

Pattern: [a-zA-Z0-9.\_-]+

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AuthenticationFailedException

An authentication error occurred.

HTTP Status Code: 400

### ClientException

A client exception has occurred.

HTTP Status Code: 400

### EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

### InsufficientPermissionsException

The account does not have sufficient permission to perform the operation.

HTTP Status Code: 400

## ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of `DisableSso`.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 80
X-Amz-Target: DirectoryService_20150416.DisableSso
X-Amz-Date: 20161214T221722Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161214/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=b68ee7e88af7fc741471e9098dbc1636979ae461f0b9cd2f187124abbf762455

{
  "UserName": "Admin",
  "DirectoryId": "d-926example",
  "Password": "Str0ngP@ssw0rd"
}
```

### Example Response

This example illustrates one usage of `DisableSso`.

```
HTTP/1.1 200 OK
x-amzn-RequestId: fcd40ac9-c247-11e6-a7ca-f9a52a6a0390
Content-Type: application/x-amz-json-1.1
Content-Length: 2
Date: Wed, 14 Dec 2016 22:17:12 GMT
```

```
{  
  
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# EnableClientAuthentication

Enables alternative client authentication methods for the specified directory.

## Request Syntax

```
{  
  "DirectoryId": "string",  
  "Type": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The identifier of the specified directory.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### Type

The type of client authentication to enable. Currently only the value `SmartCard` is supported. Smart card authentication in AD Connector requires that you enable Kerberos Constrained Delegation for the Service User to the LDAP service in your self-managed AD.

Type: String

Valid Values: `SmartCard` | `SmartCardOrPassword`

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.



## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

Client authentication is not available in this region at this time.

HTTP Status Code: 400

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **DirectoryDoesNotExistException**

The specified directory does not exist in the system.

HTTP Status Code: 400

### **InvalidClientAuthStatusException**

Client authentication is already enabled.

HTTP Status Code: 400

### **NoAvailableCertificateException**

Client authentication setup could not be completed because at least one valid certificate must be registered in the system.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

### **UnsupportedOperationException**

The operation is not supported.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# EnableLDAPS

Activates the switch for the specific directory to always use LDAP secure calls.

## Request Syntax

```
{  
  "DirectoryId": "string",  
  "Type": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The identifier of the directory.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### Type

The type of LDAP security to enable. Currently only the value `Client` is supported.

Type: String

Valid Values: `Client`

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## **ClientException**

A client exception has occurred.

HTTP Status Code: 400

## **DirectoryDoesNotExistException**

The specified directory does not exist in the system.

HTTP Status Code: 400

## **DirectoryUnavailableException**

The specified directory is unavailable or could not be found.

HTTP Status Code: 400

## **InvalidLDAPSStatusException**

The LDAP activities could not be performed because they are limited by the LDAPS status.

HTTP Status Code: 400

## **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

## **NoAvailableCertificateException**

Client authentication setup could not be completed because at least one valid certificate must be registered in the system.

HTTP Status Code: 400

## **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## **UnsupportedOperationException**

The operation is not supported.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# EnableRadius

Enables multi-factor authentication (MFA) with the Remote Authentication Dial In User Service (RADIUS) server for an AD Connector or Microsoft AD directory.

## Request Syntax

```
{
  "DirectoryId": "string",
  "RadiusSettings": {
    "AuthenticationProtocol": "string",
    "DisplayLabel": "string",
    "RadiusPort": number,
    "RadiusRetries": number,
    "RadiusServers": [ "string" ],
    "RadiusTimeout": number,
    "SharedSecret": "string",
    "UseSameUsername": boolean
  }
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The identifier of the directory for which to enable MFA.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### RadiusSettings

A [RadiusSettings](#) object that contains information about the RADIUS server.

Type: [RadiusSettings](#) object

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ClientException

A client exception has occurred.

HTTP Status Code: 400

### EntityAlreadyExistsException

The specified entity already exists.

HTTP Status Code: 400

### EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

### InvalidParameterException

One or more parameters are not valid.

HTTP Status Code: 400

### ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of EnableRadius.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 259
X-Amz-Target: DirectoryService_20150416.EnableRadius
X-Amz-Date: 20161214T214103Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161214/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=4ba918cf440a45fddd5fcd1bd65207f94e760cebbd7de404d0096c6b1e652d4e

{
  "DirectoryId":"d-926example",
  "RadiusSettings":{
    "DisplayLabel":"MyRadius",
    "UseSameUsername":true,
    "RadiusTimeout":1,
    "AuthenticationProtocol":"PAP",
    "RadiusPort":1200,
    "RadiusRetries":2,
    "SharedSecret":"12345678",
    "RadiusServers":[
      "172.168.111.12"
    ]
  }
}
```

## Example Response

This example illustrates one usage of EnableRadius.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 045cabd8-c246-11e6-ad7a-a9557d30f017
Content-Type: application/x-amz-json-1.1
Content-Length: 2
Date: Wed, 14 Dec 2016 21:41:05 GMT

{
}
```



## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# EnableSso

Enables single sign-on for a directory. Single sign-on allows users in your directory to access certain AWS services from a computer joined to the directory without having to enter their credentials separately.

## Request Syntax

```
{
  "DirectoryId": "string",
  "Password": "string",
  "UserName": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The identifier of the directory for which to enable single-sign on.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### Password

The password of an alternate account to use to enable single-sign on. This is only used for AD Connector directories. For more information, see the *UserName* parameter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### UserName

The username of an alternate account to use to enable single-sign on. This is only used for AD Connector directories. This account must have privileges to add a service principal name.

If the AD Connector service account does not have privileges to add a service principal name, you can specify an alternate account with the *UserName* and *Password* parameters. These credentials are only used to enable single sign-on and are not stored by the service. The AD Connector service account is not changed.

Type: String

Length Constraints: Minimum length of 1.

Pattern: [a-zA-Z0-9.\_-]+

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AuthenticationFailedException**

An authentication error occurred.

HTTP Status Code: 400

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **EntityDoesNotExistException**

The specified entity could not be found.

HTTP Status Code: 400

### **InsufficientPermissionsException**

The account does not have sufficient permission to perform the operation.

HTTP Status Code: 400

## ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of EnableSso.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 80
X-Amz-Target: DirectoryService_20150416.EnableSso
X-Amz-Date: 20161214T220301Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161214/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=88acc99818605aa438eb86b5be59daecce370c7db16e5e84311508e575ea0515

{
  "UserName": "Admin",
  "DirectoryId": "d-926example",
  "Password": "Str0ngP@ssw0rd"
}
```

### Example Response

This example illustrates one usage of EnableSso.

```
HTTP/1.1 200 OK
x-amzn-RequestId: fcd40ac9-c247-11e6-a7ca-f9a52a6a0390
Content-Type: application/x-amz-json-1.1
Content-Length: 2
Date: Wed, 14 Dec 2016 22:03:03 GMT
```

```
{  
  
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetDirectoryLimits

Obtains directory limit information for the current Region.

## Response Syntax

```
{
  "DirectoryLimits": {
    "CloudOnlyDirectoriesCurrentCount": number,
    "CloudOnlyDirectoriesLimit": number,
    "CloudOnlyDirectoriesLimitReached": boolean,
    "CloudOnlyMicrosoftADCurrentCount": number,
    "CloudOnlyMicrosoftADLimit": number,
    "CloudOnlyMicrosoftADLimitReached": boolean,
    "ConnectedDirectoriesCurrentCount": number,
    "ConnectedDirectoriesLimit": number,
    "ConnectedDirectoriesLimitReached": boolean
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### DirectoryLimits

A [DirectoryLimits](#) object that contains the directory limits for the current Region.

Type: [DirectoryLimits](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ClientException

A client exception has occurred.

HTTP Status Code: 400

## EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

## ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of `GetDirectoryLimits`.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: DirectoryService_20150416.GetDirectoryLimits
X-Amz-Date: 20161214T223512Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 boto3/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161214/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=550da3fb7986c02e54cb35d644fd6601bfe823c3956e9471308682df2c1977ac

{

}
```

### Example Response

This example illustrates one usage of `GetDirectoryLimits`.

```
HTTP/1.1 200 OK
```

```
x-amzn-RequestId: 9526b149-c24d-11e6-bc3e-5ffd5f600cd8
Content-Type: application/x-amz-json-1.1
Content-Length: 348
Date: Wed, 14 Dec 2016 22:35:14 GMT

{
  "DirectoryLimits":{
    "CloudOnlyDirectoriesCurrentCount":2,
    "CloudOnlyDirectoriesLimit":10,
    "CloudOnlyDirectoriesLimitReached":false,
    "CloudOnlyMicrosoftADCurrentCount":2,
    "CloudOnlyMicrosoftADLimit":10,
    "CloudOnlyMicrosoftADLimitReached":false,
    "ConnectedDirectoriesCurrentCount":1,
    "ConnectedDirectoriesLimit":10,
    "ConnectedDirectoriesLimitReached":false
  }
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# GetSnapshotLimits

Obtains the manual snapshot limits for a directory.

## Request Syntax

```
{  
  "DirectoryId": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

Contains the identifier of the directory to obtain the limits for.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

## Response Syntax

```
{  
  "SnapshotLimits": {  
    "ManualSnapshotsCurrentCount": number,  
    "ManualSnapshotsLimit": number,  
    "ManualSnapshotsLimitReached": boolean  
  }  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## [SnapshotLimits](#)

A [SnapshotLimits](#) object that contains the manual snapshot limits for the specified directory.

Type: [SnapshotLimits](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ClientException

A client exception has occurred.

HTTP Status Code: 400

### EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

### ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of `GetSnapshotLimits`.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 31
X-Amz-Target: DirectoryService_20150416.GetSnapshotLimits
X-Amz-Date: 20161214T224507Z
```

```
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 boto-core/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161214/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=f9ba790cf905e14fa97fd1ed6a961c72d83a23f3e54ab126d8e4a30ec14d3cdb

{
  "DirectoryId": "d-926example"
}
```

## Example Response

This example illustrates one usage of `GetSnapshotLimits`.

```
HTTP/1.1 200 OK
x-amzn-RequestId: f7895979-c24e-11e6-a0ba-6bb2a89ebc49
Content-Type: application/x-amz-json-1.1
Content-Length: 113
Date: Wed, 14 Dec 2016 22:45:09 GMT

{
  "SnapshotLimits":{
    "ManualSnapshotsCurrentCount":1,
    "ManualSnapshotsLimit":5,
    "ManualSnapshotsLimitReached":false
  }
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListCertificates

For the specified directory, lists all the certificates registered for a secure LDAP or client certificate authentication.

## Request Syntax

```
{
  "DirectoryId": "string",
  "Limit": number,
  "NextToken": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The identifier of the directory.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### Limit

The number of items that should show up on one page

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

### NextToken

A token for requesting another page of certificates if the NextToken response element indicates that more certificates are available. Use the value of the returned NextToken element in your request until the token comes back as null. Pass null if this is the first call.

Type: String

Required: No

## Response Syntax

```
{
  "CertificatesInfo": [
    {
      "CertificateId": "string",
      "CommonName": "string",
      "ExpiryDateTime": number,
      "State": "string",
      "Type": "string"
    }
  ],
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [CertificatesInfo](#)

A list of certificates with basic details including certificate ID, certificate common name, certificate state.

Type: Array of [CertificateInfo](#) objects

### [NextToken](#)

Indicates whether another page of certificates is available when the number of available certificates exceeds the page limit.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## ClientException

A client exception has occurred.

HTTP Status Code: 400

## DirectoryDoesNotExistException

The specified directory does not exist in the system.

HTTP Status Code: 400

## InvalidNextTokenException

The NextToken value is not valid.

HTTP Status Code: 400

## InvalidParameterException

One or more parameters are not valid.

HTTP Status Code: 400

## ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## UnsupportedOperationException

The operation is not supported.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# ListIpRoutes

Lists the address blocks that you have added to a directory.

## Request Syntax

```
{  
  "DirectoryId": "string",  
  "Limit": number,  
  "NextToken": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

Identifier (ID) of the directory for which you want to retrieve the IP addresses.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### Limit

Maximum number of items to return. If this value is zero, the maximum number of items is specified by the limitations of the operation.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

### NextToken

The *ListIpRoutes.NextToken* value from a previous call to [ListIpRoutes](#). Pass null if this is the first call.

Type: String

Required: No

## Response Syntax

```
{
  "IpRoutesInfo": [
    {
      "AddedDateTime": number,
      "CidrIp": "string",
      "Description": "string",
      "DirectoryId": "string",
      "IpRouteStatusMsg": "string",
      "IpRouteStatusReason": "string"
    }
  ],
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [IpRoutesInfo](#)

A list of [IpRoutes](#).

Type: Array of [IpRouteInfo](#) objects

### [NextToken](#)

If not null, more results are available. Pass this value for the *NextToken* parameter in a subsequent call to [ListIpRoutes](#) to retrieve the next set of items.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## ClientException

A client exception has occurred.

HTTP Status Code: 400

## EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

## InvalidNextTokenException

The NextToken value is not valid.

HTTP Status Code: 400

## InvalidParameterException

One or more parameters are not valid.

HTTP Status Code: 400

## ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of ListIpRoutes.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 43
X-Amz-Target: DirectoryService_20150416.ListIpRoutes
X-Amz-Date: 20161214T225328Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 boto3/1.4.81
```

```
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161214/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=4dcb72aae179937790f5b061ceb1c697ac434b27891014b609671e49e52be1dd

{
  "DirectoryId":"d-926example",
  "Limit": 0
}
```

## Example Response

This example illustrates one usage of ListIpRoutes.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 2214ceaa-c250-11e6-a7ca-f9a52a6a0390
Content-Type: application/x-amz-json-1.1
Content-Length: 155
Date: Wed, 14 Dec 2016 22:53:30 GMT

{
  "IpRoutesInfo":[
    {
      "AddedDateTime":1.48157763163E9,
      "CidrIp":"12.12.12.12/32",
      "Description":"example",
      "DirectoryId":"d-926example",
      "IpRouteStatusMsg":"Added"
    }
  ]
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListLogSubscriptions

Lists the active log subscriptions for the AWS account.

## Request Syntax

```
{  
  "DirectoryId": "string",  
  "Limit": number,  
  "NextToken": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

If a *DirectoryID* is provided, lists only the log subscription associated with that directory. If no *DirectoryId* is provided, lists all log subscriptions associated with your AWS account. If there are no log subscriptions for the AWS account or the directory, an empty list will be returned.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: No

### Limit

The maximum number of items returned.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

### NextToken

The token for the next set of items to return.

Type: String

Required: No

## Response Syntax

```
{
  "LogSubscriptions": [
    {
      "DirectoryId": "string",
      "LogGroupName": "string",
      "SubscriptionCreatedDateTime": number
    }
  ],
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### LogSubscriptions

A list of active [LogSubscription](#) objects for calling the AWS account.

Type: Array of [LogSubscription](#) objects

### NextToken

The token for the next set of items to return.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ClientException

A client exception has occurred.

HTTP Status Code: 400

## EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

## InvalidNextTokenException

The NextToken value is not valid.

HTTP Status Code: 400

## ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# ListSchemaExtensions

Lists all schema extensions applied to a Microsoft AD Directory.

## Request Syntax

```
{
  "DirectoryId": "string",
  "Limit": number,
  "NextToken": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The identifier of the directory from which to retrieve the schema extension information.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### Limit

The maximum number of items to return.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

### NextToken

The `ListSchemaExtensions.NextToken` value from a previous call to `ListSchemaExtensions`. Pass null if this is the first call.

Type: String

Required: No

## Response Syntax

```
{
  "NextToken": "string",
  "SchemaExtensionsInfo": [
    {
      "Description": "string",
      "DirectoryId": "string",
      "EndDateTime": number,
      "SchemaExtensionId": "string",
      "SchemaExtensionStatus": "string",
      "SchemaExtensionStatusReason": "string",
      "StartDateTime": number
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [NextToken](#)

If not null, more results are available. Pass this value for the NextToken parameter in a subsequent call to ListSchemaExtensions to retrieve the next set of items.

Type: String

### [SchemaExtensionsInfo](#)

Information about the schema extensions applied to the directory.

Type: Array of [SchemaExtensionInfo](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## ClientException

A client exception has occurred.

HTTP Status Code: 400

## EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

## InvalidNextTokenException

The NextToken value is not valid.

HTTP Status Code: 400

## ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of ListSchemaExtensions.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 43
X-Amz-Target: DirectoryService_20150416.ListSchemaExtensions
X-Amz-Date: 20161214T230332Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161214/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=39aa3aec95444a9bf6dff7fc57d3178c9364b5d2fd560380e8fbc6eee13b3cf1
```

```
{
  "DirectoryId": "d-926example",
  "Limit": 0
}
```

## Example Response

This example illustrates one usage of ListSchemaExtensions.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 89f9aea0-c251-11e6-b0d6-83af322c90cd
Content-Type: application/x-amz-json-1.1
Content-Length: 333
Date: Wed, 14 Dec 2016 23:03:34 GMT

{
  "SchemaExtensionsInfo":[
    {
      "Description":"example text",
      "DirectoryId":"d-926example",
      "EndDateTime":1.481586088301E9,
      "SchemaExtensionId":"e-926731d2a0",
      "SchemaExtensionStatus":"Cancelled",
      "SchemaExtensionStatusReason":"Cancellation is complete. No schema updates
were applied to your directory.",
      "StartDateTime":1.481584463548E9
    }
  ]
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListTagsForResource

Lists all tags on a directory.

## Request Syntax

```
{  
  "Limit": number,  
  "NextToken": "string",  
  "ResourceId": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### Limit

Reserved for future use.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

### NextToken

Reserved for future use.

Type: String

Required: No

### ResourceId

Identifier (ID) of the directory for which you want to retrieve tags.

Type: String

Pattern: `^[d]-[0-9a-f]{10}$`

Required: Yes

## Response Syntax

```
{
  "NextToken": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [NextToken](#)

Reserved for future use.

Type: String

### [Tags](#)

List of tags returned by the ListTagsForResource operation.

Type: Array of [Tag](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **EntityDoesNotExistException**

The specified entity could not be found.

HTTP Status Code: 400

### **InvalidNextTokenException**

The NextToken value is not valid.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## **Examples**

The following examples are formatted for legibility.

### **Example Request**

This example illustrates one usage of ListTagsForResource.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 42
X-Amz-Target: DirectoryService_20150416.ListTagsForResource
X-Amz-Date: 20161214T231352Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161214/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=72d8e8988d5a206b4e218f406544b06cb4f6fd9d8927a270317509c9861b0826

{
  "ResourceId": "d-926example",
  "Limit": 0
}
```



```
}
```

## Example Response

This example illustrates one usage of ListTagsForResource.

```
HTTP/1.1 200 OK
x-amzn-RequestId: fb7da12c-c252-11e6-a96d-2b0686697d23
Content-Type: application/x-amz-json-1.1
Content-Length: 53
Date: Wed, 14 Dec 2016 23:13:54 GMT

{
  "Tags": [
    {
      "Key": "environment",
      "Value": "production"
    }
  ]
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# RegisterCertificate

Registers a certificate for a secure LDAP or client certificate authentication.

## Request Syntax

```
{
  "CertificateData": "string",
  "ClientCertAuthSettings": {
    "OCSPUrl": "string"
  },
  "DirectoryId": "string",
  "Type": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### CertificateData

The certificate PEM string that needs to be registered.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8192.

Required: Yes

### ClientCertAuthSettings

A ClientCertAuthSettings object that contains client certificate authentication settings.

Type: [ClientCertAuthSettings](#) object

Required: No

### DirectoryId

The identifier of the directory.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

## Type

The function that the registered certificate performs. Valid values include `ClientLDAPS` or `ClientCertAuth`. The default value is `ClientLDAPS`.

Type: String

Valid Values: `ClientCertAuth` | `ClientLDAPS`

Required: No

## Response Syntax

```
{
  "CertificateId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### CertificateId

The identifier of the certificate.

Type: String

Pattern: `^c-[0-9a-f]{10}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **CertificateAlreadyExistsException**

The certificate has already been registered into the system.

HTTP Status Code: 400

### **CertificateLimitExceededException**

The certificate could not be added because the certificate limit has been reached.

HTTP Status Code: 400

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **DirectoryDoesNotExistException**

The specified directory does not exist in the system.

HTTP Status Code: 400

### **DirectoryUnavailableException**

The specified directory is unavailable or could not be found.

HTTP Status Code: 400

### **InvalidCertificateException**

The certificate PEM that was provided has incorrect encoding.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

### **UnsupportedOperationException**

The operation is not supported.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# RegisterEventTopic

Associates a directory with an Amazon SNS topic. This establishes the directory as a publisher to the specified Amazon SNS topic. You can then receive email or text (SMS) messages when the status of your directory changes. You get notified if your directory goes from an Active status to an Impaired or Inoperable status. You also receive a notification when the directory returns to an Active status.

## Request Syntax

```
{
  "DirectoryId": "string",
  "TopicName": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The Directory ID that will publish status messages to the Amazon SNS topic.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### TopicName

The Amazon SNS topic name to which the directory will publish status messages. This Amazon SNS topic must be in the same region as the specified Directory ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9_-]+`

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ClientException

A client exception has occurred.

HTTP Status Code: 400

### EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

### InvalidParameterException

One or more parameters are not valid.

HTTP Status Code: 400

### ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of RegisterEventTopic.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
```

```
Content-Length: 63
X-Amz-Target: DirectoryService_20150416.RegisterEventTopic
X-Amz-Date: 20161214T232258Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161214/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=6e1e2996789f568cf057fa66e70b1ba114d7388510787be6092055ab97a07828

{
  "DirectoryId": "d-926example",
  "TopicName": "snstopicexample"
}
```

## Example Response

This example illustrates one usage of RegisterEventTopic.

```
HTTP/1.1 200 OK
x-amzn-RequestId: a68a1e79-c19b-11e6-870b-c3330207df37
Content-Type: application/x-amz-json-1.1
Content-Length: 29
Date: Wed, 14 Dec 2016 23:23:01 GMT

{
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)



- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# RejectSharedDirectory

Rejects a directory sharing request that was sent from the directory owner account.

## Request Syntax

```
{  
  "SharedDirectoryId": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### [SharedDirectoryId](#)

Identifier of the shared directory in the directory consumer account. This identifier is different for each directory owner account.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

## Response Syntax

```
{  
  "SharedDirectoryId": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [SharedDirectoryId](#)

Identifier of the shared directory in the directory consumer account.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ClientException

A client exception has occurred.

HTTP Status Code: 400

### DirectoryAlreadySharedException

The specified directory has already been shared with this AWS account.

HTTP Status Code: 400

### EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

### InvalidParameterException

One or more parameters are not valid.

HTTP Status Code: 400

### ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# RemoveIpRoutes

Removes IP address blocks from a directory.

## Request Syntax

```
{  
  "CidrIps": [ "string" ],  
  "DirectoryId": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### CidrIps

IP address blocks that you want to remove.

Type: Array of strings

Pattern: `^(( [0-9] | [1-9][0-9] | 1[0-9]{2} | 2[0-4][0-9] | 25[0-5])\.) {3} ([0-9] | [1-9][0-9] | 1[0-9]{2} | 2[0-4][0-9] | 25[0-5]) (\ / ([1-9] | [1-2][0-9] | 3[0-2])) )$`

Required: Yes

### DirectoryId

Identifier (ID) of the directory from which you want to remove the IP addresses.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ClientException

A client exception has occurred.

HTTP Status Code: 400

### DirectoryUnavailableException

The specified directory is unavailable or could not be found.

HTTP Status Code: 400

### EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

### InvalidParameterException

One or more parameters are not valid.

HTTP Status Code: 400

### ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of `RemoveRoutes`.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
```

```
Content-Length: 62
X-Amz-Target: DirectoryService_20150416.RemoveIpRoutes
X-Amz-Date: 20161214T233152Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161214/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=b3413802dda807a99b3a5783eef6fc3599eefa200820af9842cc5b24becb1802

{
  "DirectoryId": "d-926example",
  "CidrIps": ["12.12.12.12/32"]
}
```

## Example Response

This example illustrates one usage of `RemoveIpRoutes`.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 7f62aa28-c255-11e6-b3d3-bf8f15b8b2ee
Content-Type: application/x-amz-json-1.1
Content-Length: 2
Date: Wed, 14 Dec 2016 23:31:54 GMT

{
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# RemoveRegion

Stops all replication and removes the domain controllers from the specified Region. You cannot remove the primary Region with this operation. Instead, use the `DeleteDirectory` API.

## Request Syntax

```
{
  "DirectoryId": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The identifier of the directory for which you want to remove Region replication.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

Client authentication is not available in this region at this time.

HTTP Status Code: 400

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **DirectoryDoesNotExistException**

The specified directory does not exist in the system.

HTTP Status Code: 400

### **DirectoryUnavailableException**

The specified directory is unavailable or could not be found.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

### **UnsupportedOperationException**

The operation is not supported.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# RemoveTagsFromResource

Removes tags from a directory.

## Request Syntax

```
{
  "ResourceId": "string",
  "TagKeys": [ "string" ]
}
```

## Request Parameters

The request accepts the following data in JSON format.

### ResourceId

Identifier (ID) of the directory from which to remove the tag.

Type: String

Pattern: `^[d]-[0-9a-f]{10}$`

Required: Yes

### TagKeys

The tag key (name) of the tag to be removed.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^([\p{L}\p{Z}\p{N}_ . :/=+\-@]*)$`

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ClientException

A client exception has occurred.

HTTP Status Code: 400

### EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

### InvalidParameterException

One or more parameters are not valid.

HTTP Status Code: 400

### ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of `RemoveTagsFromResource`.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 58
X-Amz-Target: DirectoryService_20150416.RemoveTagsFromResource
X-Amz-Date: 20161214T234556Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
```

```
Authorization: AWS4-HMAC-SHA256
Credential=AKIAI7E3BYXS3example/20161214/us-west-2/ds/aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target,
Signature=707f9d53696de7adc446b3bd54404571011febc29e9b76c6aed793767639bf47

{
  "ResourceId":"d-926example",
  "TagKeys": ["environment"]
}
```

## Example Response

This example illustrates one usage of `RemoveTagsFromResource`.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 767374a0-c257-11e6-ad7a-a9557d30f017
Content-Type: application/x-amz-json-1.1
Content-Length: 2
Date: Wed, 14 Dec 2016 23:45:58 GMT

{
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# ResetUserPassword

Resets the password for any user in your AWS Managed Microsoft AD or Simple AD directory. Disabled users will become enabled and can be authenticated following the API call.

You can reset the password for any user in your directory with the following exceptions:

- For Simple AD, you cannot reset the password for any user that is a member of either the **Domain Admins** or **Enterprise Admins** group except for the administrator user.
- For AWS Managed Microsoft AD, you can only reset the password for a user that is in an OU based off of the NetBIOS name that you typed when you created your directory. For example, you cannot reset the password for a user in the **AWS Reserved** OU. For more information about the OU structure for an AWS Managed Microsoft AD directory, see [What Gets Created](#) in the *AWS Directory Service Administration Guide*.

## Request Syntax

```
{  
  "DirectoryId": "string",  
  "NewPassword": "string",  
  "UserName": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### [DirectoryId](#)

Identifier of the AWS Managed Microsoft AD or Simple AD directory in which the user resides.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### [NewPassword](#)

The new password that will be reset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 127.

Required: Yes

### UserName

The user name of the user whose password will be reset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^(?!.*\\|.*"|.*/|.*\[|.*\]|.*:|.*;|.*\||.*=|.*,|.*\+|.*\*|.*\?|.*<|.*>|.*@).*$`

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ClientException

A client exception has occurred.

HTTP Status Code: 400

### DirectoryUnavailableException

The specified directory is unavailable or could not be found.

HTTP Status Code: 400

### EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400



## **InvalidPasswordException**

The new password provided by the user does not meet the password complexity requirements defined in your directory.

HTTP Status Code: 400

## **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## **UnsupportedOperationException**

The operation is not supported.

HTTP Status Code: 400

## **UserDoesNotExistException**

The user provided a username that does not exist in your directory.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# RestoreFromSnapshot

Restores a directory using an existing directory snapshot.

When you restore a directory from a snapshot, any changes made to the directory after the snapshot date are overwritten.

This action returns as soon as the restore operation is initiated. You can monitor the progress of the restore operation by calling the [DescribeDirectories](#) operation with the directory identifier. When the **DirectoryDescription.Stage** value changes to `Active`, the restore operation is complete.

## Request Syntax

```
{  
  "SnapshotId": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### [SnapshotId](#)

The identifier of the snapshot to restore from.

Type: String

Pattern: `^s-[0-9a-f]{10}$`

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## ClientException

A client exception has occurred.

HTTP Status Code: 400

## EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

## InvalidParameterException

One or more parameters are not valid.

HTTP Status Code: 400

## ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of RestoreFromSnapshot.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 30
X-Amz-Target: DirectoryService_20150416.RestoreFromSnapshot
X-Amz-Date: 20161214T235310Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161214/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=5c6be5a543a9df855e15ed75c131318330c4acf9b791515e8b3524e2430c180f
```

```
{  
  "SnapshotId": "s-9267f6da4e"  
}
```

## Example Response

This example illustrates one usage of `RestoreFromSnapshot`.

```
HTTP/1.1 200 OK  
x-amzn-RequestId: 78ebab96-c258-11e6-a4dc-e5519684970a  
Content-Type: application/x-amz-json-1.1  
Content-Length: 2  
Date: Wed, 14 Dec 2016 23:53:12 GMT  
  
{  
  
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ShareDirectory

Shares a specified directory (`DirectoryId`) in your AWS account (directory owner) with another AWS account (directory consumer). With this operation you can use your directory from any AWS account and from any Amazon VPC within an AWS Region.

When you share your AWS Managed Microsoft AD directory, AWS Directory Service creates a shared directory in the directory consumer account. This shared directory contains the metadata to provide access to the directory within the directory owner account. The shared directory is visible in all VPCs in the directory consumer account.

The `ShareMethod` parameter determines whether the specified directory can be shared between AWS accounts inside the same AWS organization (ORGANIZATIONS). It also determines whether you can share the directory with any other AWS account either inside or outside of the organization (HANDSHAKE).

The `ShareNotes` parameter is only used when HANDSHAKE is called, which sends a directory sharing request to the directory consumer.

## Request Syntax

```
{
  "DirectoryId": "string",
  "ShareMethod": "string",
  "ShareNotes": "string",
  "ShareTarget": {
    "Id": "string",
    "Type": "string"
  }
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

Identifier of the AWS Managed Microsoft AD directory that you want to share with other AWS accounts.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### ShareMethod

The method used when sharing a directory to determine whether the directory should be shared within your AWS organization (ORGANIZATIONS) or with any AWS account by sending a directory sharing request (HANDSHAKE).

Type: String

Valid Values: ORGANIZATIONS | HANDSHAKE

Required: Yes

### ShareNotes

A directory share request that is sent by the directory owner to the directory consumer. The request includes a typed message to help the directory consumer administrator determine whether to approve or reject the share invitation.

Type: String

Length Constraints: Maximum length of 1024.

Required: No

### ShareTarget

Identifier for the directory consumer account with whom the directory is to be shared.

Type: [ShareTarget](#) object

Required: Yes

## Response Syntax

```
{  
  "SharedDirectoryId": "string"
```

```
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### SharedDirectoryId

Identifier of the directory that is stored in the directory consumer account that is shared from the specified directory (DirectoryId).

Type: String

Pattern: `^d-[0-9a-f]{10}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

Client authentication is not available in this region at this time.

HTTP Status Code: 400

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **DirectoryAlreadySharedException**

The specified directory has already been shared with this AWS account.

HTTP Status Code: 400

### **EntityDoesNotExistException**

The specified entity could not be found.

HTTP Status Code: 400

## **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

## **InvalidTargetException**

The specified shared target is not valid.

HTTP Status Code: 400

## **OrganizationsException**

Exception encountered while trying to access your AWS organization.

HTTP Status Code: 400

## **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## **ShareLimitExceededException**

The maximum number of AWS accounts that you can share with this directory has been reached.

HTTP Status Code: 400

## **UnsupportedOperationException**

The operation is not supported.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)



- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# StartSchemaExtension

Applies a schema extension to a Microsoft AD directory.

## Request Syntax

```
{  
  "CreateSnapshotBeforeSchemaExtension": boolean,  
  "Description": "string",  
  "DirectoryId": "string",  
  "LdifContent": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### CreateSnapshotBeforeSchemaExtension

If true, creates a snapshot of the directory before applying the schema extension.

Type: Boolean

Required: Yes

### Description

A description of the schema extension.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `^([a-zA-Z0-9_])[\a-zA-Z0-9_@#%*+=:?./!\s-]*$`

Required: Yes

### DirectoryId

The identifier of the directory for which the schema extension will be applied to.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### LdifContent

The LDIF file represented as a string. To construct the LdifContent string, precede each line as it would be formatted in an ldif file with `\n`. See the example request below for more details. The file size can be no larger than 1MB.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 500000.

Required: Yes

## Response Syntax

```
{
  "SchemaExtensionId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### SchemaExtensionId

The identifier of the schema extension that will be applied.

Type: String

Pattern: `^e-[0-9a-f]{10}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## ClientException

A client exception has occurred.

HTTP Status Code: 400

## DirectoryUnavailableException

The specified directory is unavailable or could not be found.

HTTP Status Code: 400

## EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

## InvalidParameterException

One or more parameters are not valid.

HTTP Status Code: 400

## ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## SnapshotLimitExceededException

The maximum number of manual snapshots for the directory has been reached. You can use the [GetSnapshotLimits](#) operation to determine the snapshot limits for a directory.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of StartSchemaExtension.

```

POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 320
X-Amz-Target: DirectoryService_20150416.StartSchemaExtension
X-Amz-Date: 20161219T190703Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 boto3/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161219/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=5c1200f494c1771770d7aa964e45ee36d80e724e0d9a8e62ab9822574c8cc915

{
  "CreateSnapshotBeforeSchemaExtension":true,
  "DirectoryId":"d-926example",
  "LdifContent":"dn: CN=User,CN=Schema,CN=Configuration,DC=sales,DC=example,DC=com
\nchangetype: modify\nadd: mayContain\nmayContain: drink\n-\n\nDN:\nchangetype: modify
\nreplace: schemaupdatenow\nschemaupdatenow: 1\n-",
  "Description":"Adds may contain attribute to user class. To construct the
LdifContent string, precede each line as it would be formatted in an ldif file with
\n. For example the LdifContent string above is formatted the following way in an Ldif
file:

  dn: CN=User,CN=Schema,CN=Configuration,DC=sales,DC=example,DC=com
  changetype: modify
  add: mayContain
  mayContain: drink
  -

  dn:
  changetype: modify
  replace: schemaupdatenow
  schemaupdatenow: 1
  -"
}

```

## Example Response

This example illustrates one usage of StartSchemaExtension.

```
HTTP/1.1 200 OK
```

```
x-amzn-RequestId: 54723d00-c61e-11e6-a96d-2b0686697d23
Content-Type: application/x-amz-json-1.1
Content-Length: 36
Date: Mon, 19 Dec 2016 19:07:04 GMT

{
  "SchemaExtensionId": "e-926731dc50"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UnshareDirectory

Stops the directory sharing between the directory owner and consumer accounts.

## Request Syntax

```
{
  "DirectoryId": "string",
  "UnshareTarget": {
    "Id": "string",
    "Type": "string"
  }
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The identifier of the AWS Managed Microsoft AD directory that you want to stop sharing.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### UnshareTarget

Identifier for the directory consumer account with whom the directory has to be unshared.

Type: [UnshareTarget](#) object

Required: Yes

## Response Syntax

```
{
  "SharedDirectoryId": "string"
}
```

```
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### SharedDirectoryId

Identifier of the directory stored in the directory consumer account that is to be unshared from the specified directory (`DirectoryId`).

Type: String

Pattern: `^d-[0-9a-f]{10}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **DirectoryNotSharedException**

The specified directory has not been shared with this AWS account.

HTTP Status Code: 400

### **EntityDoesNotExistException**

The specified entity could not be found.

HTTP Status Code: 400

### **InvalidTargetException**

The specified shared target is not valid.

HTTP Status Code: 400



## ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateConditionalForwarder

Updates a conditional forwarder that has been set up for your AWS directory.

## Request Syntax

```
{  
  "DirectoryId": "string",  
  "DnsIpAddrs": [ "string" ],  
  "RemoteDomainName": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The directory ID of the AWS directory for which to update the conditional forwarder.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### DnsIpAddrs

The updated IP addresses of the remote DNS server associated with the conditional forwarder.

Type: Array of strings

Pattern: `^(?:((?:25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)\.)){3}(?:25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)$`

Required: Yes

### RemoteDomainName

The fully qualified domain name (FQDN) of the remote domain with which you will set up a trust relationship.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^([a-zA-Z0-9]+[\.\-])+( [a-zA-Z0-9] )+[\.]?$`

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ClientException

A client exception has occurred.

HTTP Status Code: 400

### DirectoryUnavailableException

The specified directory is unavailable or could not be found.

HTTP Status Code: 400

### EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

### InvalidParameterException

One or more parameters are not valid.

HTTP Status Code: 400

### ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## UnsupportedOperationException

The operation is not supported.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of UpdateConditionalForwarder.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 107
X-Amz-Target: DirectoryService_20150416.UpdateConditionalForwarder
X-Amz-Date: 20161215T183823Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161215/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=84648cead858ef1efd7db75ce248aa3e22a78139b109eec6122dc3c495b71085

{
  "DirectoryId":"d-926example",
  "RemoteDomainName":"sales.example.com",
  "DnsIpAddrs": ["172.168.101.11"]
}
```

### Example Response

This example illustrates one usage of UpdateConditionalForwarder.

```
HTTP/1.1 200 OK
x-amzn-RequestId: aa015a05-c2f5-11e6-b3d3-bf8f15b8b2ee
Content-Type: application/x-amz-json-1.1
Content-Length: 2
Date: Thu, 15 Dec 2016 18:38:27 GMT
```

```
{  
  
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateDirectorySetup

Updates the directory for a particular update type.

## Request Syntax

```
{
  "CreateSnapshotBeforeUpdate": boolean,
  "DirectoryId": "string",
  "OSUpdateSettings": {
    "OSVersion": "string"
  },
  "UpdateType": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### CreateSnapshotBeforeUpdate

The boolean that specifies if a snapshot for the directory needs to be taken before updating the directory.

Type: Boolean

Required: No

### DirectoryId

The identifier of the directory on which you want to perform the update.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### OSUpdateSettings

The settings for the OS update that needs to be performed on the directory.

Type: [OSUpdateSettings](#) object

Required: No

### UpdateType

The type of update that needs to be performed on the directory. For example, OS.

Type: String

Valid Values: OS

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

Client authentication is not available in this region at this time.

HTTP Status Code: 400

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **DirectoryDoesNotExistException**

The specified directory does not exist in the system.

HTTP Status Code: 400

### **DirectoryInDesiredStateException**

The directory is already updated to desired update type settings.

HTTP Status Code: 400

## DirectoryUnavailableException

The specified directory is unavailable or could not be found.

HTTP Status Code: 400

## InvalidParameterException

One or more parameters are not valid.

HTTP Status Code: 400

## ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## SnapshotLimitExceededException

The maximum number of manual snapshots for the directory has been reached. You can use the [GetSnapshotLimits](#) operation to determine the snapshot limits for a directory.

HTTP Status Code: 400

## UnsupportedOperationException

The operation is not supported.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)



- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateNumberOfDomainControllers

Adds or removes domain controllers to or from the directory. Based on the difference between current value and new value (provided through this API call), domain controllers will be added or removed. It may take up to 45 minutes for any new domain controllers to become fully active once the requested number of domain controllers is updated. During this time, you cannot make another update request.

## Request Syntax

```
{
  "DesiredNumber": number,
  "DirectoryId": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DesiredNumber

The number of domain controllers desired in the directory.

Type: Integer

Valid Range: Minimum value of 2.

Required: Yes

### DirectoryId

Identifier of the directory to which the domain controllers will be added or removed.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ClientException

A client exception has occurred.

HTTP Status Code: 400

### DirectoryUnavailableException

The specified directory is unavailable or could not be found.

HTTP Status Code: 400

### DomainControllerLimitExceededException

The maximum allowed number of domain controllers per directory was exceeded. The default limit per directory is 20 domain controllers.

HTTP Status Code: 400

### EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

### InvalidParameterException

One or more parameters are not valid.

HTTP Status Code: 400

### ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

### UnsupportedOperationException

The operation is not supported.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateRadius

Updates the Remote Authentication Dial In User Service (RADIUS) server information for an AD Connector or Microsoft AD directory.

## Request Syntax

```
{
  "DirectoryId": "string",
  "RadiusSettings": {
    "AuthenticationProtocol": "string",
    "DisplayLabel": "string",
    "RadiusPort": number,
    "RadiusRetries": number,
    "RadiusServers": [ "string" ],
    "RadiusTimeout": number,
    "SharedSecret": "string",
    "UseSameUsername": boolean
  }
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The identifier of the directory for which to update the RADIUS server information.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### RadiusSettings

A [RadiusSettings](#) object that contains information about the RADIUS server.

Type: [RadiusSettings](#) object

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ClientException

A client exception has occurred.

HTTP Status Code: 400

### EntityDoesNotExistException

The specified entity could not be found.

HTTP Status Code: 400

### InvalidParameterException

One or more parameters are not valid.

HTTP Status Code: 400

### ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## Examples

The following examples are formatted for legibility.

### Example Request

This example illustrates one usage of UpdateRadius.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 262
X-Amz-Target: DirectoryService_20150416.UpdateRadius
```

```
X-Amz-Date: 20161215T184937Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161215/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=6cc8097b61ad0ee23e166193d317a066feeea582d252b57923a0781dc011a686

{
  "DirectoryId":"d-926example",
  "RadiusSettings":{
    "DisplayLabel":"MyRadius",
    "UseSameUsername":true,
    "RadiusTimeout":1,
    "AuthenticationProtocol":"PAP",
    "RadiusPort":1027,
    "RadiusRetries":1,
    "SharedSecret":"12345678",
    "RadiusServers":[
      "172.168.101.113"
    ]
  }
}
```

## Example Response

This example illustrates one usage of UpdateRadius.

```
HTTP/1.1 200 OK
x-amzn-RequestId: fcd40ac9-c247-11e6-a7ca-f9a52a6a0390
Content-Type: application/x-amz-json-1.1
Content-Length: 2
Date: Thu, 15 Dec 2016 18:49:39 GMT

{
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# UpdateSettings

Updates the configurable settings for the specified directory.

## Request Syntax

```
{
  "DirectoryId": "string",
  "Settings": [
    {
      "Name": "string",
      "Value": "string"
    }
  ]
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DirectoryId

The identifier of the directory for which to update settings.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: Yes

### Settings

The list of [Setting](#) objects.

Type: Array of [Setting](#) objects

Required: Yes

## Response Syntax

```
{
```

```
"DirectoryId": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### DirectoryId

The identifier of the directory.

Type: String

Pattern: ^d-[0-9a-f]{10}\$

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **DirectoryDoesNotExistException**

The specified directory does not exist in the system.

HTTP Status Code: 400

### **DirectoryUnavailableException**

The specified directory is unavailable or could not be found.

HTTP Status Code: 400

### **IncompatibleSettingsException**

The specified directory setting is not compatible with other settings.

HTTP Status Code: 400

## InvalidParameterException

One or more parameters are not valid.

HTTP Status Code: 400

## ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## UnsupportedOperationException

The operation is not supported.

HTTP Status Code: 400

## UnsupportedSettingsException

The specified directory setting is not supported.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateTrust

Updates the trust that has been set up between your AWS Managed Microsoft AD directory and an self-managed Active Directory.

## Request Syntax

```
{
  "SelectiveAuth": "string",
  "TrustId": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### SelectiveAuth

Updates selective authentication for the trust.

Type: String

Valid Values: Enabled | Disabled

Required: No

### TrustId

Identifier of the trust relationship.

Type: String

Pattern: `^t-[0-9a-f]{10}$`

Required: Yes

## Response Syntax

```
{
  "RequestId": "string",
  "TrustId": "string"
}
```

```
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### RequestId

The AWS request identifier.

Type: String

Pattern: `^[A-Fa-f0-9]{8}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{12}$`

### TrustId

Identifier of the trust relationship.

Type: String

Pattern: `^t-[0-9a-f]{10}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **EntityDoesNotExistException**

The specified entity could not be found.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

## ServiceException

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# VerifyTrust

AWS Directory Service for Microsoft Active Directory allows you to configure and verify trust relationships.

This action verifies a trust relationship between your AWS Managed Microsoft AD directory and an external domain.

## Request Syntax

```
{  
  "TrustId": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### TrustId

The unique Trust ID of the trust relationship to verify.

Type: String

Pattern: `^t-[0-9a-f]{10}$`

Required: Yes

## Response Syntax

```
{  
  "TrustId": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## **TrustId**

The unique Trust ID of the trust relationship that was verified.

Type: String

Pattern: `^t-[0-9a-f]{10}$`

## **Errors**

For information about the errors that are common to all actions, see [Common Errors](#).

### **ClientException**

A client exception has occurred.

HTTP Status Code: 400

### **EntityDoesNotExistException**

The specified entity could not be found.

HTTP Status Code: 400

### **InvalidParameterException**

One or more parameters are not valid.

HTTP Status Code: 400

### **ServiceException**

An exception has occurred in AWS Directory Service.

HTTP Status Code: 500

### **UnsupportedOperationException**

The operation is not supported.

HTTP Status Code: 400

## **Examples**

The following examples are formatted for legibility.



## Example Request

This example illustrates one usage of VerifyTrust.

```
POST / HTTP/1.1
Host: ds.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 27
X-Amz-Target: DirectoryService_20150416.VerifyTrust
X-Amz-Date: 20161215T191010Z
User-Agent: aws-cli/1.11.24 Python/2.7.9 Windows/7 botocore/1.4.81
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256
  Credential=AKIAI7E3BYXS3example/20161215/us-west-2/ds/aws4_request,
  SignedHeaders=content-type;host;x-amz-date;x-amz-target,
  Signature=249c3fb0ac94d57cc9abb43f6422fe237fce723ddd9462a4666712e46e3b5371

{
  "TrustId": "t-9267353df0"
}
```

## Example Response

This example illustrates one usage of VerifyTrust.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 3343bc79-c18f-11e6-ba7f-e33ae22bc363
Content-Type: application/x-amz-json-1.1
Content-Length: 26
Date: Thu, 15 Dec 2016 19:10:12 GMT

{
  "TrustId": "t-9267353df0"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# Data Types

The AWS Directory Service API contains several data types that various actions use. This section describes each data type in detail.

## Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [Attribute](#)
- [Certificate](#)
- [CertificateInfo](#)
- [ClientAuthenticationSettingInfo](#)
- [ClientCertAuthSettings](#)
- [Computer](#)
- [ConditionalForwarder](#)
- [DirectoryConnectSettings](#)
- [DirectoryConnectSettingsDescription](#)
- [DirectoryDescription](#)
- [DirectoryLimits](#)
- [DirectoryVpcSettings](#)
- [DirectoryVpcSettingsDescription](#)
- [DomainController](#)
- [EventTopic](#)
- [IpRoute](#)
- [IpRouteInfo](#)
- [LDAPSSettingInfo](#)
- [LogSubscription](#)
- [OSUpdateSettings](#)

- [OwnerDirectoryDescription](#)
- [RadiusSettings](#)
- [RegionDescription](#)
- [RegionsInfo](#)
- [SchemaExtensionInfo](#)
- [Setting](#)
- [SettingEntry](#)
- [SharedDirectory](#)
- [ShareTarget](#)
- [Snapshot](#)
- [SnapshotLimits](#)
- [Tag](#)
- [Trust](#)
- [UnshareTarget](#)
- [UpdateInfoEntry](#)
- [UpdateValue](#)

# Attribute

Represents a named directory attribute.

## Contents

### Name

The name of the attribute.

Type: String

Length Constraints: Minimum length of 1.

Required: No

### Value

The value of the attribute.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Certificate

Information about the certificate.

## Contents

### **CertificateId**

The identifier of the certificate.

Type: String

Pattern: `^c-[0-9a-f]{10}$`

Required: No

### **ClientCertAuthSettings**

A `ClientCertAuthSettings` object that contains client certificate authentication settings.

Type: [ClientCertAuthSettings](#) object

Required: No

### **CommonName**

The common name for the certificate.

Type: String

Required: No

### **ExpiryDateTime**

The date and time when the certificate will expire.

Type: Timestamp

Required: No

### **RegisteredDateTime**

The date and time that the certificate was registered.

Type: Timestamp

Required: No

### State

The state of the certificate.

Type: String

Valid Values: Registering | Registered | RegisterFailed | Deregistering | Deregistered | DeregisterFailed

Required: No

### StateReason

Describes a state change for the certificate.

Type: String

Required: No

### Type

The function that the registered certificate performs. Valid values include `ClientLDAPS` or `ClientCertAuth`. The default value is `ClientLDAPS`.

Type: String

Valid Values: `ClientCertAuth` | `ClientLDAPS`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# CertificateInfo

Contains general information about a certificate.

## Contents

### CertificateId

The identifier of the certificate.

Type: String

Pattern: `^c-[0-9a-f]{10}$`

Required: No

### CommonName

The common name for the certificate.

Type: String

Required: No

### ExpiryDateTime

The date and time when the certificate will expire.

Type: Timestamp

Required: No

### State

The state of the certificate.

Type: String

Valid Values: `Registering` | `Registered` | `RegisterFailed` | `Deregistering` | `Deregistered` | `DeregisterFailed`

Required: No

### Type

The function that the registered certificate performs. Valid values include `ClientLDAPS` or `ClientCertAuth`. The default value is `ClientLDAPS`.



Type: String

Valid Values: ClientCertAuth | ClientLDAPS

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ClientAuthenticationSettingInfo

Contains information about a client authentication method for a directory.

## Contents

### LastUpdatedDateTime

The date and time when the status of the client authentication type was last updated.

Type: Timestamp

Required: No

### Status

Whether the client authentication type is enabled or disabled for the specified directory.

Type: String

Valid Values: Enabled | Disabled

Required: No

### Type

The type of client authentication for the specified directory. If no type is specified, a list of all client authentication types that are supported for the directory is retrieved.

Type: String

Valid Values: SmartCard | SmartCardOrPassword

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

# ClientCertAuthSettings

Contains information about the client certificate authentication settings for the RegisterCertificate and DescribeCertificate operations.

## Contents

### OCSPUrl

Specifies the URL of the default OCSP server used to check for revocation status. A secondary value to any OCSP address found in the AIA extension of the user certificate.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^(https?|ftp|file|ldaps?)://[a-zA-Z0-9+&@#/%?~_|!:,.;()]*[a-zA-Z0-9+&@#/%=~_|()]`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Computer

Contains information about a computer account in a directory.

## Contents

### ComputerAttributes

An array of [Attribute](#) objects containing the LDAP attributes that belong to the computer account.

Type: Array of [Attribute](#) objects

Required: No

### ComputerId

The identifier of the computer.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [[&\w+- .@](#)]+

Required: No

### ComputerName

The computer name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 15.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ConditionalForwarder

Points to a remote domain with which you are setting up a trust relationship. Conditional forwarders are required in order to set up a trust relationship with another domain.

## Contents

### DnsIpAddrs

The IP addresses of the remote DNS server associated with RemoteDomainName. This is the IP address of the DNS server that your conditional forwarder points to.

Type: Array of strings

Pattern: `^(?:(:25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)\.)}{3}(?:25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)$`

Required: No

### RemoteDomainName

The fully qualified domain name (FQDN) of the remote domains pointed to by the conditional forwarder.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^([a-zA-Z0-9]+[\.\-])+( [a-zA-Z0-9] )+[\.]?$`

Required: No

### ReplicationScope

The replication scope of the conditional forwarder. The only allowed value is `Domain`, which will replicate the conditional forwarder to all of the domain controllers for your AWS directory.

Type: String

Valid Values: `Domain`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# DirectoryConnectSettings

Contains information for the [ConnectDirectory](#) operation when an AD Connector directory is being created.

## Contents

### CustomerDnsIps

A list of one or more IP addresses of DNS servers or domain controllers in your self-managed directory.

Type: Array of strings

Pattern: `^(?:(:25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)\.)}{3}(?:25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)$`

Required: Yes

### CustomerUserName

The user name of an account in your self-managed directory that is used to connect to the directory. This account must have the following permissions:

- Read users and groups
- Create computer objects
- Join computers to the domain

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[a-zA-Z0-9._-]+`

Required: Yes

### SubnetIds

A list of subnet identifiers in the VPC in which the AD Connector is created.

Type: Array of strings

Pattern: `^(subnet-[0-9a-f]{8}|subnet-[0-9a-f]{17})$`

Required: Yes

## VpcId

The identifier of the VPC in which the AD Connector is created.

Type: String

Pattern: `^(vpc-[0-9a-f]{8}|vpc-[0-9a-f]{17})$`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DirectoryConnectSettingsDescription

Contains information about an AD Connector directory.

## Contents

### AvailabilityZones

A list of the Availability Zones that the directory is in.

Type: Array of strings

Required: No

### ConnectIps

The IP addresses of the AD Connector servers.

Type: Array of strings

Pattern: `^(?:(:25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)\.)}{3}(?:25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)$`

Required: No

### CustomerUserName

The user name of the service account in your self-managed directory.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[a-zA-Z0-9._-]+`

Required: No

### SecurityGroupId

The security group identifier for the AD Connector directory.

Type: String

Pattern: `^(sg-[0-9a-f]{8}|sg-[0-9a-f]{17})$`

Required: No

### **SubnetIds**

A list of subnet identifiers in the VPC that the AD Connector is in.

Type: Array of strings

Pattern: `^(subnet-[0-9a-f]{8}|subnet-[0-9a-f]{17})$`

Required: No

### **VpcId**

The identifier of the VPC that the AD Connector is in.

Type: String

Pattern: `^(vpc-[0-9a-f]{8}|vpc-[0-9a-f]{17})$`

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DirectoryDescription

Contains information about an AWS Directory Service directory.

## Contents

### AccessUrl

The access URL for the directory, such as `http://<alias>.awsapps.com`. If no alias has been created for the directory, `<alias>` is the directory identifier, such as `d-XXXXXXXXXX`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### Alias

The alias for the directory. If no alias has been created for the directory, the alias is the directory identifier, such as `d-XXXXXXXXXX`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 62.

Pattern: `^(?!D-|d-)([\da-zA-Z]+)([-]*[\da-zA-Z])*`

Required: No

### ConnectSettings

A [DirectoryConnectSettingsDescription](#) object that contains additional information about an AD Connector directory. This member is only present if the directory is an AD Connector directory.

Type: [DirectoryConnectSettingsDescription](#) object

Required: No

### Description

The description for the directory.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `^([\a-zA-Z0-9_][\a-zA-Z0-9_@#%*+=:?./!\s-]*)*$`

Required: No

### **DesiredNumberOfDomainControllers**

The desired number of domain controllers in the directory if the directory is Microsoft AD.

Type: Integer

Valid Range: Minimum value of 2.

Required: No

### **DirectoryId**

The directory identifier.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: No

### **DnsIpAddrs**

The IP addresses of the DNS servers for the directory. For a Simple AD or Microsoft AD directory, these are the IP addresses of the Simple AD or Microsoft AD directory servers. For an AD Connector directory, these are the IP addresses of the DNS servers or domain controllers in your self-managed directory to which the AD Connector is connected.

Type: Array of strings

Pattern: `^(?:((?:25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)\.){3}(?:25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)$`

Required: No

### **Edition**

The edition associated with this directory.

Type: String

Valid Values: Enterprise | Standard

Required: No

### LaunchTime

Specifies when the directory was created.

Type: Timestamp

Required: No

### Name

The fully qualified name of the directory.

Type: String

Pattern: `^([a-zA-Z0-9]+[\\\. -])+([a-zA-Z0-9])+$`

Required: No

### OsVersion

The operating system (OS) version of the directory.

Type: String

Valid Values: SERVER\_2012 | SERVER\_2019

Required: No

### OwnerDirectoryDescription

Describes the AWS Managed Microsoft AD directory in the directory owner account.

Type: [OwnerDirectoryDescription](#) object

Required: No

### RadiusSettings

A [RadiusSettings](#) object that contains information about the RADIUS server configured for this directory.

Type: [RadiusSettings](#) object

Required: No

### **RadiusStatus**

The status of the RADIUS MFA server connection.

Type: String

Valid Values: `Creating` | `Completed` | `Failed`

Required: No

### **RegionsInfo**

Lists the Regions where the directory has replicated.

Type: [RegionsInfo](#) object

Required: No

### **ShareMethod**

The method used when sharing a directory to determine whether the directory should be shared within your AWS organization (ORGANIZATIONS) or with any AWS account by sending a shared directory request (HANDSHAKE).

Type: String

Valid Values: `ORGANIZATIONS` | `HANDSHAKE`

Required: No

### **ShareNotes**

A directory share request that is sent by the directory owner to the directory consumer. The request includes a typed message to help the directory consumer administrator determine whether to approve or reject the share invitation.

Type: String

Length Constraints: Maximum length of 1024.

Required: No

### **ShareStatus**

Current directory status of the shared AWS Managed Microsoft AD directory.



Type: String

Valid Values: Shared | PendingAcceptance | Rejected | Rejecting | RejectFailed | Sharing | ShareFailed | Deleted | Deleting

Required: No

### ShortName

The short name of the directory.

Type: String

Pattern: `^[^\\\/:*?"<>|.]+[^\\/:*?"<>|]*$`

Required: No

### Size

The directory size.

Type: String

Valid Values: Small | Large

Required: No

### SsoEnabled

Indicates if single sign-on is enabled for the directory. For more information, see [EnableSso](#) and [DisableSso](#).

Type: Boolean

Required: No

### Stage

The current stage of the directory.

Type: String

Valid Values: Requested | Creating | Created | Active | Inoperable | Impaired | Restoring | RestoreFailed | Deleting | Deleted | Failed | Updating

Required: No

### **StageLastUpdatedDateTime**

The date and time that the stage was last updated.

Type: Timestamp

Required: No

### **StageReason**

Additional information about the directory stage.

Type: String

Required: No

### **Type**

The directory type.

Type: String

Valid Values: SimpleAD | ADConnector | MicrosoftAD | SharedMicrosoftAD

Required: No

### **VpcSettings**

A [DirectoryVpcSettingsDescription](#) object that contains additional information about a directory. This member is only present if the directory is a Simple AD or AWS Managed Microsoft AD directory.

Type: [DirectoryVpcSettingsDescription](#) object

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DirectoryLimits

Contains directory limit information for a Region.

## Contents

### CloudOnlyDirectoriesCurrentCount

The current number of cloud directories in the Region.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

### CloudOnlyDirectoriesLimit

The maximum number of cloud directories allowed in the Region.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

### CloudOnlyDirectoriesLimitReached

Indicates if the cloud directory limit has been reached.

Type: Boolean

Required: No

### CloudOnlyMicrosoftADCurrentCount

The current number of AWS Managed Microsoft AD directories in the region.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

### CloudOnlyMicrosoftADLimit

The maximum number of AWS Managed Microsoft AD directories allowed in the region.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

### **CloudOnlyMicrosoftADLimitReached**

Indicates if the AWS Managed Microsoft AD directory limit has been reached.

Type: Boolean

Required: No

### **ConnectedDirectoriesCurrentCount**

The current number of connected directories in the Region.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

### **ConnectedDirectoriesLimit**

The maximum number of connected directories allowed in the Region.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

### **ConnectedDirectoriesLimitReached**

Indicates if the connected directory limit has been reached.

Type: Boolean

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DirectoryVpcSettings

Contains VPC information for the [CreateDirectory](#) or [CreateMicrosoftAD](#) operation.

## Contents

### SubnetIds

The identifiers of the subnets for the directory servers. The two subnets must be in different Availability Zones. AWS Directory Service creates a directory server and a DNS server in each of these subnets.

Type: Array of strings

Pattern: `^(subnet-[0-9a-f]{8}|subnet-[0-9a-f]{17})$`

Required: Yes

### VpcId

The identifier of the VPC in which to create the directory.

Type: String

Pattern: `^(vpc-[0-9a-f]{8}|vpc-[0-9a-f]{17})$`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DirectoryVpcSettingsDescription

Contains information about the directory.

## Contents

### AvailabilityZones

The list of Availability Zones that the directory is in.

Type: Array of strings

Required: No

### SecurityGroupId

The domain controller security group identifier for the directory.

Type: String

Pattern: `^(sg-[0-9a-f]{8}|sg-[0-9a-f]{17})$`

Required: No

### SubnetIds

The identifiers of the subnets for the directory servers.

Type: Array of strings

Pattern: `^(subnet-[0-9a-f]{8}|subnet-[0-9a-f]{17})$`

Required: No

### VpcId

The identifier of the VPC that the directory is in.

Type: String

Pattern: `^(vpc-[0-9a-f]{8}|vpc-[0-9a-f]{17})$`

Required: No



## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DomainController

Contains information about the domain controllers for a specified directory.

## Contents

### AvailabilityZone

The Availability Zone where the domain controller is located.

Type: String

Required: No

### DirectoryId

Identifier of the directory where the domain controller resides.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: No

### DnsIpAddr

The IP address of the domain controller.

Type: String

Pattern: `^(?:(:25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)\.)?{3}(:25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)$`

Required: No

### DomainControllerId

Identifies a specific domain controller in the directory.

Type: String

Pattern: `^dc-[0-9a-f]{10}$`

Required: No

## LaunchTime

Specifies when the domain controller was created.

Type: Timestamp

Required: No

## Status

The status of the domain controller.

Type: String

Valid Values: Creating | Active | Impaired | Restoring | Deleting | Deleted  
| Failed | Updating

Required: No

## StatusLastUpdatedDateTime

The date and time that the status was last updated.

Type: Timestamp

Required: No

## StatusReason

A description of the domain controller state.

Type: String

Required: No

## SubnetId

Identifier of the subnet in the VPC that contains the domain controller.

Type: String

Pattern: `^(subnet-[0-9a-f]{8}|subnet-[0-9a-f]{17})$`

Required: No

## VpcId

The identifier of the VPC that contains the domain controller.

Type: String

Pattern: `^(vpc-[0-9a-f]{8}|vpc-[0-9a-f]{17})$`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# EventTopic

Information about Amazon SNS topic and AWS Directory Service directory associations.

## Contents

### CreatedDateTime

The date and time of when you associated your directory with the Amazon SNS topic.

Type: Timestamp

Required: No

### DirectoryId

The Directory ID of an AWS Directory Service directory that will publish status messages to an Amazon SNS topic.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: No

### Status

The topic registration status.

Type: String

Valid Values: Registered | Topic not found | Failed | Deleted

Required: No

### TopicArn

The Amazon SNS topic ARN (Amazon Resource Name).

Type: String

Required: No

### TopicName

The name of an Amazon SNS topic the receives status messages from the directory.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9\_-]+

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# IpRoute

IP address block. This is often the address block of the DNS server used for your self-managed domain.

## Contents

### CidrIp

IP address block using CIDR format, for example 10.0.0.0/24. This is often the address block of the DNS server used for your self-managed domain. For a single IP address use a CIDR address block with /32. For example 10.0.0.0/32.

Type: String

Pattern: `^(([0-9]|[1-9][0-9]|1[0-9]{2}|2[0-4][0-9]|25[0-5])\.){3}([0-9]|[1-9][0-9]|1[0-9]{2}|2[0-4][0-9]|25[0-5])|(\/([1-9]|[1-2][0-9]|3[0-2]))$`

Required: No

### Description

Description of the address block.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_][\a-zA-Z0-9_@#%*+=:?./!\s-]*$`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)





# IpRouteInfo

Information about one or more IP address blocks.

## Contents

### AddedDateTime

The date and time the address block was added to the directory.

Type: Timestamp

Required: No

### CidrIp

IP address block in the [IpRoute](#).

Type: String

Pattern: `^(([0-9]|[1-9][0-9]|1[0-9]{2}|2[0-4][0-9]|25[0-5])\.){3}([0-9]|[1-9][0-9]|1[0-9]{2}|2[0-4][0-9]|25[0-5])`(`\`(`[1-9]`|`[1-2][0-9]`|`3[0-2]`))`)$`

Required: No

### Description

Description of the [IpRouteInfo](#).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `^([a-zA-Z0-9_])`(`\\``a-zA-Z0-9_@#%*+=:?./!\s-`)\*`$`

Required: No

### DirectoryId

Identifier (ID) of the directory associated with the IP addresses.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: No

### **IpRouteStatusMsg**

The status of the IP address block.

Type: String

Valid Values: Adding | Added | Removing | Removed | AddFailed | RemoveFailed

Required: No

### **IpRouteStatusReason**

The reason for the IpRouteStatusMsg.

Type: String

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# LDAPSSettingInfo

Contains general information about the LDAPS settings.

## Contents

### LastUpdatedDateTime

The date and time when the LDAPS settings were last updated.

Type: Timestamp

Required: No

### LDAPSStatus

The state of the LDAPS settings.

Type: String

Valid Values: Enabling | Enabled | EnableFailed | Disabled

Required: No

### LDAPSStatusReason

Describes a state change for LDAPS.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# LogSubscription

Represents a log subscription, which tracks real-time data from a chosen log group to a specified destination.

## Contents

### DirectoryId

Identifier (ID) of the directory that you want to associate with the log subscription.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: No

### LogGroupName

The name of the log group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `[- . _ / # A - Z a - z 0 - 9 ] +`

Required: No

### SubscriptionCreatedDateTime

The date and time that the log subscription was created.

Type: Timestamp

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# OSUpdateSettings

OS version that the directory needs to be updated to.

## Contents

### OSVersion

OS version that the directory needs to be updated to.

Type: String

Valid Values: SERVER\_2012 | SERVER\_2019

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# OwnerDirectoryDescription

Describes the directory owner account details that have been shared to the directory consumer account.

## Contents

### AccountId

Identifier of the directory owner account.

Type: String

Pattern: `^\d{12}$`

Required: No

### DirectoryId

Identifier of the AWS Managed Microsoft AD directory in the directory owner account.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: No

### DnsIpAddrs

IP address of the directory's domain controllers.

Type: Array of strings

Pattern: `^(?:((?:25[0-5]|2[0-4][0-9]|01?[0-9][0-9]?)\.)?){3}(?:25[0-5]|2[0-4][0-9]|01?[0-9][0-9]?)$`

Required: No

### RadiusSettings

A [RadiusSettings](#) object that contains information about the RADIUS server.

Type: [RadiusSettings](#) object

Required: No

## RadiusStatus

Information about the status of the RADIUS server.

Type: String

Valid Values: `Creating` | `Completed` | `Failed`

Required: No

## VpcSettings

Information about the VPC settings for the directory.

Type: [DirectoryVpcSettingsDescription](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# RadiusSettings

Contains information about a Remote Authentication Dial In User Service (RADIUS) server.

## Contents

### AuthenticationProtocol

The protocol specified for your RADIUS endpoints.

Type: String

Valid Values: PAP | CHAP | MS-CHAPv1 | MS-CHAPv2

Required: No

### DisplayLabel

Not currently used.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

### RadiusPort

The port that your RADIUS server is using for communications. Your self-managed network must allow inbound traffic over this port from the AWS Directory Service servers.

Type: Integer

Valid Range: Minimum value of 1025. Maximum value of 65535.

Required: No

### RadiusRetries

The maximum number of times that communication with the RADIUS server is retried after the initial attempt.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 10.

Required: No

### **RadiusServers**

An array of strings that contains the fully qualified domain name (FQDN) or IP addresses of the RADIUS server endpoints, or the FQDN or IP addresses of your RADIUS server load balancer.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

### **RadiusTimeout**

The amount of time, in seconds, to wait for the RADIUS server to respond.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 20.

Required: No

### **SharedSecret**

Required for enabling RADIUS on the directory.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 512.

Pattern:  $^{\backslash}p\{LD\}|\backslash}p\{Punct\}|\ )+\$$

Required: No

### **UseSameUsername**

Not currently used.

Type: Boolean

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RegionDescription

The replicated Region information for a directory.

## Contents

### DesiredNumberOfDomainControllers

The desired number of domain controllers in the specified Region for the specified directory.

Type: Integer

Valid Range: Minimum value of 2.

Required: No

### DirectoryId

The identifier of the directory.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: No

### LastUpdatedDateTime

The date and time that the Region description was last updated.

Type: Timestamp

Required: No

### LaunchTime

Specifies when the Region replication began.

Type: Timestamp

Required: No

### RegionName

The name of the Region. For example, `us-east-1`.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 32.

Required: No

### RegionType

Specifies whether the Region is the primary Region or an additional Region.

Type: String

Valid Values: `Primary` | `Additional`

Required: No

### Status

The status of the replication process for the specified Region.

Type: String

Valid Values: `Requested` | `Creating` | `Created` | `Active` | `Inoperable` | `Impaired` | `Restoring` | `RestoreFailed` | `Deleting` | `Deleted` | `Failed` | `Updating`

Required: No

### StatusLastUpdatedDateTime

The date and time that the Region status was last updated.

Type: Timestamp

Required: No

### VpcSettings

Contains VPC information for the [CreateDirectory](#) or [CreateMicrosoftAD](#) operation.

Type: [DirectoryVpcSettings](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RegionsInfo

Provides information about the Regions that are configured for multi-Region replication.

## Contents

### AdditionalRegions

Lists the Regions where the directory has been replicated, excluding the primary Region.

Type: Array of strings

Length Constraints: Minimum length of 8. Maximum length of 32.

Required: No

### PrimaryRegion

The Region where the AWS Managed Microsoft AD directory was originally created.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 32.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# SchemaExtensionInfo

Information about a schema extension.

## Contents

### Description

A description of the schema extension.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `^([\a-zA-Z0-9_][\a-zA-Z0-9_@#%*+=:?./!\s-])*`

Required: No

### DirectoryId

The identifier of the directory to which the schema extension is applied.

Type: String

Pattern: `^d-[0-9a-f]{10}`

Required: No

### EndTime

The date and time that the schema extension was completed.

Type: Timestamp

Required: No

### SchemaExtensionId

The identifier of the schema extension.

Type: String

Pattern: `^e-[0-9a-f]{10}`

Required: No



## SchemaExtensionStatus

The current status of the schema extension.

Type: String

Valid Values: Initializing | CreatingSnapshot | UpdatingSchema | Replicating | CancelInProgress | RollbackInProgress | Cancelled | Failed | Completed

Required: No

## SchemaExtensionStatusReason

The reason for the SchemaExtensionStatus.

Type: String

Required: No

## StartDateTime

The date and time that the schema extension started being applied to the directory.

Type: Timestamp

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Setting

Contains information about the configurable settings for a directory.

## Contents

### Name

The name of the directory setting. For example:

TLS\_1\_0

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9-/. _]*$`

Required: Yes

### Value

The value of the directory setting for which to retrieve information. For example, for TLS\_1\_0, the valid values are: Enable and Disable.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9_]*$`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# SettingEntry

Contains information about the specified configurable setting for a directory.

## Contents

### AllowedValues

The valid range of values for the directory setting. These values depend on the `DataType` of your directory.

Type: String

Required: No

### AppliedValue

The value of the directory setting that is applied to the directory.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9_]*$`

Required: No

### DataType

The data type of a directory setting. This is used to define the `AllowedValues` of a setting. For example a data type can be `Boolean`, `DurationInSeconds`, or `Enum`.

Type: String

Required: No

### LastRequestedDateTime

The date and time when the request to update a directory setting was last submitted.

Type: Timestamp

Required: No

## LastUpdatedDateTime

The date and time when the directory setting was last updated.

Type: Timestamp

Required: No

## Name

The name of the directory setting. For example:

TLS\_1\_0

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9-/. _]*$`

Required: No

## RequestDetailedStatus

Details about the status of the request to update the directory setting. If the directory setting is deployed in more than one region, status is returned for the request in each region where the setting is deployed.

Type: String to string map

Key Length Constraints: Minimum length of 8. Maximum length of 32.

Valid Values: Requested | Updating | Updated | Failed | Default

Required: No

## RequestedValue

The value that was last requested for the directory setting.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9_]*$`

Required: No

### **RequestStatus**

The overall status of the request to update the directory setting request. If the directory setting is deployed in more than one region, and the request fails in any region, the overall status is `Failed`.

Type: String

Valid Values: `Requested` | `Updating` | `Updated` | `Failed` | `Default`

Required: No

### **RequestStatusMessage**

The last status message for the directory status request.

Type: String

Required: No

### **Type**

The type, or category, of a directory setting. Similar settings have the same type. For example, `Protocol`, `Cipher`, or `Certificate-Based Authentication`.

Type: String

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# SharedDirectory

Details about the shared directory in the directory owner account for which the share request in the directory consumer account has been accepted.

## Contents

### CreatedDateTime

The date and time that the shared directory was created.

Type: Timestamp

Required: No

### LastUpdatedDateTime

The date and time that the shared directory was last updated.

Type: Timestamp

Required: No

### OwnerAccountId

Identifier of the directory owner account, which contains the directory that has been shared to the consumer account.

Type: String

Pattern: `^\d{12}$`

Required: No

### OwnerDirectoryId

Identifier of the directory in the directory owner account.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: No

## SharedAccountId

Identifier of the directory consumer account that has access to the shared directory (`OwnerDirectoryId`) in the directory owner account.

Type: String

Pattern: `^\d{12}$`

Required: No

## SharedDirectoryId

Identifier of the shared directory in the directory consumer account. This identifier is different for each directory owner account.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: No

## ShareMethod

The method used when sharing a directory to determine whether the directory should be shared within your AWS organization (`ORGANIZATIONS`) or with any AWS account by sending a shared directory request (`HANDSHAKE`).

Type: String

Valid Values: `ORGANIZATIONS | HANDSHAKE`

Required: No

## ShareNotes

A directory share request that is sent by the directory owner to the directory consumer. The request includes a typed message to help the directory consumer administrator determine whether to approve or reject the share invitation.

Type: String

Length Constraints: Maximum length of 1024.

Required: No



## ShareStatus

Current directory status of the shared AWS Managed Microsoft AD directory.

Type: String

Valid Values: Shared | PendingAcceptance | Rejected | Rejecting | RejectFailed | Sharing | ShareFailed | Deleted | Deleting

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ShareTarget

Identifier that contains details about the directory consumer account.

## Contents

### Id

Identifier of the directory consumer account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

### Type

Type of identifier to be used in the Id field.

Type: String

Valid Values: ACCOUNT

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Snapshot

Describes a directory snapshot.

## Contents

### DirectoryId

The directory identifier.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: No

### Name

The descriptive name of the snapshot.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `^([a-zA-Z0-9_])[\a-zA-Z0-9_@#%*+=:?./!\s-]*$`

Required: No

### SnapshotId

The snapshot identifier.

Type: String

Pattern: `^s-[0-9a-f]{10}$`

Required: No

### StartTime

The date and time that the snapshot was taken.

Type: Timestamp

Required: No

## Status

The snapshot status.

Type: String

Valid Values: `Creating` | `Completed` | `Failed`

Required: No

## Type

The snapshot type.

Type: String

Valid Values: `Auto` | `Manual`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# SnapshotLimits

Contains manual snapshot limit information for a directory.

## Contents

### ManualSnapshotsCurrentCount

The current number of manual snapshots of the directory.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

### ManualSnapshotsLimit

The maximum number of manual snapshots allowed.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

### ManualSnapshotsLimitReached

Indicates if the manual snapshot limit has been reached.

Type: Boolean

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# Tag

Metadata assigned to a directory consisting of a key-value pair.

## Contents

### Key

Required name of the tag. The string value can be Unicode characters and cannot be prefixed with "aws:". The string can contain only the set of Unicode letters, digits, white-space, '\_', ':', '/', '=', '+', '-', ':', '@' (Java regex: "`^[\\p{L}\\p{Z}\\p{N}_:/=+\\-]*`").

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[\\p{L}\\p{Z}\\p{N}_:/=+\\-@]*`

Required: Yes

### Value

The optional value of the tag. The string value can be Unicode characters. The string can contain only the set of Unicode letters, digits, white-space, '\_', ':', '/', '=', '+', '-', ':', '@' (Java regex: "`^[\\p{L}\\p{Z}\\p{N}_:/=+\\-]*`").

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `^[\\p{L}\\p{Z}\\p{N}_:/=+\\-@]*`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)



# Trust

Describes a trust relationship between an AWS Managed Microsoft AD directory and an external domain.

## Contents

### CreatedDateTime

The date and time that the trust relationship was created.

Type: Timestamp

Required: No

### DirectoryId

The Directory ID of the AWS directory involved in the trust relationship.

Type: String

Pattern: `^d-[0-9a-f]{10}$`

Required: No

### LastUpdatedDateTime

The date and time that the trust relationship was last updated.

Type: Timestamp

Required: No

### RemoteDomainName

The Fully Qualified Domain Name (FQDN) of the external domain involved in the trust relationship.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^([a-zA-Z0-9]+[\\.\-])+([a-zA-Z0-9])+[.]?$`

Required: No

## SelectiveAuth

Current state of selective authentication for the trust.

Type: String

Valid Values: Enabled | Disabled

Required: No

## StateLastUpdatedDateTime

The date and time that the TrustState was last updated.

Type: Timestamp

Required: No

## TrustDirection

The trust relationship direction.

Type: String

Valid Values: One-Way: Outgoing | One-Way: Incoming | Two-Way

Required: No

## TrustId

The unique ID of the trust relationship.

Type: String

Pattern: `^t-[0-9a-f]{10}$`

Required: No

## TrustState

The trust relationship state.

Type: String

Valid Values: Creating | Created | Verifying | VerifyFailed | Verified | Updating | UpdateFailed | Updated | Deleting | Deleted | Failed

Required: No

### **TrustStateReason**

The reason for the TrustState.

Type: String

Required: No

### **TrustType**

The trust relationship type. Forest is the default.

Type: String

Valid Values: Forest | External

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# UnshareTarget

Identifier that contains details about the directory consumer account with whom the directory is being unshared.

## Contents

### Id

Identifier of the directory consumer account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

### Type

Type of identifier to be used in the *Id* field.

Type: String

Valid Values: ACCOUNT

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# UpdateInfoEntry

An entry of update information related to a requested update type.

## Contents

### InitiatedBy

This specifies if the update was initiated by the customer or by the service team.

Type: String

Required: No

### LastUpdatedDateTime

The last updated date and time of a particular directory setting.

Type: Timestamp

Required: No

### NewValue

The new value of the target setting.

Type: [UpdateValue](#) object

Required: No

### PreviousValue

The old value of the target setting.

Type: [UpdateValue](#) object

Required: No

### Region

The name of the Region.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 32.

Required: No

### **StartTime**

The start time of the UpdateDirectorySetup for the particular type.

Type: Timestamp

Required: No

### **Status**

The status of the update performed on the directory.

Type: String

Valid Values: Updated | Updating | UpdateFailed

Required: No

### **StatusReason**

The reason for the current status of the update type activity.

Type: String

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# UpdateValue

The value for a given type of `UpdateSettings`.

## Contents

### OSUpdateSettings

The OS update related settings.

Type: [OSUpdateSettings](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Logging AWS Directory Service API Calls with CloudTrail

The AWS Directory Service API is integrated with AWS CloudTrail, a service that captures API calls made by or on behalf of AWS Directory Service in your AWS account and delivers the log files to an Amazon S3 bucket that you specify. CloudTrail captures API calls from the AWS Directory Service console and from code calls to the AWS Directory Service APIs. Using the information collected by CloudTrail, you can determine what request was made to AWS Directory Service, the source IP address from which the request was made, who made the request, when it was made, and so on. To learn more about CloudTrail, see the [AWS CloudTrail User Guide](#).

## AWS Directory Service Information in CloudTrail

CloudTrail is enabled on your AWS account when you create the account. When activity occurs in AWS Directory Service, that activity is recorded in a CloudTrail event along with other AWS service events in **Event history**. You can view, search, and download recent events in your AWS account. For more information, see [Viewing Events with CloudTrail Event History](#).

For an ongoing record of events in your AWS account, including events for AWS Directory Service, create a trail. A *trail* enables CloudTrail to deliver log files to an Amazon S3 bucket. By default, when you create a trail in the console, the trail applies to all AWS Regions. The trail logs events from all Regions in the AWS partition and delivers the log files to the Amazon S3 bucket that you specify. Additionally, you can configure other AWS services to further analyze and act upon the event data collected in CloudTrail logs. For more information, see the following:

- [Overview for Creating a Trail](#)
- [CloudTrail Supported Services and Integrations](#)
- [Configuring Amazon SNS Notifications for CloudTrail](#)
- [Receiving CloudTrail Log Files from Multiple Regions](#) and [Receiving CloudTrail Log Files from Multiple Accounts](#)

When CloudTrail logging is enabled in your AWS account, all API calls made to AWS Directory Service actions are tracked in log files. AWS Directory Service records are written together with other AWS service records in a log file. CloudTrail determines when to create and write to a new file based on a time period and file size. All calls made to the AWS Directory Service API or CLI calls are logged by CloudTrail.



Every log entry contains information about who generated the request. The user identity information in the log helps you determine whether the request was made with root or IAM user credentials, with temporary security credentials for a role or federated user, or by another AWS service. For more information, see the **userIdentity** field in the [CloudTrail Event Reference](#).

You can store your log files in your bucket for as long as you want, but you can also define Amazon S3 lifecycle rules to archive or delete log files automatically. By default, your log files are encrypted by using Amazon S3 server-side encryption (SSE).

You can choose to have CloudTrail publish Amazon SNS notifications when new log files are delivered if you want to take quick action upon log file delivery. For more information, see [Configuring Amazon SNS Notifications](#).

You can also aggregate AWS Directory Service log files from multiple AWS Regions and AWS accounts into a single Amazon S3 bucket. For more information, see [Aggregating CloudTrail Log Files to a Single Amazon S3 Bucket](#).

## Understanding AWS Directory Service Log File Entries

CloudTrail log files can contain one or more log entries, where each entry is made up of multiple JSON-formatted events. A log entry represents a single request from any source and includes information about the requested action, any parameters, the date and time of the action, and so on. The log entries are not guaranteed to be in any particular order; that is, they are not an ordered stack trace of the public API calls.

Sensitive information, such as passwords, authentication tokens, file comments, and file contents are redacted in the log entries.

The following example shows an example of a CloudTrail log entry for AWS Directory Service:

```
{
  "Records" : [
    {
      "eventVersion" : "1.02",
      "userIdentity" :
      {
        "type" : "IAMUser",
        "principalId" : "<user_id>",
        "arn" : "<user_arn>",
        "accountId" : "<account_id>",
```

```
    "accessKeyId" : "<access_key_id>",
    "userName" : "<username>"
  },
  "eventTime" : "<event_time>",
  "eventSource" : "ds.amazonaws.com",
  "eventName" : "CreateDirectory",
  "awsRegion" : "<region>",
  "sourceIPAddress" : "<IP_address>",
  "userAgent" : "<user_agent>",
  "requestParameters" :
  {
    "name" : "<name>",
    "shortName" : "<short_name>",
    "vpcSettings" :
    {
      "vpcId" : "<vpc_id>",
      "subnetIds" : [
        "<subnet_id_1>",
        "<subnet_id_2>"
      ]
    },
    "type" : "<size>",
    "setAsDefault" : <option>,
    "password" : "****OMITTED****"
  },
  "responseElements" :
  {
    "requestId" : "<request_id>",
    "directoryId" : "<directory_id>"
  },
  "requestID" : "<request_id>",
  "eventID" : "<event_id>",
  "eventType" : "AwsApiCall",
  "recipientAccountId" : "<account_id>"
}
]
```

# Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

## **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

## **IncompleteSignature**

The request signature does not conform to AWS standards.

HTTP Status Code: 400

## **InternalFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## **InvalidAction**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

## **InvalidClientTokenId**

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

## **NotAuthorized**

You do not have permission to perform this action.

HTTP Status Code: 400

## **OptInRequired**

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

**RequestExpired**

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

**ServiceUnavailable**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

**ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

**ValidationError**

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

## Document History

The following table describes the important changes to the documentation in this release of the *AWS Directory Service API Reference*.

- **Latest documentation update:** October 5, 2018

Change	Description	Date Changed
Trusts	Added updates to support selective authentication and external trusts	October 5, 2018
Directory sharing	Added directory sharing related APIs	September 25, 2018
Log subscription	Added 3 APIs to support log subscriptions	September 25, 2018
Reset password	Added reset user password APIs	May 8, 2018
Domain controllers	Added domain controller related APIs	July 6, 2017
New API examples	Added examples to each API in the guide.	December 16, 2016
Schema extensions	Added 3 APIs for schema extensions with AWS Managed Microsoft AD.	November 14, 2016
Microsoft AD	Added documentation for AWS Managed Microsoft AD.	November 17, 2015
New guide	This is the first release of the AWS Directory Service API Reference Guide.	May 14, 2015