



Welcome

Amazon Elastic VMware Service



API Version 2023-07-27

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon Elastic VMware Service: Welcome

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
AssociateEipToVlan	3
Request Syntax	3
Request Parameters	3
Response Syntax	4
Response Elements	5
Errors	5
See Also	6
CreateEnvironment	8
Request Syntax	8
Request Parameters	10
Response Syntax	15
Response Elements	17
Errors	17
See Also	17
CreateEnvironmentHost	19
Request Syntax	19
Request Parameters	19
Response Syntax	21
Response Elements	21
Errors	22
See Also	23
DeleteEnvironment	24
Request Syntax	24
Request Parameters	24
Response Syntax	25
Response Elements	26
Errors	27
See Also	28
DeleteEnvironmentHost	29
Request Syntax	29
Request Parameters	29
Response Syntax	30

Response Elements	31
Errors	31
See Also	32
DisassociateEipFromVlan	34
Request Syntax	34
Request Parameters	34
Response Syntax	35
Response Elements	36
Errors	36
See Also	37
GetEnvironment	39
Request Syntax	39
Request Parameters	39
Response Syntax	39
Response Elements	41
Errors	41
See Also	42
ListEnvironmentHosts	43
Request Syntax	43
Request Parameters	43
Response Syntax	44
Response Elements	44
Errors	45
See Also	46
ListEnvironments	47
Request Syntax	47
Request Parameters	47
Response Syntax	48
Response Elements	48
Errors	49
See Also	49
ListEnvironmentVlans	51
Request Syntax	51
Request Parameters	51
Response Syntax	52
Response Elements	52

Errors	53
See Also	54
ListTagsForResource	55
Request Syntax	55
Request Parameters	55
Response Syntax	55
Response Elements	56
Errors	56
See Also	57
TagResource	58
Request Syntax	58
Request Parameters	58
Response Elements	59
Errors	59
See Also	61
UntagResource	62
Request Syntax	62
Request Parameters	62
Response Elements	63
Errors	63
See Also	64
Data Types	65
Check	66
Contents	66
See Also	67
ConnectivityInfo	68
Contents	68
See Also	68
EipAssociation	69
Contents	69
See Also	70
Environment	71
Contents	71
See Also	75
EnvironmentSummary	77
Contents	77

See Also	79
Host	80
Contents	80
See Also	83
HostInfoForCreate	84
Contents	84
See Also	85
InitialVlanInfo	86
Contents	86
See Also	86
InitialVlans	88
Contents	88
See Also	91
LicenseInfo	92
Contents	92
See Also	92
NetworkInterface	94
Contents	94
See Also	94
Secret	95
Contents	95
See Also	95
ServiceAccessSecurityGroups	96
Contents	96
See Also	96
ValidationExceptionField	97
Contents	97
See Also	97
VcfHostnames	98
Contents	98
See Also	100
Vlan	101
Contents	101
See Also	103
Service-specific Errors	104
ResourceNotFoundException	105

Contents	105
See Also	105
ServiceQuotaExceededException	106
Contents	106
See Also	106
TagPolicyException	107
Contents	107
See Also	107
ThrottlingException	108
Contents	108
See Also	108
TooManyTagsException	109
Contents	109
See Also	109
ValidationException	110
Contents	110
See Also	110
Common Parameters	111
Common Errors	114

Welcome

Amazon Elastic VMware Service (Amazon EVS) is a service that you can use to deploy a VMware Cloud Foundation (VCF) software environment directly on EC2 bare metal instances within an Amazon Virtual Private Cloud (VPC).

Workloads running on Amazon EVS are fully compatible with workloads running on any standard VMware vSphere environment. This means that you can migrate any VMware-based workload to Amazon EVS without workload modification.

This document was last published on November 1, 2025.

Actions

The following actions are supported:

- [AssociateEipToVlan](#)
- [CreateEnvironment](#)
- [CreateEnvironmentHost](#)
- [DeleteEnvironment](#)
- [DeleteEnvironmentHost](#)
- [DisassociateEipFromVlan](#)
- [GetEnvironment](#)
- [ListEnvironmentHosts](#)
- [ListEnvironments](#)
- [ListEnvironmentVlans](#)
- [ListTagsForResource](#)
- [TagResource](#)
- [UntagResource](#)

AssociateEipToVlan

Associates an Elastic IP address with a public HCX VLAN. This operation is only allowed for public HCX VLANs at this time.

Request Syntax

```
{  
  "allocationId": "string",  
  "clientToken": "string",  
  "environmentId": "string",  
  "vlanName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Note

In the following list, the required parameters are described first.

allocationId

The Elastic IP address allocation ID.

Type: String

Length Constraints: Minimum length of 9. Maximum length of 26.

Pattern: eipalloc-[a-zA-Z0-9_-]+

Required: Yes

environmentId

A unique ID for the environment containing the VLAN that the Elastic IP address associates with.

Type: String

Pattern: (env-[a-zA-Z0-9]{10})

Required: Yes

vlanName

The name of the VLAN. hcx is the only accepted VLAN name at this time.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: Yes

clientToken

Note

This parameter is not used in Amazon EVS currently. If you supply input for this parameter, it will have no effect.

A unique, case-sensitive identifier that you provide to ensure the idempotency of the environment creation request. If you do not specify a client token, a randomly generated token is used for the request to ensure idempotency.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [!-~]+

Required: No

Response Syntax

```
{
  "vlan": {
    "availabilityZone": "string",
    "cidr": "string",
    "createdAt": number,
    "eipAssociations": [
      {
```

```
        "allocationId": "string",
        "associationId": "string",
        "ipAddress": "string"
    }
],
"functionName": "string",
"isPublic": boolean,
"modifiedAt": number,
"networkAclId": "string",
"stateDetails": "string",
"subnetId": "string",
"vlanId": number,
"vlanState": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

vlan

The VLANs that Amazon EVS creates during environment creation.

Type: [Vlan](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

A service resource associated with the request could not be found. The resource might not be specified correctly, or it may have a state of DELETED.

message

Describes the error encountered.

resourceId

The ID of the resource that could not be found.

resourceType

The type of the resource that is associated with the error.

HTTP Status Code: 400

[ThrottlingException](#)

The operation couldn't be performed because the service is throttling requests. This exception is thrown when there are too many requests accepted concurrently from the service endpoint.

message

Describes the error encountered.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 400

[ValidationException](#)

The input fails to satisfy the specified constraints. You will see this exception if invalid inputs are provided for any of the Amazon EVS environment operations, or if a list operation is performed on an environment resource that is still initializing.

fieldList

A list of fields that didn't validate.

message

Describes the error encountered.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateEnvironment

Creates an Amazon EVS environment that runs VCF software, such as SDDC Manager, NSX Manager, and vCenter Server.

During environment creation, Amazon EVS performs validations on DNS settings, provisions VLAN subnets and hosts, and deploys the supplied version of VCF.

It can take several hours to create an environment. After the deployment completes, you can configure VCF in the vSphere user interface according to your needs.

Note

You cannot use the `dedicatedHostId` and `placementGroupId` parameters together in the same `CreateEnvironment` action. This results in a `ValidationException` response.

Request Syntax

```
{
  "clientToken": "string",
  "connectivityInfo": {
    "privateRouteServerPeerings": [ "string" ]
  },
  "environmentName": "string",
  "hosts": [
    {
      "dedicatedHostId": "string",
      "hostName": "string",
      "instanceType": "string",
      "keyName": "string",
      "placementGroupId": "string"
    }
  ],
  "initialVlans": {
    "edgeVTep": {
      "cidr": "string"
    },
    "expansionVlan1": {
      "cidr": "string"
    },
    "expansionVlan2": {
```

```

    "cidr": "string"
  },
  "hcx": {
    "cidr": "string"
  },
  "hcxNetworkAclId": "string",
  "isHcxPublic": boolean,
  "nsxUplink": {
    "cidr": "string"
  },
  "vmkManagement": {
    "cidr": "string"
  },
  "vmManagement": {
    "cidr": "string"
  },
  "vMotion": {
    "cidr": "string"
  },
  "vSan": {
    "cidr": "string"
  },
  "vTep": {
    "cidr": "string"
  }
},
"kmsKeyId": "string",
"licenseInfo": [
  {
    "solutionKey": "string",
    "vsanKey": "string"
  }
],
"serviceAccessSecurityGroups": {
  "securityGroups": [ "string" ]
},
"serviceAccessSubnetId": "string",
"siteId": "string",
"tags": {
  "string" : "string"
},
"termsAccepted": boolean,
"vcfHostnames": {
  "cloudBuilder": "string",

```

```
"nsx": "string",
"nsxEdge1": "string",
"nsxEdge2": "string",
"nsxManager1": "string",
"nsxManager2": "string",
"nsxManager3": "string",
"sddcManager": "string",
"vCenter": "string"
},
"vcfVersion": "string",
"vpcId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Note

In the following list, the required parameters are described first.

connectivityInfo

The connectivity configuration for the environment. Amazon EVS requires that you specify two route server peer IDs. During environment creation, the route server endpoints peer with the NSX edges over the NSX uplink subnet, providing BGP-based dynamic routing for overlay networks.

Type: [ConnectivityInfo](#) object

Required: Yes

hosts

The ESXi hosts to add to the environment. Amazon EVS requires that you provide details for a minimum of 4 hosts during environment creation.

For each host, you must provide the desired hostname, EC2 SSH keypair name, and EC2 instance type. Optionally, you can also provide a partition or cluster placement group to use, or use Amazon EC2 Dedicated Hosts.

Type: Array of [HostInfoForCreate](#) objects

Array Members: Fixed number of 4 items.

Required: Yes

[initialVlans](#)

The initial VLAN subnets for the Amazon EVS environment.

Note

For each Amazon EVS VLAN subnet, you must specify a non-overlapping CIDR block. Amazon EVS VLAN subnets have a minimum CIDR block size of /28 and a maximum size of /24.

Type: [InitialVlans](#) object

Required: Yes

[licenseInfo](#)

The license information that Amazon EVS requires to create an environment. Amazon EVS requires two license keys: a VCF solution key and a vSAN license key. The VCF solution key must cover a minimum of 256 cores. The vSAN license key must provide at least 110 TiB of vSAN capacity.

VCf licenses can be used for only one Amazon EVS environment. Amazon EVS does not support reuse of VCF licenses for multiple environments.

VCf license information can be retrieved from the Broadcom portal.

Type: Array of [LicenseInfo](#) objects

Array Members: Fixed number of 1 item.

Required: Yes

[serviceAccessSubnetId](#)

The subnet that is used to establish connectivity between the Amazon EVS control plane and VPC. Amazon EVS uses this subnet to validate mandatory DNS records for your VCF appliances and hosts and create the environment.

Type: String

Length Constraints: Minimum length of 15. Maximum length of 24.

Pattern: subnet-[a-f0-9]{8}([a-f0-9]{9})?

Required: Yes

siteId

The Broadcom Site ID that is allocated to you as part of your electronic software delivery. This ID allows customer access to the Broadcom portal, and is provided to you by Broadcom at the close of your software contract or contract renewal. Amazon EVS uses the Broadcom Site ID that you provide to meet Broadcom VCF license usage reporting requirements for Amazon EVS.

Type: String

Required: Yes

termsAccepted

Customer confirmation that the customer has purchased and will continue to maintain the required number of VCF software licenses to cover all physical processor cores in the Amazon EVS environment. Information about your VCF software in Amazon EVS will be shared with Broadcom to verify license compliance. Amazon EVS does not validate license keys. To validate license keys, visit the Broadcom support portal.

Type: Boolean

Required: Yes

vcfHostnames

The DNS hostnames for the virtual machines that host the VCF management appliances. Amazon EVS requires that you provide DNS hostnames for the following appliances: vCenter, NSX Manager, SDDC Manager, and Cloud Builder.

Type: [VcfHostnames](#) object

Required: Yes

vcfVersion

The VCF version to use for the environment. Amazon EVS only supports VCF version 5.2.1 at this time.

Type: String

Valid Values: VCF-5.2.1

Required: Yes

vpclId

A unique ID for the VPC that the environment is deployed inside.

Amazon EVS requires that all VPC subnets exist in a single Availability Zone in a Region where the service is available.

The VPC that you specify must have a valid DHCP option set with domain name, at least two DNS servers, and an NTP server. These settings are used to configure your VCF appliances and hosts. The VPC cannot be used with any other deployed Amazon EVS environment. Amazon EVS does not provide multi-VPC support for environments at this time.

Amazon EVS does not support the following AWS networking options for NSX overlay connectivity: cross-Region VPC peering, Amazon S3 gateway endpoints, or AWS Direct Connect virtual private gateway associations.

Note

Ensure that you specify a VPC that is adequately sized to accommodate the {evws} subnets.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 21.

Pattern: vpc-[a-f0-9]{8}([a-f0-9]{9})?

Required: Yes

clientToken

Note

This parameter is not used in Amazon EVS currently. If you supply input for this parameter, it will have no effect.

A unique, case-sensitive identifier that you provide to ensure the idempotency of the environment creation request. If you do not specify a client token, a randomly generated token is used for the request to ensure idempotency.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [!-~]+

Required: No

environmentName

The name to give to your environment. The name can contain only alphanumeric characters (case-sensitive), hyphens, and underscores. It must start with an alphanumeric character, and can't be longer than 100 characters. The name must be unique within the AWS Region and AWS account that you're creating the environment in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9_-]+

Required: No

kmsKeyId

A unique ID for the customer-managed KMS key that is used to encrypt the VCF credential pairs for SDDC Manager, NSX Manager, and vCenter appliances. These credentials are stored in AWS Secrets Manager.

Type: String

Required: No

serviceAccessSecurityGroups

The security group that controls communication between the Amazon EVS control plane and VPC. The default security group is used if a custom security group isn't specified.

The security group should allow access to the following.

- TCP/UDP access to the DNS servers
- HTTPS/SSH access to the host management VLAN subnet

- HTTPS/SSH access to the Management VM VLAN subnet

You should avoid modifying the security group rules after deployment, as this can break the persistent connection between the Amazon EVS control plane and VPC. This can cause future environment actions like adding or removing hosts to fail.

Type: [ServiceAccessSecurityGroups](#) object

Required: No

[tags](#)

Metadata that assists with categorization and organization. Each tag consists of a key and an optional value. You define both. Tags don't propagate to any other cluster or AWS resources.

Type: String to string map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `[\w.:/=+-@]+`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `[\w.:/=+-@]+|`

Required: No

Response Syntax

```
{
  "environment": {
    "checks": [
      {
        "impairedSince": number,
        "result": "string",
        "type": "string"
      }
    ],
    "connectivityInfo": {
      "privateRouteServerPeerings": [ "string" ]
    },
    "createdAt": number,
```

```

    "credentials": [
      {
        "secretArn": "string"
      }
    ],
    "environmentArn": "string",
    "environmentId": "string",
    "environmentName": "string",
    "environmentState": "string",
    "environmentStatus": "string",
    "kmsKeyId": "string",
    "licenseInfo": [
      {
        "solutionKey": "string",
        "vsanKey": "string"
      }
    ],
    "modifiedAt": number,
    "serviceAccessSecurityGroups": {
      "securityGroups": [ "string" ]
    },
    "serviceAccessSubnetId": "string",
    "siteId": "string",
    "stateDetails": "string",
    "termsAccepted": boolean,
    "vcfHostnames": {
      "cloudBuilder": "string",
      "nsx": "string",
      "nsxEdge1": "string",
      "nsxEdge2": "string",
      "nsxManager1": "string",
      "nsxManager2": "string",
      "nsxManager3": "string",
      "sddcManager": "string",
      "vCenter": "string"
    },
    "vcfVersion": "string",
    "vpcId": "string"
  }
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

environment

A description of the created environment.

Type: [Environment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ValidationException

The input fails to satisfy the specified constraints. You will see this exception if invalid inputs are provided for any of the Amazon EVS environment operations, or if a list operation is performed on an environment resource that is still initializing.

fieldList

A list of fields that didn't validate.

message

Describes the error encountered.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateEnvironmentHost

Creates an ESXi host and adds it to an Amazon EVS environment. Amazon EVS supports 4-16 hosts per environment.

This action can only be used after the Amazon EVS environment is deployed.

You can use the `dedicatedHostId` parameter to specify an Amazon EC2 Dedicated Host for ESXi host creation.

You can use the `placementGroupId` parameter to specify a cluster or partition placement group to launch EC2 instances into.

Note

You cannot use the `dedicatedHostId` and `placementGroupId` parameters together in the same `CreateEnvironmentHost` action. This results in a `ValidationException` response.

Request Syntax

```
{
  "clientToken": "string",
  "environmentId": "string",
  "host": {
    "dedicatedHostId": "string",
    "hostName": "string",
    "instanceType": "string",
    "keyName": "string",
    "placementGroupId": "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Note

In the following list, the required parameters are described first.

environmentId

A unique ID for the environment that the host is added to.

Type: String

Pattern: (env-[a-zA-Z0-9]{10})

Required: Yes

host

The host that is created and added to the environment.

Type: [HostInfoForCreate](#) object

Required: Yes

clientToken**Note**

This parameter is not used in Amazon EVS currently. If you supply input for this parameter, it will have no effect.

A unique, case-sensitive identifier that you provide to ensure the idempotency of the host creation request. If you do not specify a client token, a randomly generated token is used for the request to ensure idempotency.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [!-~]+

Required: No

Response Syntax

```
{
  "environmentSummary": {
    "createdAt": number,
    "environmentArn": "string",
    "environmentId": "string",
    "environmentName": "string",
    "environmentState": "string",
    "environmentStatus": "string",
    "modifiedAt": number,
    "vcfVersion": "string"
  },
  "host": {
    "createdAt": number,
    "dedicatedHostId": "string",
    "ec2InstanceId": "string",
    "hostName": "string",
    "hostState": "string",
    "instanceType": "string",
    "ipAddress": "string",
    "keyName": "string",
    "modifiedAt": number,
    "networkInterfaces": [
      {
        "networkInterfaceId": "string"
      }
    ],
    "placementGroupId": "string",
    "stateDetails": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

environmentSummary

A summary of the environment that the host is created in.

Type: [EnvironmentSummary](#) object

[host](#)

A description of the created host.

Type: [Host](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[ThrottlingException](#)

The operation couldn't be performed because the service is throttling requests. This exception is thrown when there are too many requests accepted concurrently from the service endpoint.

message

Describes the error encountered.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 400

[ValidationException](#)

The input fails to satisfy the specified constraints. You will see this exception if invalid inputs are provided for any of the Amazon EVS environment operations, or if a list operation is performed on an environment resource that is still initializing.

fieldList

A list of fields that didn't validate.

message

Describes the error encountered.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteEnvironment

Deletes an Amazon EVS environment.

Amazon EVS environments will only be enabled for deletion once the hosts are deleted. You can delete hosts using the `DeleteEnvironmentHost` action.

Environment deletion also deletes the associated Amazon EVS VLAN subnets and AWS Secrets Manager secrets that Amazon EVS created. AWS resources that you create are not deleted. These resources may continue to incur costs.

Request Syntax

```
{  
  "clientToken": "string",  
  "environmentId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Note

In the following list, the required parameters are described first.

environmentId

A unique ID associated with the environment to be deleted.

Type: String

Pattern: (env-[a-zA-Z0-9]{10})

Required: Yes

clientToken

Note

This parameter is not used in Amazon EVS currently. If you supply input for this parameter, it will have no effect.

A unique, case-sensitive identifier that you provide to ensure the idempotency of the environment deletion request. If you do not specify a client token, a randomly generated token is used for the request to ensure idempotency.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [!-~]+

Required: No

Response Syntax

```
{
  "environment": {
    "checks": [
      {
        "impairedSince": number,
        "result": "string",
        "type": "string"
      }
    ],
    "connectivityInfo": {
      "privateRouteServerPeerings": [ "string" ]
    },
    "createdAt": number,
    "credentials": [
      {
        "secretArn": "string"
      }
    ],
    "environmentArn": "string",
    "environmentId": "string",
```

```

    "environmentName": "string",
    "environmentState": "string",
    "environmentStatus": "string",
    "kmsKeyId": "string",
    "licenseInfo": [
      {
        "solutionKey": "string",
        "vsanKey": "string"
      }
    ],
    "modifiedAt": number,
    "serviceAccessSecurityGroups": {
      "securityGroups": [ "string" ]
    },
    "serviceAccessSubnetId": "string",
    "siteId": "string",
    "stateDetails": "string",
    "termsAccepted": boolean,
    "vcfHostnames": {
      "cloudBuilder": "string",
      "nsx": "string",
      "nsxEdge1": "string",
      "nsxEdge2": "string",
      "nsxManager1": "string",
      "nsxManager2": "string",
      "nsxManager3": "string",
      "sddcManager": "string",
      "vCenter": "string"
    },
    "vcfVersion": "string",
    "vpcId": "string"
  }
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

environment

A description of the deleted environment.

Type: [Environment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[ResourceNotFoundException](#)

A service resource associated with the request could not be found. The resource might not be specified correctly, or it may have a state of DELETED.

message

Describes the error encountered.

resourceId

The ID of the resource that could not be found.

resourceType

The type of the resource that is associated with the error.

HTTP Status Code: 400

[ValidationException](#)

The input fails to satisfy the specified constraints. You will see this exception if invalid inputs are provided for any of the Amazon EVS environment operations, or if a list operation is performed on an environment resource that is still initializing.

fieldList

A list of fields that didn't validate.

message

Describes the error encountered.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteEnvironmentHost

Deletes a host from an Amazon EVS environment.

Note

Before deleting a host, you must unassign and decommission the host from within the SDDC Manager user interface. Not doing so could impact the availability of your virtual machines or result in data loss.

Request Syntax

```
{
  "clientToken": "string",
  "environmentId": "string",
  "hostName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Note

In the following list, the required parameters are described first.

environmentId

A unique ID for the host's environment.

Type: String

Pattern: (env-[a-zA-Z0-9]{10})

Required: Yes

hostName

The DNS hostname associated with the host to be deleted.

Type: String

Pattern: ([a-zA-Z0-9\ -] *)

Required: Yes

clientToken

Note

This parameter is not used in Amazon EVS currently. If you supply input for this parameter, it will have no effect.

A unique, case-sensitive identifier that you provide to ensure the idempotency of the host deletion request. If you do not specify a client token, a randomly generated token is used for the request to ensure idempotency.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [!-~]+

Required: No

Response Syntax

```
{
  "environmentSummary": {
    "createdAt": number,
    "environmentArn": "string",
    "environmentId": "string",
    "environmentName": "string",
    "environmentState": "string",
    "environmentStatus": "string",
    "modifiedAt": number,
```

```
    "vcfVersion": "string"
  },
  "host": {
    "createdAt": number,
    "dedicatedHostId": "string",
    "ec2InstanceId": "string",
    "hostName": "string",
    "hostState": "string",
    "instanceType": "string",
    "ipAddress": "string",
    "keyName": "string",
    "modifiedAt": number,
    "networkInterfaces": [
      {
        "networkInterfaceId": "string"
      }
    ],
    "placementGroupId": "string",
    "stateDetails": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

environmentSummary

A summary of the environment that the host was deleted from.

Type: [EnvironmentSummary](#) object

host

A description of the deleted host.

Type: [Host](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[ResourceNotFoundException](#)

A service resource associated with the request could not be found. The resource might not be specified correctly, or it may have a state of DELETED.

message

Describes the error encountered.

resourceId

The ID of the resource that could not be found.

resourceType

The type of the resource that is associated with the error.

HTTP Status Code: 400

[ValidationException](#)

The input fails to satisfy the specified constraints. You will see this exception if invalid inputs are provided for any of the Amazon EVS environment operations, or if a list operation is performed on an environment resource that is still initializing.

fieldList

A list of fields that didn't validate.

message

Describes the error encountered.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisassociateEipFromVlan

Disassociates an Elastic IP address from a public HCX VLAN. This operation is only allowed for public HCX VLANs at this time.

Request Syntax

```
{  
  "associationId": "string",  
  "clientToken": "string",  
  "environmentId": "string",  
  "vlanName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Note

In the following list, the required parameters are described first.

associationId

A unique ID for the Elastic IP address association.

Type: String

Length Constraints: Minimum length of 9. Maximum length of 26.

Pattern: eipassoc-[a-zA-Z0-9_-]+

Required: Yes

environmentId

A unique ID for the environment containing the VLAN that the Elastic IP address disassociates from.

Type: String

Pattern: (env-[a-zA-Z0-9]{10})

Required: Yes

vlanName

The name of the VLAN. hcx is the only accepted VLAN name at this time.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: Yes

clientToken

Note

This parameter is not used in Amazon EVS currently. If you supply input for this parameter, it will have no effect.

A unique, case-sensitive identifier that you provide to ensure the idempotency of the environment creation request. If you do not specify a client token, a randomly generated token is used for the request to ensure idempotency.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [!-~]+

Required: No

Response Syntax

```
{
  "vlan": {
    "availabilityZone": "string",
    "cidr": "string",
    "createdAt": number,
    "eipAssociations": [
      {
```

```
        "allocationId": "string",
        "associationId": "string",
        "ipAddress": "string"
    }
],
"functionName": "string",
"isPublic": boolean,
"modifiedAt": number,
"networkAclId": "string",
"stateDetails": "string",
"subnetId": "string",
"vlanId": number,
"vlanState": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

vlan

The VLANs that Amazon EVS creates during environment creation.

Type: [Vlan](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

A service resource associated with the request could not be found. The resource might not be specified correctly, or it may have a state of DELETED.

message

Describes the error encountered.

resourceId

The ID of the resource that could not be found.

resourceType

The type of the resource that is associated with the error.

HTTP Status Code: 400

[ThrottlingException](#)

The operation couldn't be performed because the service is throttling requests. This exception is thrown when there are too many requests accepted concurrently from the service endpoint.

message

Describes the error encountered.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 400

[ValidationException](#)

The input fails to satisfy the specified constraints. You will see this exception if invalid inputs are provided for any of the Amazon EVS environment operations, or if a list operation is performed on an environment resource that is still initializing.

fieldList

A list of fields that didn't validate.

message

Describes the error encountered.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetEnvironment

Returns a description of the specified environment.

Request Syntax

```
{  
  "environmentId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Note

In the following list, the required parameters are described first.

environmentId

A unique ID for the environment.

Type: String

Pattern: (env-[a-zA-Z0-9]{10})

Required: Yes

Response Syntax

```
{  
  "environment": {  
    "checks": [  
      {  
        "impairedSince": number,  
        "result": "string",  
        "type": "string"  
      }  
    ]  
  }
```

```

],
  "connectivityInfo": {
    "privateRouteServerPeerings": [ "string" ]
  },
  "createdAt": number,
  "credentials": [
    {
      "secretArn": "string"
    }
  ],
  "environmentArn": "string",
  "environmentId": "string",
  "environmentName": "string",
  "environmentState": "string",
  "environmentStatus": "string",
  "kmsKeyId": "string",
  "licenseInfo": [
    {
      "solutionKey": "string",
      "vsanKey": "string"
    }
  ],
  "modifiedAt": number,
  "serviceAccessSecurityGroups": {
    "securityGroups": [ "string" ]
  },
  "serviceAccessSubnetId": "string",
  "siteId": "string",
  "stateDetails": "string",
  "termsAccepted": boolean,
  "vcfHostnames": {
    "cloudBuilder": "string",
    "nsx": "string",
    "nsxEdge1": "string",
    "nsxEdge2": "string",
    "nsxManager1": "string",
    "nsxManager2": "string",
    "nsxManager3": "string",
    "sddcManager": "string",
    "vCenter": "string"
  },
  "vcfVersion": "string",
  "vpcId": "string"
}

```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

environment

A description of the requested environment.

Type: [Environment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

A service resource associated with the request could not be found. The resource might not be specified correctly, or it may have a state of DELETED.

message

Describes the error encountered.

resourceId

The ID of the resource that could not be found.

resourceType

The type of the resource that is associated with the error.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the specified constraints. You will see this exception if invalid inputs are provided for any of the Amazon EVS environment operations, or if a list operation is performed on an environment resource that is still initializing.

fieldList

A list of fields that didn't validate.

message

Describes the error encountered.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListEnvironmentHosts

List the hosts within an environment.

Request Syntax

```
{  
  "environmentId": "string",  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Note

In the following list, the required parameters are described first.

environmentId

A unique ID for the environment.

Type: String

Pattern: (env-[a-zA-Z0-9]{10})

Required: Yes

maxResults

The maximum number of results to return. If you specify `MaxResults` in the request, the response includes information up to the limit specified.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

A unique pagination token for each page. If nextToken is returned, there are more results available. Make the call again using the returned token with all other arguments unchanged to retrieve the next page. Each pagination token expires after 24 hours. Using an expired pagination token will return an *HTTP 400 InvalidToken* error.

Type: String

Required: No

Response Syntax

```
{
  "environmentHosts": [
    {
      "createdAt": number,
      "dedicatedHostId": "string",
      "ec2InstanceId": "string",
      "hostName": "string",
      "hostState": "string",
      "instanceType": "string",
      "ipAddress": "string",
      "keyName": "string",
      "modifiedAt": number,
      "networkInterfaces": [
        {
          "networkInterfaceId": "string"
        }
      ],
      "placementGroupId": "string",
      "stateDetails": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

environmentHosts

A list of hosts in the environment.

Type: Array of [Host](#) objects

nextToken

A unique pagination token for next page results. Make the call again using this token to retrieve the next page.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

A service resource associated with the request could not be found. The resource might not be specified correctly, or it may have a state of DELETED.

message

Describes the error encountered.

resourceId

The ID of the resource that could not be found.

resourceType

The type of the resource that is associated with the error.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the specified constraints. You will see this exception if invalid inputs are provided for any of the Amazon EVS environment operations, or if a list operation is performed on an environment resource that is still initializing.

fieldList

A list of fields that didn't validate.

message

Describes the error encountered.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListEnvironments

Lists the Amazon EVS environments in your AWS account in the specified AWS Region.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string",  
  "state": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Note

In the following list, the required parameters are described first.

maxResults

The maximum number of results to return. If you specify `MaxResults` in the request, the response includes information up to the limit specified.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

A unique pagination token for each page. If `nextToken` is returned, there are more results available. Make the call again using the returned token with all other arguments unchanged to retrieve the next page. Each pagination token expires after 24 hours. Using an expired pagination token will return an *HTTP 400 InvalidToken* error.

Type: String

Required: No

state

The state of an environment. Used to filter response results to return only environments with the specified `environmentState`.

Type: Array of strings

Valid Values: CREATING | CREATED | DELETING | DELETED | CREATE_FAILED

Required: No

Response Syntax

```
{
  "environmentSummaries": [
    {
      "createdAt": number,
      "environmentArn": "string",
      "environmentId": "string",
      "environmentName": "string",
      "environmentState": "string",
      "environmentStatus": "string",
      "modifiedAt": number,
      "vcfVersion": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

environmentSummaries

A list of environments with summarized environment details.

Type: Array of [EnvironmentSummary](#) objects

[nextToken](#)

A unique pagination token for next page results. Make the call again using this token to retrieve the next page.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[ValidationException](#)

The input fails to satisfy the specified constraints. You will see this exception if invalid inputs are provided for any of the Amazon EVS environment operations, or if a list operation is performed on an environment resource that is still initializing.

fieldList

A list of fields that didn't validate.

message

Describes the error encountered.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListEnvironmentVlans

Lists environment VLANs that are associated with the specified environment.

Request Syntax

```
{  
  "environmentId": "string",  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Note

In the following list, the required parameters are described first.

environmentId

A unique ID for the environment.

Type: String

Pattern: (env-[a-zA-Z0-9]{10})

Required: Yes

maxResults

The maximum number of results to return. If you specify `MaxResults` in the request, the response includes information up to the limit specified.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

A unique pagination token for each page. If `nextToken` is returned, there are more results available. Make the call again using the returned token with all other arguments unchanged to retrieve the next page. Each pagination token expires after 24 hours. Using an expired pagination token will return an *HTTP 400 InvalidToken* error.

Type: String

Required: No

Response Syntax

```
{
  "environmentVlans": [
    {
      "availabilityZone": "string",
      "cidr": "string",
      "createdAt": number,
      "eipAssociations": [
        {
          "allocationId": "string",
          "associationId": "string",
          "ipAddress": "string"
        }
      ],
      "functionName": "string",
      "isPublic": boolean,
      "modifiedAt": number,
      "networkAclId": "string",
      "stateDetails": "string",
      "subnetId": "string",
      "vlanId": number,
      "vlanState": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

environmentVlans

A list of VLANs that are associated with the specified environment.

Type: Array of [Vlan](#) objects

nextToken

A unique pagination token for next page results. Make the call again using this token to retrieve the next page.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

A service resource associated with the request could not be found. The resource might not be specified correctly, or it may have a state of DELETED.

message

Describes the error encountered.

resourceId

The ID of the resource that could not be found.

resourceType

The type of the resource that is associated with the error.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the specified constraints. You will see this exception if invalid inputs are provided for any of the Amazon EVS environment operations, or if a list operation is performed on an environment resource that is still initializing.

fieldList

A list of fields that didn't validate.

message

Describes the error encountered.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Lists the tags for an Amazon EVS resource.

Request Syntax

```
{  
  "resourceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Note

In the following list, the required parameters are described first.

[resourceArn](#)

The Amazon Resource Name (ARN) that identifies the resource to list tags for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws:evs:[a-z]{2}-[a-z]+-[0-9]:[0-9]{12}:(?:environment|subscription)/[a-zA-Z0-9_-]+`

Required: Yes

Response Syntax

```
{  
  "tags": {  
    "string" : "string"  
  }  
}
```

```
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags

The tags for the resource.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `[\w.:/=-@]+`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `[\w.:/=-@]+|`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

A service resource associated with the request could not be found. The resource might not be specified correctly, or it may have a state of DELETED.

message

Describes the error encountered.

resourceId

The ID of the resource that could not be found.

resourceType

The type of the resource that is associated with the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Associates the specified tags to an Amazon EVS resource with the specified `resourceArn`. If existing tags on a resource are not specified in the request parameters, they aren't changed. When a resource is deleted, the tags associated with that resource are also deleted. Tags that you create for Amazon EVS resources don't propagate to any other resources associated with the environment. For example, if you tag an environment with this operation, that tag doesn't automatically propagate to the VLAN subnets and hosts associated with the environment.

Request Syntax

```
{
  "resourceArn": "string",
  "tags": {
    "string" : "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Note

In the following list, the required parameters are described first.

resourceArn

The Amazon Resource Name (ARN) of the resource to add tags to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws:evs:[a-z]{2}-[a-z]+-[0-9]:[0-9]{12}:(?:environment|subscription)/[a-zA-Z0-9_-]+`

Required: Yes

tags

Metadata that assists with categorization and organization. Each tag consists of a key and an optional value. You define both. Tags don't propagate to any other environment or AWS resources.

Type: String to string map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `[\w . : / = + - @ ] +`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `[\w . : / = + - @ ] + |`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

A service resource associated with the request could not be found. The resource might not be specified correctly, or it may have a state of DELETED.

message

Describes the error encountered.

resourceId

The ID of the resource that could not be found.

resourceType

The type of the resource that is associated with the error.

HTTP Status Code: 400

[ServiceQuotaExceededException](#)

The number of one or more Amazon EVS resources exceeds the maximum allowed. For a list of Amazon EVS quotas, see [Amazon EVS endpoints and quotas](#) in the *Amazon EVS User Guide*. Delete some resources or request an increase in your service quota. To request an increase, see [AWS Service Quotas](#) in the *AWS General Reference Guide*.

message

Describes the error encountered.

HTTP Status Code: 400

[TagPolicyException](#)

Note

TagPolicyException is deprecated. See [ValidationException](#) instead.

The request doesn't comply with IAM tag policy. Correct your request and then retry it.

message

Describes the error encountered

HTTP Status Code: 400

[TooManyTagsException](#)

Note

TooManyTagsException is deprecated. See [ServiceQuotaExceededException](#) instead.

A service resource associated with the request has more than 200 tags.

message

Describes the error encountered.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Deletes specified tags from an Amazon EVS resource.

Request Syntax

```
{  
  "resourceArn": "string",  
  "tagKeys": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Note

In the following list, the required parameters are described first.

resourceArn

The Amazon Resource Name (ARN) of the resource to delete tags from.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws:evs:[a-z]{2}-[a-z]+-[0-9]:[0-9]{12}:(?:environment|subscription)/[a-zA-Z0-9_-]+`

Required: Yes

tagKeys

The keys of the tags to delete.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 200 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w.:/=-@]+`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[ResourceNotFoundException](#)

A service resource associated with the request could not be found. The resource might not be specified correctly, or it may have a state of DELETED.

message

Describes the error encountered.

resourceId

The ID of the resource that could not be found.

resourceType

The type of the resource that is associated with the error.

HTTP Status Code: 400

[TagPolicyException](#)

Note

TagPolicyException is deprecated. See [ValidationException](#) instead.

The request doesn't comply with IAM tag policy. Correct your request and then retry it.

message

Describes the error encountered

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The Amazon Elastic VMware Service API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [Check](#)
- [ConnectivityInfo](#)
- [EipAssociation](#)
- [Environment](#)
- [EnvironmentSummary](#)
- [Host](#)
- [HostInfoForCreate](#)
- [InitialVlanInfo](#)
- [InitialVlans](#)
- [LicenseInfo](#)
- [NetworkInterface](#)
- [Secret](#)
- [ServiceAccessSecurityGroups](#)
- [ValidationExceptionField](#)
- [VcfHostnames](#)
- [Vlan](#)

Check

A check on the environment to identify environment health and validate VMware VCF licensing compliance.

Contents

Note

In the following list, the required parameters are described first.

impairedSince

The time when environment health began to be impaired.

Type: Timestamp

Required: No

result

The check result.

Type: String

Valid Values: PASSED | FAILED | UNKNOWN

Required: No

type

The check type. Amazon EVS performs the following checks.

- **KEY_REUSE**: checks that the VCF license key is not used by another Amazon EVS environment. This check fails if a used license is added to the environment.
- **KEY_COVERAGE**: checks that your VCF license key allocates sufficient vCPU cores for all deployed hosts. The check fails when any assigned hosts in the EVS environment are not covered by license keys, or when any unassigned hosts cannot be covered by available vCPU cores in keys.
- **REACHABILITY**: checks that the Amazon EVS control plane has a persistent connection to SDDC Manager. If Amazon EVS cannot reach the environment, this check fails.

- **HOST_COUNT**: Checks that your environment has a minimum of 4 hosts, which is a requirement for VCF 5.2.1.

If this check fails, you will need to add hosts so that your environment meets this minimum requirement. Amazon EVS only supports environments with 4-16 hosts.

Type: String

Valid Values: KEY_REUSE | KEY_COVERAGE | REACHABILITY | HOST_COUNT

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ConnectivityInfo

The connectivity configuration for the environment. Amazon EVS requires that you specify two route server peer IDs. During environment creation, the route server endpoints peer with the NSX uplink VLAN for connectivity to the NSX overlay network.

Contents

Note

In the following list, the required parameters are described first.

privateRouteServerPeerings

The unique IDs for private route server peers.

Type: Array of strings

Array Members: Fixed number of 2 items.

Length Constraints: Minimum length of 3. Maximum length of 21.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EipAssociation

An Elastic IP address association with the elastic network interface in the VLAN subnet.

Contents

Note

In the following list, the required parameters are described first.

allocationId

The Elastic IP address allocation ID.

Type: String

Length Constraints: Minimum length of 9. Maximum length of 26.

Pattern: eipalloc-[a-zA-Z0-9_-]+

Required: No

associationId

A unique ID for the elastic IP address association with the VLAN subnet.

Type: String

Length Constraints: Minimum length of 9. Maximum length of 26.

Pattern: eipassoc-[a-zA-Z0-9_-]+

Required: No

ipAddress

The Elastic IP address.

Type: String

Pattern: (\d{1,3}\.){3}\d{1,3}

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Environment

An object that represents an Amazon EVS environment.

Contents

Note

In the following list, the required parameters are described first.

checks

A check on the environment to identify instance health and VMware VCF licensing issues.

Type: Array of [Check](#) objects

Required: No

connectivityInfo

The connectivity configuration for the environment. Amazon EVS requires that you specify two route server peer IDs. During environment creation, the route server endpoints peer with the NSX uplink VLAN for connectivity to the NSX overlay network.

Type: [ConnectivityInfo](#) object

Required: No

createdAt

The date and time that the environment was created.

Type: Timestamp

Required: No

credentials

The VCF credentials that are stored as Amazon EVS managed secrets in AWS Secrets Manager.

Amazon EVS stores credentials that are needed to install vCenter Server, NSX, and SDDC Manager.

Type: Array of [Secret](#) objects

Required: No

environmentArn

The Amazon Resource Name (ARN) that is associated with the environment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws:evs:[a-z]{2}-[a-z]+-[0-9]:[0-9]{12}:(?:environment|subscription)/[a-zA-Z0-9_-]+`

Required: No

environmentId

The unique ID for the environment.

Type: String

Pattern: `(env-[a-zA-Z0-9]{10})`

Required: No

environmentName

The name of the environment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[a-zA-Z0-9_-]+`

Required: No

environmentState

The state of an environment.

Type: String

Valid Values: `CREATING` | `CREATED` | `DELETING` | `DELETED` | `CREATE_FAILED`

Required: No

environmentStatus

Reports impaired functionality that stems from issues internal to the environment, such as impaired reachability.

Type: String

Valid Values: PASSED | FAILED | UNKNOWN

Required: No

kmsKeyId

The AWS KMS key ID that AWS Secrets Manager uses to encrypt secrets that are associated with the environment. These secrets contain the VCF credentials that are needed to install vCenter Server, NSX, and SDDC Manager.

By default, Amazon EVS use the AWS Secrets Manager managed key `aws/secretsmanager`. You can also specify a customer managed key.

Type: String

Required: No

licenseInfo

The license information that Amazon EVS requires to create an environment. Amazon EVS requires two license keys: a VCF solution key and a vSAN license key. The VCF solution key must cover a minimum of 256 cores. The vSAN license key must provide at least 110 TiB of vSAN capacity.

Type: Array of [LicenseInfo](#) objects

Array Members: Fixed number of 1 item.

Required: No

modifiedAt

The date and time that the environment was modified.

Type: Timestamp

Required: No

serviceAccessSecurityGroups

The security groups that allow traffic between the Amazon EVS control plane and your VPC for service access. If a security group is not specified, Amazon EVS uses the default security group in your account for service access.

Type: [ServiceAccessSecurityGroups](#) object

Required: No

serviceAccessSubnetId

The subnet that is used to establish connectivity between the Amazon EVS control plane and VPC. Amazon EVS uses this subnet to perform validations and create the environment.

Type: String

Length Constraints: Minimum length of 15. Maximum length of 24.

Pattern: subnet-[a-f0-9]{8}([a-f0-9]{9})?

Required: No

siteId

The Broadcom Site ID that is associated with your Amazon EVS environment. Amazon EVS uses the Broadcom Site ID that you provide to meet Broadcom VCF license usage reporting requirements for Amazon EVS.

Type: String

Required: No

stateDetails

A detailed description of the `environmentState` of an environment.

Type: String

Required: No

termsAccepted

Customer confirmation that the customer has purchased and will continue to maintain the required number of VCF software licenses to cover all physical processor cores in the Amazon EVS environment. Information about your VCF software in Amazon EVS will be shared with

Broadcom to verify license compliance. Amazon EVS does not validate license keys. To validate license keys, visit the Broadcom support portal.

Type: Boolean

Required: No

vcfHostnames

The DNS hostnames to be used by the VCF management appliances in your environment.

For environment creation to be successful, each hostname entry must resolve to a domain name that you've registered in your DNS service of choice and configured in the DHCP option set of your VPC. DNS hostnames cannot be changed after environment creation has started.

Type: [VcfHostnames](#) object

Required: No

vcfVersion

The VCF version of the environment.

Type: String

Valid Values: VCF-5.2.1

Required: No

vpclId

The VPC associated with the environment.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 21.

Pattern: vpc-[a-f0-9]{8}([a-f0-9]{9})?

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EnvironmentSummary

A list of environments with summarized environment details.

Contents

Note

In the following list, the required parameters are described first.

createdAt

The date and time that the environment was created.

Type: Timestamp

Required: No

environmentArn

The Amazon Resource Name (ARN) that is associated with the environment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws:evs:[a-z]{2}-[a-z]+-[0-9]:[0-9]{12}:(?:environment|subscription)/[a-zA-Z0-9_-]+`

Required: No

environmentId

A unique ID for the environment.

Type: String

Pattern: `(env-[a-zA-Z0-9]{10})`

Required: No

environmentName

The name of the environment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9_-]+

Required: No

environmentState

The state of an environment.

Type: String

Valid Values: CREATING | CREATED | DELETING | DELETED | CREATE_FAILED

Required: No

environmentStatus

Reports impaired functionality that stems from issues internal to the environment, such as impaired reachability.

Type: String

Valid Values: PASSED | FAILED | UNKNOWN

Required: No

modifiedAt

The date and time that the environment was modified.

Type: Timestamp

Required: No

vcfVersion

The VCF version of the environment.

Type: String

Valid Values: VCF-5.2.1

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Host

An ESXi host that runs on an Amazon EC2 bare metal instance. Four hosts are created in an Amazon EVS environment during environment creation. You can add hosts to an environment using the `CreateEnvironmentHost` operation. Amazon EVS supports 4-16 hosts per environment.

Contents

Note

In the following list, the required parameters are described first.

createdAt

The date and time that the host was created.

Type: Timestamp

Required: No

dedicatedHostId

The unique ID of the Amazon EC2 Dedicated Host.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 25.

Pattern: `h-[a-f0-9]{8}([a-f0-9]{9})?`

Required: No

ec2InstanceId

The unique ID of the EC2 instance that represents the host.

Type: String

Required: No

hostName

The DNS hostname of the host. DNS hostnames for hosts must be unique across Amazon EVS environments and within VCF.

Type: String

Pattern: ([a-zA-Z0-9\-*])

Required: No

hostState

The state of the host.

Type: String

Valid Values: CREATING | CREATED | UPDATING | DELETING | DELETED |
CREATE_FAILED | UPDATE_FAILED

Required: No

instanceType

The EC2 instance type of the host.

Note

EC2 instances created through Amazon EVS do not support associating an IAM instance profile.

Type: String

Valid Values: i4i.metal

Required: No

ipAddress

The IP address of the host.

Type: String

Pattern: (\d{1,3}\.){3}\d{1,3}

Required: No

keyName

The name of the SSH key that is used to access the host.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9_-]+

Required: No

modifiedAt

The date and time that the host was modified.

Type: Timestamp

Required: No

networkInterfaces

The elastic network interfaces that are attached to the host.

Type: Array of [NetworkInterface](#) objects

Array Members: Minimum number of 0 items. Maximum number of 2 items.

Required: No

placementGroupId

The unique ID of the placement group where the host is placed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 25.

Pattern: pg-[a-f0-9]{8}([a-f0-9]{9})?

Required: No

stateDetails

A detailed description of the hostState of a host.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HostInfoForCreate

An object that represents a host.

Note

You cannot use `dedicatedHostId` and `placementGroupId` together in the same `HostInfoForCreate` object. This results in a `ValidationException` response.

Contents

Note

In the following list, the required parameters are described first.

hostName

The DNS hostname of the host. DNS hostnames for hosts must be unique across Amazon EVS environments and within VCF.

Type: String

Pattern: (`[a-zA-Z0-9\ -]*`)

Required: Yes

instanceType

The EC2 instance type that represents the host.

Type: String

Valid Values: `i4i.metal`

Required: Yes

keyName

The name of the SSH key that is used to access the host.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

dedicatedHostId

The unique ID of the Amazon EC2 Dedicated Host.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 25.

Pattern: h-[a-f0-9]{8}([a-f0-9]{9})?

Required: No

placementGroupId

The unique ID of the placement group where the host is placed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 25.

Pattern: pg-[a-f0-9]{8}([a-f0-9]{9})?

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InitialVlanInfo

An object that represents an initial VLAN subnet for the Amazon EVS environment. Amazon EVS creates initial VLAN subnets when you first create the environment. Amazon EVS creates the following 10 VLAN subnets: host management VLAN, vMotion VLAN, vSAN VLAN, VTEP VLAN, Edge VTEP VLAN, Management VM VLAN, HCX uplink VLAN, NSX uplink VLAN, expansion VLAN 1, expansion VLAN 2.

Note

For each Amazon EVS VLAN subnet, you must specify a non-overlapping CIDR block. Amazon EVS VLAN subnets have a minimum CIDR block size of /28 and a maximum size of /24.

Contents

Note

In the following list, the required parameters are described first.

cidr

The CIDR block that you provide to create an Amazon EVS VLAN subnet. Amazon EVS VLAN subnets have a minimum CIDR block size of /28 and a maximum size of /24. Amazon EVS VLAN subnet CIDR blocks must not overlap with other subnets in the VPC.

Type: String

Pattern: ((25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)\.){3}(25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)/(3[0-2]|[1-2][0-9]|[0-9])

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InitialVlans

The initial VLAN subnets for the environment. Amazon EVS VLAN subnets have a minimum CIDR block size of /28 and a maximum size of /24. Amazon EVS VLAN subnet CIDR blocks must not overlap with other subnets in the VPC.

Contents

Note

In the following list, the required parameters are described first.

edgeVTep

The edge VTEP VLAN subnet. This VLAN subnet manages traffic flowing between the internal network and external networks, including internet access and other site connections.

Type: [InitialVlanInfo](#) object

Required: Yes

expansionVlan1

An additional VLAN subnet that can be used to extend VCF capabilities once configured. For example, you can configure an expansion VLAN subnet to use NSX Federation for centralized management and synchronization of multiple NSX deployments across different locations.

Type: [InitialVlanInfo](#) object

Required: Yes

expansionVlan2

An additional VLAN subnet that can be used to extend VCF capabilities once configured. For example, you can configure an expansion VLAN subnet to use NSX Federation for centralized management and synchronization of multiple NSX deployments across different locations.

Type: [InitialVlanInfo](#) object

Required: Yes

hcx

The HCX VLAN subnet. This VLAN subnet allows the HCX Interconnect (IX) and HCX Network Extension (NE) to reach their peers and enable HCX Service Mesh creation.

If you plan to use a public HCX VLAN subnet, the following requirements must be met:

- Must have a /28 netmask and be allocated from the IPAM public pool. Required for HCX internet access configuration.
- The HCX public VLAN CIDR block must be added to the VPC as a secondary CIDR block.
- Must have at least two Elastic IP addresses to be allocated from the public IPAM pool for HCX components.

Type: [InitialVlanInfo](#) object

Required: Yes

nsxUplink

The NSX uplink VLAN subnet. This VLAN subnet allows connectivity to the NSX overlay network.

Type: [InitialVlanInfo](#) object

Required: Yes

vmkManagement

The host VMkernel management VLAN subnet. This VLAN subnet carries traffic for managing ESXi hosts and communicating with VMware vCenter Server.

Type: [InitialVlanInfo](#) object

Required: Yes

vmManagement

The VM management VLAN subnet. This VLAN subnet carries traffic for vSphere virtual machines.

Type: [InitialVlanInfo](#) object

Required: Yes

vMotion

The vMotion VLAN subnet. This VLAN subnet carries traffic for vSphere vMotion.

Type: [InitialVlanInfo](#) object

Required: Yes

vSan

The vSAN VLAN subnet. This VLAN subnet carries the communication between ESXi hosts to implement a vSAN shared storage pool.

Type: [InitialVlanInfo](#) object

Required: Yes

vTep

The VTEP VLAN subnet. This VLAN subnet handles internal network traffic between virtual machines within a VCF instance.

Type: [InitialVlanInfo](#) object

Required: Yes

hcxNetworkAclId

A unique ID for a network access control list that the HCX VLAN uses. Required when `isHcxPublic` is set to `true`.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 21.

Pattern: `acl-[a-zA-Z0-9_-]+`

Required: No

isHcxPublic

Determines if the HCX VLAN that Amazon EVS provisions is public or private.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LicenseInfo

The license information that Amazon EVS requires to create an environment. Amazon EVS requires two license keys: a VCF solution key and a vSAN license key.

Contents

Note

In the following list, the required parameters are described first.

solutionKey

The VCF solution key. This license unlocks VMware VCF product features, including vSphere, NSX, SDDC Manager, and vCenter Server. The VCF solution key must cover a minimum of 256 cores.

Type: String

Pattern: [a-zA-Z0-9]{5}-[a-zA-Z0-9]{5}-[a-zA-Z0-9]{5}-[a-zA-Z0-9]{5}-[a-zA-Z0-9]{5}

Required: Yes

vsanKey

The VSAN license key. This license unlocks vSAN features. The vSAN license key must provide at least 110 TiB of vSAN capacity.

Type: String

Pattern: [a-zA-Z0-9]{5}-[a-zA-Z0-9]{5}-[a-zA-Z0-9]{5}-[a-zA-Z0-9]{5}-[a-zA-Z0-9]{5}

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NetworkInterface

An elastic network interface (ENI) that connects hosts to the VLAN subnets. Amazon EVS provisions two identically configured ENIs in the VMkernel management subnet during host creation. One ENI is active, and the other is in standby mode for automatic switchover during a failure scenario.

Contents

Note

In the following list, the required parameters are described first.

networkInterfaceId

The unique ID of the elastic network interface.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Secret

A managed secret that contains the credentials for installing vCenter Server, NSX, and SDDC Manager. During environment creation, the Amazon EVS control plane uses AWS Secrets Manager to create, encrypt, validate, and store secrets. If you choose to delete your environment, Amazon EVS also deletes the secrets that are associated with your environment. Amazon EVS does not provide managed rotation of secrets. We recommend that you rotate secrets regularly to ensure that secrets are not long-lived.

Contents

Note

In the following list, the required parameters are described first.

secretArn

The Amazon Resource Name (ARN) of the secret.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceAccessSecurityGroups

The security groups that allow traffic between the Amazon EVS control plane and your VPC for Amazon EVS service access. If a security group is not specified, Amazon EVS uses the default security group in your account for service access.

Contents

Note

In the following list, the required parameters are described first.

securityGroups

The security groups that allow service access.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 2 items.

Length Constraints: Minimum length of 3. Maximum length of 25.

Pattern: sg-[0-9a-zA-Z]*

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ValidationExceptionField

Stores information about a field passed inside a request that resulted in an exception.

Contents

Note

In the following list, the required parameters are described first.

message

A message describing why the field failed validation.

Type: String

Required: Yes

name

The field name.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VcfHostnames

The DNS hostnames that Amazon EVS uses to install VMware vCenter Server, NSX, SDDC Manager, and Cloud Builder. Each hostname must be unique, and resolve to a domain name that you've registered in your DNS service of choice. Hostnames cannot be changed.

VMware VCF requires the deployment of two NSX Edge nodes, and three NSX Manager virtual machines.

Contents

Note

In the following list, the required parameters are described first.

cloudBuilder

The hostname for VMware Cloud Builder.

Type: String

Pattern: ([a-zA-Z0-9\ -] *)

Required: Yes

nsx

The VMware NSX hostname.

Type: String

Pattern: ([a-zA-Z0-9\ -] *)

Required: Yes

nsxEdge1

The hostname for the first NSX Edge node.

Type: String

Pattern: ([a-zA-Z0-9\ -] *)

Required: Yes

nsxEdge2

The hostname for the second NSX Edge node.

Type: String

Pattern: ([a-zA-Z0-9\ -] *)

Required: Yes

nsxManager1

The hostname for the first VMware NSX Manager virtual machine (VM).

Type: String

Pattern: ([a-zA-Z0-9\ -] *)

Required: Yes

nsxManager2

The hostname for the second VMware NSX Manager virtual machine (VM).

Type: String

Pattern: ([a-zA-Z0-9\ -] *)

Required: Yes

nsxManager3

The hostname for the third VMware NSX Manager virtual machine (VM).

Type: String

Pattern: ([a-zA-Z0-9\ -] *)

Required: Yes

sddcManager

The hostname for SDDC Manager.

Type: String

Pattern: ([a-zA-Z0-9\-]*)

Required: Yes

vCenter

The VMware vCenter hostname.

Type: String

Pattern: ([a-zA-Z0-9\-]*)

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Vlan

The VLANs that Amazon EVS creates during environment creation.

Contents

Note

In the following list, the required parameters are described first.

availabilityZone

The availability zone of the VLAN.

Type: String

Required: No

cidr

The CIDR block of the VLAN. Amazon EVS VLAN subnets have a minimum CIDR block size of /28 and a maximum size of /24.

Type: String

Pattern: ((25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)\.){3}(25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)/(3[0-2]|[1-2][0-9]|[0-9])

Required: No

createdAt

The date and time that the VLAN was created.

Type: Timestamp

Required: No

eipAssociations

An array of Elastic IP address associations.

Type: Array of [EipAssociation](#) objects

Required: No

functionName

The VMware VCF traffic type that is carried over the VLAN. For example, a VLAN with a `functionName` of `hcx` is being used to carry VMware HCX traffic.

Type: String

Required: No

isPublic

Determines if the VLAN that Amazon EVS provisions is public or private.

Type: Boolean

Required: No

modifiedAt

The date and time that the VLAN was modified.

Type: Timestamp

Required: No

networkAclId

A unique ID for a network access control list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 21.

Pattern: `ac1-[a-zA-Z0-9_-]+`

Required: No

stateDetails

The state details of the VLAN.

Type: String

Required: No

subnetId

The unique ID of the VLAN subnet.

Type: String

Length Constraints: Minimum length of 15. Maximum length of 24.

Pattern: subnet-[a-f0-9]{8}([a-f0-9]{9})?

Required: No

vlanId

The unique ID of the VLAN.

Type: Integer

Required: No

vlanState

The state of the VLAN.

Type: String

Valid Values: CREATING | CREATED | DELETING | DELETED | CREATE_FAILED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Service-specific Errors

The Amazon Elastic VMware Service API contains service-specific exceptions that various actions return. This section describes each exception in detail.

The following service-specific exceptions are returned:

- [ResourceNotFoundException](#)
- [ServiceQuotaExceededException](#)
- [TagPolicyException](#)
- [ThrottlingException](#)
- [TooManyTagsException](#)
- [ValidationException](#)

ResourceNotFoundException

A service resource associated with the request could not be found. The resource might not be specified correctly, or it may have a state of DELETED.

HTTP Status Code returned: 400

Contents

message

Describes the error encountered.

Type: String

Required: Yes

resourceId

The ID of the resource that could not be found.

Type: String

Required: Yes

resourceType

The type of the resource that is associated with the error.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for Ruby V3](#)

ServiceQuotaExceededException

The number of one or more Amazon EVS resources exceeds the maximum allowed. For a list of Amazon EVS quotas, see [Amazon EVS endpoints and quotas](#) in the *Amazon EVS User Guide*. Delete some resources or request an increase in your service quota. To request an increase, see [AWS Service Quotas](#) in the *AWS General Reference Guide*.

HTTP Status Code returned: 400

Contents

message

Describes the error encountered.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for Ruby V3](#)

TagPolicyException

Note

TagPolicyException is deprecated. See [ValidationException](#) instead.

The request doesn't comply with IAM tag policy. Correct your request and then retry it.

HTTP Status Code returned: 400

Contents

message

Describes the error encountered

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for Ruby V3](#)

ThrottlingException

The operation couldn't be performed because the service is throttling requests. This exception is thrown when there are too many requests accepted concurrently from the service endpoint.

HTTP Status Code returned: 400

Contents

message

Describes the error encountered.

Type: String

Required: Yes

retryAfterSeconds

The seconds to wait to retry.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for Ruby V3](#)

TooManyTagsException

Note

TooManyTagsException is deprecated. See [ServiceQuotaExceededException](#) instead.

A service resource associated with the request has more than 200 tags.

HTTP Status Code returned: 400

Contents

message

Describes the error encountered.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for Ruby V3](#)

ValidationException

The input fails to satisfy the specified constraints. You will see this exception if invalid inputs are provided for any of the Amazon EVS environment operations, or if a list operation is performed on an environment resource that is still initializing.

HTTP Status Code returned: 400

Contents

message

Describes the error encountered.

Type: String

Required: Yes

reason

The reason for the exception.

Type: String

Valid Values: `unknownOperation` | `cannotParse` | `fieldValidationFailed` | `other`

Required: Yes

fieldList

A list of fields that didn't validate.

Type: Array of [ValidationExceptionField](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400