



Projects API Reference

AWS IoT 1-Click



API Version 2018-05-14

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS IoT 1-Click: Projects API Reference

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
AssociateDeviceWithPlacement	3
Request Syntax	3
URI Request Parameters	3
Request Body	4
Response Syntax	4
Response Elements	4
Errors	4
See Also	5
CreatePlacement	6
Request Syntax	6
URI Request Parameters	6
Request Body	6
Response Syntax	7
Response Elements	7
Errors	7
See Also	8
CreateProject	9
Request Syntax	9
URI Request Parameters	9
Request Body	9
Response Syntax	11
Response Elements	11
Errors	11
See Also	11
DeletePlacement	13
Request Syntax	13
URI Request Parameters	13
Request Body	13
Response Syntax	14
Response Elements	14
Errors	14
See Also	14

DeleteProject	16
Request Syntax	16
URI Request Parameters	16
Request Body	16
Response Syntax	16
Response Elements	16
Errors	17
See Also	17
DescribePlacement	18
Request Syntax	18
URI Request Parameters	18
Request Body	18
Response Syntax	18
Response Elements	19
Errors	19
See Also	20
DescribeProject	21
Request Syntax	21
URI Request Parameters	21
Request Body	21
Response Syntax	21
Response Elements	22
Errors	22
See Also	23
DisassociateDeviceFromPlacement	24
Request Syntax	24
URI Request Parameters	24
Request Body	25
Response Syntax	25
Response Elements	25
Errors	25
See Also	25
GetDevicesInPlacement	27
Request Syntax	27
URI Request Parameters	27
Request Body	27

Response Syntax	27
Response Elements	28
Errors	28
See Also	29
ListPlacements	30
Request Syntax	30
URI Request Parameters	30
Request Body	30
Response Syntax	30
Response Elements	31
Errors	31
See Also	32
ListProjects	33
Request Syntax	33
URI Request Parameters	33
Request Body	33
Response Syntax	33
Response Elements	34
Errors	34
See Also	35
ListTagsForResource	36
Request Syntax	36
URI Request Parameters	36
Request Body	36
Response Syntax	36
Response Elements	36
Errors	37
See Also	37
TagResource	39
Request Syntax	39
URI Request Parameters	39
Request Body	39
Response Syntax	40
Response Elements	40
Errors	40
See Also	40

UntagResource	42
Request Syntax	42
URI Request Parameters	42
Request Body	42
Response Syntax	42
Response Elements	43
Errors	43
See Also	43
UpdatePlacement	44
Request Syntax	44
URI Request Parameters	44
Request Body	44
Response Syntax	45
Response Elements	45
Errors	45
See Also	46
UpdateProject	47
Request Syntax	47
URI Request Parameters	47
Request Body	48
Response Syntax	48
Response Elements	48
Errors	48
See Also	49
Data Types	50
DeviceTemplate	51
Contents	51
See Also	51
PlacementDescription	52
Contents	52
See Also	53
PlacementSummary	54
Contents	54
See Also	55
PlacementTemplate	56
Contents	56

See Also	56
ProjectDescription	57
Contents	57
See Also	58
ProjectSummary	60
Contents	60
See Also	61
Common Parameters	62
Common Errors	65

Welcome

The AWS IoT 1-Click Projects API Reference

Important

AWS will discontinue AWS IoT 1-Click service on December 16, 2024. For more information, see [AWS IoT 1-Click end-of-life FAQs](#). For additional help, visit [AWS support center](#).

This document was last published on July 3, 2024.

Actions

The following actions are supported:

- [AssociateDeviceWithPlacement](#)
- [CreatePlacement](#)
- [CreateProject](#)
- [DeletePlacement](#)
- [DeleteProject](#)
- [DescribePlacement](#)
- [DescribeProject](#)
- [DisassociateDeviceFromPlacement](#)
- [GetDevicesInPlacement](#)
- [ListPlacements](#)
- [ListProjects](#)
- [ListTagsForResource](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdatePlacement](#)
- [UpdateProject](#)

AssociateDeviceWithPlacement

Associates a physical device with a placement.

Request Syntax

```
PUT /projects/projectName/placements/placementName/devices/deviceTemplateName HTTP/1.1
Content-type: application/json

{
  "deviceId": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

deviceTemplateName

The device template name to associate with the device ID.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_-]+\$

Required: Yes

placementName

The name of the placement in which to associate the device.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_-]+\$

Required: Yes

projectId

The name of the project containing the placement in which to associate the device.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[0-9A-Za-z_-]+\$

Required: Yes

Request Body

The request accepts the following data in JSON format.

deviceId

The ID of the physical device to be associated with the given placement in the project. Note that a mandatory 4 character prefix is required for all deviceId values.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

Response Syntax

HTTP/1.1 200

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

HTTP Status Code: 500

InvalidRequestException

HTTP Status Code: 400

ResourceConflictException

HTTP Status Code: 409

ResourceNotFoundException

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreatePlacement

Creates an empty placement.

Request Syntax

```
POST /projects/projectName/placements HTTP/1.1
Content-type: application/json

{
  "attributes": {
    "string": "string"
  },
  "placementName": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

projectName

The name of the project in which to create the placement.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[0-9A-Za-z_-]+\$

Required: Yes

Request Body

The request accepts the following data in JSON format.

attributes

Optional user-defined key/value pairs providing contextual data (such as location or function) for the placement.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Maximum length of 800.

Required: No

placementName

The name of the placement to be created.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_-]+\$

Required: Yes

Response Syntax

HTTP/1.1 200

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

HTTP Status Code: 500

InvalidRequestException

HTTP Status Code: 400

ResourceConflictException

HTTP Status Code: 409

ResourceNotFoundException

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateProject

Creates an empty project with a placement template. A project contains zero or more placements that adhere to the placement template defined in the project.

Request Syntax

```
POST /projects HTTP/1.1
Content-type: application/json

{
  "description": "string",
  "placementTemplate": {
    "defaultAttributes": {
      "string" : "string"
    },
    "deviceTemplates": {
      "string" : {
        "callbackOverrides": {
          "string" : "string"
        },
        "deviceType": "string"
      }
    }
  },
  "projectName": "string",
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

description

An optional description for the project.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

placementTemplate

The schema defining the placement to be created. A placement template defines placement default attributes and device templates. You cannot add or remove device templates after the project has been created. However, you can update `callbackOverrides` for the device templates using the `UpdateProject` API.

Type: [PlacementTemplate](#) object

Required: No

projectName

The name of the project to create.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[0-9A-Za-z_-]+\$

Required: Yes

tags

Optional tags (metadata key/value pairs) to be associated with the project. For example, { {"key1": "value1", "key2": "value2"} }. For more information, see [AWS Tagging Strategies](#).

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: ^(?!aws:)[a-zA-Z+=_.:_:/]+\$

Value Length Constraints: Maximum length of 256.

Required: No

Response Syntax

HTTP/1.1 200

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

HTTP Status Code: 500

InvalidRequestException

HTTP Status Code: 400

ResourceConflictException

HTTP Status Code: 409

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeletePlacement

Deletes a placement. To delete a placement, it must not have any devices associated with it.

Note

When you delete a placement, all associated data becomes irretrievable.

Request Syntax

```
DELETE /projects/ projectName /placements/ placementName  HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

placementName

The name of the empty placement to delete.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_-]+\$

Required: Yes

projectName

The project containing the empty placement to delete.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[0-9A-Za-z_-]+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

HTTP/1.1 200

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

HTTP Status Code: 500

InvalidRequestException

HTTP Status Code: 400

ResourceNotFoundException

HTTP Status Code: 404

TooManyRequestsException

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteProject

Deletes a project. To delete a project, it must not have any placements associated with it.

Note

When you delete a project, all associated data becomes irretrievable.

Request Syntax

```
DELETE /projects/projectName HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

projectName

The name of the empty project to delete.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[0-9A-Za-z_-]+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

HTTP Status Code: 500

InvalidRequestException

HTTP Status Code: 400

ResourceNotFoundException

HTTP Status Code: 404

TooManyRequestsException

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribePlacement

Describes a placement in a project.

Request Syntax

```
GET /projects/ projectName /placements/ placementName  HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

placementName

The name of the placement within a project.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_-]+\$

Required: Yes

projectName

The project containing the placement to be described.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[0-9A-Za-z_-]+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{  
  "placement": {  
    "attributes": {  
      "string" : "string"  
    },  
    "createdDate": number,  
    "placementName": "string",  
    "projectName": "string",  
    "updatedDate": number  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

placement

An object describing the placement.

Type: [PlacementDescription](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

HTTP Status Code: 500

InvalidRequestException

HTTP Status Code: 400

ResourceNotFoundException

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeProject

Returns an object describing a project.

Request Syntax

```
GET /projects/projectName HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[projectName](#)

The name of the project to be described.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[0-9A-Za-z_-]+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "project": {
    "arn": "string",
    "createdDate": number,
    "description": "string",
    "placementTemplate": {
      "defaultAttributes": {
        "string" : "string"
      },
      "deviceTemplates": {
```

```
        "string" : {
            "callbackOverrides": {
                "string" : "string"
            },
            "deviceType": "string"
        }
    }
},
"projectName": "string",
"tags": {
    "string" : "string"
},
"updatedDate": number
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

project

An object describing the project.

Type: [ProjectDescription](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

HTTP Status Code: 500

InvalidRequestException

HTTP Status Code: 400

ResourceNotFoundException

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisassociateDeviceFromPlacement

Removes a physical device from a placement.

Request Syntax

```
DELETE /projects/ projectName /placements/ placementName /devices/ deviceTemplateName   
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

deviceTemplateName

The device ID that should be removed from the placement.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_-]+\$

Required: Yes

placementName

The name of the placement that the device should be removed from.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_-]+\$

Required: Yes

projectName

The name of the project that contains the placement.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[0-9A-Za-z_-]+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

HTTP Status Code: 500

InvalidRequestException

HTTP Status Code: 400

ResourceNotFoundException

HTTP Status Code: 404

TooManyRequestsException

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDevicesInPlacement

Returns an object enumerating the devices in a placement.

Request Syntax

```
GET /projects/projectName/placements/placementName/devices HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

placementName

The name of the placement to get the devices from.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_-]+\$

Required: Yes

projectName

The name of the project containing the placement.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[0-9A-Za-z_-]+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{  
  "devices": {  
    "string" : "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

devices

An object containing the devices (zero or more) within the placement.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: ^[a-zA-Z0-9_-]+\$

Value Length Constraints: Minimum length of 1. Maximum length of 32.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

HTTP Status Code: 500

InvalidRequestException

HTTP Status Code: 400

ResourceNotFoundException

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPlacements

Lists the placement(s) of a project.

Request Syntax

```
GET /projects/projectId/placements?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to return per request. If not set, a default value of 100 is used.

Valid Range: Minimum value of 1. Maximum value of 250.

nextToken

The token to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 1024.

projectId

The project containing the placements to be listed.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[0-9A-Za-z_-]+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "nextToken": "string",
  "placements": [
    {
      "createdDate": number,
      "placementName": "string",
      "projectName": "string",
      "updatedDate": number
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

The token used to retrieve the next set of results - will be effectively empty if there are no further results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

[placements](#)

An object listing the requested placements.

Type: Array of [PlacementSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

HTTP Status Code: 500

InvalidRequestException

HTTP Status Code: 400

ResourceNotFoundException

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListProjects

Lists the AWS IoT 1-Click project(s) associated with your AWS account and region.

Request Syntax

```
GET /projects?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to return per request. If not set, a default value of 100 is used.

Valid Range: Minimum value of 1. Maximum value of 250.

nextToken

The token to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextTokenprojectsarncreatedDateprojectName
```

```
  "tags": {  
    "string" : "string"  
  },  
  "updatedDate": number  
}  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

The token used to retrieve the next set of results - will be effectively empty if there are no further results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

[projects](#)

An object containing the list of projects.

Type: Array of [ProjectSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

HTTP Status Code: 500

InvalidRequestException

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Lists the tags (metadata key/value pairs) which you have assigned to the resource.

Request Syntax

```
GET /tags/resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the resource whose tags you want to list.

Pattern: ^arn:aws:iot1click:[A-Za-z0-9_/.-]{0,63}:\d+:projects/[0-9A-Za-z_-]{1,128}\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "tags": {
    "string": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags

The tags (metadata key/value pairs) which you have assigned to the resource.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: ^(?!\aws:)[a-zA-Z+-.=:_:/]+\$

Value Length Constraints: Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

HTTP Status Code: 500

InvalidRequestException

HTTP Status Code: 400

ResourceNotFoundException

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Creates or modifies tags for a resource. Tags are key/value pairs (metadata) that can be used to manage a resource. For more information, see [AWS Tagging Strategies](#).

Request Syntax

```
POST /tags/resourceArn HTTP/1.1
Content-type: application/json

{
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the resource for which tag(s) should be added or modified.

Pattern: ^arn:aws:iot1click:[A-Za-z0-9_/.-]{0,63}:\d+:projects/[0-9A-Za-z_-]{1,128}\$

Required: Yes

Request Body

The request accepts the following data in JSON format.

tags

The new or modifying tag(s) for the resource. See [AWS IoT 1-Click Service Limits](#) for the maximum number of tags allowed per resource.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z+-=.:_:/]+$`

Value Length Constraints: Maximum length of 256.

Required: Yes

Response Syntax

HTTP/1.1 200

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

HTTP Status Code: 500

InvalidRequestException

HTTP Status Code: 400

ResourceNotFoundException

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Removes one or more tags (metadata key/value pairs) from a resource.

Request Syntax

```
DELETE /tags/resourceArn?tagKeys=tagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the resource whose tag you want to remove.

Pattern: ^arn:aws:iot1click:[A-Za-z0-9_/.-]{0,63}:\d+:projects/[0-9A-Za-z_-]{1,128}\$

Required: Yes

tagKeys

The keys of those tags which you want to remove.

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^(? !aws :)[a-zA-Z+-=._:/]+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

HTTP Status Code: 500

InvalidRequestException

HTTP Status Code: 400

ResourceNotFoundException

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdatePlacement

Updates a placement with the given attributes. To clear an attribute, pass an empty value (i.e., "").

Request Syntax

```
PUT /projects/projectName/placements/placementName HTTP/1.1
Content-type: application/json

{
  "attributes": {
    "string": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

placementName

The name of the placement to update.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_-]+\$

Required: Yes

projectName

The name of the project containing the placement to be updated.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[0-9A-Za-z_-]+\$

Required: Yes

Request Body

The request accepts the following data in JSON format.

attributes

The user-defined object of attributes used to update the placement. The maximum number of key/value pairs is 50.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Maximum length of 800.

Required: No

Response Syntax

HTTP/1.1 200

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

HTTP Status Code: 500

InvalidRequestException

HTTP Status Code: 400

ResourceNotFoundException

HTTP Status Code: 404

TooManyRequestsException

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateProject

Updates a project associated with your AWS account and region. With the exception of device template names, you can pass just the values that need to be updated because the update request will change only the values that are provided. To clear a value, pass the empty string (i.e., "").

Request Syntax

```
PUT /projects/projectName HTTP/1.1
Content-type: application/json

{
  "description": "string",
  "placementTemplate": {
    "defaultAttributesstring : "string"
    },
    "deviceTemplates": {
      "string : {
        "callbackOverrides": {
          "string : "string"
        },
        "deviceType": "string"
      }
    }
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

projectName

The name of the project to be updated.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[0-9A-Za-z_-]+\$

Required: Yes

Request Body

The request accepts the following data in JSON format.

[description](#)

An optional user-defined description for the project.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

[placementTemplate](#)

An object defining the project update. Once a project has been created, you cannot add device template names to the project. However, for a given placementTemplate, you can update the associated callbackOverrides for the device definition using this API.

Type: [PlacementTemplate](#) object

Required: No

Response Syntax

HTTP/1.1 200

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

HTTP Status Code: 500

InvalidRequestException

HTTP Status Code: 400

ResourceNotFoundException

HTTP Status Code: 404

TooManyRequestsException

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS IoT 1-Click Projects Service API contains several data types that various actions use. This section describes each data type in detail.

 **Note**

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [DeviceTemplate](#)
- [PlacementDescription](#)
- [PlacementSummary](#)
- [PlacementTemplate](#)
- [ProjectDescription](#)
- [ProjectSummary](#)

DeviceTemplate

An object representing a device for a placement template (see [PlacementTemplate](#)).

Contents

callbackOverrides

An optional Lambda function to invoke instead of the default Lambda function provided by the placement template.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Maximum length of 200.

Required: No

deviceType

The device type, which currently must be "button".

Type: String

Length Constraints: Maximum length of 128.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PlacementDescription

An object describing a project's placement.

Contents

attributes

The user-defined attributes associated with the placement.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Maximum length of 800.

Required: Yes

createdAt

The date when the placement was initially created, in UNIX epoch time format.

Type: Timestamp

Required: Yes

placementName

The name of the placement.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_-]+\$

Required: Yes

projectName

The name of the project containing the placement.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[0-9A-Za-z_-]+\$

Required: Yes

updatedDate

The date when the placement was last updated, in UNIX epoch time format. If the placement was not updated, then `createdAt` and `updatedDate` are the same.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PlacementSummary

An object providing summary information for a particular placement.

Contents

createdDate

The date when the placement was originally created, in UNIX epoch time format.

Type: Timestamp

Required: Yes

placementName

The name of the placement being summarized.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_-]+\$

Required: Yes

projectName

The name of the project containing the placement.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[0-9A-Za-z_-]+\$

Required: Yes

updatedDate

The date when the placement was last updated, in UNIX epoch time format. If the placement was not updated, then `createdAt` and `updatedAt` are the same.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PlacementTemplate

An object defining the template for a placement.

Contents

defaultAttributes

The default attributes (key/value pairs) to be applied to all placements using this template.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Maximum length of 800.

Required: No

deviceTemplates

An object specifying the [DeviceTemplate](#) for all placements using this ([PlacementTemplate](#)) template.

Type: String to [DeviceTemplate](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: ^[a-zA-Z0-9_-]+\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ProjectDescription

An object providing detailed information for a particular project associated with an AWS account and region.

Contents

createdDate

The date when the project was originally created, in UNIX epoch time format.

Type: Timestamp

Required: Yes

projectName

The name of the project for which to obtain information from.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[0-9A-Za-z_-]+\$

Required: Yes

updatedDate

The date when the project was last updated, in UNIX epoch time format. If the project was not updated, then `createdDate` and `updatedDate` are the same.

Type: Timestamp

Required: Yes

arn

The ARN of the project.

Type: String

Pattern: ^arn:aws:iot1click:[A-Za-z0-9_/-]{0,63}:\d+:projects/[0-9A-Za-z_-]{1,128}\$

Required: No

description

The description of the project.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

placementTemplate

An object describing the project's placement specifications.

Type: [PlacementTemplate](#) object

Required: No

tags

The tags (metadata key/value pairs) associated with the project.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: ^(?!\aws:)[a-zA-Z+-.=:_:/]+\$

Value Length Constraints: Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ProjectSummary

An object providing summary information for a particular project for an associated AWS account and region.

Contents

createdDate

The date when the project was originally created, in UNIX epoch time format.

Type: Timestamp

Required: Yes

projectName

The name of the project being summarized.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[0-9A-Za-z_-]+\$

Required: Yes

updatedDate

The date when the project was last updated, in UNIX epoch time format. If the project was not updated, then `createdDate` and `updatedDate` are the same.

Type: Timestamp

Required: Yes

arn

The ARN of the project.

Type: String

Pattern: ^arn:aws:iot1click:[A-Za-z0-9_/-]{0,63}:\d+:projects/[0-9A-Za-z_-]{1,128}\$

Required: No

tags

The tags (metadata key/value pairs) associated with the project.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z+-=._:/]+$`

Value Length Constraints: Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request").

The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request is expired

HTTP Status Code: 403

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 403

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

MalformedHttpRequestException

Problems with the request at the HTTP level, e.g. we can't decompress the body according to the decompression algorithm specified by the content-encoding.

HTTP Status Code: 400

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 401

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestAbortedException

Convenient exception that can be used when a request is aborted before a reply is sent back (e.g. client closed connection).

HTTP Status Code: 400

RequestEntityTooLargeException

Problems with the request at the HTTP level. The request entity is too large.

HTTP Status Code: 413

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

RequestTimeoutException

Problems with the request at the HTTP level. Reading the Request timed out.

HTTP Status Code: 408

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

UnrecognizedClientException

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

UnknownOperationException

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 404

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400