



API Reference

# AWS Mainframe Modernization



**API Version 2021-04-28**

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

# AWS Mainframe Modernization: API Reference

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

---

# Table of Contents

<b>Welcome</b> .....	<b>1</b>
<b>Actions</b> .....	<b>2</b>
<b>CancelBatchJobExecution</b> .....	<b>4</b>
Request Syntax .....	4
URI Request Parameters .....	4
Request Body .....	4
Response Syntax .....	4
Response Elements .....	4
Errors .....	5
See Also .....	5
<b>CreateApplication</b> .....	<b>7</b>
Request Syntax .....	7
URI Request Parameters .....	7
Request Body .....	7
Response Syntax .....	9
Response Elements .....	10
Errors .....	10
See Also .....	11
<b>CreateDataSetImportTask</b> .....	<b>13</b>
Request Syntax .....	13
URI Request Parameters .....	13
Request Body .....	13
Response Syntax .....	14
Response Elements .....	14
Errors .....	14
See Also .....	15
<b>CreateDeployment</b> .....	<b>17</b>
Request Syntax .....	17
URI Request Parameters .....	17
Request Body .....	17
Response Syntax .....	18
Response Elements .....	18
Errors .....	19
See Also .....	20

CreateEnvironment .....	21
Request Syntax .....	21
URI Request Parameters .....	21
Request Body .....	21
Response Syntax .....	25
Response Elements .....	25
Errors .....	25
See Also .....	26
DeleteApplication .....	27
Request Syntax .....	27
URI Request Parameters .....	27
Request Body .....	27
Response Syntax .....	27
Response Elements .....	27
Errors .....	27
See Also .....	28
DeleteApplicationFromEnvironment .....	29
Request Syntax .....	29
URI Request Parameters .....	29
Request Body .....	29
Response Syntax .....	29
Response Elements .....	30
Errors .....	30
See Also .....	31
DeleteEnvironment .....	32
Request Syntax .....	32
URI Request Parameters .....	32
Request Body .....	32
Response Syntax .....	32
Response Elements .....	32
Errors .....	32
See Also .....	33
GetApplication .....	34
Request Syntax .....	34
URI Request Parameters .....	34
Request Body .....	34

Response Syntax .....	34
Response Elements .....	35
Errors .....	39
See Also .....	40
<b>GetApplicationVersion .....</b>	<b>41</b>
Request Syntax .....	41
URI Request Parameters .....	41
Request Body .....	41
Response Syntax .....	41
Response Elements .....	42
Errors .....	43
See Also .....	44
<b>GetBatchJobExecution .....</b>	<b>45</b>
Request Syntax .....	45
URI Request Parameters .....	45
Request Body .....	45
Response Syntax .....	45
Response Elements .....	46
Errors .....	48
See Also .....	49
<b>GetDataSetDetails .....</b>	<b>50</b>
Request Syntax .....	50
URI Request Parameters .....	50
Request Body .....	50
Response Syntax .....	50
Response Elements .....	51
Errors .....	52
See Also .....	53
<b>GetDataSetImportTask .....</b>	<b>55</b>
Request Syntax .....	55
URI Request Parameters .....	55
Request Body .....	55
Response Syntax .....	55
Response Elements .....	56
Errors .....	56
See Also .....	57

GetDeployment .....	58
Request Syntax .....	58
URI Request Parameters .....	58
Request Body .....	58
Response Syntax .....	58
Response Elements .....	59
Errors .....	60
See Also .....	61
GetEnvironment .....	62
Request Syntax .....	62
URI Request Parameters .....	62
Request Body .....	62
Response Syntax .....	62
Response Elements .....	63
Errors .....	67
See Also .....	68
GetSignedBluinsightsUrl .....	69
Request Syntax .....	69
URI Request Parameters .....	69
Request Body .....	69
Response Syntax .....	69
Response Elements .....	69
Errors .....	69
See Also .....	70
ListApplications .....	71
Request Syntax .....	71
URI Request Parameters .....	71
Request Body .....	72
Response Syntax .....	72
Response Elements .....	72
Errors .....	73
See Also .....	73
ListApplicationVersions .....	75
Request Syntax .....	75
URI Request Parameters .....	75
Request Body .....	75

Response Syntax .....	75
Response Elements .....	76
Errors .....	76
See Also .....	77
ListBatchJobDefinitions .....	78
Request Syntax .....	78
URI Request Parameters .....	78
Request Body .....	78
Response Syntax .....	79
Response Elements .....	79
Errors .....	79
See Also .....	80
ListBatchJobExecutions .....	81
Request Syntax .....	81
URI Request Parameters .....	81
Request Body .....	82
Response Syntax .....	82
Response Elements .....	83
Errors .....	83
See Also .....	84
ListBatchJobRestartPoints .....	85
Request Syntax .....	85
URI Request Parameters .....	85
Request Body .....	85
Response Syntax .....	85
Response Elements .....	86
Errors .....	86
See Also .....	87
ListDataSetImportHistory .....	88
Request Syntax .....	88
URI Request Parameters .....	88
Request Body .....	88
Response Syntax .....	88
Response Elements .....	89
Errors .....	89
See Also .....	90

ListDataSets .....	92
Request Syntax .....	92
URI Request Parameters .....	92
Request Body .....	93
Response Syntax .....	93
Response Elements .....	93
Errors .....	94
See Also .....	95
ListDeployments .....	96
Request Syntax .....	96
URI Request Parameters .....	96
Request Body .....	96
Response Syntax .....	96
Response Elements .....	97
Errors .....	97
See Also .....	98
ListEngineVersions .....	100
Request Syntax .....	100
URI Request Parameters .....	100
Request Body .....	100
Response Syntax .....	100
Response Elements .....	101
Errors .....	101
See Also .....	102
ListEnvironments .....	103
Request Syntax .....	103
URI Request Parameters .....	103
Request Body .....	103
Response Syntax .....	104
Response Elements .....	104
Errors .....	105
See Also .....	105
ListTagsForResource .....	107
Request Syntax .....	107
URI Request Parameters .....	107
Request Body .....	107



Response Syntax .....	107
Response Elements .....	107
Errors .....	108
See Also .....	109
<b>StartApplication</b> .....	<b>110</b>
Request Syntax .....	110
URI Request Parameters .....	110
Request Body .....	110
Response Syntax .....	110
Response Elements .....	110
Errors .....	110
See Also .....	111
<b>StartBatchJob</b> .....	<b>113</b>
Request Syntax .....	113
URI Request Parameters .....	113
Request Body .....	113
Response Syntax .....	114
Response Elements .....	114
Errors .....	115
See Also .....	115
<b>StopApplication</b> .....	<b>117</b>
Request Syntax .....	117
URI Request Parameters .....	117
Request Body .....	117
Response Syntax .....	118
Response Elements .....	118
Errors .....	118
See Also .....	119
<b>TagResource</b> .....	<b>120</b>
Request Syntax .....	120
URI Request Parameters .....	120
Request Body .....	120
Response Syntax .....	121
Response Elements .....	121
Errors .....	121
See Also .....	122

UntagResource .....	123
Request Syntax .....	123
URI Request Parameters .....	123
Request Body .....	123
Response Syntax .....	123
Response Elements .....	124
Errors .....	124
See Also .....	124
UpdateApplication .....	126
Request Syntax .....	126
URI Request Parameters .....	126
Request Body .....	126
Response Syntax .....	127
Response Elements .....	127
Errors .....	128
See Also .....	128
UpdateEnvironment .....	130
Request Syntax .....	130
URI Request Parameters .....	130
Request Body .....	130
Response Syntax .....	132
Response Elements .....	132
Errors .....	132
See Also .....	133
<b>Data Types .....</b>	<b>135</b>
AlternateKey .....	137
Contents .....	137
See Also .....	137
ApplicationSummary .....	139
Contents .....	139
See Also .....	142
ApplicationVersionSummary .....	143
Contents .....	143
See Also .....	143
BatchJobDefinition .....	145
Contents .....	145

See Also .....	145
BatchJobExecutionSummary .....	146
Contents .....	146
See Also .....	148
BatchJobIdentifier .....	149
Contents .....	149
See Also .....	150
DataSet .....	151
Contents .....	151
See Also .....	152
DatasetDetailOrgAttributes .....	153
Contents .....	153
See Also .....	154
DataSetImportConfig .....	155
Contents .....	155
See Also .....	155
DataSetImportItem .....	157
Contents .....	157
See Also .....	157
DataSetImportSummary .....	158
Contents .....	158
See Also .....	159
DataSetImportTask .....	160
Contents .....	160
See Also .....	160
DatasetOrgAttributes .....	162
Contents .....	162
See Also .....	163
DataSetSummary .....	164
Contents .....	164
See Also .....	165
Definition .....	166
Contents .....	166
See Also .....	166
DeployedVersionSummary .....	168
Contents .....	168

See Also .....	168
DeploymentSummary .....	170
Contents .....	170
See Also .....	171
EfsStorageConfiguration .....	172
Contents .....	172
See Also .....	172
EngineVersionsSummary .....	173
Contents .....	173
See Also .....	173
EnvironmentSummary .....	174
Contents .....	174
See Also .....	175
ExternalLocation .....	177
Contents .....	177
See Also .....	177
FileBatchJobDefinition .....	178
Contents .....	178
See Also .....	178
FileBatchJobIdentifier .....	179
Contents .....	179
See Also .....	179
FsxStorageConfiguration .....	180
Contents .....	180
See Also .....	180
GdgAttributes .....	181
Contents .....	181
See Also .....	181
GdgDetailAttributes .....	182
Contents .....	182
See Also .....	182
HighAvailabilityConfig .....	183
Contents .....	183
See Also .....	183
JobIdentifier .....	184
Contents .....	184

See Also .....	184
JobStep .....	185
Contents .....	185
See Also .....	186
JobStepRestartMarker .....	187
Contents .....	187
See Also .....	187
LogGroupSummary .....	189
Contents .....	189
See Also .....	189
MaintenanceSchedule .....	190
Contents .....	190
See Also .....	190
PendingMaintenance .....	191
Contents .....	191
See Also .....	191
PoAttributes .....	192
Contents .....	192
See Also .....	192
PoDetailAttributes .....	194
Contents .....	194
See Also .....	194
PrimaryKey .....	195
Contents .....	195
See Also .....	195
PsAttributes .....	196
Contents .....	196
See Also .....	196
PsDetailAttributes .....	197
Contents .....	197
See Also .....	197
RecordLength .....	198
Contents .....	198
See Also .....	198
RestartBatchJobIdentifier .....	199
Contents .....	199

---

See Also .....	199
S3BatchJobIdentifier .....	200
Contents .....	200
See Also .....	200
ScriptBatchJobDefinition .....	202
Contents .....	202
See Also .....	202
ScriptBatchJobIdentifier .....	203
Contents .....	203
See Also .....	203
StorageConfiguration .....	204
Contents .....	204
See Also .....	204
ValidationExceptionField .....	205
Contents .....	205
See Also .....	205
VsamAttributes .....	206
Contents .....	206
See Also .....	207
VsamDetailAttributes .....	208
Contents .....	208
See Also .....	209
<b>Common Parameters .....</b>	<b>210</b>
<b>Common Errors .....</b>	<b>213</b>

# Welcome

AWS Mainframe Modernization provides tools and resources to help you plan and implement migration and modernization from mainframes to AWS managed runtime environments. It provides tools for analyzing existing mainframe applications, developing or updating mainframe applications using COBOL or PL/I, and implementing an automated pipeline for continuous integration and continuous delivery (CI/CD) of the applications.

This document was last published on July 4, 2024.

# Actions

The following actions are supported:

- [CancelBatchJobExecution](#)
- [CreateApplication](#)
- [CreateDataSetImportTask](#)
- [CreateDeployment](#)
- [CreateEnvironment](#)
- [DeleteApplication](#)
- [DeleteApplicationFromEnvironment](#)
- [DeleteEnvironment](#)
- [GetApplication](#)
- [GetApplicationVersion](#)
- [GetBatchJobExecution](#)
- [GetDataSetDetails](#)
- [GetDataSetImportTask](#)
- [GetDeployment](#)
- [GetEnvironment](#)
- [GetSignedBluinsightsUrl](#)
- [ListApplications](#)
- [ListApplicationVersions](#)
- [ListBatchJobDefinitions](#)
- [ListBatchJobExecutions](#)
- [ListBatchJobRestartPoints](#)
- [ListDataSetImportHistory](#)
- [ListDataSets](#)
- [ListDeployments](#)
- [ListEngineVersions](#)
- [ListEnvironments](#)
- [ListTagsForResource](#)



- [StartApplication](#)
- [StartBatchJob](#)
- [StopApplication](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateApplication](#)
- [UpdateEnvironment](#)

# CancelBatchJobExecution

Cancels the running of a specific batch job execution.

## Request Syntax

```
POST /applications/applicationId/batch-job-executions/executionId/cancel HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### applicationId

The unique identifier of the application.

Pattern:  $^{\wedge}\backslash S\{1,80\}\$$

Required: Yes

### executionId

The unique identifier of the batch job execution.

Pattern:  $^{\wedge}\backslash S\{1,80\}\$$

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### **ConflictException**

The parameters provided in the request conflict with existing resources.

HTTP Status Code: 409

### **InternalServerErrorException**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### **ResourceNotFoundException**

The specified resource was not found.

HTTP Status Code: 404

### **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

### **ValidationException**

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateApplication

Creates a new application with given parameters. Requires an existing runtime environment and application definition file.

## Request Syntax

```
POST /applications HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "definition": { ... },
  "description": "string",
  "engineType": "string",
  "kmsKeyId": "string",
  "name": "string",
  "roleArn": "string",
  "tags": {
    "string" : "string"
  }
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### clientToken

Unique, case-sensitive identifier the service generates to ensure the idempotency of the request to create an application. The service generates the clientToken when the API call is triggered. The token expires after one hour, so if you retry the API within this timeframe with the same clientToken, you will get the same response. The service also handles deleting the clientToken after it expires.

Type: String

Required: No

### definition

The application definition for this application. You can specify either inline JSON or an S3 bucket location.

Type: [Definition](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

### description

The description of the application.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

### engineType

The type of the target platform for this application.

Type: String

Valid Values: `microfocus` | `bluage`

Required: Yes

### kmsKeyId

The identifier of a customer managed key.

Type: String

Required: No

### name

The unique identifier of the application.

Type: String

Pattern: `^[A-Za-z0-9][A-Za-z0-9_\-]{1,59}$`

Required: Yes

### roleArn

The Amazon Resource Name (ARN) that identifies a role that the application uses to access AWS resources that are not part of the application or are in a different AWS account.

Type: String

Pattern: `^arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]|):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+=@.-]{0,1023}$`

Required: No

### tags

A list of tags to apply to the application.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:).+$`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "applicationArn": "string",
  "applicationId": "string",
  "applicationVersion": number
```

```
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### applicationArn

The Amazon Resource Name (ARN) of the application.

Type: String

Pattern: `^arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]|):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+=@.-]{0,1023}$`

### applicationId

The unique application identifier.

Type: String

Pattern: `^\S{1,80}$`

### applicationVersion

The version number of the application.

Type: Integer

Valid Range: Minimum value of 1.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403



## **ConflictException**

The parameters provided in the request conflict with existing resources.

HTTP Status Code: 409

## **InternalServerErrorException**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

## **ServiceQuotaExceededException**

One or more quotas for AWS Mainframe Modernization exceeds the limit.

HTTP Status Code: 402

## **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

## **ValidationException**

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateDataSetImportTask

Starts a data set import task for a specific application.

## Request Syntax

```
POST /applications/applicationId/dataset-import-task HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "importConfig": { ... }
}
```

## URI Request Parameters

The request uses the following URI parameters.

### applicationId

The unique identifier of the application for which you want to import data sets.

Pattern: `^\S{1,80}$`

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### clientToken

Unique, case-sensitive identifier you provide to ensure the idempotency of the request to create a data set import. The service generates the `clientToken` when the API call is triggered. The token expires after one hour, so if you retry the API within this timeframe with the same `clientToken`, you will get the same response. The service also handles deleting the `clientToken` after it expires.

Type: String

Required: No

## importConfig

The data set import task configuration.

Type: [DataSetImportConfig](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "taskId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### taskId

The task identifier. This operation is asynchronous. Use this identifier with the [GetDataSetImportTask](#) operation to obtain the status of this task.

Type: String

Pattern: `^\S{1,80}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### **ConflictException**

The parameters provided in the request conflict with existing resources.

HTTP Status Code: 409

### **InternalServerErrorException**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### **ResourceNotFoundException**

The specified resource was not found.

HTTP Status Code: 404

### **ServiceQuotaExceededException**

One or more quotas for AWS Mainframe Modernization exceeds the limit.

HTTP Status Code: 402

### **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

### **ValidationException**

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateDeployment

Creates and starts a deployment to deploy an application into a runtime environment.

## Request Syntax

```
POST /applications/applicationId/deployments HTTP/1.1
Content-type: application/json
```

```
{
  "applicationVersion": number,
  "clientToken": "string",
  "environmentId": "string"
}
```

## URI Request Parameters

The request uses the following URI parameters.

### applicationId

The application identifier.

Pattern:  $^{\backslash}S\{1, 80\}$

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### applicationVersion

The version of the application to deploy.

Type: Integer

Valid Range: Minimum value of 1.

Required: Yes

## clientToken

Unique, case-sensitive identifier you provide to ensure the idempotency of the request to create a deployment. The service generates the clientToken when the API call is triggered. The token expires after one hour, so if you retry the API within this timeframe with the same clientToken, you will get the same response. The service also handles deleting the clientToken after it expires.

Type: String

Required: No

## environmentId

The identifier of the runtime environment where you want to deploy this application.

Type: String

Pattern: `^\S{1,80}$`

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "deploymentId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### deploymentId

The unique identifier of the deployment.

Type: String



Pattern: `^\S{1,80}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### **ConflictException**

The parameters provided in the request conflict with existing resources.

HTTP Status Code: 409

### **InternalServerErrorException**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### **ResourceNotFoundException**

The specified resource was not found.

HTTP Status Code: 404

### **ServiceQuotaExceededException**

One or more quotas for AWS Mainframe Modernization exceeds the limit.

HTTP Status Code: 402

### **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

### **ValidationException**

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateEnvironment

Creates a runtime environment for a given runtime engine.

## Request Syntax

```
POST /environments HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "description": "string",
  "engineType": "string",
  "engineVersion": "string",
  "highAvailabilityConfig": {
    "desiredCapacity": number
  },
  "instanceType": "string",
  "kmsKeyId": "string",
  "name": "string",
  "preferredMaintenanceWindow": "string",
  "publiclyAccessible": boolean,
  "securityGroupIds": [ "string" ],
  "storageConfigurations": [
    { ... }
  ],
  "subnetIds": [ "string" ],
  "tags": {
    "string" : "string"
  }
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

## clientToken

Unique, case-sensitive identifier you provide to ensure the idempotency of the request to create an environment. The service generates the clientToken when the API call is triggered. The token expires after one hour, so if you retry the API within this timeframe with the same clientToken, you will get the same response. The service also handles deleting the clientToken after it expires.

Type: String

Required: No

## description

The description of the runtime environment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

## engineType

The engine type for the runtime environment.

Type: String

Valid Values: microfocus | bluage

Required: Yes

## engineVersion

The version of the engine type for the runtime environment.

Type: String

Pattern:  $^{\wedge}\S\{1,10\}\$$

Required: No

## highAvailabilityConfig

The details of a high availability configuration for this runtime environment.

Type: [HighAvailabilityConfig](#) object

Required: No

### [instanceType](#)

The type of instance for the runtime environment.

Type: String

Pattern: `^\S{1,20}$`

Required: Yes

### [kmsKeyId](#)

The identifier of a customer managed key.

Type: String

Required: No

### [name](#)

The name of the runtime environment. Must be unique within the account.

Type: String

Pattern: `^[A-Za-z0-9][A-Za-z0-9_\-]{1,59}$`

Required: Yes

### [preferredMaintenanceWindow](#)

Configures the maintenance window that you want for the runtime environment. The maintenance window must have the format `ddd:hh24:mi-ddd:hh24:mi` and must be less than 24 hours. The following two examples are valid maintenance windows: `sun:23:45-mon:00:15` or `sat:01:00-sat:03:00`.

If you do not provide a value, a random system-generated value will be assigned.

Type: String

Pattern: `^\S{1,50}$`

Required: No

### publiclyAccessible

Specifies whether the runtime environment is publicly accessible.

Type: Boolean

Required: No

### securityGroupIds

The list of security groups for the VPC associated with this runtime environment.

Type: Array of strings

Pattern:  $^{\backslash}S\{1, 50\}\$$

Required: No

### storageConfigurations

Optional. The storage configurations for this runtime environment.

Type: Array of [StorageConfiguration](#) objects

Required: No

### subnetIds

The list of subnets associated with the VPC for this runtime environment.

Type: Array of strings

Pattern:  $^{\backslash}S\{1, 50\}\$$

Required: No

### tags

The tags for the runtime environment.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern:  $^{\backslash}(?!aws:)\.+\$$

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "environmentId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [environmentId](#)

The unique identifier of the runtime environment.

Type: String

Pattern: `^\S{1,80}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### **ConflictException**

The parameters provided in the request conflict with existing resources.

HTTP Status Code: 409

## InternalServerErrorException

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

## ServiceQuotaExceededException

One or more quotas for AWS Mainframe Modernization exceeds the limit.

HTTP Status Code: 402

## ThrottlingException

The number of requests made exceeds the limit.

HTTP Status Code: 429

## ValidationException

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# DeleteApplication

Deletes a specific application. You cannot delete a running application.

## Request Syntax

```
DELETE /applications/applicationId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### applicationId

The unique identifier of the application you want to delete.

Pattern: `^\S{1,80}$`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### **ConflictException**

The parameters provided in the request conflict with existing resources.

HTTP Status Code: 409

### **InternalServerErrorException**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

### **ValidationException**

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteApplicationFromEnvironment

Deletes a specific application from the specific runtime environment where it was previously deployed. You cannot delete a runtime environment using DeleteEnvironment if any application has ever been deployed to it. This API removes the association of the application with the runtime environment so you can delete the environment smoothly.

## Request Syntax

```
DELETE /applications/applicationId/environment/environmentId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### applicationId

The unique identifier of the application you want to delete.

Pattern: `^\S{1,80}$`

Required: Yes

### environmentId

The unique identifier of the runtime environment where the application was previously deployed.

Pattern: `^\S{1,80}$`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### **ConflictException**

The parameters provided in the request conflict with existing resources.

HTTP Status Code: 409

### **InternalServerError**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### **ResourceNotFoundException**

The specified resource was not found.

HTTP Status Code: 404

### **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

### **ValidationException**

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteEnvironment

Deletes a specific runtime environment. The environment cannot contain deployed applications. If it does, you must delete those applications before you delete the environment.

## Request Syntax

```
DELETE /environments/environmentId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### environmentId

The unique identifier of the runtime environment you want to delete.

Pattern: `^\S{1,80}$`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### **ConflictException**

The parameters provided in the request conflict with existing resources.

HTTP Status Code: 409

### **InternalServerErrorException**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

### **ValidationException**

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetApplication

Describes the details of a specific application.

## Request Syntax

```
GET /applications/applicationId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### applicationId

The identifier of the application.

Pattern: `^\S{1,80}$`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "applicationArn": "string",
  "applicationId": "string",
  "creationTime": number,
  "deployedVersion": {
    "applicationVersion": number,
    "status": "string",
    "statusReason": "string"
  },
  "description": "string",
  "engineType": "string",
```



```

"environmentId": "string",
"kmsKeyId": "string",
"lastStartTime": number,
"latestVersion": {
  "applicationVersion": number,
  "creationTime": number,
  "status": "string",
  "statusReason": "string"
},
"listenerArns": [ "string" ],
"listenerPorts": [ number ],
"loadBalancerDnsName": "string",
"logGroups": [
  {
    "logGroupName": "string",
    "logType": "string"
  }
],
"name": "string",
"roleArn": "string",
"status": "string",
"statusReason": "string",
"tags": {
  "string" : "string"
},
"targetGroupArns": [ "string" ]
}

```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### applicationArn

The Amazon Resource Name (ARN) of the application.

Type: String

Pattern: `^arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]|):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+=@.-]{0,1023}$`

### applicationId

The identifier of the application.

Type: String

Pattern: `^\S{1,80}$`

### creationTime

The timestamp when this application was created.

Type: Timestamp

### deployedVersion

The version of the application that is deployed.

Type: [DeployedVersionSummary](#) object

### description

The description of the application.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

### engineType

The type of the target platform for the application.

Type: String

Valid Values: `microfocus` | `bluage`

### environmentId

The identifier of the runtime environment where you want to deploy the application.

Type: String

Pattern: `^\S{1,80}$`

### kmsKeyId

The identifier of a customer managed key.

Type: String

### lastStartTime

The timestamp when you last started the application. Null until the application runs for the first time.

Type: Timestamp

### latestVersion

The latest version of the application.

Type: [ApplicationVersionSummary](#) object

### listenerArns

The Amazon Resource Name (ARN) for the network load balancer listener created in your AWS account. AWS Mainframe Modernization creates this listener for you the first time you deploy an application.

Type: Array of strings

Array Members: Minimum number of 1 item.

Pattern: `^arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]|):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+=@.-]{0,1023}$`

### listenerPorts

The port associated with the network load balancer listener created in your AWS account.

Type: Array of integers

Array Members: Minimum number of 1 item.

### loadBalancerDnsName

The public DNS name of the load balancer created in your AWS account.

Type: String

Pattern: `^\S{1,100}$`

## logGroups

The list of log summaries. Each log summary includes the log type as well as the log group identifier. These are CloudWatch logs. AWS Mainframe Modernization pushes the application log to CloudWatch under the customer's account.

Type: Array of [LogGroupSummary](#) objects

### name

The unique identifier of the application.

Type: String

Pattern: `^[A-Za-z0-9][A-Za-z0-9_\-]{1,59}$`

### roleArn

The Amazon Resource Name (ARN) of the role associated with the application.

Type: String

Pattern: `^arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]|):[0-9]{12}:[A-Za-z0-9/] [A-Za-z0-9:_/+ =, @. -]{0,1023}$`

### status

The status of the application.

Type: String

Valid Values: `Creating | Created | Available | Ready | Starting | Running | Stopping | Stopped | Failed | Deleting | Deleting From Environment`

### statusReason

The reason for the reported status.

Type: String

### tags

A list of tags associated with the application.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:).+$`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

### targetGroupArns

Returns the Amazon Resource Names (ARNs) of the target groups that are attached to the network load balancer.

Type: Array of strings

Array Members: Minimum number of 1 item.

Pattern: `^arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]|):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+=@.-]{0,1023}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### **InternalServerErrorException**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### **ResourceNotFoundException**

The specified resource was not found.

HTTP Status Code: 404

### **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

## ValidationException

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetApplicationVersion

Returns details about a specific version of a specific application.

## Request Syntax

```
GET /applications/applicationId/versions/applicationVersion HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### applicationId

The unique identifier of the application.

Pattern: `^\S{1,80}$`

Required: Yes

### applicationVersion

The specific version of the application.

Valid Range: Minimum value of 1.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "applicationVersion": number,
  "creationTime": number,
  "definitionContent": "string",
```

```
"description": "string",  
"name": "string",  
"status": "string",  
"statusReason": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### applicationVersion

The specific version of the application.

Type: Integer

Valid Range: Minimum value of 1.

### creationTime

The timestamp when the application version was created.

Type: Timestamp

### definitionContent

The content of the application definition. This is a JSON object that contains the resource configuration and definitions that identify an application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65000.

### description

The application description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

### name

The name of the application version.



Type: String

Pattern: `^[A-Za-z0-9][A-Za-z0-9_\-]{1,59}$`

### status

The status of the application version.

Type: String

Valid Values: `Creating` | `Available` | `Failed`

### statusReason

The reason for the reported status.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### **InternalServerErrorException**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### **ResourceNotFoundException**

The specified resource was not found.

HTTP Status Code: 404

### **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

## ValidationException

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetBatchJobExecution

Gets the details of a specific batch job execution for a specific application.

## Request Syntax

```
GET /applications/applicationId/batch-job-executions/executionId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### applicationId

The identifier of the application.

Pattern: `^\S{1,80}$`

Required: Yes

### executionId

The unique identifier of the batch job execution.

Pattern: `^\S{1,80}$`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "applicationId": string,
  "batchJobIdentifier": { ... },
  "endTime": number,
```

```
"executionId": "string",
"jobId": "string",
"jobName": "string",
"jobStepRestartMarker": {
  "fromProcStep": "string",
  "fromStep": "string",
  "toProcStep": "string",
  "toStep": "string"
},
"jobType": "string",
"jobUser": "string",
"returnCode": "string",
"startTime": number,
"status": "string",
"statusReason": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### applicationId

The identifier of the application.

Type: String

Pattern: `^\S{1,80}$`

### batchJobIdentifier

The unique identifier of this batch job.

Type: [BatchJobIdentifier](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

### endTime

The timestamp when the batch job execution ended.

Type: Timestamp

### executionId

The unique identifier for this batch job execution.

Type: String

Pattern: `^\S{1,80}$`

### jobId

The unique identifier for this batch job.

Type: String

Pattern: `^\S{1,100}$`

### jobName

The name of this batch job.

Type: String

Pattern: `^\S{1,100}$`

### jobStepRestartMarker

The step/procedure step information for the restart batch job operation.

Type: [JobStepRestartMarker](#) object

### jobType

The type of job.

Type: String

Valid Values: VSE | JES2 | JES3

### jobUser

The user for the job.

Type: String

Pattern: `^\S{1,100}$`

## returnCode

The batch job return code from either the Blu Age or Micro Focus runtime engines. For more information, see [Batch return codes](#) in the *IBM WebSphere Application Server* documentation.

Type: String

## startTime

The timestamp when the batch job execution started.

Type: Timestamp

## status

The status of the batch job execution.

Type: String

Valid Values: Submitting | Holding | Dispatching | Running | Cancelling | Cancelled | Succeeded | Failed | Purged | Succeeded With Warning

## statusReason

The reason for the reported status.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### **InternalServerError**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

## ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 404

## ThrottlingException

The number of requests made exceeds the limit.

HTTP Status Code: 429

## ValidationException

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetDataSetDetails

Gets the details of a specific data set.

## Request Syntax

```
GET /applications/applicationId/datasets/dataSetName HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### applicationId

The unique identifier of the application that this data set is associated with.

Pattern: `^\S{1,80}$`

Required: Yes

### dataSetName

The name of the data set.

Pattern: `^\S{1,200}$`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "blocksize": number,
  "creationTime": number,
  "dataSetName": "string",
```



```
"dataSetOrg": { ... },  
"fileSize": number,  
"lastReferencedTime": number,  
"lastUpdatedTime": number,  
"location": "string",  
"recordLength": number  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### blocksize

The size of the block on disk.

Type: Integer

### creationTime

The timestamp when the data set was created.

Type: Timestamp

### dataSetName

The name of the data set.

Type: String

Pattern: `^\S{1,200}$`

### dataSetOrg

The type of data set. The only supported value is VSAM.

Type: [DatasetDetailOrgAttributes](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

### fileSize

File size of the dataset.

Type: Long

### lastReferencedTime

The last time the data set was referenced.

Type: Timestamp

### lastUpdatedTime

The last time the data set was updated.

Type: Timestamp

### location

The location where the data set is stored.

Type: String

Pattern: `^\S{1,2000}$`

### recordLength

The length of records in the data set.

Type: Integer

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### **ConflictException**

The parameters provided in the request conflict with existing resources.

HTTP Status Code: 409

### **ExecutionTimeoutException**

Failed to connect to server, or didn't receive response within expected time period.

HTTP Status Code: 504

### **InternalServerErrorException**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### **ResourceNotFoundException**

The specified resource was not found.

HTTP Status Code: 404

### **ServiceUnavailableException**

Server cannot process the request at the moment.

HTTP Status Code: 503

### **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

### **ValidationException**

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetDataSetImportTask

Gets the status of a data set import task initiated with the [CreateDataSetImportTask](#) operation.

## Request Syntax

```
GET /applications/applicationId/dataset-import-tasks/taskId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### [applicationId](#)

The application identifier.

Pattern: `^\S{1,80}$`

Required: Yes

### [taskId](#)

The task identifier returned by the [CreateDataSetImportTask](#) operation.

Pattern: `^\S{1,80}$`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "status": "string",
  "summary": {
    "failed": number,
```

```
    "inProgress": number,
    "pending": number,
    "succeeded": number,
    "total": number
  },
  "taskId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### status

The status of the task.

Type: String

Valid Values: Creating | Running | Completed | Failed

### summary

A summary of the status of the task.

Type: [DataSetImportSummary](#) object

### taskId

The task identifier.

Type: String

Pattern: `^\S{1,80}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### **InternalServerErrorException**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### **ResourceNotFoundException**

The specified resource was not found.

HTTP Status Code: 404

### **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

### **ValidationException**

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetDeployment

Gets details of a specific deployment with a given deployment identifier.

## Request Syntax

```
GET /applications/applicationId/deployments/deploymentId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### applicationId

The unique identifier of the application.

Pattern: `^\S{1,80}$`

Required: Yes

### deploymentId

The unique identifier for the deployment.

Pattern: `^\S{1,80}$`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "applicationId": string,
  "applicationVersion": number,
  "creationTime": number,
```



```
"deploymentId": "string",  
"environmentId": "string",  
"status": "string",  
"statusReason": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### applicationId

The unique identifier of the application.

Type: String

Pattern:  $^{\backslash}S\{1,80\}$

### applicationVersion

The application version.

Type: Integer

Valid Range: Minimum value of 1.

### creationTime

The timestamp when the deployment was created.

Type: Timestamp

### deploymentId

The unique identifier of the deployment.

Type: String

Pattern:  $^{\backslash}S\{1,80\}$

### environmentId

The unique identifier of the runtime environment.

Type: String

Pattern: `^\S{1,80}$`

### status

The status of the deployment.

Type: String

Valid Values: Deploying | Succeeded | Failed | Updating Deployment

### statusReason

The reason for the reported status.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### **InternalServerErrorException**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### **ResourceNotFoundException**

The specified resource was not found.

HTTP Status Code: 404

### **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

## ValidationException

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetEnvironment

Describes a specific runtime environment.

## Request Syntax

```
GET /environments/environmentId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### environmentId

The unique identifier of the runtime environment.

Pattern: `^\S{1,80}$`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "actualCapacity": number,
  "creationTime": number,
  "description": "string",
  "engineType": "string",
  "engineVersion": "string",
  "environmentArn": "string",
  "environmentId": "string",
  "highAvailabilityConfig": {
    "desiredCapacity": number
  },
}
```

```
"instanceType": "string",
"kmsKeyId": "string",
"loadBalancerArn": "string",
"name": "string",
"pendingMaintenance": {
  "engineVersion": "string",
  "schedule": {
    "endTime": number,
    "startTime": number
  }
},
"preferredMaintenanceWindow": "string",
"publiclyAccessible": boolean,
"securityGroupIds": [ "string" ],
"status": "string",
"statusReason": "string",
"storageConfigurations": [
  { ... }
],
"subnetIds": [ "string" ],
"tags": {
  "string" : "string"
},
"vpcId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### actualCapacity

The number of instances included in the runtime environment. A standalone runtime environment has a maximum of one instance. Currently, a high availability runtime environment has a maximum of two instances.

Type: Integer

### creationTime

The timestamp when the runtime environment was created.

Type: Timestamp

### description

The description of the runtime environment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

### engineType

The target platform for the runtime environment.

Type: String

Valid Values: microfocus | bluage

### engineVersion

The version of the runtime engine.

Type: String

Pattern: `^\S{1,10}$`

### environmentArn

The Amazon Resource Name (ARN) of the runtime environment.

Type: String

Pattern: `^arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]|):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+=@.-]{0,1023}$`

### environmentId

The unique identifier of the runtime environment.

Type: String

Pattern: `^\S{1,80}$`

### highAvailabilityConfig

The desired capacity of the high availability configuration for the runtime environment.

Type: [HighAvailabilityConfig](#) object

### [instanceType](#)

The type of instance underlying the runtime environment.

Type: String

Pattern: `^\S{1,20}$`

### [kmsKeyId](#)

The identifier of a customer managed key.

Type: String

### [loadBalancerArn](#)

The Amazon Resource Name (ARN) for the load balancer used with the runtime environment.

Type: String

### [name](#)

The name of the runtime environment. Must be unique within the account.

Type: String

Pattern: `^[A-Za-z0-9][A-Za-z0-9_\-]{1,59}$`

### [pendingMaintenance](#)

Indicates the pending maintenance scheduled on this environment.

Type: [PendingMaintenance](#) object

### [preferredMaintenanceWindow](#)

The maintenance window for the runtime environment. If you don't provide a value for the maintenance window, the service assigns a random value.

Type: String

Pattern: `^\S{1,50}$`

### [publiclyAccessible](#)

Whether applications running in this runtime environment are publicly accessible.

Type: Boolean

### securityGroupIds

The unique identifiers of the security groups assigned to this runtime environment.

Type: Array of strings

Pattern: `^\S{1,50}$`

### status

The status of the runtime environment. If the M2 environment is missing a connection to the customer owned dependent resource, the status will be Unhealthy.

Type: String

Valid Values: Creating | Available | Updating | Deleting | Failed | UnHealthy

### statusReason

The reason for the reported status.

Type: String

### storageConfigurations

The storage configurations defined for the runtime environment.

Type: Array of [StorageConfiguration](#) objects

### subnetIds

The unique identifiers of the subnets assigned to this runtime environment.

Type: Array of strings

Pattern: `^\S{1,50}$`

### tags

The tags defined for this runtime environment.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.



Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:).+$`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

## vpcId

The unique identifier for the VPC used with this runtime environment.

Type: String

Pattern: `^\S{1,50}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### **InternalServerError**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### **ResourceNotFoundException**

The specified resource was not found.

HTTP Status Code: 404

### **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

### **ValidationException**

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetSignedBluinsightsUrl

Gets a single sign-on URL that can be used to connect to AWS Blu Insights.

## Request Syntax

```
GET /signed-bi-url HTTP/1.1
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "signedBiUrl": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [signedBiUrl](#)

Single sign-on AWS Blu Insights URL.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## AccessDeniedException

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

## InternalServerErrorException

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

## ThrottlingException

The number of requests made exceeds the limit.

HTTP Status Code: 429

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListApplications

Lists the applications associated with a specific AWS account. You can provide the unique identifier of a specific runtime environment in a query parameter to see all applications associated with that environment.

## Request Syntax

```
GET /applications?  
environmentId=environmentId&maxResults=maxResults&names=names&nextToken=nextToken  
HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### environmentId

The unique identifier of the runtime environment where the applications are deployed.

Pattern:  $^{\backslash}S\{1, 80\}\$$

### maxResults

The maximum number of applications to return.

Valid Range: Minimum value of 1. Maximum value of 2000.

### names

The names of the applications.

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Pattern:  $^{\backslash}[A-Za-z0-9][A-Za-z0-9\_\\-]\{1, 59\}\$$

### nextToken

A pagination token to control the number of applications displayed in the list.

Pattern:  $^{\backslash}S\{1, 2000\}\$$

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "applications": [
    {
      "applicationArn": "string",
      "applicationId": "string",
      "applicationVersion": number,
      "creationTime": number,
      "deploymentStatus": "string",
      "description": "string",
      "engineType": "string",
      "environmentId": "string",
      "lastStartTime": number,
      "name": "string",
      "roleArn": "string",
      "status": "string",
      "versionStatus": "string"
    }
  ],
  "nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [applications](#)

Returns a list of summary details for all the applications in a runtime environment.

Type: Array of [ApplicationSummary](#) objects

## **nextToken**

A pagination token that's returned when the response doesn't contain all applications.

Type: String

Pattern: `^\S{1,2000}$`

## **Errors**

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### **InternalServerErrorException**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

### **ValidationException**

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# ListApplicationVersions

Returns a list of the application versions for a specific application.

## Request Syntax

```
GET /applications/applicationId/versions?maxResults=maxResults&nextToken=nextToken  
HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### applicationId

The unique identifier of the application.

Pattern:  $^{\backslash}S\{1, 80\}$

Required: Yes

### maxResults

The maximum number of application versions to return.

Valid Range: Minimum value of 1. Maximum value of 2000.

### nextToken

A pagination token returned from a previous call to this operation. This specifies the next item to return. To return to the beginning of the list, exclude this parameter.

Pattern:  $^{\backslash}S\{1, 2000\}$

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "applicationVersions": [
    {
      "applicationVersion": number,
      "creationTime": number,
      "status": "string",
      "statusReason": "string"
    }
  ],
  "nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### applicationVersions

The list of application versions.

Type: Array of [ApplicationVersionSummary](#) objects

### nextToken

If there are more items to return, this contains a token that is passed to a subsequent call to this operation to retrieve the next set of items.

Type: String

Pattern: `^\S{1,2000}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### **InternalServerErrorException**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### **ResourceNotFoundException**

The specified resource was not found.

HTTP Status Code: 404

### **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

### **ValidationException**

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListBatchJobDefinitions

Lists all the available batch job definitions based on the batch job resources uploaded during the application creation. You can use the batch job definitions in the list to start a batch job.

## Request Syntax

```
GET /applications/applicationId/batch-job-definitions?  
maxResults=maxResults&nextToken=nextToken&prefix=prefix HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### applicationId

The identifier of the application.

Pattern:  $^{\backslash}S\{1,80\}$ \$

Required: Yes

### maxResults

The maximum number of batch job definitions to return.

Valid Range: Minimum value of 1. Maximum value of 2000.

### nextToken

A pagination token returned from a previous call to this operation. This specifies the next item to return. To return to the beginning of the list, exclude this parameter.

Pattern:  $^{\backslash}S\{1,2000\}$ \$

### prefix

If the batch job definition is a FileBatchJobDefinition, the prefix allows you to search on the file names of FileBatchJobDefinitions.

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "batchJobDefinitions": [
    { ... }
  ],
  "nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [batchJobDefinitions](#)

The list of batch job definitions.

Type: Array of [BatchJobDefinition](#) objects

### [nextToken](#)

If there are more items to return, this contains a token that is passed to a subsequent call to this operation to retrieve the next set of items.

Type: String

Pattern: `^\S{1,2000}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

## InternalServerErrorException

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

## ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 404

## ThrottlingException

The number of requests made exceeds the limit.

HTTP Status Code: 429

## ValidationException

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListBatchJobExecutions

Lists historical, current, and scheduled batch job executions for a specific application.

## Request Syntax

```
GET /applications/applicationId/batch-job-executions?  
executionIds=executionIds&jobName=jobName&maxResults=maxResults&nextToken=nextToken&startedAfter=startedAfter  
HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### applicationId

The unique identifier of the application.

Pattern:  $^{\backslash}S\{1,80\}$

Required: Yes

### executionIds

The unique identifier of each batch job execution.

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Pattern:  $^{\backslash}S\{1,80\}$

### jobName

The name of each batch job execution.

Pattern:  $^{\backslash}S\{1,100\}$

### maxResults

The maximum number of batch job executions to return.

Valid Range: Minimum value of 1. Maximum value of 2000.

### nextToken

A pagination token to control the number of batch job executions displayed in the list.

Pattern: `^\S{1,2000}$`

### startedAfter

The time after which the batch job executions started.

### startedBefore

The time before the batch job executions started.

### status

The status of the batch job executions.

Valid Values: Submitting | Holding | Dispatching | Running | Cancelling | Cancelled | Succeeded | Failed | Purged | Succeeded With Warning

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "batchJobExecutions": [
    {
      "applicationId": "string",
      "batchJobIdentifier": { ... },
      "endTime": number,
      "executionId": "string",
      "jobId": "string",
      "jobName": "string",
      "jobType": "string",
      "returnCode": "string",
      "startTime": number,
      "status": "string"
    }
  ],
  "nextToken": "string"
}
```



## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### batchJobExecutions

Returns a list of batch job executions for an application.

Type: Array of [BatchJobExecutionSummary](#) objects

### nextToken

A pagination token that's returned when the response doesn't contain all batch job executions.

Type: String

Pattern: `^\S{1,2000}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### **InternalServerErrorException**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### **ResourceNotFoundException**

The specified resource was not found.

HTTP Status Code: 404

### **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

## ValidationException

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListBatchJobRestartPoints

Lists all the job steps for a JCL file to restart a batch job. This is only applicable for Micro Focus engine with versions 8.0.6 and above.

## Request Syntax

```
GET /applications/applicationId/batch-job-executions/executionId/steps HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### applicationId

The unique identifier of the application.

Pattern: `^\S{1,80}$`

Required: Yes

### executionId

The unique identifier of the batch job execution.

Pattern: `^\S{1,80}$`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "batchJobSteps": [
    {
```

```
    "procStepName": "string",
    "procStepNumber": number,
    "stepCondCode": "string",
    "stepName": "string",
    "stepNumber": number,
    "stepRestartable": boolean
  }
]
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### batchJobSteps

Returns all the batch job steps and related information for a batch job that previously ran.

Type: Array of [JobStep](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### **ConflictException**

The parameters provided in the request conflict with existing resources.

HTTP Status Code: 409

### **InternalServerErrorException**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

## ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 404

## ThrottlingException

The number of requests made exceeds the limit.

HTTP Status Code: 429

## ValidationException

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListDataSetImportHistory

Lists the data set imports for the specified application.

## Request Syntax

```
GET /applications/applicationId/dataset-import-tasks?  
maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### applicationId

The unique identifier of the application.

Pattern:  $^{\wedge}\backslash S\{1,80\}\$$

Required: Yes

### maxResults

The maximum number of objects to return.

Valid Range: Minimum value of 1. Maximum value of 2000.

### nextToken

A pagination token returned from a previous call to this operation. This specifies the next item to return. To return to the beginning of the list, exclude this parameter.

Pattern:  $^{\wedge}\backslash S\{1,2000\}\$$

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{
  "dataSetImportTasks": [
    {
      "status": "string",
      "statusReason": "string",
      "summary": {
        "failed": number,
        "inProgress": number,
        "pending": number,
        "succeeded": number,
        "total": number
      },
      "taskId": "string"
    }
  ],
  "nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### dataSetImportTasks

The data set import tasks.

Type: Array of [DataSetImportTask](#) objects

### nextToken

If there are more items to return, this contains a token that is passed to a subsequent call to this operation to retrieve the next set of items.

Type: String

Pattern: `^\S{1,2000}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

## **InternalServerErrorException**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

## **ResourceNotFoundException**

The specified resource was not found.

HTTP Status Code: 404

## **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

## **ValidationException**

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)



- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListDataSets

Lists the data sets imported for a specific application. In AWS Mainframe Modernization, data sets are associated with applications deployed on runtime environments. This is known as importing data sets. Currently, AWS Mainframe Modernization can import data sets into catalogs using [CreateDataSetImportTask](#).

## Request Syntax

```
GET /applications/applicationId/datasets?  
maxResults=maxResults&nameFilter=nameFilter&nextToken=nextToken&prefix=prefix HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### [applicationId](#)

The unique identifier of the application for which you want to list the associated data sets.

Pattern:  $^{\backslash}S\{1, 80\}$

Required: Yes

### [maxResults](#)

The maximum number of objects to return.

Valid Range: Minimum value of 1. Maximum value of 2000.

### [nameFilter](#)

Filter dataset name matching the specified pattern. Can use \* and % as wild cards.

Pattern:  $^{\backslash}S\{1, 200\}$

### [nextToken](#)

A pagination token returned from a previous call to this operation. This specifies the next item to return. To return to the beginning of the list, exclude this parameter.

Pattern:  $^{\backslash}S\{1, 2000\}$

## [prefix](#)

The prefix of the data set name, which you can use to filter the list of data sets.

Pattern: `^\S{1,200}$`

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "dataSets": [
    {
      "creationTime": number,
      "dataSetName": "string",
      "dataSetOrg": "string",
      "format": "string",
      "lastReferencedTime": number,
      "lastUpdatedTime": number
    }
  ],
  "nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [dataSets](#)

The list of data sets, containing information including the creation time, the data set name, the data set organization, the data set format, and the last time the data set was referenced or updated.

Type: Array of [DataSetSummary](#) objects

## nextToken

If there are more items to return, this contains a token that is passed to a subsequent call to this operation to retrieve the next set of items.

Type: String

Pattern: `^\S{1,2000}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### **ConflictException**

The parameters provided in the request conflict with existing resources.

HTTP Status Code: 409

### **ExecutionTimeoutException**

Failed to connect to server, or didn't receive response within expected time period.

HTTP Status Code: 504

### **InternalServerException**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### **ResourceNotFoundException**

The specified resource was not found.

HTTP Status Code: 404

### **ServiceUnavailableException**

Server cannot process the request at the moment.

HTTP Status Code: 503

### **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

### **ValidationException**

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListDeployments

Returns a list of all deployments of a specific application. A deployment is a combination of a specific application and a specific version of that application. Each deployment is mapped to a particular application version.

## Request Syntax

```
GET /applications/applicationId/deployments?maxResults=maxResults&nextToken=nextToken
HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### applicationId

The application identifier.

Pattern:  $^{\backslash}S\{1,80\}$

Required: Yes

### maxResults

The maximum number of objects to return.

Valid Range: Minimum value of 1. Maximum value of 2000.

### nextToken

A pagination token returned from a previous call to this operation. This specifies the next item to return. To return to the beginning of the list, exclude this parameter.

Pattern:  $^{\backslash}S\{1,2000\}$

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "deployments": [
    {
      "applicationId": "string",
      "applicationVersion": number,
      "creationTime": number,
      "deploymentId": "string",
      "environmentId": "string",
      "status": "string",
      "statusReason": "string"
    }
  ],
  "nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### deployments

The list of deployments that is returned.

Type: Array of [DeploymentSummary](#) objects

### nextToken

If there are more items to return, this contains a token that is passed to a subsequent call to this operation to retrieve the next set of items.

Type: String

Pattern: `^\S{1,2000}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

## **InternalServerError**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

## **ResourceNotFoundException**

The specified resource was not found.

HTTP Status Code: 404

## **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

## **ValidationException**

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)



- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListEngineVersions

Lists the available engine versions.

## Request Syntax

```
GET /engine-versions?engineType=engineType&maxResults=maxResults&nextToken=nextToken
HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### engineType

The type of target platform.

Valid Values: microfocus | bluage

### maxResults

The maximum number of objects to return.

Valid Range: Minimum value of 1. Maximum value of 2000.

### nextToken

A pagination token returned from a previous call to this operation. This specifies the next item to return. To return to the beginning of the list, exclude this parameter.

Pattern:  $^{\backslash}S\{1,2000\}\$$

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"engineVersions": [  
  {  
    "engineType": "string",  
    "engineVersion": "string"  
  }  
],  
"nextToken": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### engineVersions

Returns the engine versions.

Type: Array of [EngineVersionsSummary](#) objects

### nextToken

If there are more items to return, this contains a token that is passed to a subsequent call to this operation to retrieve the next set of items.

Type: String

Pattern: `^\S{1,2000}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### **InternalServerErrorException**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

### **ValidationException**

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListEnvironments

Lists the runtime environments.

## Request Syntax

```
GET /environments?  
engineType=engineType&maxResults=maxResults&names=names&nextToken=nextToken HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### engineType

The engine type for the runtime environment.

Valid Values: microfocus | bluage

### maxResults

The maximum number of runtime environments to return.

Valid Range: Minimum value of 1. Maximum value of 2000.

### names

The names of the runtime environments. Must be unique within the account.

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Pattern: `^[A-Za-z0-9][A-Za-z0-9_\-]{1,59}$`

### nextToken

A pagination token to control the number of runtime environments displayed in the list.

Pattern: `^\S{1,2000}$`

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "environments": [
    {
      "creationTime": number,
      "engineType": "string",
      "engineVersion": "string",
      "environmentArn": "string",
      "environmentId": "string",
      "instanceType": "string",
      "name": "string",
      "status": "string"
    }
  ],
  "nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### environments

Returns a list of summary details for all the runtime environments in your account.

Type: Array of [EnvironmentSummary](#) objects

### nextToken

A pagination token that's returned when the response doesn't contain all the runtime environments.

Type: String

Pattern: `^\S{1,2000}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### InternalServerError

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### ThrottlingException

The number of requests made exceeds the limit.

HTTP Status Code: 429

### ValidationException

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)



# ListTagsForResource

Lists the tags for the specified resource.

## Request Syntax

```
GET /tags/resourceArn HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### resourceArn

The Amazon Resource Name (ARN) of the resource.

Pattern: `^arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]|):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+=@.-]{0,1023}$`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "tags": {
    "string" : "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## tags

The tags for the resource.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:).+$`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### **InternalServerErrorException**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### **ResourceNotFoundException**

The specified resource was not found.

HTTP Status Code: 404

### **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

## ValidationException

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# StartApplication

Starts an application that is currently stopped.

## Request Syntax

```
POST /applications/applicationId/start HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### applicationId

The unique identifier of the application you want to start.

Pattern: `^\S{1,80}$`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### **ConflictException**

The parameters provided in the request conflict with existing resources.

HTTP Status Code: 409

### **InternalServerErrorException**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### **ResourceNotFoundException**

The specified resource was not found.

HTTP Status Code: 404

### **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

### **ValidationException**

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# StartBatchJob

Starts a batch job and returns the unique identifier of this execution of the batch job. The associated application must be running in order to start the batch job.

## Request Syntax

```
POST /applications/applicationId/batch-job HTTP/1.1
Content-type: application/json
```

```
{
  "batchJobIdentifier": { ... },
  "jobParams": {
    "string" : "string"
  }
}
```

## URI Request Parameters

The request uses the following URI parameters.

### [applicationId](#)

The unique identifier of the application associated with this batch job.

Pattern: `^\S{1,80}$`

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### [batchJobIdentifier](#)

The unique identifier of the batch job.

Type: [BatchJobIdentifier](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

## jobParams

The collection of batch job parameters. For details about limits for keys and values, see [Coding variables in JCL](#).

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 500 items.

Key Length Constraints: Minimum length of 1. Maximum length of 32.

Key Pattern: `^[A-Za-z][A-Za-z0-9]{1,7}$`

Value Length Constraints: Minimum length of 0. Maximum length of 80.

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "executionId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### executionId

The unique identifier of this execution of the batch job.

Type: String

Pattern: `^\S{1,80}$`



## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### **ConflictException**

The parameters provided in the request conflict with existing resources.

HTTP Status Code: 409

### **InternalServerErrorException**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### **ResourceNotFoundException**

The specified resource was not found.

HTTP Status Code: 404

### **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

### **ValidationException**

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# StopApplication

Stops a running application.

## Request Syntax

```
POST /applications/applicationId/stop HTTP/1.1
Content-type: application/json

{
  "forceStop": boolean
}
```

## URI Request Parameters

The request uses the following URI parameters.

### applicationId

The unique identifier of the application you want to stop.

Pattern: `^\S{1,80}$`

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### forceStop

Stopping an application process can take a long time. Setting this parameter to true lets you force stop the application so you don't need to wait until the process finishes to apply another action on the application. The default value is false.

Type: Boolean

Required: No

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### ConflictException

The parameters provided in the request conflict with existing resources.

HTTP Status Code: 409

### InternalServerError

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 404

### ThrottlingException

The number of requests made exceeds the limit.

HTTP Status Code: 429

### ValidationException

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# TagResource

Adds one or more tags to the specified resource.

## Request Syntax

```
POST /tags/resourceArn HTTP/1.1
Content-type: application/json

{
  "tags": {
    "string" : "string"
  }
}
```

## URI Request Parameters

The request uses the following URI parameters.

### resourceArn

The Amazon Resource Name (ARN) of the resource.

Pattern: `^arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]|):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+=@.-]{0,1023}$`

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### tags

The tags to add to the resource.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:).+$`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### InternalServerError

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 404

### ServiceQuotaExceededException

One or more quotas for AWS Mainframe Modernization exceeds the limit.

HTTP Status Code: 402

## ThrottlingException

The number of requests made exceeds the limit.

HTTP Status Code: 429

## ValidationException

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# UntagResource

Removes one or more tags from the specified resource.

## Request Syntax

```
DELETE /tags/resourceArn?tagKeys=tagKeys HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### resourceArn

The Amazon Resource Name (ARN) of the resource.

Pattern: `^arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]|):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+=@.-]{0,1023}$`

Required: Yes

### tagKeys

The keys of the tags to remove.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^(?!aws:).+$`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### InternalServerError

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 404

### ThrottlingException

The number of requests made exceeds the limit.

HTTP Status Code: 429

### ValidationException

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateApplication

Updates an application and creates a new version.

## Request Syntax

```
PATCH /applications/applicationId HTTP/1.1
Content-type: application/json

{
  "currentApplicationVersion": number,
  "definition": { ... },
  "description": "string"
}
```

## URI Request Parameters

The request uses the following URI parameters.

### applicationId

The unique identifier of the application you want to update.

Pattern:  $^{\backslash}S\{1, 80\}$

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### currentApplicationVersion

The current version of the application to update.

Type: Integer

Valid Range: Minimum value of 1.

Required: Yes

## definition

The application definition for this application. You can specify either inline JSON or an S3 bucket location.

Type: [Definition](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: No

## description

The description of the application to update.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "applicationVersion": number
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### applicationVersion

The new version of the application.

Type: Integer

Valid Range: Minimum value of 1.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

### **ConflictException**

The parameters provided in the request conflict with existing resources.

HTTP Status Code: 409

### **InternalServerErrorException**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

### **ResourceNotFoundException**

The specified resource was not found.

HTTP Status Code: 404

### **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

### **ValidationException**

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateEnvironment

Updates the configuration details for a specific runtime environment.

## Request Syntax

```
PATCH /environments/environmentId HTTP/1.1
Content-type: application/json

{
  "applyDuringMaintenanceWindow": boolean,
  "desiredCapacity": number,
  "engineVersion": "string",
  "forceUpdate": boolean,
  "instanceType": "string",
  "preferredMaintenanceWindow": "string"
}
```

## URI Request Parameters

The request uses the following URI parameters.

### environmentId

The unique identifier of the runtime environment that you want to update.

Pattern:  $^{\backslash}S\{1,80\}\$$

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### applyDuringMaintenanceWindow

Indicates whether to update the runtime environment during the maintenance window.

The default is false. Currently, AWS Mainframe Modernization accepts the `engineVersion` parameter only if `applyDuringMaintenanceWindow` is true. If any parameter other than `engineVersion` is provided in `UpdateEnvironmentRequest`, it will fail if `applyDuringMaintenanceWindow` is set to true.



Type: Boolean

Required: No

### desiredCapacity

The desired capacity for the runtime environment to update. The minimum possible value is 0 and the maximum is 100.

Type: Integer

Required: No

### engineVersion

The version of the runtime engine for the runtime environment.

Type: String

Pattern:  $^{\backslash}S\{1,10\}$ \$

Required: No

### forceUpdate

Forces the updates on the environment. This option is needed if the applications in the environment are not stopped or if there are ongoing application-related activities in the environment.

If you use this option, be aware that it could lead to data corruption in the applications, and that you might need to perform repair and recovery procedures for the applications.

This option is not needed if the attribute being updated is `preferredMaintenanceWindow`.

Type: Boolean

Required: No

### instanceType

The instance type for the runtime environment to update.

Type: String

Pattern:  $^{\backslash}S\{1,20\}$ \$

Required: No

### preferredMaintenanceWindow

Configures the maintenance window that you want for the runtime environment. The maintenance window must have the format `ddd:hh24:mi-ddd:hh24:mi` and must be less than 24 hours. The following two examples are valid maintenance windows: `sun:23:45-mon:00:15` or `sat:01:00-sat:03:00`.

If you do not provide a value, a random system-generated value will be assigned.

Type: String

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "environmentId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### environmentId

The unique identifier of the runtime environment that was updated.

Type: String

Pattern: `^\S{1,80}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## **AccessDeniedException**

The account or role doesn't have the right permissions to make the request.

HTTP Status Code: 403

## **ConflictException**

The parameters provided in the request conflict with existing resources.

HTTP Status Code: 409

## **InternalServerErrorException**

An unexpected error occurred during the processing of the request.

HTTP Status Code: 500

## **ResourceNotFoundException**

The specified resource was not found.

HTTP Status Code: 404

## **ServiceQuotaExceededException**

One or more quotas for AWS Mainframe Modernization exceeds the limit.

HTTP Status Code: 402

## **ThrottlingException**

The number of requests made exceeds the limit.

HTTP Status Code: 429

## **ValidationException**

One or more parameters provided in the request is not valid.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# Data Types

The AWSMainframeModernization API contains several data types that various actions use. This section describes each data type in detail.

## Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AlternateKey](#)
- [ApplicationSummary](#)
- [ApplicationVersionSummary](#)
- [BatchJobDefinition](#)
- [BatchJobExecutionSummary](#)
- [BatchJobIdentifier](#)
- [DataSet](#)
- [DatasetDetailOrgAttributes](#)
- [DataSetImportConfig](#)
- [DataSetImportItem](#)
- [DataSetImportSummary](#)
- [DataSetImportTask](#)
- [DatasetOrgAttributes](#)
- [DataSetSummary](#)
- [Definition](#)
- [DeployedVersionSummary](#)
- [DeploymentSummary](#)
- [EfsStorageConfiguration](#)
- [EngineVersionsSummary](#)
- [EnvironmentSummary](#)

- [ExternalLocation](#)
- [FileBatchJobDefinition](#)
- [FileBatchJobIdentifier](#)
- [FsxStorageConfiguration](#)
- [GdgAttributes](#)
- [GdgDetailAttributes](#)
- [HighAvailabilityConfig](#)
- [JobIdentifier](#)
- [JobStep](#)
- [JobStepRestartMarker](#)
- [LogGroupSummary](#)
- [MaintenanceSchedule](#)
- [PendingMaintenance](#)
- [PoAttributes](#)
- [PoDetailAttributes](#)
- [PrimaryKey](#)
- [PsAttributes](#)
- [PsDetailAttributes](#)
- [RecordLength](#)
- [RestartBatchJobIdentifier](#)
- [S3BatchJobIdentifier](#)
- [ScriptBatchJobDefinition](#)
- [ScriptBatchJobIdentifier](#)
- [StorageConfiguration](#)
- [ValidationExceptionField](#)
- [VsamAttributes](#)
- [VsamDetailAttributes](#)

# AlternateKey

Defines an alternate key. This value is optional. A legacy data set might not have any alternate key defined but if those alternate keys definitions exist, provide them, as some applications will make use of them.

## Contents

### length

A strictly positive integer value representing the length of the alternate key.

Type: Integer

Required: Yes

### offset

A positive integer value representing the offset to mark the start of the alternate key part in the record byte array.

Type: Integer

Required: Yes

### allowDuplicates

Indicates whether the alternate key values are supposed to be unique for the given data set.

Type: Boolean

Required: No

### name

The name of the alternate key.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# ApplicationSummary

A subset of the possible application attributes. Used in the application list.

## Contents

### **applicationArn**

The Amazon Resource Name (ARN) of the application.

Type: String

Pattern: `^arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]|):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+=@.-]{0,1023}$`

Required: Yes

### **applicationId**

The unique identifier of the application.

Type: String

Pattern: `^\S{1,80}$`

Required: Yes

### **applicationVersion**

The version of the application.

Type: Integer

Valid Range: Minimum value of 1.

Required: Yes

### **creationTime**

The timestamp when the application was created.

Type: Timestamp

Required: Yes

### **engineType**

The type of the target platform for this application.

Type: String

Valid Values: `microfocus` | `bluage`

Required: Yes

### **name**

The name of the application.

Type: String

Pattern: `^[A-Za-z0-9][A-Za-z0-9_\-]{1,59}$`

Required: Yes

### **status**

The status of the application.

Type: String

Valid Values: `Creating` | `Created` | `Available` | `Ready` | `Starting` | `Running` | `Stopping` | `Stopped` | `Failed` | `Deleting` | `Deleting From Environment`

Required: Yes

### **deploymentStatus**

Indicates either an ongoing deployment or if the application has ever deployed successfully.

Type: String

Valid Values: `Deploying` | `Deployed`

Required: No

### **description**

The description of the application.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

### **environmentId**

The unique identifier of the runtime environment that hosts this application.

Type: String

Pattern: `^\S{1,80}$`

Required: No

### **lastStartTime**

The timestamp when you last started the application. Null until the application runs for the first time.

Type: Timestamp

Required: No

### **roleArn**

The Amazon Resource Name (ARN) of the role associated with the application.

Type: String

Pattern: `^arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]|):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+=@.-]{0,1023}$`

Required: No

### **versionStatus**

Indicates the status of the latest version of the application.

Type: String

Valid Values: `Creating` | `Available` | `Failed`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ApplicationVersionSummary

Defines an application version summary.

## Contents

### **applicationVersion**

The application version.

Type: Integer

Valid Range: Minimum value of 1.

Required: Yes

### **creationTime**

The timestamp when the application version was created.

Type: Timestamp

Required: Yes

### **status**

The status of the application.

Type: String

Valid Values: `Creating` | `Available` | `Failed`

Required: Yes

### **statusReason**

The reason for the reported status.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# BatchJobDefinition

Defines the details of a batch job.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

### fileBatchJobDefinition

Specifies a file containing a batch job definition.

Type: [FileBatchJobDefinition](#) object

Required: No

### scriptBatchJobDefinition

A script containing a batch job definition.

Type: [ScriptBatchJobDefinition](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# BatchJobExecutionSummary

A subset of the possible batch job attributes. Used in the batch job list.

## Contents

### **applicationId**

The unique identifier of the application that hosts this batch job.

Type: String

Pattern: `^\S{1,80}$`

Required: Yes

### **executionId**

The unique identifier of this execution of the batch job.

Type: String

Pattern: `^\S{1,80}$`

Required: Yes

### **startTime**

The timestamp when a particular batch job execution started.

Type: Timestamp

Required: Yes

### **status**

The status of a particular batch job execution.

Type: String

Valid Values: `Submitting | Holding | Dispatching | Running | Cancelling | Cancelled | Succeeded | Failed | Purged | Succeeded With Warning`

Required: Yes



## **batchJobIdentifier**

The unique identifier of this batch job.

Type: [BatchJobIdentifier](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: No

## **endTime**

The timestamp when this batch job execution ended.

Type: Timestamp

Required: No

## **jobId**

The unique identifier of a particular batch job.

Type: String

Pattern: `^\S{1,100}$`

Required: No

## **jobName**

The name of a particular batch job.

Type: String

Pattern: `^\S{1,100}$`

Required: No

## **jobType**

The type of a particular batch job execution.

Type: String

Valid Values: VSE | JES2 | JES3

Required: No

## returnCode

The batch job return code from either the Blu Age or Micro Focus runtime engines. For more information, see [Batch return codes](#) in the *IBM WebSphere Application Server* documentation.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# BatchJobIdentifier

Identifies a specific batch job.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

### **fileBatchJobIdentifier**

Specifies a file associated with a specific batch job.

Type: [FileBatchJobIdentifier](#) object

Required: No

### **restartBatchJobIdentifier**

Specifies the required information for restart, including `executionId` and `JobStepRestartMarker`.

Type: [RestartBatchJobIdentifier](#) object

Required: No

### **s3BatchJobIdentifier**

Specifies an Amazon S3 location that identifies the batch jobs that you want to run. Use this identifier to run ad hoc batch jobs.

Type: [S3BatchJobIdentifier](#) object

Required: No

### **scriptBatchJobIdentifier**

A batch job identifier in which the batch job to run is identified by the script name.

Type: [ScriptBatchJobIdentifier](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DataSet

Defines a data set.

## Contents

### datasetName

The logical identifier for a specific data set (in mainframe format).

Type: String

Required: Yes

### datasetOrg

The type of dataset. The only supported value is VSAM.

Type: [DatasetOrgAttributes](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

### recordLength

The length of a record.

Type: [RecordLength](#) object

Required: Yes

### relativePath

The relative location of the data set in the database or file system.

Type: String

Required: No

### storageType

The storage type of the data set: database or file system. For Micro Focus, database corresponds to datastore and file system corresponds to EFS/FSX. For Blu Age, there is no support of file system and database corresponds to Blusam.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DatasetDetailOrgAttributes

Additional details about the data set. Different attributes correspond to different data set organizations. The values are populated based on datasetOrg, storageType and backend (Blu Age or Micro Focus).

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

### **gdg**

The generation data group of the data set.

Type: [GdgDetailAttributes](#) object

Required: No

### **po**

The details of a PO type data set.

Type: [PoDetailAttributes](#) object

Required: No

### **ps**

The details of a PS type data set.

Type: [PsDetailAttributes](#) object

Required: No

### **vsam**

The details of a VSAM data set.

Type: [VsamDetailAttributes](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# DataSetImportConfig

Identifies one or more data sets you want to import with the [CreateDataSetImportTask](#) operation.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

### dataSets

The data sets.

Type: Array of [DataSetImportItem](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

### s3Location

The Amazon S3 location of the data sets.

Type: String

Pattern: `^\S{1,2000}$`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# DataSetImportItem

Identifies a specific data set to import from an external location.

## Contents

### dataSet

The data set.

Type: [DataSet](#) object

Required: Yes

### externalLocation

The location of the data set.

Type: [ExternalLocation](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DataSetImportSummary

Represents a summary of data set imports.

## Contents

### **failed**

The number of data set imports that have failed.

Type: Integer

Required: Yes

### **inProgress**

The number of data set imports that are in progress.

Type: Integer

Required: Yes

### **pending**

The number of data set imports that are pending.

Type: Integer

Required: Yes

### **succeeded**

The number of data set imports that have succeeded.

Type: Integer

Required: Yes

### **total**

The total number of data set imports.

Type: Integer

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DataSetImportTask

Contains information about a data set import task.

## Contents

### status

The status of the data set import task.

Type: String

Valid Values: `Creating` | `Running` | `Completed` | `Failed`

Required: Yes

### summary

A summary of the data set import task.

Type: [DataSetImportSummary](#) object

Required: Yes

### taskId

The identifier of the data set import task.

Type: String

Pattern: `^\S{1,80}$`

Required: Yes

### statusReason

If dataset import failed, the failure reason will show here.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DatasetOrgAttributes

Additional details about the data set. Different attributes correspond to different data set organizations. The values are populated based on datasetOrg, storageType and backend (Blu Age or Micro Focus).

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

### **gdg**

The generation data group of the data set.

Type: [GdgAttributes](#) object

Required: No

### **po**

The details of a PO type data set.

Type: [PoAttributes](#) object

Required: No

### **ps**

The details of a PS type data set.

Type: [PsAttributes](#) object

Required: No

### **vsam**

The details of a VSAM data set.

Type: [VsamAttributes](#) object



Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DataSetSummary

A subset of the possible data set attributes.

## Contents

### **dataSetName**

The name of the data set.

Type: String

Pattern: `^\S{1,200}$`

Required: Yes

### **creationTime**

The timestamp when the data set was created.

Type: Timestamp

Required: No

### **dataSetOrg**

The type of data set. The only supported value is VSAM.

Type: String

Pattern: `^\S{1,20}$`

Required: No

### **format**

The format of the data set.

Type: String

Pattern: `^\S{1,20}$`

Required: No

**lastReferencedTime**

The last time the data set was referenced.

Type: Timestamp

Required: No

**lastUpdatedTime**

The last time the data set was updated.

Type: Timestamp

Required: No

**See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

## Definition

The application definition for a particular application.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

### content

The content of the application definition. This is a JSON object that contains the resource configuration/definitions that identify an application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65000.

Required: No

### s3Location

The S3 bucket that contains the application definition.

Type: String

Pattern:  $^{\wedge}\backslash S\{1, 2000\}\$$

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

# DeployedVersionSummary

Contains a summary of a deployed application.

## Contents

### **applicationVersion**

The version of the deployed application.

Type: Integer

Valid Range: Minimum value of 1.

Required: Yes

### **status**

The status of the deployment.

Type: String

Valid Values: Deploying | Succeeded | Failed | Updating Deployment

Required: Yes

### **statusReason**

The reason for the reported status.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# DeploymentSummary

A subset of information about a specific deployment.

## Contents

### **applicationId**

The unique identifier of the application.

Type: String

Pattern: `^\S{1,80}$`

Required: Yes

### **applicationVersion**

The version of the application.

Type: Integer

Valid Range: Minimum value of 1.

Required: Yes

### **creationTime**

The timestamp when the deployment was created.

Type: Timestamp

Required: Yes

### **deploymentId**

The unique identifier of the deployment.

Type: String

Pattern: `^\S{1,80}$`

Required: Yes

### **environmentId**

The unique identifier of the runtime environment.



Type: String

Pattern: `^\S{1,80}$`

Required: Yes

### **status**

The current status of the deployment.

Type: String

Valid Values: Deploying | Succeeded | Failed | Updating Deployment

Required: Yes

### **statusReason**

The reason for the reported status.

Type: String

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# EfsStorageConfiguration

Defines the storage configuration for an Amazon EFS file system.

## Contents

### file-system-id

The file system identifier.

Type: String

Pattern: `^\S{1,200}$`

Required: Yes

### mount-point

The mount point for the file system.

Type: String

Pattern: `^\S{1,200}$`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# EngineVersionsSummary

A subset of information about the engine version for a specific application.

## Contents

### **engineType**

The type of target platform for the application.

Type: String

Required: Yes

### **engineVersion**

The version of the engine type used by the application.

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# EnvironmentSummary

Contains a subset of the possible runtime environment attributes. Used in the environment list.

## Contents

### creationTime

The timestamp when the runtime environment was created.

Type: Timestamp

Required: Yes

### engineType

The target platform for the runtime environment.

Type: String

Valid Values: microfocus | bluage

Required: Yes

### engineVersion

The version of the runtime engine.

Type: String

Pattern: `^\S{1,10}$`

Required: Yes

### environmentArn

The Amazon Resource Name (ARN) of a particular runtime environment.

Type: String

Pattern: `^arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]|):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+=@.-]{0,1023}$`

Required: Yes

**environmentId**

The unique identifier of a particular runtime environment.

Type: String

Pattern: `^\S{1,80}$`

Required: Yes

**instanceType**

The instance type of the runtime environment.

Type: String

Pattern: `^\S{1,20}$`

Required: Yes

**name**

The name of the runtime environment.

Type: String

Pattern: `^[A-Za-z0-9][A-Za-z0-9_\-]{1,59}$`

Required: Yes

**status**

The status of the runtime environment

Type: String

Valid Values: `Creating` | `Available` | `Updating` | `Deleting` | `Failed` | `UnHealthy`

Required: Yes

**See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ExternalLocation

Defines an external storage location.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

### s3Location

The URI of the Amazon S3 bucket.

Type: String

Pattern: `^\S{1,2000}$`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# FileBatchJobDefinition

A file containing a batch job definition.

## Contents

### fileName

The name of the file containing the batch job definition.

Type: String

Required: Yes

### folderPath

The path to the file containing the batch job definition.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# FileBatchJobIdentifier

A batch job identifier in which the batch job to run is identified by the file name and the relative path to the file name.

## Contents

### fileName

The file name for the batch job identifier.

Type: String

Required: Yes

### folderPath

The relative path to the file name for the batch job identifier.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# FsxStorageConfiguration

Defines the storage configuration for an Amazon FSx file system.

## Contents

### file-system-id

The file system identifier.

Type: String

Pattern: `^\S{1,200}$`

Required: Yes

### mount-point

The mount point for the file system.

Type: String

Pattern: `^\S{1,200}$`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# GdgAttributes

The required attributes for a generation data group data set. A generation data set is one of a collection of successive, historically related, catalogued data sets that together are known as a generation data group (GDG). Use this structure when you want to import a GDG. For more information on GDG, see [Generation data sets](#).

## Contents

### limit

The maximum number of generation data sets, up to 255, in a GDG.

Type: Integer

Required: No

### rollDisposition

The disposition of the data set in the catalog.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# GdgDetailAttributes

The required attributes for a generation data group data set. A generation data set is one of a collection of successive, historically related, catalogued data sets that together are known as a generation data group (GDG). Use this structure when you want to import a GDG. For more information on GDG, see [Generation data sets](#).

## Contents

### limit

The maximum number of generation data sets, up to 255, in a GDG.

Type: Integer

Required: No

### rollDisposition

The disposition of the data set in the catalog.

Type: String

Pattern:  $^{\backslash}S\{1, 50\}$

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# HighAvailabilityConfig

Defines the details of a high availability configuration.

## Contents

### desiredCapacity

The number of instances in a high availability configuration. The minimum possible value is 1 and the maximum is 100.

Type: Integer

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# JobIdentifier

Identifies a specific batch job.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

### fileName

The name of the file that contains the batch job definition.

Type: String

Required: No

### scriptName

The name of the script that contains the batch job definition.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# JobStep

Provides information related to a job step.

## Contents

### **procStepName**

The name of a procedure step.

Type: String

Required: No

### **procStepNumber**

The number of a procedure step.

Type: Integer

Required: No

### **stepCondCode**

The condition code of a step.

Type: String

Required: No

### **stepName**

The name of a step.

Type: String

Required: No

### **stepNumber**

The number of a step.

Type: Integer

Required: No

## **stepRestartable**

Specifies if a step can be restarted or not.

Type: Boolean

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# JobStepRestartMarker

Provides step/procedure step information for a restart batch job operation.

## Contents

### fromStep

The step name that a batch job was restarted from.

Type: String

Required: Yes

### fromProcStep

The procedure step name that a batch job was restarted from.

Type: String

Required: No

### toProcStep

The procedure step name that a batch job was restarted to.

Type: String

Required: No

### toStep

The step name that a batch job was restarted to.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# LogGroupSummary

A subset of the attributes that describe a log group. In CloudWatch a log group is a group of log streams that share the same retention, monitoring, and access control settings.

## Contents

### logGroupName

The name of the log group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: Yes

### logType

The type of log.

Type: String

Pattern: `^\S{1,20}$`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# MaintenanceSchedule

The information about the maintenance schedule.

## Contents

### endTime

The time the scheduled maintenance is to end.

Type: Timestamp

Required: No

### startTime

The time the scheduled maintenance is to start.

Type: Timestamp

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# PendingMaintenance

The scheduled maintenance for a runtime engine.

## Contents

### engineVersion

The specific runtime engine that the maintenance schedule applies to.

Type: String

Required: No

### schedule

The maintenance schedule for the runtime engine version.

Type: [MaintenanceSchedule](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# PoAttributes

The supported properties for a PO type data set.

## Contents

### format

The format of the data set records.

Type: String

Required: Yes

### memberFileExtensions

An array containing one or more filename extensions, allowing you to specify which files to be included as PDS member.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Pattern: `^\S{1,20}$`

Required: Yes

### encoding

The character set encoding of the data set.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

# PoDetailAttributes

The supported properties for a PO type data set.

## Contents

### encoding

The character set encoding of the data set.

Type: String

Required: Yes

### format

The format of the data set records.

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# PrimaryKey

The primary key for a KSDS data set.

## Contents

### length

A strictly positive integer value representing the length of the primary key.

Type: Integer

Required: Yes

### offset

A positive integer value representing the offset to mark the start of the primary key in the record byte array.

Type: Integer

Required: Yes

### name

A name for the Primary Key.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# PsAttributes

The supported properties for a PS type data set.

## Contents

### format

The format of the data set records.

Type: String

Required: Yes

### encoding

The character set encoding of the data set.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# PsDetailAttributes

The supported properties for a PS type data set.

## Contents

### encoding

The character set encoding of the data set.

Type: String

Required: Yes

### format

The format of the data set records.

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RecordLength

The length of the records in the data set.

## Contents

### max

The maximum record length. In case of fixed, both minimum and maximum are the same.

Type: Integer

Required: Yes

### min

The minimum record length of a record.

Type: Integer

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RestartBatchJobIdentifier

An identifier for the StartBatchJob API to show that it is a restart operation.

## Contents

### executionId

The executionId from the StartBatchJob response when the job ran for the first time.

Type: String

Pattern: `^\S{1,80}$`

Required: Yes

### jobStepRestartMarker

The step/procedure step information for a restart batch job operation.

Type: [JobStepRestartMarker](#) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# S3BatchJobIdentifier

A batch job identifier in which the batch jobs to run are identified by an Amazon S3 location.

## Contents

### bucket

The Amazon S3 bucket that contains the batch job definitions.

Type: String

Required: Yes

### identifier

Identifies the batch job definition. This identifier can also point to any batch job definition that already exists in the application or to one of the batch job definitions within the directory that is specified in `keyPrefix`.

Type: [JobIdentifier](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

### keyPrefix

The key prefix that specifies the path to the folder in the S3 bucket that has the batch job definitions.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

# ScriptBatchJobDefinition

A batch job definition contained in a script.

## Contents

### scriptName

The name of the script containing the batch job definition.

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# ScriptBatchJobIdentifier

A batch job identifier in which the batch job to run is identified by the script name.

## Contents

### scriptName

The name of the script containing the batch job definition.

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# StorageConfiguration

Defines the storage configuration for a runtime environment.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

### efs

Defines the storage configuration for an Amazon EFS file system.

Type: [EfsStorageConfiguration](#) object

Required: No

### fsx

Defines the storage configuration for an Amazon FSx file system.

Type: [FsxStorageConfiguration](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ValidationExceptionField

Contains information about a validation exception field.

## Contents

### message

The message of the exception field.

Type: String

Required: Yes

### name

The name of the exception field.

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# VsamAttributes

The attributes of a VSAM type data set.

## Contents

### format

The record format of the data set.

Type: String

Required: Yes

### alternateKeys

The alternate key definitions, if any. A legacy dataset might not have any alternate key defined, but if those alternate keys definitions exist, provide them as some applications will make use of them.

Type: Array of [AlternateKey](#) objects

Required: No

### compressed

Indicates whether indexes for this dataset are stored as compressed values. If you have a large data set (typically > 100 Mb), consider setting this flag to True.

Type: Boolean

Required: No

### encoding

The character set used by the data set. Can be ASCII, EBCDIC, or unknown.

Type: String

Required: No

### primaryKey

The primary key of the data set.

Type: [PrimaryKey](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# VsamDetailAttributes

The attributes of a VSAM type data set.

## Contents

### alternateKeys

The alternate key definitions, if any. A legacy dataset might not have any alternate key defined, but if those alternate keys definitions exist, provide them as some applications will make use of them.

Type: Array of [AlternateKey](#) objects

Required: No

### cacheAtStartup

If set to True, enforces loading the data set into cache before it's used by the application.

Type: Boolean

Required: No

### compressed

Indicates whether indexes for this dataset are stored as compressed values. If you have a large data set (typically > 100 Mb), consider setting this flag to True.

Type: Boolean

Required: No

### encoding

The character set used by the data set. Can be ASCII, EBCDIC, or unknown.

Type: String

Pattern: `^\S{1,20}$`

Required: No

### primaryKey

The primary key of the data set.

Type: [PrimaryKey](#) object

Required: No

### **recordFormat**

The record format of the data set.

Type: String

Pattern: `^\S{1,20}$`

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

## Action

The action to be performed.

Type: string

Required: Yes

## Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

## X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

## X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4\_request"). The value is expressed in the following format: *access\_key/YYYYMMDD/region/service/aws4\_request*.



For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

### **X-Amz-Date**

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

### **X-Amz-Security-Token**

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

### **X-Amz-Signature**

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

### **X-Amz-SignedHeaders**

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

# Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

## **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 403

## **ExpiredTokenException**

The security token included in the request is expired

HTTP Status Code: 403

## **IncompleteSignature**

The request signature does not conform to AWS standards.

HTTP Status Code: 403

## **InternalFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## **MalformedHttpRequestException**

Problems with the request at the HTTP level, e.g. we can't decompress the body according to the decompression algorithm specified by the content-encoding.

HTTP Status Code: 400

## **NotAuthorized**

You do not have permission to perform this action.

HTTP Status Code: 401

## **OptInRequired**

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

### **RequestAbortedException**

Convenient exception that can be used when a request is aborted before a reply is sent back (e.g. client closed connection).

HTTP Status Code: 400

### **RequestEntityTooLargeException**

Problems with the request at the HTTP level. The request entity is too large.

HTTP Status Code: 413

### **RequestExpired**

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

### **RequestTimeoutException**

Problems with the request at the HTTP level. Reading the Request timed out.

HTTP Status Code: 408

### **ServiceUnavailable**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

### **ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

### **UnrecognizedClientException**

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

**UnknownOperationException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 404

**ValidationError**

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400