



API Reference

AWS Outposts



API Version 2019-12-03

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS Outposts: API Reference

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
CancelCapacityTask	4
Request Syntax	4
URI Request Parameters	4
Request Body	4
Response Syntax	4
Response Elements	5
Errors	5
See Also	5
CancelOrder	7
Request Syntax	7
URI Request Parameters	7
Request Body	7
Response Syntax	7
Response Elements	7
Errors	7
See Also	8
CreateOrder	10
Request Syntax	10
URI Request Parameters	10
Request Body	10
Response Syntax	11
Response Elements	12
Errors	12
See Also	13
CreateOutpost	15
Request Syntax	15
URI Request Parameters	15
Request Body	15
Response Syntax	17
Response Elements	18
Errors	18
See Also	19

CreateSite	20
Request Syntax	20
URI Request Parameters	21
Request Body	21
Response Syntax	23
Response Elements	24
Errors	24
See Also	25
DeleteOutpost	26
Request Syntax	26
URI Request Parameters	26
Request Body	26
Response Syntax	26
Response Elements	26
Errors	27
See Also	27
DeleteSite	29
Request Syntax	29
URI Request Parameters	29
Request Body	29
Response Syntax	29
Response Elements	29
Errors	30
See Also	30
GetCapacityTask	32
Request Syntax	32
URI Request Parameters	32
Request Body	32
Response Syntax	32
Response Elements	33
Errors	35
See Also	36
GetCatalogItem	37
Request Syntax	37
URI Request Parameters	37
Request Body	37

Response Syntax	37
Response Elements	38
Errors	38
See Also	39
GetConnection	40
Request Syntax	40
URI Request Parameters	40
Request Body	40
Response Syntax	40
Response Elements	41
Errors	41
See Also	42
GetOrder	43
Request Syntax	43
URI Request Parameters	43
Request Body	43
Response Syntax	43
Response Elements	44
Errors	44
See Also	45
GetOutpost	46
Request Syntax	46
URI Request Parameters	46
Request Body	46
Response Syntax	46
Response Elements	47
Errors	47
See Also	48
GetOutpostInstanceTypes	49
Request Syntax	49
URI Request Parameters	49
Request Body	50
Response Syntax	50
Response Elements	50
Errors	51
See Also	52

GetOutpostSupportedInstanceTypes	53
Request Syntax	53
URI Request Parameters	53
Request Body	54
Response Syntax	54
Response Elements	54
Errors	55
See Also	55
GetSite	57
Request Syntax	57
URI Request Parameters	57
Request Body	57
Response Syntax	57
Response Elements	58
Errors	58
See Also	59
GetSiteAddress	60
Request Syntax	60
URI Request Parameters	60
Request Body	60
Response Syntax	61
Response Elements	61
Errors	62
See Also	62
ListAssets	64
Request Syntax	64
URI Request Parameters	64
Request Body	65
Response Syntax	65
Response Elements	66
Errors	66
See Also	67
ListCapacityTasks	68
Request Syntax	68
URI Request Parameters	68
Request Body	69

Response Syntax	69
Response Elements	69
Errors	70
See Also	70
ListCatalogItems	72
Request Syntax	72
URI Request Parameters	72
Request Body	73
Response Syntax	73
Response Elements	73
Errors	74
See Also	74
ListOrders	76
Request Syntax	76
URI Request Parameters	76
Request Body	76
Response Syntax	77
Response Elements	77
Errors	78
See Also	78
ListOutposts	80
Request Syntax	80
URI Request Parameters	80
Request Body	81
Response Syntax	81
Response Elements	82
Errors	82
See Also	83
ListSites	84
Request Syntax	84
URI Request Parameters	84
Request Body	85
Response Syntax	85
Response Elements	86
Errors	86
See Also	87

ListTagsForResource	88
Request Syntax	88
URI Request Parameters	88
Request Body	88
Response Syntax	88
Response Elements	88
Errors	89
See Also	89
StartCapacityTask	91
Request Syntax	91
URI Request Parameters	91
Request Body	91
Response Syntax	92
Response Elements	93
Errors	95
See Also	95
StartConnection	97
Request Syntax	97
URI Request Parameters	97
Request Body	97
Response Syntax	98
Response Elements	99
Errors	99
See Also	100
TagResource	101
Request Syntax	101
URI Request Parameters	101
Request Body	101
Response Syntax	102
Response Elements	102
Errors	102
See Also	103
UntagResource	104
Request Syntax	104
URI Request Parameters	104
Request Body	104

Response Syntax	104
Response Elements	105
Errors	105
See Also	105
UpdateOutpost	107
Request Syntax	107
URI Request Parameters	107
Request Body	107
Response Syntax	108
Response Elements	109
Errors	109
See Also	110
UpdateSite	111
Request Syntax	111
URI Request Parameters	111
Request Body	111
Response Syntax	112
Response Elements	113
Errors	113
See Also	114
UpdateSiteAddress	116
Request Syntax	116
URI Request Parameters	116
Request Body	117
Response Syntax	117
Response Elements	118
Errors	118
See Also	119
UpdateSiteRackPhysicalProperties	120
Request Syntax	120
URI Request Parameters	120
Request Body	121
Response Syntax	124
Response Elements	125
Errors	125
See Also	126

Data Types	127
Address	129
Contents	129
See Also	131
AssetInfo	133
Contents	133
See Also	134
AssetLocation	135
Contents	135
See Also	135
CapacityTaskFailure	136
Contents	136
See Also	136
CapacityTaskSummary	137
Contents	137
See Also	138
CatalogItem	139
Contents	139
See Also	140
ComputeAttributes	141
Contents	141
See Also	142
ConnectionDetails	143
Contents	143
See Also	144
EC2Capacity	145
Contents	145
See Also	145
InstanceTypeCapacity	147
Contents	147
See Also	147
InstanceTypeItem	148
Contents	148
See Also	148
LineItem	149
Contents	149

See Also	150
LineItemAssetInformation	152
Contents	152
See Also	152
LineItemRequest	153
Contents	153
See Also	153
Order	154
Contents	154
See Also	156
OrderSummary	157
Contents	157
See Also	159
Outpost	160
Contents	160
See Also	163
RackPhysicalProperties	164
Contents	164
See Also	166
ShipmentInformation	167
Contents	167
See Also	167
Site	168
Contents	168
See Also	171
Common Parameters	172
Common Errors	175

Welcome

AWS Outposts is a fully managed service that extends AWS infrastructure, APIs, and tools to customer premises. By providing local access to AWS managed infrastructure, AWS Outposts enables customers to build and run applications on premises using the same programming interfaces as in AWS Regions, while using local compute and storage resources for lower latency and local data processing needs.

This document was last published on July 2, 2024.

Actions

The following actions are supported:

- [CancelCapacityTask](#)
- [CancelOrder](#)
- [CreateOrder](#)
- [CreateOutpost](#)
- [CreateSite](#)
- [DeleteOutpost](#)
- [DeleteSite](#)
- [GetCapacityTask](#)
- [GetCatalogItem](#)
- [GetConnection](#)
- [GetOrder](#)
- [GetOutpost](#)
- [GetOutpostInstanceTypes](#)
- [GetOutpostSupportedInstanceTypes](#)
- [GetSite](#)
- [GetSiteAddress](#)
- [ListAssets](#)
- [ListCapacityTasks](#)
- [ListCatalogItems](#)
- [ListOrders](#)
- [ListOutposts](#)
- [ListSites](#)
- [ListTagsForResource](#)
- [StartCapacityTask](#)
- [StartConnection](#)
- [TagResource](#)
- [UntagResource](#)

- [UpdateOutpost](#)
- [UpdateSite](#)
- [UpdateSiteAddress](#)
- [UpdateSiteRackPhysicalProperties](#)

CancelCapacityTask

Cancels the capacity task.

Request Syntax

```
POST /outposts/OutpostId/capacity/CapacityTaskId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

CapacityTaskId

ID of the capacity task that you want to cancel.

Length Constraints: Fixed length of 21.

Pattern: `^cap-[a-f0-9]{17}$`

Required: Yes

OutpostId

ID or ARN of the Outpost associated with the capacity task that you want to cancel.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ : \d{12} :outpost/)?op-[a-f0-9]{17}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CancelOrder

Cancels the specified order for an Outpost.

Request Syntax

```
POST /orders/OrderId/cancel HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

OrderId

The ID of the order.

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: oo-[a-f0-9]{17}\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateOrder

Creates an order for an Outpost.

Request Syntax

```
POST /orders HTTP/1.1
Content-type: application/json

{
  "LineItems": [
    {
      "CatalogItemId": "string",
      "Quantity": number
    }
  ],
  "OutpostIdentifier": "string",
  "PaymentOption": "string",
  "PaymentTerm": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

LineItems

The line items that make up the order.

Type: Array of [LineItemRequest](#) objects

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Required: Yes

OutpostIdentifier

The ID or the Amazon Resource Name (ARN) of the Outpost.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ : \d{12}:outpost/)?op-[a-f0-9]{17}$`

Required: Yes

PaymentOption

The payment option.

Type: String

Valid Values: ALL_UPFRONT | NO_UPFRONT | PARTIAL_UPFRONT

Required: Yes

PaymentTerm

The payment terms.

Type: String

Valid Values: THREE_YEARS | ONE_YEAR

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Order": {
    "LineItems": [
      {
        "AssetInformationList": [
          {
            "AssetId": "string",
            "MacAddressList": [ "string" ]
          }
        ]
      }
    ],
  },
}
```

```
    "CatalogItemId": "string",
    "LineItemId": "string",
    "PreviousLineItemId": "string",
    "PreviousOrderId": "string",
    "Quantity": number,
    "ShipmentInformation": {
      "ShipmentCarrier": "string",
      "ShipmentTrackingNumber": "string"
    },
    "Status": "string"
  }
],
"OrderFulfilledDate": number,
"OrderId": "string",
"OrderSubmissionDate": number,
"OrderType": "string",
"OutpostId": "string",
"PaymentOption": "string",
"PaymentTerm": "string",
"Status": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Order

Information about this order.

Type: [Order](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ServiceQuotaExceededException

You have exceeded a service quota.

HTTP Status Code: 402

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateOutpost

Creates an Outpost.

You can specify either an Availability one or an AZ ID.

Request Syntax

```
POST /outposts HTTP/1.1
Content-type: application/json

{
  "AvailabilityZone": "string",
  "AvailabilityZoneId": "string",
  "Description": "string",
  "Name": "string",
  "SiteId": "string",
  "SupportedHardwareType": "string",
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

AvailabilityZone

The Availability Zone.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `^([a-zA-Z]+-){1,3}([a-zA-Z]+)?(\d+[a-zA-Z])?$`

Required: No

AvailabilityZoneId

The ID of the Availability Zone.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z]+\d-[a-zA-Z]+\d$`

Required: No

Description

The description of the Outpost.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Pattern: `^[\\S]*$`

Required: No

Name

The name of the Outpost.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[\\S]+$`

Required: Yes

SiteId

The ID or the Amazon Resource Name (ARN) of the site.

Note

Despite the parameter name, you can make the request with an ARN. The parameter name is `SiteId` for backward compatibility.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^(arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:site/)?(os-[a-f0-9]{17})$`

Required: Yes

SupportedHardwareType

The type of hardware for this Outpost.

Type: String

Valid Values: RACK | SERVER

Required: No

Tags

The tags to apply to the Outpost.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z+-._: /]+$`

Value Length Constraints: Maximum length of 256.

Value Pattern: `^[\S \n]+$`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"Outpost": {
  "AvailabilityZone": "string",
  "AvailabilityZoneId": "string",
  "Description": "string",
  "LifecycleStatus": "string",
  "Name": "string",
  "OutpostArn": "string",
  "OutpostId": "string",
  "OwnerId": "string",
  "SiteArn": "string",
  "SiteId": "string",
  "SupportedHardwareType": "string",
  "Tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Outpost

Information about an Outpost.

Type: [Outpost](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ServiceQuotaExceededException

You have exceeded a service quota.

HTTP Status Code: 402

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateSite

Creates a site for an Outpost.

Request Syntax

```
POST /sites HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "Description": "string",
  "Name": "string",
  "Notes": "string",
  "OperatingAddress": {
    "AddressLine1": "string",
    "AddressLine2": "string",
    "AddressLine3": "string",
    "City": "string",
    "ContactName": "string",
    "ContactPhoneNumber": "string",
    "CountryCode": "string",
    "DistrictOrCounty": "string",
    "Municipality": "string",
    "PostalCode": "string",
    "StateOrRegion": "string"
  },
  "RackPhysicalProperties": {
    "FiberOpticCableType": "string",
    "MaximumSupportedWeightLbs": "string",
    "OpticalStandard": "string",
    "PowerConnector": "string",
    "PowerDrawKva": "string",
    "PowerFeedDrop": "string",
    "PowerPhase": "string",
    "UplinkCount": "string",
    "UplinkGbps": "string"
  },
  "ShippingAddress": {
    "AddressLine1": "string",
    "AddressLine2": "string",
    "AddressLine3": "string",
    "City": "string",
    "ContactName": "string",
```

```
    "ContactPhoneNumber": "string",
    "CountryCode": "string",
    "DistrictOrCounty": "string",
    "Municipality": "string",
    "PostalCode": "string",
    "StateOrRegion": "string"
  },
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Description

The description of the site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1001.

Pattern: `^[\\S]+$`

Required: No

Name

The name of the site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `^[\\S]+$`

Required: Yes

Notes

Additional information that you provide about site access requirements, electrician scheduling, personal protective equipment, or regulation of equipment materials that could affect your installation process.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `^[\\S \\n]+$`

Required: No

OperatingAddress

The location to install and power on the hardware. This address might be different from the shipping address.

Type: [Address](#) object

Required: No

RackPhysicalProperties

Information about the physical and logistical details for the rack at this site. For more information about hardware requirements for racks, see [Network readiness checklist](#) in the AWS Outposts User Guide.

Type: [RackPhysicalProperties](#) object

Required: No

ShippingAddress

The location to ship the hardware. This address might be different from the operating address.

Type: [Address](#) object

Required: No

Tags

The tags to apply to a site.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z+-. _:/]+$`

Value Length Constraints: Maximum length of 256.

Value Pattern: `^[\\S \\n]+$`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Site": {
    "AccountId": "string",
    "Description": "string",
    "Name": "string",
    "Notes": "string",
    "OperatingAddressCity": "string",
    "OperatingAddressCountryCode": "string",
    "OperatingAddressStateOrRegion": "string",
    "RackPhysicalProperties": {
      "FiberOpticCableType": "string",
      "MaximumSupportedWeightLbs": "string",
      "OpticalStandard": "string",
      "PowerConnector": "string",
      "PowerDrawKva": "string",
      "PowerFeedDrop": "string",
      "PowerPhase": "string",
      "UplinkCount": "string",
      "UplinkGbps": "string"
    },
    "SiteArn": "string",
    "SiteId": "string",
    "Tags": {
      "string" : "string"
    }
  }
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Site

Information about a site.

Type: [Site](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An internal error has occurred.

HTTP Status Code: 500

ServiceQuotaExceededException

You have exceeded a service quota.

HTTP Status Code: 402

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteOutpost

Deletes the specified Outpost.

Request Syntax

```
DELETE /outposts/OutpostId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

OutpostId

The ID or ARN of the Outpost.

Note

Despite the parameter name, you can make the request with an ARN. The parameter name is `OutpostId` for backward compatibility.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ : \d{12} :outpost/)?op-[a-f0-9]{17}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteSite

Deletes the specified site.

Request Syntax

```
DELETE /sites/SiteId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

SiteId

The ID or the Amazon Resource Name (ARN) of the site.

Note

Despite the parameter name, you can make the request with an ARN. The parameter name is `SiteId` for backward compatibility.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ : \d{12} :site/)?(os-[a-f0-9]{17})$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetCapacityTask

Gets details of the specified capacity task.

Request Syntax

```
GET /outposts/OutpostId/capacity/CapacityTaskId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

CapacityTaskId

ID of the capacity task.

Length Constraints: Fixed length of 21.

Pattern: `^cap-[a-f0-9]{17}$`

Required: Yes

OutpostId

ID or ARN of the Outpost associated with the specified capacity task.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ : \d{12} :outpost/)?op-[a-f0-9]{17}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "CapacityTaskId": "string",
  "CapacityTaskStatus": "string",
  "CompletionDate": number,
  "CreationDate": number,
  "DryRun": boolean,
  "Failed": {
    "Reason": "string",
    "Type": "string"
  },
  "LastModifiedDate": number,
  "OrderId": "string",
  "OutpostId": "string",
  "RequestedInstancePools": [
    {
      "Count": number,
      "InstanceType": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CapacityTaskId

ID of the capacity task.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `^cap-[a-f0-9]{17}$`

CapacityTaskStatus

Status of the capacity task.

A capacity task can have one of the following statuses:

- **REQUESTED** - The capacity task was created and is awaiting the next step by AWS Outposts.
- **IN_PROGRESS** - The capacity task is running and cannot be cancelled.
- **WAITING_FOR_EVACUATION** - The capacity task requires capacity to run. You must stop the recommended EC2 running instances to free up capacity for the task to run.

Type: String

Valid Values: REQUESTED | IN_PROGRESS | FAILED | COMPLETED | CANCELLED

CompletionDate

The date the capacity task ran successfully.

Type: Timestamp

CreationDate

The date the capacity task was created.

Type: Timestamp

DryRun

Performs a dry run to determine if you are above or below instance capacity.

Type: Boolean

Failed

Reason why the capacity task failed.

Type: [CapacityTaskFailure](#) object

LastModifiedDate

The date the capacity task was last modified.

Type: Timestamp

OrderId

ID of the AWS Outposts order associated with the specified capacity task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: oo-[a-f0-9]{17}\$

OutpostId

ID of the Outpost associated with the specified capacity task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: ^(arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:outpost/)?op-[a-f0-9]{17}\$

RequestedInstancePools

List of instance pools requested in the capacity task.

Type: Array of [InstanceTypeCapacity](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerErrorException

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetCatalogItem

Gets information about the specified catalog item.

Request Syntax

```
GET /catalog/item/CatalogItemId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

CatalogItemId

The ID of the catalog item.

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: OR-[A-Z0-9]{7}

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CatalogItem": {
    "CatalogItemId": "string",
    "EC2Capacities": [
      {
        "Family": "string",
        "MaxSize": "string",
        "Quantity": "string"
      }
    ]
  }
}
```



```
    ],  
    "ItemStatus": "string",  
    "PowerKva": number,  
    "SupportedStorage": [ "string" ],  
    "SupportedUplinkGbps": [ number ],  
    "WeightLbs": number  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CatalogItem

Information about this catalog item.

Type: [CatalogItem](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetConnection

Note

AWS uses this action to install Outpost servers.

Gets information about the specified connection.

Use CloudTrail to monitor this action or AWS managed policy for AWS Outposts to secure it. For more information, see [AWS managed policies for AWS Outposts](#) and [Logging AWS Outposts API calls with AWS CloudTrail](#) in the *AWS Outposts User Guide*.

Request Syntax

```
GET /connections/ConnectionId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ConnectionId

The ID of the connection.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^[a-zA-Z0-9+/=]{1,1024}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "ConnectionDetails": {
    "AllowedIps": [ "string" ],
    "ClientPublicKey": "string",
    "ClientTunnelAddress": "string",
    "ServerEndpoint": "string",
    "ServerPublicKey": "string",
    "ServerTunnelAddress": "string"
  },
  "ConnectionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ConnectionDetails

Information about the connection.

Type: [ConnectionDetails](#) object

ConnectionId

The ID of the connection.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^[a-zA-Z0-9+/=]{1,1024}$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerErrorException

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetOrder

Gets information about the specified order.

Request Syntax

```
GET /orders/OrderId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

OrderId

The ID of the order.

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: oo-[a-f0-9]{17}\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Order": {
    "LineItems": [
      {
        "AssetInformationList": [
          {
            "AssetId": "string",
            "MacAddressList": [ "string" ]
          }
        ],
      },
    ],
  },
}
```

```
    "CatalogItemId": "string",
    "LineItemId": "string",
    "PreviousLineItemId": "string",
    "PreviousOrderId": "string",
    "Quantity": number,
    "ShipmentInformation": {
      "ShipmentCarrier": "string",
      "ShipmentTrackingNumber": "string"
    },
    "Status": "string"
  }
],
"OrderFulfilledDate": number,
"OrderId": "string",
"OrderSubmissionDate": number,
"OrderType": "string",
"OutpostId": "string",
"PaymentOption": "string",
"PaymentTerm": "string",
"Status": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Order

Information about an order.

Type: [Order](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetOutpost

Gets information about the specified Outpost.

Request Syntax

```
GET /outposts/OutpostId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

OutpostId

The ID or ARN of the Outpost.

Note

Despite the parameter name, you can make the request with an ARN. The parameter name is `OutpostId` for backward compatibility.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:outpost/)?op-[a-f0-9]{17}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"Outpost": {
  "AvailabilityZone": "string",
  "AvailabilityZoneId": "string",
  "Description": "string",
  "LifecycleStatus": "string",
  "Name": "string",
  "OutpostArn": "string",
  "OutpostId": "string",
  "OwnerId": "string",
  "SiteArn": "string",
  "SiteId": "string",
  "SupportedHardwareType": "string",
  "Tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Outpost

Information about an Outpost.

Type: [Outpost](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetOutpostInstanceTypes

Gets the instance types for the specified Outpost.

Request Syntax

```
GET /outposts/OutpostId/instanceTypes?MaxResults=MaxResults&NextToken=NextToken  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum page size.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

The pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: $^(\d+)\##(\S+)\$$

OutpostId

The ID or ARN of the Outpost.

Note

Despite the parameter name, you can make the request with an ARN. The parameter name is `OutpostId` for backward compatibility.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: $^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ : \d{12} :outpost/)?op-[a-f0-9]{17}\$$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "InstanceTypes": [
    {
      "InstanceType": "string"
    }
  ],
  "NextToken": "string",
  "OutpostArn": "string",
  "OutpostId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InstanceTypes

Information about the instance types.

Type: Array of [InstanceTypeItem](#) objects

NextToken

The pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(\\d+)##(\\S+)$`

OutpostArn

The Amazon Resource Name (ARN) of the Outpost.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^arn:aws([a-z-]+)?:outposts:[a-z\\d-]+:\\d{12}:outpost/op-[a-f0-9]{17}$`

OutpostId

The ID of the Outpost.

Note

Despite the parameter name, you can make the request with an ARN. The parameter name is `OutpostId` for backward compatibility.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)?:outposts:[a-z\\d-]+:\\d{12}:outpost/)?op-[a-f0-9]{17}$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerErrorException

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetOutpostSupportedInstanceTypes

Gets the instance types that an Outpost can support in InstanceTypeCapacity. This will generally include instance types that are not currently configured and therefore cannot be launched with the current Outpost capacity configuration.

Request Syntax

```
GET /outposts/OutpostId/supportedInstanceTypes?  
MaxResults=MaxResults&NextToken=NextToken&OrderId=OrderId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum page size.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

The pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: $^(\backslash d+)##(\backslash S+)\$$

OrderId

The ID for the AWS Outposts order.

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: $oo-[a-f0-9]{17}\$$

Required: Yes

OutpostId

The ID or ARN of the Outpost.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:outpost/)?op-[a-f0-9]{17}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "InstanceTypes": [
    {
      "InstanceType": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InstanceTypes

Information about the instance types.

Type: Array of [InstanceTypeItem](#) objects

NextToken

The pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(\\d+)##(\\S+)$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerErrorException

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetSite

Gets information about the specified Outpost site.

Request Syntax

```
GET /sites/SiteId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

SiteId

The ID or the Amazon Resource Name (ARN) of the site.

Note

Despite the parameter name, you can make the request with an ARN. The parameter name is `SiteId` for backward compatibility.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^(arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:site/)?(os-[a-f0-9]{17})$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"Site": {
  "AccountId": "string",
  "Description": "string",
  "Name": "string",
  "Notes": "string",
  "OperatingAddressCity": "string",
  "OperatingAddressCountryCode": "string",
  "OperatingAddressStateOrRegion": "string",
  "RackPhysicalProperties": {
    "FiberOpticCableType": "string",
    "MaximumSupportedWeightLbs": "string",
    "OpticalStandard": "string",
    "PowerConnector": "string",
    "PowerDrawKva": "string",
    "PowerFeedDrop": "string",
    "PowerPhase": "string",
    "UplinkCount": "string",
    "UplinkGbps": "string"
  },
  "SiteArn": "string",
  "SiteId": "string",
  "Tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Site

Information about a site.

Type: [Site](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerErrorException

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetSiteAddress

Gets the site address of the specified site.

Request Syntax

```
GET /sites/SiteId/address?AddressType=AddressType HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

AddressType

The type of the address you request.

Valid Values: SHIPPING_ADDRESS | OPERATING_ADDRESS

Required: Yes

SiteId

The ID or the Amazon Resource Name (ARN) of the site.

Note

Despite the parameter name, you can make the request with an ARN. The parameter name is `SiteId` for backward compatibility.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^(arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:site/)?(os-[a-f0-9]{17})$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Address": {
    "AddressLine1": "string",
    "AddressLine2": "string",
    "AddressLine3": "string",
    "City": "string",
    "ContactName": "string",
    "ContactPhoneNumber": "string",
    "CountryCode": "string",
    "DistrictOrCounty": "string",
    "Municipality": "string",
    "PostalCode": "string",
    "StateOrRegion": "string"
  },
  "AddressType": "string",
  "SiteId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Address

Information about the address.

Type: [Address](#) object

AddressType

The type of the address you receive.

Type: String

Valid Values: SHIPPING_ADDRESS | OPERATING_ADDRESS

Siteld

The ID of the site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ : \d{12}:site/)?(os-[a-f0-9]{17})$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAssets

Lists the hardware assets for the specified Outpost.

Use filters to return specific results. If you specify multiple filters, the results include only the resources that match all of the specified filters. For a filter where you can specify multiple values, the results include items that match any of the values that you specify for the filter.

Request Syntax

```
GET /outposts/OutpostId/assets?  
HostIdFilter=HostIdFilter&MaxResults=MaxResults&NextToken=NextToken&StatusFilter=StatusFilter  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

HostIdFilter

Filters the results by the host ID of a Dedicated Host.

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `^[A-Za-z0-9-]*$`

MaxResults

The maximum page size.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

The pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(\\d+)##(\\S+)$`

OutpostId

The ID or the Amazon Resource Name (ARN) of the Outpost.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ : \d{12} :outpost/)?op-[a-f0-9]{17}$`

Required: Yes

StatusFilter

Filters the results by state.

Array Members: Minimum number of 1 item. Maximum number of 3 items.

Valid Values: ACTIVE | RETIRING | ISOLATED

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Assets": [
    {
      "AssetId": "string",
      "AssetLocation": {
        "RackElevation": number
      },
      "AssetType": "string",
      "ComputeAttributes": {
        "HostId": "string",
        "InstanceFamilies": [ "string" ],
        "State": "string"
      },
      "RackId": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Assets

Information about the hardware assets.

Type: Array of [AssetInfo](#) objects

NextToken

The pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(\\d+)##(\\S+)$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListCapacityTasks

Lists the capacity tasks for your AWS account.

Use filters to return specific results. If you specify multiple filters, the results include only the resources that match all of the specified filters. For a filter where you can specify multiple values, the results include items that match any of the values that you specify for the filter.

Request Syntax

```
GET /capacity/tasks?  
CapacityTaskStatusFilter=CapacityTaskStatusFilter&MaxResults=MaxResults&NextToken=NextToken&Out  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

CapacityTaskStatusFilter

A list of statuses. For example, REQUESTED or WAITING_FOR_EVACUATION.

Valid Values: REQUESTED | IN_PROGRESS | FAILED | COMPLETED | CANCELLED

MaxResults

The maximum page size.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

The pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: $^(\d+)\##(\S+)\$$

OutpostIdentifierFilter

Filters the results by an Outpost ID or an Outpost ARN.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:outpost/)?op-[a-f0-9]{17}$`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CapacityTasks": [
    {
      "CapacityTaskId": "string",
      "CapacityTaskStatus": "string",
      "CompletionDate": number,
      "CreationDate": number,
      "LastModifiedDate": number,
      "OrderId": "string",
      "OutpostId": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CapacityTasks

Lists all the capacity tasks.

Type: Array of [CapacityTaskSummary](#) objects

NextToken

The pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^\d+##\S+$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListCatalogItems

Lists the items in the catalog.

Use filters to return specific results. If you specify multiple filters, the results include only the resources that match all of the specified filters. For a filter where you can specify multiple values, the results include items that match any of the values that you specify for the filter.

Request Syntax

```
GET /catalog/items?  
EC2FamilyFilter=EC2FamilyFilter&ItemClassFilter=ItemClassFilter&MaxResults=MaxResults&NextToken=NextToken  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

EC2FamilyFilter

Filters the results by EC2 family (for example, M5).

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: [a-z0-9]+

ItemClassFilter

Filters the results by item class.

Valid Values: RACK | SERVER

MaxResults

The maximum page size.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

The pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: ^(\d+)##(\S+)\$

SupportedStorageFilter

Filters the results by storage option.

Valid Values: EBS | S3

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CatalogItems": [
    {
      "CatalogItemId": "string",
      "EC2Capacities": [
        {
          "Family": "string",
          "MaxSize": "string",
          "Quantity": "string"
        }
      ],
      "ItemStatus": "string",
      "PowerKva": number,
      "SupportedStorage": [ "string" ],
      "SupportedUplinkGbps": [ number ],
      "WeightLbs": number
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[CatalogItems](#)

Information about the catalog items.

Type: Array of [CatalogItem](#) objects

[NextToken](#)

The pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(\\d+)##(\\S+)$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListOrders

Lists the Outpost orders for your AWS account.

Request Syntax

```
GET /list-orders?  
MaxResults=MaxResults&NextToken=NextToken&OutpostIdentifierFilter=OutpostIdentifierFilter  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum page size.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

The pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: $^(\backslash d+)##(\backslash S+)$$

OutpostIdentifierFilter

The ID or the Amazon Resource Name (ARN) of the Outpost.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: $^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ : \d{12} :outpost/)?op-[a-f0-9]{17}$$

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "Orders": [
    {
      "LineItemCountsByStatus": {
        "string" : number
      },
      "OrderFulfilledDate": number,
      "OrderId": "string",
      "OrderSubmissionDate": number,
      "OrderType": "string",
      "OutpostId": "string",
      "Status": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: $^(\d+)\#\#(\S+)\$$

Orders

Information about the orders.

Type: Array of [OrderSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerErrorException

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

ListOutposts

Lists the Outposts for your AWS account.

Use filters to return specific results. If you specify multiple filters, the results include only the resources that match all of the specified filters. For a filter where you can specify multiple values, the results include items that match any of the values that you specify for the filter.

Request Syntax

```
GET /outposts?  
AvailabilityZoneFilter=AvailabilityZoneFilter&AvailabilityZoneIdFilter=AvailabilityZoneIdFilter  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[AvailabilityZoneFilter](#)

Filters the results by Availability Zone (for example, us-east-1a).

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: $^([a-zA-Z]+-){1,3}([a-zA-Z]+)(\d+[a-zA-Z])?$$$

[AvailabilityZoneIdFilter](#)

Filters the results by AZ ID (for example, use1-az1).

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: $^[a-zA-Z]+\d-[a-zA-Z]+\d$$$

[LifeCycleStatusFilter](#)

Filters the results by the lifecycle status.

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `^[A-Za-z]+$`

MaxResults

The maximum page size.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

The pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(\\d+)##(\\S+)$`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "Outposts": [
    {
      "AvailabilityZone": "string",
      "AvailabilityZoneId": "string",
      "Description": "string",
      "LifecycleStatus": "string",
      "Name": "string",
      "OutpostArn": "string",
      "OutpostId": "string",
      "OwnerId": "string",
      "SiteArn": "string",
      "SiteId": "string",
      "SupportedHardwareType": "string",
      "Tags": {
```

```
        "string" : "string"  
      }  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(\\d+)##(\\S+)$`

Outposts

Information about the Outposts.

Type: Array of [Outpost](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListSites

Lists the Outpost sites for your AWS account. Use filters to return specific results.

Use filters to return specific results. If you specify multiple filters, the results include only the resources that match all of the specified filters. For a filter where you can specify multiple values, the results include items that match any of the values that you specify for the filter.

Request Syntax

```
GET /sites?
MaxResults=MaxResults&NextToken=NextToken&OperatingAddressCityFilter=OperatingAddressCityFilter
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum page size.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

The pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(\\d+)##(\\S+)$`

OperatingAddressCityFilter

Filters the results by city.

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `^\\S[\\S]*$`

OperatingAddressCountryCodeFilter

Filters the results by country code.

Length Constraints: Fixed length of 2.

Pattern: `^[A-Z]{2}$`

OperatingAddressStateOrRegionFilter

Filters the results by state or region.

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `^\S[\S]*$`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "Sites": [
    {
      "AccountId": "string",
      "Description": "string",
      "Name": "string",
      "Notes": "string",
      "OperatingAddressCity": "string",
      "OperatingAddressCountryCode": "string",
      "OperatingAddressStateOrRegion": "string",
      "RackPhysicalProperties": {
        "FiberOpticCableType": "string",
        "MaximumSupportedWeightLbs": "string",
        "OpticalStandard": "string",
        "PowerConnector": "string",
        "PowerDrawKva": "string",
        "PowerFeedDrop": "string",
        "PowerPhase": "string",
        "UplinkCount": "string",
        "UplinkGbps": "string"
      }
    },
  ],
}
```



```
    "SiteArn": "string",
    "SiteId": "string",
    "Tags": {
      "string" : "string"
    }
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: $^(\d+)\#\#(\S+)\$$

Sites

Information about the sites.

Type: Array of [Site](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Lists the tags for the specified resource.

Request Syntax

```
GET /tags/ResourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ResourceArn

The Amazon Resource Name (ARN) of the resource.

Length Constraints: Maximum length of 1011.

Pattern: `^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+\:\d{12}:([a-z\d-]+)/)[a-z]{2,8}-[a-f0-9]{17}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Tags

The resource tags.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z+-._:/$]+`

Value Length Constraints: Maximum length of 256.

Value Pattern: `^[\\S \\n]+$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartCapacityTask

Starts the specified capacity task. You can have one active capacity task for an order.

Request Syntax

```
POST /outposts/OutpostId/capacity HTTP/1.1
Content-type: application/json
```

```
{
  "DryRun": boolean,
  "InstancePools": [
    {
      "Count": number,
      "InstanceType": "string"
    }
  ],
  "OrderId": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

OutpostId

The ID or ARN of the Outposts associated with the specified capacity task.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: $^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ : \d{12} :outpost/)?op-[a-f0-9]{17}\$$

Required: Yes

Request Body

The request accepts the following data in JSON format.

DryRun

You can request a dry run to determine if the instance type and instance size changes is above or below available instance capacity. Requesting a dry run does not make any changes to your plan.

Type: Boolean

Required: No

InstancePools

The instance pools specified in the capacity task.

Type: Array of [InstanceTypeCapacity](#) objects

Required: Yes

OrderId

The ID of the AWS Outposts order associated with the specified capacity task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: oo-[a-f0-9]{17}\$

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CapacityTaskId": "string",
  "CapacityTaskStatus": "string",
  "CompletionDate": number,
  "CreationDate": number,
  "DryRun": boolean,
  "Failed": {
    "Reason": "string",
    "Type": "string"
  }
}
```

```
},
  "LastModifiedDate": number,
  "OrderId": "string",
  "OutpostId": "string",
  "RequestedInstancePools": [
    {
      "Count": number,
      "InstanceType": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CapacityTaskId

ID of the capacity task that you want to start.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `^cap-[a-f0-9]{17}$`

CapacityTaskStatus

Status of the specified capacity task.

Type: String

Valid Values: REQUESTED | IN_PROGRESS | FAILED | COMPLETED | CANCELLED

CompletionDate

Date that the specified capacity task ran successfully.

Type: Timestamp

CreationDate

Date that the specified capacity task was created.

Type: Timestamp

DryRun

Results of the dry run showing if the specified capacity task is above or below the available instance capacity.

Type: Boolean

Failed

Reason that the specified capacity task failed.

Type: [CapacityTaskFailure](#) object

LastModifiedDate

Date that the specified capacity task was last modified.

Type: Timestamp

OrderId

ID of the AWS Outposts order of the host associated with the capacity task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: oo-[a-f0-9]{17}\$

OutpostId

ID of the Outpost associated with the capacity task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: ^(arn:aws([a-z-]+)? :outposts : [a-z\d-]+ : \d{12} :outpost/)?op-[a-f0-9]{17}\$

RequestedInstancePools

List of the instance pools requested in the specified capacity task.

Type: Array of [InstanceTypeCapacity](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartConnection

Note

AWS uses this action to install Outpost servers.

Starts the connection required for Outpost server installation.

Use CloudTrail to monitor this action or AWS managed policy for AWS Outposts to secure it. For more information, see [AWS managed policies for AWS Outposts](#) and [Logging AWS Outposts API calls with AWS CloudTrail](#) in the *AWS Outposts User Guide*.

Request Syntax

```
POST /connections HTTP/1.1
Content-type: application/json

{
  "AssetId": "string",
  "ClientPublicKey": "string",
  "DeviceSerialNumber": "string",
  "NetworkInterfaceDeviceIndex": number
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

AssetId

The ID of the Outpost server.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: $^(\backslash w+)\$$

Required: Yes

ClientPublicKey

The public key of the client.

Type: String

Length Constraints: Fixed length of 44.

Pattern: $^[a-zA-Z0-9/+]{43}=\$$

Required: Yes

DeviceSerialNumber

The serial number of the dongle.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: $^(\backslash w+)\$$

Required: No

NetworkInterfaceDeviceIndex

The device index of the network interface on the Outpost server.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 1.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"ConnectionId": "string",  
"UnderlayIpAddress": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ConnectionId](#)

The ID of the connection.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^[a-zA-Z0-9+/=]{1,1024}$`

[UnderlayIpAddress](#)

The underlay IP address.

Type: String

Length Constraints: Minimum length of 7. Maximum length of 15.

Pattern: `^([\d]{1,3}\.){3}[\d]{1,3}$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Adds tags to the specified resource.

Request Syntax

```
POST /tags/ResourceArn HTTP/1.1
Content-type: application/json
```

```
{
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

ResourceArn

The Amazon Resource Name (ARN) of the resource.

Length Constraints: Maximum length of 1011.

Pattern: `^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+:\d{12}:([a-z\d-]+)/)[a-z]{2,8}-[a-f0-9]{17}$`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Tags

The tags to add to the resource.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z+-. _:/]+$`

Value Length Constraints: Maximum length of 256.

Value Pattern: `^[\\S \\n]+$`

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Removes tags from the specified resource.

Request Syntax

```
DELETE /tags/ResourceArn?tagKeys=TagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ResourceArn

The Amazon Resource Name (ARN) of the resource.

Length Constraints: Maximum length of 1011.

Pattern: `^(arn:aws([a-z-]+)?outposts:[a-z\d-]+:\d{12}:([a-z\d-]+)/)[a-z]{2,8}-[a-f0-9]{17}$`

Required: Yes

TagKeys

The tag keys.

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^(?!aws:)[a-zA-Z+-. _:/]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateOutpost

Updates an Outpost.

Request Syntax

```
PATCH /outposts/OutpostId HTTP/1.1
Content-type: application/json

{
  "Description": "string",
  "Name": "string",
  "SupportedHardwareType": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

OutpostId

The ID or ARN of the Outpost.

Note

Despite the parameter name, you can make the request with an ARN. The parameter name is `OutpostId` for backward compatibility.

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+:\d{12}:outpost/)?op-[a-f0-9]{17}$`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Description

The description of the Outpost.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Pattern: `^\[\\S]*$`

Required: No

Name

The name of the Outpost.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^\[\\S]+$`

Required: No

SupportedHardwareType

The type of hardware for this Outpost.

Type: String

Valid Values: RACK | SERVER

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Outpost": {
    "AvailabilityZone": "string",
    "AvailabilityZoneId": "string",
```

```
"Description": "string",
"LifecycleStatus": "string",
"Name": "string",
"OutpostArn": "string",
"OutpostId": "string",
"OwnerId": "string",
"SiteArn": "string",
"SiteId": "string",
"SupportedHardwareType": "string",
"Tags": {
  "string" : "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Outpost

Information about an Outpost.

Type: [Outpost](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateSite

Updates the specified site.

Request Syntax

```
PATCH /sites/SiteId HTTP/1.1
Content-type: application/json

{
  "Description": "string",
  "Name": "string",
  "Notes": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

SiteId

The ID or the Amazon Resource Name (ARN) of the site.

Note

Despite the parameter name, you can make the request with an ARN. The parameter name is `SiteId` for backward compatibility.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+\ :d{12}:site/)?(os-[a-f0-9]{17})$`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Description

The description of the site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1001.

Pattern: `^[\\S]+$`

Required: No

Name

The name of the site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `^[\\S]+$`

Required: No

Notes

Notes about a site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `^[\\S \\n]+$`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"Site": {
  "AccountId": "string",
  "Description": "string",
  "Name": "string",
  "Notes": "string",
  "OperatingAddressCity": "string",
  "OperatingAddressCountryCode": "string",
  "OperatingAddressStateOrRegion": "string",
  "RackPhysicalProperties": {
    "FiberOpticCableType": "string",
    "MaximumSupportedWeightLbs": "string",
    "OpticalStandard": "string",
    "PowerConnector": "string",
    "PowerDrawKva": "string",
    "PowerFeedDrop": "string",
    "PowerPhase": "string",
    "UplinkCount": "string",
    "UplinkGbps": "string"
  },
  "SiteArn": "string",
  "SiteId": "string",
  "Tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Site

Information about a site.

Type: [Site](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateSiteAddress

Updates the address of the specified site.

You can't update a site address if there is an order in progress. You must wait for the order to complete or cancel the order.

You can update the operating address before you place an order at the site, or after all Outposts that belong to the site have been deactivated.

Request Syntax

```
PUT /sites/SiteId/address HTTP/1.1
Content-type: application/json

{
  "Address": {
    "AddressLine1": "string",
    "AddressLine2": "string",
    "AddressLine3": "string",
    "City": "string",
    "ContactName": "string",
    "ContactPhoneNumber": "string",
    "CountryCode": "string",
    "DistrictOrCounty": "string",
    "Municipality": "string",
    "PostalCode": "string",
    "StateOrRegion": "string"
  },
  "AddressType": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

SiteId

The ID or the Amazon Resource Name (ARN) of the site.

Note

Despite the parameter name, you can make the request with an ARN. The parameter name is `SiteId` for backward compatibility.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^(arn:aws([a-z-]+)? :outposts:[a-z\d-]+ :d{12}:site/)?(os-[a-f0-9]{17})$`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Address

The address for the site.

Type: [Address](#) object

Required: Yes

AddressType

The type of the address.

Type: String

Valid Values: SHIPPING_ADDRESS | OPERATING_ADDRESS

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```



```
"Address": {
  "AddressLine1": "string",
  "AddressLine2": "string",
  "AddressLine3": "string",
  "City": "string",
  "ContactName": "string",
  "ContactPhoneNumber": "string",
  "CountryCode": "string",
  "DistrictOrCounty": "string",
  "Municipality": "string",
  "PostalCode": "string",
  "StateOrRegion": "string"
},
"AddressType": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Address

Information about an address.

Type: [Address](#) object

AddressType

The type of the address.

Type: String

Valid Values: SHIPPING_ADDRESS | OPERATING_ADDRESS

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateSiteRackPhysicalProperties

Update the physical and logistical details for a rack at a site. For more information about hardware requirements for racks, see [Network readiness checklist](#) in the AWS Outposts User Guide.

To update a rack at a site with an order of IN_PROGRESS, you must wait for the order to complete or cancel the order.

Request Syntax

```
PATCH /sites/SiteId/rackPhysicalProperties HTTP/1.1
Content-type: application/json
```

```
{
  "FiberOpticCableType": "string",
  "MaximumSupportedWeightLbs": "string",
  "OpticalStandard": "string",
  "PowerConnector": "string",
  "PowerDrawKva": "string",
  "PowerFeedDrop": "string",
  "PowerPhase": "string",
  "UplinkCount": "string",
  "UplinkGbps": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

SiteId

The ID or the Amazon Resource Name (ARN) of the site.

Note

Despite the parameter name, you can make the request with an ARN. The parameter name is `SiteId` for backward compatibility.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^(arn:aws([a-z-]+)?outposts:[a-z\d-]+:\d{12}:site/)?(os-[a-f0-9]{17})$`

Required: Yes

Request Body

The request accepts the following data in JSON format.

FiberOpticCableType

The type of fiber that you will use to attach the Outpost to your network.

Type: String

Valid Values: SINGLE_MODE | MULTI_MODE

Required: No

MaximumSupportedWeightLbs

The maximum rack weight that this site can support. NO_LIMIT is over 2000lbs.

Type: String

Valid Values: NO_LIMIT | MAX_1400_LBS | MAX_1600_LBS | MAX_1800_LBS | MAX_2000_LBS

Required: No

OpticalStandard

The type of optical standard that you will use to attach the Outpost to your network. This field is dependent on uplink speed, fiber type, and distance to the upstream device. For more information about networking requirements for racks, see [Network](#) in the AWS Outposts User Guide.

- OPTIC_10GBASE_SR: 10GBASE-SR
- OPTIC_10GBASE_IR: 10GBASE-IR
- OPTIC_10GBASE_LR: 10GBASE-LR
- OPTIC_40GBASE_SR: 40GBASE-SR

- OPTIC_40GBASE_ESR: 40GBASE-ESR
- OPTIC_40GBASE_IR4_LR4L: 40GBASE-IR (LR4L)
- OPTIC_40GBASE_LR4: 40GBASE-LR4
- OPTIC_100GBASE_SR4: 100GBASE-SR4
- OPTIC_100GBASE_CWDM4: 100GBASE-CWDM4
- OPTIC_100GBASE_LR4: 100GBASE-LR4
- OPTIC_100G_PSM4_MSA: 100G PSM4 MSA
- OPTIC_1000BASE_LX: 1000Base-LX
- OPTIC_1000BASE_SX : 1000Base-SX

Type: String

Valid Values: OPTIC_10GBASE_SR | OPTIC_10GBASE_IR | OPTIC_10GBASE_LR
| OPTIC_40GBASE_SR | OPTIC_40GBASE_ESR | OPTIC_40GBASE_IR4_LR4L
| OPTIC_40GBASE_LR4 | OPTIC_100GBASE_SR4 | OPTIC_100GBASE_CWDM4
| OPTIC_100GBASE_LR4 | OPTIC_100G_PSM4_MSA | OPTIC_1000BASE_LX |
OPTIC_1000BASE_SX

Required: No

PowerConnector

The power connector that AWS should plan to provide for connections to the hardware. Note the correlation between `PowerPhase` and `PowerConnector`.

- Single-phase AC feed
 - **L6-30P** – (common in US); 30A; single phase
 - **IEC309 (blue)** – P+N+E, 6hr; 32 A; single phase
- Three-phase AC feed
 - **AH530P7W (red)** – 3P+N+E, 7hr; 30A; three phase
 - **AH532P6W (red)** – 3P+N+E, 6hr; 32A; three phase

Type: String

Valid Values: L6_30P | IEC309 | AH530P7W | AH532P6W

Required: No

PowerDrawKva

The power draw, in kVA, available at the hardware placement position for the rack.

Type: String

Valid Values: POWER_5_KVA | POWER_10_KVA | POWER_15_KVA | POWER_30_KVA

Required: No

PowerFeedDrop

Indicates whether the power feed comes above or below the rack.

Type: String

Valid Values: ABOVE_RACK | BELOW_RACK

Required: No

PowerPhase

The power option that you can provide for hardware.

- Single-phase AC feed: 200 V to 277 V, 50 Hz or 60 Hz
- Three-phase AC feed: 346 V to 480 V, 50 Hz or 60 Hz

Type: String

Valid Values: SINGLE_PHASE | THREE_PHASE

Required: No

UplinkCount

Racks come with two Outpost network devices. Depending on the supported uplink speed at the site, the Outpost network devices provide a variable number of uplinks. Specify the number of uplinks for each Outpost network device that you intend to use to connect the rack to your network. Note the correlation between UplinkGbps and UplinkCount.

- 1Gbps - Uplinks available: 1, 2, 4, 6, 8
- 10Gbps - Uplinks available: 1, 2, 4, 8, 12, 16
- 40 and 100 Gbps- Uplinks available: 1, 2, 4

Type: String

Valid Values: UPLINK_COUNT_1 | UPLINK_COUNT_2 | UPLINK_COUNT_3 |
UPLINK_COUNT_4 | UPLINK_COUNT_5 | UPLINK_COUNT_6 | UPLINK_COUNT_7 |
UPLINK_COUNT_8 | UPLINK_COUNT_12 | UPLINK_COUNT_16

Required: No

UplinkGbps

The uplink speed the rack should support for the connection to the Region.

Type: String

Valid Values: UPLINK_1G | UPLINK_10G | UPLINK_40G | UPLINK_100G

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Site": {
    "AccountId": "string",
    "Description": "string",
    "Name": "string",
    "Notes": "string",
    "OperatingAddressCity": "string",
    "OperatingAddressCountryCode": "string",
    "OperatingAddressStateOrRegion": "string",
    "RackPhysicalProperties": {
      "FiberOpticCableType": "string",
      "MaximumSupportedWeightLbs": "string",
      "OpticalStandard": "string",
      "PowerConnector": "string",
      "PowerDrawKva": "string",
      "PowerFeedDrop": "string",
      "PowerPhase": "string",
      "UplinkCount": "string",
      "UplinkGbps": "string"
    },
    "SiteArn": "string",
    "SiteId": "string",
```

```
    "Tags": {  
      "string" : "string"  
    }  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Site

Information about a site.

Type: [Site](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have permission to perform this operation.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerError

An internal error has occurred.

HTTP Status Code: 500

NotFoundException

The specified request is not valid.

HTTP Status Code: 404

ValidationException

A parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS Outposts API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [Address](#)
- [AssetInfo](#)
- [AssetLocation](#)
- [CapacityTaskFailure](#)
- [CapacityTaskSummary](#)
- [CatalogItem](#)
- [ComputeAttributes](#)
- [ConnectionDetails](#)
- [EC2Capacity](#)
- [InstanceTypeCapacity](#)
- [InstanceTypeItem](#)
- [LineItem](#)
- [LineItemAssetInformation](#)
- [LineItemRequest](#)
- [Order](#)
- [OrderSummary](#)
- [Outpost](#)
- [RackPhysicalProperties](#)
- [ShipmentInformation](#)
- [Site](#)

Address

Information about an address.

Contents

AddressLine1

The first line of the address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^\S[\S]*$`

Required: Yes

City

The city for the address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `^\S[\S]*$`

Required: Yes

CountryCode

The ISO-3166 two-letter country code for the address.

Type: String

Length Constraints: Fixed length of 2.

Pattern: `^[A-Z]{2}$`

Required: Yes

PostalCode

The postal code for the address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `^[a-zA-Z0-9 -]+$`

Required: Yes

StateOrRegion

The state for the address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `^\S[\S]*$`

Required: Yes

AddressLine2

The second line of the address.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 60.

Pattern: `^\S[\S]*$`

Required: No

AddressLine3

The third line of the address.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 60.

Pattern: `^\S[\S]*$`

Required: No

ContactName

The name of the contact.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^\S[\S]*$`

Required: No

ContactPhoneNumber

The phone number of the contact.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `^\S[\S]+$`

Required: No

DistrictOrCounty

The district or county for the address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 60.

Pattern: `^\S[\S]*`

Required: No

Municipality

The municipality for the address.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 180.

Pattern: `^\S[\S]*$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssetInfo

Information about hardware assets.

Contents

AssetId

The ID of the asset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: $^{\wedge}(\backslash w^{+})\$$

Required: No

AssetLocation

The position of an asset in a rack.

Type: [AssetLocation](#) object

Required: No

AssetType

The type of the asset.

Type: String

Valid Values: COMPUTE

Required: No

ComputeAttributes

Information about compute hardware assets.

Type: [ComputeAttributes](#) object

Required: No

RackId

The rack ID of the asset.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 20.

Pattern: `^[\\S \\n]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssetLocation

Information about the position of the asset in a rack.

Contents

RackElevation

The position of an asset in a rack measured in rack units.

Type: Float

Valid Range: Minimum value of 0. Maximum value of 99.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CapacityTaskFailure

The capacity tasks that failed.

Contents

Reason

The reason that the specified capacity task failed.

Type: String

Length Constraints: Maximum length of 128.

Required: Yes

Type

The type of failure.

Type: String

Valid Values: UNSUPPORTED_CAPACITY_CONFIGURATION

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CapacityTaskSummary

The summary of the capacity task.

Contents

CapacityTaskId

The ID of the specified capacity task.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `^cap-[a-f0-9]{17}$`

Required: No

CapacityTaskStatus

The status of the capacity task.

Type: String

Valid Values: REQUESTED | IN_PROGRESS | FAILED | COMPLETED | CANCELLED

Required: No

CompletionDate

The date that the specified capacity task successfully ran.

Type: Timestamp

Required: No

CreationDate

The date that the specified capacity task was created.

Type: Timestamp

Required: No

LastModifiedDate

The date that the specified capacity was last modified.

Type: Timestamp

Required: No

OrderId

The ID of the AWS Outposts order of the host associated with the capacity task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: oo-[a-f0-9]{17}\$

Required: No

OutpostId

The ID of the Outpost associated with the specified capacity task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: ^(arn:aws([a-z-]+)? :outposts : [a-z\d-]+ : \d{12} :outpost/)?op-[a-f0-9]{17}\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CatalogItem

Information about a catalog item.

Contents

CatalogItemId

The ID of the catalog item.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: `OR-[A-Z0-9]{7}`

Required: No

EC2Capacities

Information about the EC2 capacity of an item.

Type: Array of [EC2Capacity](#) objects

Required: No

ItemStatus

The status of a catalog item.

Type: String

Valid Values: AVAILABLE | DISCONTINUED

Required: No

PowerKva

Information about the power draw of an item.

Type: Float

Required: No

SupportedStorage

The supported storage options for the catalog item.

Type: Array of strings

Valid Values: EBS | S3

Required: No

SupportedUplinkGbps

The uplink speed this catalog item requires for the connection to the Region.

Type: Array of integers

Required: No

WeightLbs

The weight of the item in pounds.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ComputeAttributes

Information about compute hardware assets.

Contents

HostId

The host ID of the Dedicated Host on the asset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `^[A-Za-z0-9-]*$`

Required: No

InstanceFamilies

A list of the names of instance families that are currently associated with a given asset.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `^(?:.{1,200}/)?(?:[a-z0-9- _A-Z])+$`

Required: No

State

The state.

- **ACTIVE** - The asset is available and can provide capacity for new compute resources.
- **ISOLATED** - The asset is undergoing maintenance and can't provide capacity for new compute resources. Existing compute resources on the asset are not affected.
- **RETIRING** - The underlying hardware for the asset is degraded. Capacity for new compute resources is reduced. AWS sends notifications for resources that must be stopped before the asset can be replaced.

Type: String

Valid Values: ACTIVE | ISOLATED | RETIRING

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ConnectionDetails

Information about a connection.

Contents

AllowedIps

The allowed IP addresses.

Type: Array of strings

Length Constraints: Minimum length of 9. Maximum length of 18.

Pattern: `^([\d-]{1,3}\.){3}[\d-]{1,3}/[\d-]{1,2}$`

Required: No

ClientPublicKey

The public key of the client.

Type: String

Length Constraints: Fixed length of 44.

Pattern: `^[a-zA-Z\d-9/+]{44}=$`

Required: No

ClientTunnelAddress

The client tunnel address.

Type: String

Length Constraints: Minimum length of 9. Maximum length of 18.

Pattern: `^([\d-]{1,3}\.){3}[\d-]{1,3}/[\d-]{1,2}$`

Required: No

ServerEndpoint

The endpoint for the server.

Type: String

Length Constraints: Minimum length of 9. Maximum length of 21.

Pattern: `^([\d-]{1,3}\.){3}[\d-]{1,3}:[\d-]{1,5}$`

Required: No

ServerPublicKey

The public key of the server.

Type: String

Length Constraints: Fixed length of 44.

Pattern: `^[a-zA-Z\d-9/+]{44}=$`

Required: No

ServerTunnelAddress

The server tunnel address.

Type: String

Length Constraints: Minimum length of 9. Maximum length of 18.

Pattern: `^([\d-]{1,3}\.){3}[\d-]{1,3}/[\d-]{1,2}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EC2Capacity

Information about EC2 capacity.

Contents

Family

The family of the EC2 capacity.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: [a-z0-9]+

Required: No

MaxSize

The maximum size of the EC2 capacity.

Type: String

Required: No

Quantity

The quantity of the EC2 capacity.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceTypeCapacity

The instance type that you specify determines the combination of CPU, memory, storage, and networking capacity.

Contents

Count

The number of instances for the specified instance type.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 9999.

Required: Yes

InstanceType

The instance type of the hosts.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-z0-9\-\.\]+\.[a-z0-9\-\]+$`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceTypeItem

Information about an instance type.

Contents

InstanceType

The instance type.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LineItem

Information about a line item.

Contents

AssetInformationList

Information about assets.

Type: Array of [LineItemAssetInformation](#) objects

Required: No

CatalogItemId

The ID of the catalog item.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: OR- [A-Z0-9]{7}

Required: No

LineItemId

The ID of the line item.

Type: String

Pattern: ooi- [a-f0-9]{17}

Required: No

PreviousLineItemId

The ID of the previous line item.

Type: String

Pattern: ooi- [a-f0-9]{17}

Required: No

PreviousOrderId

The ID of the previous order.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: oo-[a-f0-9]{17}\$

Required: No

Quantity

The quantity of the line item.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

ShipmentInformation

Information about a line item shipment.

Type: [ShipmentInformation](#) object

Required: No

Status

The status of the line item.

Type: String

Valid Values: PREPARING | BUILDING | SHIPPED | DELIVERED | INSTALLING |
INSTALLED | ERROR | CANCELLED | REPLACED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LineItemAssetInformation

Information about a line item asset.

Contents

AssetId

The ID of the asset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^(\w+)$`

Required: No

MacAddressList

The MAC addresses of the asset.

Type: Array of strings

Length Constraints: Fixed length of 17.

Pattern: `^([\0-9A-Fa-f]{2}[:-]){5}([\0-9A-Fa-f]{2})$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LineItemRequest

Information about a line item request.

Contents

CatalogItemId

The ID of the catalog item.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: OR-[A-Z0-9]{7}

Required: No

Quantity

The quantity of a line item request.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Order

Information about an order.

Contents

LineItems

The line items for the order

Type: Array of [LineItem](#) objects

Required: No

OrderFulfilledDate

The fulfillment date of the order.

Type: Timestamp

Required: No

OrderId

The ID of the order.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: oo-[a-f0-9]{17}\$

Required: No

OrderSubmissionDate

The submission date for the order.

Type: Timestamp

Required: No

OrderType

The type of order.

Type: String

Valid Values: OUTPOST | REPLACEMENT

Required: No

OutpostId

The ID of the Outpost in the order.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `^op-[a-f0-9]{17}$`

Required: No

PaymentOption

The payment option for the order.

Type: String

Valid Values: ALL_UPFRONT | NO_UPFRONT | PARTIAL_UPFRONT

Required: No

PaymentTerm

The payment term.

Type: String

Valid Values: THREE_YEARS | ONE_YEAR


Required: No

Status

The status of the order.

- PREPARING - Order is received and being prepared.
- IN_PROGRESS - Order is either being built, shipped, or installed. To get more details, see the line item status.
- COMPLETED - Order is complete.

- CANCELLED - Order is cancelled.
- ERROR - Customer should contact support.

 **Note**

The following status are deprecated: RECEIVED, PENDING, PROCESSING, INSTALLING, and FULFILLED.

Type: String

Valid Values: RECEIVED | PENDING | PROCESSING | INSTALLING | FULFILLED | CANCELLED | PREPARING | IN_PROGRESS | COMPLETED | ERROR

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OrderSummary

A summary of line items in your order.

Contents

LineItemCountsByStatus

The status of all line items in the order.

Type: String to integer map

Valid Keys: PREPARING | BUILDING | SHIPPED | DELIVERED | INSTALLING |
INSTALLED | ERROR | CANCELLED | REPLACED

Valid Range: Minimum value of 1.

Required: No

OrderFulfilledDate

The fulfilment date for the order.

Type: Timestamp

Required: No

OrderId

The ID of the order.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: oo-[a-f0-9]{17}\$

Required: No

OrderSubmissionDate

The submission date for the order.

Type: Timestamp

Required: No

OrderType

The type of order.

Type: String

Valid Values: OUTPOST | REPLACEMENT

Required: No

OutpostId

The ID of the Outpost.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `^op-[a-f0-9]{17}$`

Required: No

Status

The status of the order.

- PREPARING - Order is received and is being prepared.
- IN_PROGRESS - Order is either being built, shipped, or installed. For more information, see the `LineItem` status.
- COMPLETED - Order is complete.
- CANCELLED - Order is cancelled.
- ERROR - Customer should contact support.

Note

The following statuses are deprecated: RECEIVED, PENDING, PROCESSING, INSTALLING, and FULFILLED.

Type: String

Valid Values: RECEIVED | PENDING | PROCESSING | INSTALLING | FULFILLED | CANCELLED | PREPARING | IN_PROGRESS | COMPLETED | ERROR

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Outpost

Information about an Outpost.

Contents

AvailabilityZone

The Availability Zone.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `^[a-zA-Z]{1,3}([a-zA-Z]+)?(\d+[a-zA-Z])?$`

Required: No

AvailabilityZoneId

The ID of the Availability Zone.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z]+\d-[a-zA-Z]+\d$`

Required: No

Description

The description of the Outpost.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Pattern: `^[\\S]*$`

Required: No

LifeCycleStatus

The life cycle status.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `^[A-Za-z]+$`

Required: No

Name

The name of the Outpost.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[\S]+$`

Required: No

OutpostArn

The Amazon Resource Name (ARN) of the Outpost.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:outpost/op-[a-f0-9]{17}$`

Required: No

OutpostId

The ID of the Outpost.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 180.

Pattern: `^(arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:outpost/)?op-[a-f0-9]{17}$`

Required: No

OwnerId

The AWS account ID of the Outpost owner.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d{12}`

Required: No

SiteArn

The Amazon Resource Name (ARN) of the site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:site/(os-[a-f0-9]{17})$`

Required: No

SiteId

The ID of the site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^(arn:aws([a-z-]+)?:outposts:[a-z\d-]+:\d{12}:site/)?(os-[a-f0-9]{17})$`

Required: No

SupportedHardwareType

The hardware type.

Type: String

Valid Values: RACK | SERVER

Required: No

Tags

The Outpost tags.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z+--=._:/]+$`

Value Length Constraints: Maximum length of 256.

Value Pattern: `^[\\S \\n]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RackPhysicalProperties

Information about the physical and logistical details for racks at sites. For more information about hardware requirements for racks, see [Network readiness checklist](#) in the AWS Outposts User Guide.

Contents

FiberOpticCableType

The type of fiber used to attach the Outpost to the network.

Type: String

Valid Values: SINGLE_MODE | MULTI_MODE

Required: No

MaximumSupportedWeightLbs

The maximum rack weight that this site can support. NO_LIMIT is over 2000 lbs (907 kg).

Type: String

Valid Values: NO_LIMIT | MAX_1400_LBS | MAX_1600_LBS | MAX_1800_LBS | MAX_2000_LBS

Required: No

OpticalStandard

The type of optical standard used to attach the Outpost to the network. This field is dependent on uplink speed, fiber type, and distance to the upstream device. For more information about networking requirements for racks, see [Network](#) in the AWS Outposts User Guide.

Type: String

Valid Values: OPTIC_10GBASE_SR | OPTIC_10GBASE_IR | OPTIC_10GBASE_LR | OPTIC_40GBASE_SR | OPTIC_40GBASE_ESR | OPTIC_40GBASE_IR4_LR4L | OPTIC_40GBASE_LR4 | OPTIC_100GBASE_SR4 | OPTIC_100GBASE_CWDM4 | OPTIC_100GBASE_LR4 | OPTIC_100G_PSM4_MSA | OPTIC_1000BASE_LX | OPTIC_1000BASE_SX

Required: No

PowerConnector

The power connector for the hardware.

Type: String

Valid Values: L6_30P | IEC309 | AH530P7W | AH532P6W

Required: No

PowerDrawKva

The power draw available at the hardware placement position for the rack.

Type: String

Valid Values: POWER_5_KVA | POWER_10_KVA | POWER_15_KVA | POWER_30_KVA

Required: No

PowerFeedDrop

The position of the power feed.

Type: String

Valid Values: ABOVE_RACK | BELOW_RACK

Required: No

PowerPhase

The power option that you can provide for hardware.

Type: String

Valid Values: SINGLE_PHASE | THREE_PHASE

Required: No

UplinkCount

The number of uplinks each Outpost network device.

Type: String

Valid Values: UPLINK_COUNT_1 | UPLINK_COUNT_2 | UPLINK_COUNT_3 |
UPLINK_COUNT_4 | UPLINK_COUNT_5 | UPLINK_COUNT_6 | UPLINK_COUNT_7 |
UPLINK_COUNT_8 | UPLINK_COUNT_12 | UPLINK_COUNT_16

Required: No

UplinkGbps

The uplink speed the rack supports for the connection to the Region.

Type: String

Valid Values: UPLINK_1G | UPLINK_10G | UPLINK_40G | UPLINK_100G

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ShipmentInformation

Information about a line item shipment.

Contents

ShipmentCarrier

The carrier of the shipment.

Type: String

Valid Values: DHL | DBS | FEDEX | UPS | EXPEDITORS

Required: No

ShipmentTrackingNumber

The tracking number of the shipment.

Type: String

Length Constraints: Minimum length of 6. Maximum length of 42.

Pattern: `^[a-zA-Z0-9]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Site

Information about a site.

Contents

AccountId

The ID of the AWS account.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d{12}`

Required: No

Description

The description of the site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1001.

Pattern: `^[\S]+$`

Required: No

Name

The name of the site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `^[\S]+$`

Required: No

Notes

Notes about a site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `^\S \n]+$`

Required: No

OperatingAddressCity

City where the hardware is installed and powered on.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `^\S[\S]*$`

Required: No

OperatingAddressCountryCode

The ISO-3166 two-letter country code where the hardware is installed and powered on.

Type: String

Length Constraints: Fixed length of 2.

Pattern: `^[A-Z]{2}$`

Required: No

OperatingAddressStateOrRegion

State or region where the hardware is installed and powered on.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `^\S[\S]*$`

Required: No

RackPhysicalProperties

Information about the physical and logistical details for a rack at the site.

Type: [RackPhysicalProperties](#) object

Required: No

SiteArn

The Amazon Resource Name (ARN) of the site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^arn:aws([a-z-]+):outposts:[a-z\d-]+:\d{12}:site/(os-[a-f0-9]{17})$`

Required: No

SiteId

The ID of the site.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^(arn:aws([a-z-]+):outposts:[a-z\d-]+:\d{12}:site/)?(os-[a-f0-9]{17})$`

Required: No

Tags

The site tags.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z+-._:/$]+$`

Value Length Constraints: Maximum length of 256.

Value Pattern: `^[\\S \\n]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request is expired

HTTP Status Code: 403

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 403

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

MalformedHttpRequestException

Problems with the request at the HTTP level, e.g. we can't decompress the body according to the decompression algorithm specified by the content-encoding.

HTTP Status Code: 400

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 401

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestAbortedException

Convenient exception that can be used when a request is aborted before a reply is sent back (e.g. client closed connection).

HTTP Status Code: 400

RequestEntityTooLargeException

Problems with the request at the HTTP level. The request entity is too large.

HTTP Status Code: 413

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

RequestTimeoutException

Problems with the request at the HTTP level. Reading the Request timed out.

HTTP Status Code: 408

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

UnrecognizedClientException

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

UnknownOperationException

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 404

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400