



API Reference

AWS Panorama



API Version 2019-07-24

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS Panorama: API Reference

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
CreateApplicationInstance	4
Request Syntax	4
URI Request Parameters	4
Request Body	4
Response Syntax	6
Response Elements	7
Errors	7
See Also	8
CreateJobForDevices	9
Request Syntax	9
URI Request Parameters	9
Request Body	9
Response Syntax	10
Response Elements	10
Errors	11
See Also	11
CreateNodeFromTemplateJob	13
Request Syntax	13
URI Request Parameters	13
Request Body	13
Response Syntax	15
Response Elements	15
Errors	16
See Also	16
CreatePackage	18
Request Syntax	18
URI Request Parameters	18
Request Body	18
Response Syntax	19
Response Elements	19
Errors	20
See Also	21

CreatePackageImportJob	22
Request Syntax	22
URI Request Parameters	22
Request Body	23
Response Syntax	24
Response Elements	24
Errors	24
See Also	25
DeleteDevice	26
Request Syntax	26
URI Request Parameters	26
Request Body	26
Response Syntax	26
Response Elements	26
Errors	27
See Also	28
DeletePackage	29
Request Syntax	29
URI Request Parameters	29
Request Body	29
Response Syntax	29
Response Elements	30
Errors	30
See Also	30
DeregisterPackageVersion	32
Request Syntax	32
URI Request Parameters	32
Request Body	33
Response Syntax	33
Response Elements	33
Errors	33
See Also	34
DescribeApplicationInstance	35
Request Syntax	35
URI Request Parameters	35
Request Body	35

Response Syntax	35
Response Elements	36
Errors	39
See Also	40
DescribeApplicationInstanceDetails	41
Request Syntax	41
URI Request Parameters	41
Request Body	41
Response Syntax	41
Response Elements	42
Errors	43
See Also	44
DescribeDevice	45
Request Syntax	45
URI Request Parameters	45
Request Body	45
Response Syntax	45
Response Elements	47
Errors	51
See Also	51
DescribeDeviceJob	53
Request Syntax	53
URI Request Parameters	53
Request Body	53
Response Syntax	53
Response Elements	54
Errors	55
See Also	56
DescribeNode	58
Request Syntax	58
URI Request Parameters	58
Request Body	58
Response Syntax	58
Response Elements	59
Errors	62
See Also	63

DescribeNodeFromTemplateJob	64
Request Syntax	64
URI Request Parameters	64
Request Body	64
Response Syntax	64
Response Elements	65
Errors	67
See Also	68
DescribePackage	69
Request Syntax	69
URI Request Parameters	69
Request Body	69
Response Syntax	69
Response Elements	70
Errors	72
See Also	72
DescribePackageImportJob	74
Request Syntax	74
URI Request Parameters	74
Request Body	74
Response Syntax	74
Response Elements	75
Errors	77
See Also	78
DescribePackageVersion	79
Request Syntax	79
URI Request Parameters	79
Request Body	80
Response Syntax	80
Response Elements	80
Errors	82
See Also	83
ListApplicationInstanceDependencies	84
Request Syntax	84
URI Request Parameters	84
Request Body	84

Response Syntax	85
Response Elements	85
Errors	85
See Also	86
ListApplicationInstanceNodeInstances	87
Request Syntax	87
URI Request Parameters	87
Request Body	87
Response Syntax	88
Response Elements	88
Errors	89
See Also	89
ListApplicationInstances	90
Request Syntax	90
URI Request Parameters	90
Request Body	91
Response Syntax	91
Response Elements	91
Errors	92
See Also	92
ListDevices	94
Request Syntax	94
URI Request Parameters	94
Request Body	95
Response Syntax	95
Response Elements	96
Errors	96
See Also	97
ListDevicesJobs	98
Request Syntax	98
URI Request Parameters	98
Request Body	98
Response Syntax	98
Response Elements	99
Errors	99
See Also	100

ListNodeFromTemplateJobs	101
Request Syntax	101
URI Request Parameters	101
Request Body	101
Response Syntax	101
Response Elements	102
Errors	102
See Also	103
ListNodes	104
Request Syntax	104
URI Request Parameters	104
Request Body	105
Response Syntax	105
Response Elements	106
Errors	106
See Also	107
ListPackageImportJobs	108
Request Syntax	108
URI Request Parameters	108
Request Body	108
Response Syntax	108
Response Elements	109
Errors	109
See Also	110
ListPackages	111
Request Syntax	111
URI Request Parameters	111
Request Body	111
Response Syntax	111
Response Elements	112
Errors	112
See Also	113
ListTagsForResource	114
Request Syntax	114
URI Request Parameters	114
Request Body	114

Response Syntax	114
Response Elements	114
Errors	115
See Also	115
ProvisionDevice	117
Request Syntax	117
URI Request Parameters	118
Request Body	118
Response Syntax	119
Response Elements	119
Errors	120
See Also	121
RegisterPackageVersion	122
Request Syntax	122
URI Request Parameters	122
Request Body	123
Response Syntax	123
Response Elements	123
Errors	123
See Also	124
RemoveApplicationInstance	125
Request Syntax	125
URI Request Parameters	125
Request Body	125
Response Syntax	125
Response Elements	125
Errors	125
See Also	126
SignalApplicationInstanceNodeInstances	128
Request Syntax	128
URI Request Parameters	128
Request Body	128
Response Syntax	129
Response Elements	129
Errors	129
See Also	130

TagResource	131
Request Syntax	131
URI Request Parameters	131
Request Body	131
Response Syntax	132
Response Elements	132
Errors	132
See Also	132
UntagResource	134
Request Syntax	134
URI Request Parameters	134
Request Body	134
Response Syntax	134
Response Elements	135
Errors	135
See Also	135
UpdateDeviceMetadata	137
Request Syntax	137
URI Request Parameters	137
Request Body	137
Response Syntax	138
Response Elements	138
Errors	138
See Also	139
Data Types	140
AlternateSoftwareMetadata	142
Contents	142
See Also	142
ApplicationInstance	143
Contents	143
See Also	146
ConflictExceptionErrorArgument	147
Contents	147
See Also	147
Device	148
Contents	148

See Also	151
DeviceJob	152
Contents	152
See Also	153
DeviceJobConfig	154
Contents	154
See Also	154
EthernetPayload	155
Contents	155
See Also	155
EthernetStatus	156
Contents	156
See Also	157
Job	158
Contents	158
See Also	158
JobResourceTags	159
Contents	159
See Also	159
LatestDeviceJob	161
Contents	161
See Also	161
ManifestOverridesPayload	163
Contents	163
See Also	163
ManifestPayload	164
Contents	164
See Also	164
NetworkPayload	165
Contents	165
See Also	165
NetworkStatus	166
Contents	166
See Also	166
Node	168
Contents	168

See Also	170
NodeFromTemplateJob	172
Contents	172
See Also	173
NodeInputPort	174
Contents	174
See Also	175
NodeInstance	176
Contents	176
See Also	177
NodeInterface	179
Contents	179
See Also	179
NodeOutputPort	180
Contents	180
See Also	180
NodeSignal	182
Contents	182
See Also	182
NtpPayload	183
Contents	183
See Also	183
NtpStatus	184
Contents	184
See Also	185
OTAJobConfig	186
Contents	186
See Also	186
OutPutS3Location	187
Contents	187
See Also	187
PackagelImportJob	188
Contents	188
See Also	189
PackagelImportJobInputConfig	190
Contents	190

See Also	190
PackageImportJobOutput	191
Contents	191
See Also	192
PackageImportJobOutputConfig	193
Contents	193
See Also	193
PackageListItem	194
Contents	194
See Also	195
PackageObject	196
Contents	196
See Also	197
PackageVersionInputConfig	198
Contents	198
See Also	198
PackageVersionOutputConfig	199
Contents	199
See Also	199
ReportedRuntimeContextState	201
Contents	201
See Also	202
S3Location	203
Contents	203
See Also	204
StaticIpConnectionInfo	205
Contents	205
See Also	206
StorageLocation	207
Contents	207
See Also	208
ValidationExceptionErrorArgument	209
Contents	209
See Also	209
ValidationExceptionField	210
Contents	210

See Also	210
Common Parameters	211
Common Errors	214

Welcome

Overview

This is the *AWS Panorama API Reference*. For an introduction to the service, see [What is AWS Panorama?](#) in the *AWS Panorama Developer Guide*.

This document was last published on July 2, 2024.

Actions

The following actions are supported:

- [CreateApplicationInstance](#)
- [CreateJobForDevices](#)
- [CreateNodeFromTemplateJob](#)
- [CreatePackage](#)
- [CreatePackageImportJob](#)
- [DeleteDevice](#)
- [DeletePackage](#)
- [DeregisterPackageVersion](#)
- [DescribeApplicationInstance](#)
- [DescribeApplicationInstanceDetails](#)
- [DescribeDevice](#)
- [DescribeDeviceJob](#)
- [DescribeNode](#)
- [DescribeNodeFromTemplateJob](#)
- [DescribePackage](#)
- [DescribePackageImportJob](#)
- [DescribePackageVersion](#)
- [ListApplicationInstanceDependencies](#)
- [ListApplicationInstanceNodeInstances](#)
- [ListApplicationInstances](#)
- [ListDevices](#)
- [ListDevicesJobs](#)
- [ListNodeFromTemplateJobs](#)
- [ListNodes](#)
- [ListPackageImportJobs](#)
- [ListPackages](#)
- [ListTagsForResource](#)

- [ProvisionDevice](#)
- [RegisterPackageVersion](#)
- [RemoveApplicationInstance](#)
- [SignalApplicationInstanceNodeInstances](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateDeviceMetadata](#)

CreateApplicationInstance

Creates an application instance and deploys it to a device.

Request Syntax

```
POST /application-instances HTTP/1.1
Content-type: application/json

{
  "ApplicationInstanceIdToReplace": "string",
  "DefaultRuntimeContextDevice": "string",
  "Description": "string",
  "ManifestOverridesPayload": { ... },
  "ManifestPayload": { ... },
  "Name": "string",
  "RuntimeRoleArn": "string",
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ApplicationInstanceIdToReplace

The ID of an application instance to replace with the new instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: No

DefaultRuntimeContextDevice

A device's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: Yes

Description

A description for the application instance.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `^.*$`

Required: No

ManifestOverridesPayload

Setting overrides for the application manifest.

Type: [ManifestOverridesPayload](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

ManifestPayload

The application's manifest document.

Type: [ManifestPayload](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

Name

A name for the application instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: No

RuntimeRoleArn

The ARN of a runtime role for the application instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^arn:[a-z0-9][-\.a-z0-9]{0,62}:iam:[0-9]{12}:role/\.+$`

Required: No

Tags

Tags for the application instance.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^\.+`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `^\.*`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"ApplicationInstanceId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationInstanceId

The application instance's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

InternalServerErrorException

An internal error occurred.

HTTP Status Code: 500

ServiceQuotaExceededException

The request would cause a limit to be exceeded.

HTTP Status Code: 402

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateJobForDevices

Creates a job to run on a device. A job can update a device's software or reboot it.

Request Syntax

```
POST /jobs HTTP/1.1
Content-type: application/json

{
  "DeviceIds": [ "string" ],
  "DeviceJobConfig": {
    "OTAJobConfig": {
      "AllowMajorVersionUpdate": boolean,
      "ImageVersion": "string"
    }
  },
  "JobType": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

DeviceIds

ID of target device.

Type: Array of strings

Array Members: Fixed number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: Yes

DeviceJobConfig

Configuration settings for a software update job.

Type: [DeviceJobConfig](#) object

Required: No

JobType

The type of job to run.

Type: String

Valid Values: OTA | REBOOT

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Jobs": [
    {
      "DeviceId": "string",
      "JobId": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Jobs

A list of jobs.

Type: Array of [Job](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerError

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The target resource was not found.

HTTP Status Code: 404

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateNodeFromTemplateJob

Creates a camera stream node.

Request Syntax

```
POST /packages/template-job HTTP/1.1
Content-type: application/json
```

```
{
  "JobTags": [
    {
      "ResourceType": "string",
      "Tags": {
        "string" : "string"
      }
    }
  ],
  "NodeDescription": "string",
  "NodeName": "string",
  "OutputPackageName": "string",
  "OutputPackageVersion": "string",
  "TemplateParameters": {
    "string" : "string"
  },
  "TemplateType": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

JobTags

Tags for the job.

Type: Array of [JobResourceTags](#) objects

Required: No

NodeDescription

A description for the node.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `^.*$`

Required: No

NodeName

A name for the node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: Yes

OutputPackageName

An output package name for the node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: Yes

OutputPackageVersion

An output package version for the node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^([0-9]+)\.([0-9]+)$`

Required: Yes

TemplateParameters

Template parameters for the node.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 255.

Key Pattern: `^\.+`

Value Length Constraints: Minimum length of 1. Maximum length of 255.

Value Pattern: `^\.+`

Required: Yes

TemplateType

The type of node.

Type: String

Valid Values: RTSP_CAMERA_STREAM

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "JobId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

JobId

The job's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerErrorException

An internal error occurred.

HTTP Status Code: 500

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreatePackage

Creates a package and storage location in an Amazon S3 access point.

Request Syntax

```
POST /packages HTTP/1.1
Content-type: application/json

{
  "PackageName": "string",
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

PackageName

A name for the package.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: Yes

Tags

Tags for the package.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^\.+`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `^\.*`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "PackageId": "string",
  "StorageLocation": {
    "BinaryPrefixLocation": "string",
    "Bucket": "string",
    "GeneratedPrefixLocation": "string",
    "ManifestPrefixLocation": "string",
    "RepoPrefixLocation": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The package's ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

PackageId

The package's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\✓]+`

StorageLocation

The package's storage location.

Type: [StorageLocation](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerError

An internal error occurred.

HTTP Status Code: 500

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreatePackageImportJob

Imports a node package.

Request Syntax

```
POST /packages/import-jobs HTTP/1.1
Content-type: application/json

{
  "ClientToken": "string",
  "InputConfig": {
    "PackageVersionInputConfig": {
      "S3Location": {
        "BucketName": "string",
        "ObjectKey": "string",
        "Region": "string"
      }
    }
  },
  "JobTags": [
    {
      "ResourceType": "string",
      "Tags": {
        "string" : "string"
      }
    }
  ],
  "JobType": "string",
  "OutputConfig": {
    "PackageVersionOutputConfig": {
      "MarkLatest": boolean,
      "PackageName": "string",
      "PackageVersion": "string"
    }
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ClientToken

A client token for the package import job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: Yes

InputConfig

An input config for the package import job.

Type: [PackageImportJobInputConfig](#) object

Required: Yes

JobTags

Tags for the package import job.

Type: Array of [JobResourceTags](#) objects

Required: No

JobType

A job type for the package import job.

Type: String

Valid Values: `NODE_PACKAGE_VERSION` | `MARKETPLACE_NODE_PACKAGE_VERSION`

Required: Yes

OutputConfig

An output config for the package import job.

Type: [PackageImportJobOutputConfig](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "JobId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[JobId](#)

The job's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerErrorException

An internal error occurred.

HTTP Status Code: 500

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteDevice

Deletes a device.

Request Syntax

```
DELETE /devices/DeviceId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

DeviceId

The device's ID.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "DeviceId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DeviceId

The device's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerError

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The target resource was not found.

HTTP Status Code: 404

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeletePackage

Deletes a package.

Note

To delete a package, you need permission to call `s3:DeleteObject` in addition to permissions for the AWS Panorama API.

Request Syntax

```
DELETE /packages/PackageId?ForceDelete=ForceDelete HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ForceDelete

Delete the package even if it has artifacts stored in its access point. Deletes the package's artifacts from Amazon S3.

PackageId

The package's ID.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\✓]+`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerErrorException

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The target resource was not found.

HTTP Status Code: 404

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeregisterPackageVersion

Deregisters a package version.

Request Syntax

```
DELETE /packages/PackageId/versions/PackageVersion/patch/PatchVersion?
OwnerAccount=OwnerAccount&UpdatedLatestPatchVersion=UpdatedLatestPatchVersion HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

OwnerAccount

An owner account.

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: `^[0-9a-z_]+$`

PackageId

A package ID.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\✓]+$`

Required: Yes

PackageVersion

A package version.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^([0-9]+\)\.([0-9]+)$`

Required: Yes

PatchVersion

A patch version.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-z0-9]+$`

Required: Yes

UpdatedLatestPatchVersion

If the version was marked latest, the new version to make as latest.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-z0-9]+$`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerErrorException

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The target resource was not found.

HTTP Status Code: 404

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeApplicationInstance

Returns information about an application instance on a device.

Request Syntax

```
GET /application-instances/ApplicationInstanceId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ApplicationInstanceid

The application instance's ID.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ApplicationInstanceId": "string",
  "ApplicationInstanceIdToReplace": "string",
  "Arn": "string",
  "CreatedTime": number,
  "DefaultRuntimeContextDevice": "string",
  "DefaultRuntimeContextDeviceName": "string",
  "Description": "string",
  "HealthStatus": "string",
```

```
"LastUpdatedTime": number,
"Name": "string",
"RuntimeContextStates": [
  {
    "DesiredState": "string",
    "DeviceReportedStatus": "string",
    "DeviceReportedTime": number,
    "RuntimeContextName": "string"
  }
],
"RuntimeRoleArn": "string",
"Status": "string",
"StatusDescription": "string",
"Tags": {
  "string" : "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationInstanceId

The application instance's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

ApplicationInstanceIdToReplace

The ID of the application instance that this instance replaced.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Arn

The application instance's ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

CreatedTime

When the application instance was created.

Type: Timestamp

DefaultRuntimeContextDevice

The device's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

DefaultRuntimeContextDeviceName

The device's name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Description

The application instance's description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `^.*$`

HealthStatus

The application instance's health status.

Type: String

Valid Values: RUNNING | ERROR | NOT_AVAILABLE

LastUpdatedTime

The application instance was updated.

Type: Timestamp

Name

The application instance's name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

RuntimeContextStates

The application instance's state.

Type: Array of [ReportedRuntimeContextState](#) objects

RuntimeRoleArn

The application instance's runtime role ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^arn:[a-z0-9][-\.a-z0-9]{0,62}:iam:[0-9]{12}:role/\.+$`

Status

The application instance's status.

Type: String

Valid Values: DEPLOYMENT_PENDING | DEPLOYMENT_REQUESTED | DEPLOYMENT_IN_PROGRESS | DEPLOYMENT_ERROR | DEPLOYMENT_SUCCEEDED | REMOVAL_PENDING | REMOVAL_REQUESTED | REMOVAL_IN_PROGRESS | REMOVAL_FAILED | REMOVAL_SUCCEEDED | DEPLOYMENT_FAILED

StatusDescription

The application instance's status description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Tags

The application instance's tags.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^ . +$`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `^ . *$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerErrorException

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The target resource was not found.

HTTP Status Code: 404

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeApplicationInstanceDetails

Returns information about an application instance's configuration manifest.

Request Syntax

```
GET /application-instances/ApplicationInstanceId/details HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ApplicationInstanceId

The application instance's ID.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ApplicationInstanceId": "string",
  "ApplicationInstanceIdToReplace": "string",
  "CreatedTime": number,
  "DefaultRuntimeContextDevice": "string",
  "Description": "string",
  "ManifestOverridesPayload": { ... },
  "ManifestPayload": { ... },
  "Name": "string"
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationInstanceId

The application instance's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

ApplicationInstanceIdToReplace

The ID of the application instance that this instance replaced.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

CreatedTime

When the application instance was created.

Type: Timestamp

DefaultRuntimeContextDevice

The application instance's default runtime context device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Description

The application instance's description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `^.*$`

ManifestOverridesPayload

Parameter overrides for the configuration manifest.

Type: [ManifestOverridesPayload](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

ManifestPayload

The application instance's configuration manifest.

Type: [ManifestPayload](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Name

The application instance's name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerErrorException

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The target resource was not found.

HTTP Status Code: 404

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeDevice

Returns information about a device.

Request Syntax

```
GET /devices/DeviceId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

DeviceId

The device's ID.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AlternateSoftwares": [
    {
      "Version": "string"
    }
  ],
  "Arn": "string",
  "Brand": "string",
  "CreatedTime": number,
  "CurrentNetworkingStatus": {
    "Ethernet0Status": {
```

```
    "ConnectionStatus": "string",
    "HwAddress": "string",
    "IpAddress": "string"
  },
  "Ethernet1Status": {
    "ConnectionStatus": "string",
    "HwAddress": "string",
    "IpAddress": "string"
  },
  "LastUpdatedTime": number,
  "NtpStatus": {
    "ConnectionStatus": "string",
    "IpAddress": "string",
    "NtpServerName": "string"
  }
},
"CurrentSoftware": "string",
"Description": "string",
"DeviceAggregatedStatus": "string",
"DeviceConnectionStatus": "string",
"DeviceId": "string",
"LatestAlternateSoftware": "string",
"LatestDeviceJob": {
  "ImageVersion": "string",
  "JobType": "string",
  "Status": "string"
},
"LatestSoftware": "string",
"LeaseExpirationTime": number,
"Name": "string",
"NetworkingConfiguration": {
  "Ethernet0": {
    "ConnectionType": "string",
    "StaticIpConnectionInfo": {
      "DefaultGateway": "string",
      "Dns": [ "string" ],
      "IpAddress": "string",
      "Mask": "string"
    }
  }
},
  "Ethernet1": {
    "ConnectionType": "string",
    "StaticIpConnectionInfo": {
      "DefaultGateway": "string",
```

```
        "Dns": [ "string" ],
        "IpAddress": "string",
        "Mask": "string"
    }
},
"Ntp": {
    "NtpServers": [ "string" ]
}
},
"ProvisioningStatus": "string",
"SerialNumber": "string",
"Tags": {
    "string" : "string"
},
"Type": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AlternateSoftwares

Beta software releases available for the device.

Type: Array of [AlternateSoftwareMetadata](#) objects

Arn

The device's ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Brand

The device's maker.

Type: String

Valid Values: AWS_PANORAMA | LENOVO

CreatedTime

When the device was created.

Type: Timestamp

CurrentNetworkingStatus

The device's networking status.

Type: [NetworkStatus](#) object

CurrentSoftware

The device's current software version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Description

The device's description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `^.*$`

DeviceAggregatedStatus

A device's aggregated status. Including the device's connection status, provisioning status, and lease status.

Type: String

Valid Values: ERROR | AWAITING_PROVISIONING | PENDING | FAILED | DELETING | ONLINE | OFFLINE | LEASE_EXPIRED | UPDATE_NEEDED | REBOOTING

DeviceConnectionStatus

The device's connection status.

Type: String

Valid Values: ONLINE | OFFLINE | AWAITING_CREDENTIALS | NOT_AVAILABLE | ERROR

DeviceId

The device's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

LatestAlternateSoftware

The most recent beta software release.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

LatestDeviceJob

A device's latest job. Includes the target image version, and the job status.

Type: [LatestDeviceJob](#) object

LatestSoftware

The latest software version available for the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

LeaseExpirationTime

The device's lease expiration time.

Type: Timestamp

Name

The device's name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

NetworkingConfiguration

The device's networking configuration.

Type: [NetworkPayload](#) object

ProvisioningStatus

The device's provisioning status.

Type: String

Valid Values: AWAITING_PROVISIONING | PENDING | SUCCEEDED | FAILED | ERROR | DELETING

SerialNumber

The device's serial number.

Type: String

Pattern: `^[0-9]{1,20}$`

Tags

The device's tags.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^\.+`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `^\.*`

Type

The device's type.

Type: String

Valid Values: PANORAMA_APPLIANCE_DEVELOPER_KIT | PANORAMA_APPLIANCE

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

InternalServerError

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The target resource was not found.

HTTP Status Code: 404

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeDeviceJob

Returns information about a device job.

Request Syntax

```
GET /jobs/JobId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

JobId

The job's ID.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{  
  "CreatedTime": number,  
  "DeviceArn": "string",  
  "DeviceId": "string",  
  "DeviceName": "string",  
  "DeviceType": "string",  
  "ImageVersion": "string",  
  "JobId": "string",  
  "JobType": "string",
```

```
"Status": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CreatedTime

When the job was created.

Type: Timestamp

DeviceArn

The device's ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

DeviceId

The device's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

DeviceName

The device's name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

DeviceType

The device's type.

Type: String

Valid Values: PANORAMA_APPLIANCE_DEVELOPER_KIT | PANORAMA_APPLIANCE

ImageVersion

For an OTA job, the target version of the device software.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^.+`

JobId

The job's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

JobType

The job's type.

Type: String

Valid Values: OTA | REBOOT

Status

The job's status.

Type: String

Valid Values: PENDING | IN_PROGRESS | VERIFYING | REBOOTING | DOWNLOADING | COMPLETED | FAILED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerError

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The target resource was not found.

HTTP Status Code: 404

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeNode

Returns information about a node.

Request Syntax

```
GET /nodes/NodeId?OwnerAccount=OwnerAccount HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

NodeId

The node's ID.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\.\.]+$`

Required: Yes

OwnerAccount

The account ID of the node's owner.

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: `^[0-9a-z_]+$`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AssetName": "string",
```



```
"Category": "string",
"CreatedTime": number,
"Description": "string",
"LastUpdatedTime": number,
"Name": "string",
"NodeId": "string",
"NodeInterface": {
  "Inputs": [
    {
      "DefaultValue": "string",
      "Description": "string",
      "MaxConnections": number,
      "Name": "string",
      "Type": "string"
    }
  ],
  "Outputs": [
    {
      "Description": "string",
      "Name": "string",
      "Type": "string"
    }
  ]
},
"OwnerAccount": "string",
"PackageArn": "string",
"PackageId": "string",
"PackageName": "string",
"PackageVersion": "string",
"PatchVersion": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AssetName

The node's asset name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_]+$`

Category

The node's category.

Type: String

Valid Values: BUSINESS_LOGIC | ML_MODEL | MEDIA_SOURCE | MEDIA_SINK

CreatedTime

When the node was created.

Type: Timestamp

Description

The node's description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `^.*$`

LastUpdatedTime

When the node was updated.

Type: Timestamp

Name

The node's name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9\-_]+$`

NodeId

The node's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\.\]+$`

NodeInterface

The node's interface.

Type: [NodeInterface](#) object

OwnerAccount

The account ID of the node's owner.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: `^[0-9a-z_]+$`

PackageArn

The node's ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

PackageId

The node's package ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\./]+$`

PackageName

The node's package name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9\-_\]+$`

PackageVersion

The node's package version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^([0-9]+\)\.([0-9]+)$`

PatchVersion

The node's patch version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-z0-9]+$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerError

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The target resource was not found.

HTTP Status Code: 404

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeNodeFromTemplateJob

Returns information about a job to create a camera stream node.

Request Syntax

```
GET /packages/template-job/JobId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

JobId

The job's ID.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CreatedTime": number,
  "JobId": "string",
  "JobTags": [
    {
      "ResourceType": "string",
      "Tags": {
        "string": "string"
      }
    }
  ]
}
```

```
],
  "LastUpdatedTime": number,
  "NodeDescription": "string",
  "NodeName": "string",
  "OutputPackageName": "string",
  "OutputPackageVersion": "string",
  "Status": "string",
  "StatusMessage": "string",
  "TemplateParameters": {
    "string" : "string"
  },
  "TemplateType": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CreatedTime

When the job was created.

Type: Timestamp

JobId

The job's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

JobTags

The job's tags.

Type: Array of [JobResourceTags](#) objects

LastUpdatedTime

When the job was updated.

Type: Timestamp

NodeDescription

The node's description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `^.*$`

NodeName

The node's name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9\-_]+$`

OutputPackageName

The job's output package name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9\-_]+$`

OutputPackageVersion

The job's output package version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^([\0-9]+\)\.([\0-9]+)$`

Status

The job's status.

Type: String

Valid Values: PENDING | SUCCEEDED | FAILED

StatusMessage

The job's status message.

Type: String

TemplateParameters

The job's template parameters.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 255.

Key Pattern: `^ . +$`

Value Length Constraints: Minimum length of 1. Maximum length of 255.

Value Pattern: `^ . +$`

TemplateType

The job's template type.

Type: String

Valid Values: RTSP_CAMERA_STREAM

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerErrorException

An internal error occurred.

HTTP Status Code: 500

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribePackage

Returns information about a package.

Request Syntax

```
GET /packages/metadata/PackageId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

PackageId

The package's ID.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\ \\/]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "CreatedTime": number,
  "PackageId": "string",
  "PackageName": "string",
  "ReadAccessPrincipalArns": [ "string" ],
  "StorageLocation": {
    "BinaryPrefixLocation": "string",
    "Bucket": "string",
```

```
    "GeneratedPrefixLocation": "string",
    "ManifestPrefixLocation": "string",
    "RepoPrefixLocation": "string"
  },
  "Tags": {
    "string" : "string"
  },
  "WriteAccessPrincipalArns": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The package's ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

CreatedTime

When the package was created.

Type: Timestamp

PackageId

The package's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\✓]+`

PackageName

The package's name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9\-_\]+$`

ReadAccessPrincipalArns

ARNs of accounts that have read access to the package.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^arn:[a-z0-9][-.a-z0-9]{0,62}:iam:[0-9]{12}:[a-zA-Z0-9+=,.\@-_\/]+$`

StorageLocation

The package's storage location.

Type: [StorageLocation](#) object

Tags

The package's tags.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^\.+`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `^\.*`

WriteAccessPrincipalArns

ARNs of accounts that have write access to the package.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^arn:[a-z0-9][-.a-z0-9]{0,62}:iam:[0-9]{12}:[a-zA-Z0-9+=,.\@-_\/]+$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerError

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The target resource was not found.

HTTP Status Code: 404

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribePackageImportJob

Returns information about a package import job.

Request Syntax

```
GET /packages/import-jobs/JobId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

JobId

The job's ID.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ClientToken": "string",
  "CreatedTime": number,
  "InputConfig": {
    "PackageVersionInputConfig": {
      "S3Location": {
        "BucketName": "string",
        "ObjectKey": "string",
        "Region": "string"
      }
    }
  }
}
```



```

    }
  }
},
"JobId": "string",
"JobTags": [
  {
    "ResourceType": "string",
    "Tags": {
      "string": "string"
    }
  }
],
"JobType": "string",
"LastUpdatedTime": number,
"Output": {
  "OutputS3Location": {
    "BucketName": "string",
    "ObjectKey": "string"
  },
  "PackageId": "string",
  "PackageVersion": "string",
  "PatchVersion": "string"
},
"OutputConfig": {
  "PackageVersionOutputConfig": {
    "MarkLatest": boolean,
    "PackageName": "string",
    "PackageVersion": "string"
  }
},
"Status": "string",
"StatusMessage": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ClientToken

The job's client token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9\-_\]+$`

CreatedTime

When the job was created.

Type: Timestamp

InputConfig

The job's input config.

Type: [PackageImportJobInputConfig](#) object

JobId

The job's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

JobTags

The job's tags.

Type: Array of [JobResourceTags](#) objects

JobType

The job's type.

Type: String

Valid Values: `NODE_PACKAGE_VERSION` | `MARKETPLACE_NODE_PACKAGE_VERSION`

LastUpdatedTime

When the job was updated.

Type: Timestamp

Output

The job's output.

Type: [PackageImportJobOutput](#) object

OutputConfig

The job's output config.

Type: [PackageImportJobOutputConfig](#) object

Status

The job's status.

Type: String

Valid Values: PENDING | SUCCEEDED | FAILED

StatusMessage

The job's status message.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerError

An internal error occurred.

HTTP Status Code: 500

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribePackageVersion

Returns information about a package version.

Request Syntax

```
GET /packages/metadata/PackageId/versions/PackageVersion?  
OwnerAccount=OwnerAccount&PatchVersion=PatchVersion HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

OwnerAccount

The version's owner account.

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: `^[0-9a-z_]+$`

PackageId

The version's ID.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\✓]+$`

Required: Yes

PackageVersion

The version's version.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^([\d-9]+\)\.([\d-9]+\))$`

Required: Yes

PatchVersion

The version's patch version.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-z0-9]+$`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "IsLatestPatch": boolean,
  "OwnerAccount": "string",
  "PackageArn": "string",
  "PackageId": "string",
  "PackageName": "string",
  "PackageVersion": "string",
  "PatchVersion": "string",
  "RegisteredTime": number,
  "Status": "string",
  "StatusDescription": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

IsLatestPatch

Whether the version is the latest available.

Type: Boolean

OwnerAccount

The account ID of the version's owner.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: `^[0-9a-z_]+$`

PackageArn

The ARN of the package.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

PackageId

The version's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\✓]+$`

PackageName

The version's name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9\-_]#$`

PackageVersion

The version's version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^([\0-9]+)\.([\0-9]+)$`

PatchVersion

The version's patch version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-z0-9]+$`

RegisteredTime

The version's registered time.

Type: Timestamp

Status

The version's status.

Type: String

Valid Values: REGISTER_PENDING | REGISTER_COMPLETED | FAILED | DELETING

StatusDescription

The version's status description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerError

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The target resource was not found.

HTTP Status Code: 404

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListApplicationInstanceDependencies

Returns a list of application instance dependencies.

Request Syntax

```
GET /application-instances/ApplicationInstanceId/package-dependencies?  
maxResults=MaxResults&nextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ApplicationInstanceId

The application instance's ID.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: Yes

MaxResults

The maximum number of application instance dependencies to return in one page of results.

Valid Range: Minimum value of 0. Maximum value of 25.

NextToken

Specify the pagination token from a previous request to retrieve the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `^\.+`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "PackageObjects": [
    {
      "Name": "string",
      "PackageVersion": "string",
      "PatchVersion": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

A pagination token that's included if more results are available.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `^\.+`

PackageObjects

A list of package objects.

Type: Array of [PackageObject](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

InternalServerError

An internal error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListApplicationInstanceNodeInstances

Returns a list of application node instances.

Request Syntax

```
GET /application-instances/ApplicationInstanceId/node-instances?  
maxResults=MaxResults&nextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ApplicationInstanceId

The node instances' application instance ID.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: Yes

MaxResults

The maximum number of node instances to return in one page of results.

Valid Range: Minimum value of 0. Maximum value of 25.

NextToken

Specify the pagination token from a previous request to retrieve the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `^\.+`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "NodeInstances": [
    {
      "CurrentStatus": "string",
      "NodeId": "string",
      "NodeInstanceId": "string",
      "NodeName": "string",
      "PackageName": "string",
      "PackagePatchVersion": "string",
      "PackageVersion": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

A pagination token that's included if more results are available.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `^\.+`

NodeInstances

A list of node instances.

Type: Array of [NodeInstance](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

InternalServerError

An internal error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListApplicationInstances

Returns a list of application instances.

Request Syntax

```
GET /application-instances?  
deviceId=DeviceId&maxResults=MaxResults&nextToken=NextToken&statusFilter=StatusFilter  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

DeviceId

The application instances' device ID.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

MaxResults

The maximum number of application instances to return in one page of results.

Valid Range: Minimum value of 0. Maximum value of 25.

NextToken

Specify the pagination token from a previous request to retrieve the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `^\.+`

StatusFilter

Only include instances with a specific status.

Valid Values: DEPLOYMENT_SUCCEEDED | DEPLOYMENT_ERROR | REMOVAL_SUCCEEDED
| REMOVAL_FAILED | PROCESSING_DEPLOYMENT | PROCESSING_REMOVAL |
DEPLOYMENT_FAILED

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ApplicationInstances": [
    {
      "ApplicationInstanceId": "string",
      "Arn": "string",
      "CreatedTime": number,
      "DefaultRuntimeContextDevice": "string",
      "DefaultRuntimeContextDeviceName": "string",
      "Description": "string",
      "HealthStatus": "string",
      "Name": "string",
      "RuntimeContextStates": [
        {
          "DesiredState": "string",
          "DeviceReportedStatus": "string",
          "DeviceReportedTime": number,
          "RuntimeContextName": "string"
        }
      ],
      "Status": "string",
      "StatusDescription": "string",
      "Tags": {
        "string" : "string"
      }
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ApplicationInstances](#)

A list of application instances.

Type: Array of [ApplicationInstance](#) objects

[NextToken](#)

A pagination token that's included if more results are available.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `^\.+`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

InternalServerErrorException

An internal error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDevices

Returns a list of devices.

Request Syntax

```
GET /devices?  
DeviceAggregatedStatusFilter=DeviceAggregatedStatusFilter&MaxResults=MaxResults&NameFilter=NameFilter  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

DeviceAggregatedStatusFilter

Filter based on a device's status.

Valid Values: ERROR | AWAITING_PROVISIONING | PENDING | FAILED | DELETING | ONLINE | OFFLINE | LEASE_EXPIRED | UPDATE_NEEDED | REBOOTING

MaxResults

The maximum number of devices to return in one page of results.

Valid Range: Minimum value of 0. Maximum value of 25.

NameFilter

Filter based on device's name. Prefixes supported.

NextToken

Specify the pagination token from a previous request to retrieve the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `^\.+`

SortBy

The target column to be sorted on. Default column sort is CREATED_TIME.

Valid Values: DEVICE_ID | CREATED_TIME | NAME | DEVICE_AGGREGATED_STATUS

SortOrder

The sorting order for the returned list. SortOrder is DESCENDING by default based on CREATED_TIME. Otherwise, SortOrder is ASCENDING.

Valid Values: ASCENDING | DESCENDING

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Devices": [
    {
      "Brand": "string",
      "CreatedTime": number,
      "CurrentSoftware": "string",
      "Description": "string",
      "DeviceAggregatedStatus": "string",
      "DeviceId": "string",
      "LastUpdatedTime": number,
      "LatestDeviceJob": {
        "ImageVersion": "string",
        "JobType": "string",
        "Status": "string"
      },
      "LeaseExpirationTime": number,
      "Name": "string",
      "ProvisioningStatus": "string",
      "Tags": {
        "string" : "string"
      },
      "Type": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Devices

A list of devices.

Type: Array of [Device](#) objects

NextToken

A pagination token that's included if more results are available.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `^\.+`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerErrorException

An internal error occurred.

HTTP Status Code: 500

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDevicesJobs

Returns a list of jobs.

Request Syntax

```
GET /jobs?DeviceId=DeviceId&MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

DeviceId

Filter results by the job's target device ID.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

MaxResults

The maximum number of device jobs to return in one page of results.

Valid Range: Minimum value of 0. Maximum value of 25.

NextToken

Specify the pagination token from a previous request to retrieve the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `^\.+`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```



```
{
  "DeviceJobs": [
    {
      "CreatedTime": number,
      "DeviceId": "string",
      "DeviceName": "string",
      "JobId": "string",
      "JobType": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[DeviceJobs](#)

A list of jobs.

Type: Array of [DeviceJob](#) objects

[NextToken](#)

A pagination token that's included if more results are available.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `^\.+`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerErrorException

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The target resource was not found.

HTTP Status Code: 404

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListNodeFromTemplateJobs

Returns a list of camera stream node jobs.

Request Syntax

```
GET /packages/template-job?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of node from template jobs to return in one page of results.

Valid Range: Minimum value of 0. Maximum value of 25.

NextToken

Specify the pagination token from a previous request to retrieve the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `^\.+`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "NodeFromTemplateJobs": [
    {
      "CreatedTime": number,
      "JobId": "string",
```

```
    "NodeName": "string",
    "Status": "string",
    "StatusMessage": "string",
    "TemplateType": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

A pagination token that's included if more results are available.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: ^.+

NodeFromTemplateJobs

A list of jobs.

Type: Array of [NodeFromTemplateJob](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerErrorException

An internal error occurred.

HTTP Status Code: 500

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListNodes

Returns a list of nodes.

Request Syntax

```
GET /nodes?  
category=Category&maxResults=MaxResults&nextToken=NextToken&ownerAccount=OwnerAccount&packageName=PackageName  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Category

Search for nodes by category.

Valid Values: BUSINESS_LOGIC | ML_MODEL | MEDIA_SOURCE | MEDIA_SINK

MaxResults

The maximum number of nodes to return in one page of results.

Valid Range: Minimum value of 0. Maximum value of 25.

NextToken

Specify the pagination token from a previous request to retrieve the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: $^{\wedge}.\+{\$}$

OwnerAccount

Search for nodes by the account ID of the nodes' owner.

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: $^{\wedge}[0-9a-z_]{1,12}\+{\$}$

PackageName

Search for nodes by name.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9\-_\]+$`

PackageVersion

Search for nodes by version.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^([\d-]+)\.([\d-]+)$`

PatchVersion

Search for nodes by patch version.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-z0-9]+$`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "Nodes": [
    {
      "Category": "string",
      "CreatedTime": number,
      "Description": "string",
      "Name": "string",
      "NodeId": "string",
      "OwnerAccount": "string",
      "PackageArn": "string",
      "PackageId": "string",
      "PackageName": "string",
      "PackageVersion": "string",
      "PatchVersion": "string"
    }
  ]
}
```

```
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

A pagination token that's included if more results are available.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: ^ . +\$

Nodes

A list of nodes.

Type: Array of [Node](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerErrorException

An internal error occurred.

HTTP Status Code: 500

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPackageImportJobs

Returns a list of package import jobs.

Request Syntax

```
GET /packages/import-jobs?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of package import jobs to return in one page of results.

Valid Range: Minimum value of 0. Maximum value of 25.

NextToken

Specify the pagination token from a previous request to retrieve the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `^\.+`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "PackageImportJobs": [
    {
      "CreatedTime": number,
      "JobId": "string",
```

```
    "JobType": "string",
    "LastUpdatedTime": number,
    "Status": "string",
    "StatusMessage": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

A pagination token that's included if more results are available.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: ^.+

PackageImportJobs

A list of package import jobs.

Type: Array of [PackageImportJob](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerErrorException

An internal error occurred.

HTTP Status Code: 500

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPackages

Returns a list of packages.

Request Syntax

```
GET /packages?maxResults=MaxResults&nextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of packages to return in one page of results.

Valid Range: Minimum value of 0. Maximum value of 25.

NextToken

Specify the pagination token from a previous request to retrieve the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `^\.+`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "Packages": [
    {
      "Arn": "string",
      "CreatedTime": number,
```

```
    "PackageId": "string",
    "PackageName": "string",
    "Tags": {
      "string" : "string"
    }
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

A pagination token that's included if more results are available.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: ^.+\$

Packages

A list of packages.

Type: Array of [PackageListItem](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerErrorException

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The target resource was not found.

HTTP Status Code: 404

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Returns a list of tags for a resource.

Request Syntax

```
GET /tags/ResourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ResourceArn

The resource's ARN.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^.+`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Tags

A list of tags.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^ . + $`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `^ . * $`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The target resource was not found.

HTTP Status Code: 404

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ProvisionDevice

Creates a device and returns a configuration archive. The configuration archive is a ZIP file that contains a provisioning certificate that is valid for 5 minutes. Name the configuration archive `certificates-omni_device-name.zip` and transfer it to the device within 5 minutes. Use the included USB storage device and connect it to the USB 3.0 port next to the HDMI output.

Request Syntax

```
POST /devices HTTP/1.1
Content-type: application/json

{
  "Description": "string",
  "Name": "string",
  "NetworkingConfiguration": {
    "Ethernet0": {
      "ConnectionType": "string",
      "StaticIpConnectionInfo": {
        "DefaultGateway": "string",
        "Dns": [ "string" ],
        "IpAddress": "string",
        "Mask": "string"
      }
    },
    "Ethernet1": {
      "ConnectionType": "string",
      "StaticIpConnectionInfo": {
        "DefaultGateway": "string",
        "Dns": [ "string" ],
        "IpAddress": "string",
        "Mask": "string"
      }
    },
    "Ntp": {
      "NtpServers": [ "string" ]
    }
  },
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Description

A description for the device.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `^.*$`

Required: No

Name

A name for the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: Yes

NetworkingConfiguration

A networking configuration for the device.

Type: [NetworkPayload](#) object

Required: No

Tags

Tags for the device.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^\.+`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `^\.*`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "Certificates": blob,
  "DeviceId": "string",
  "IotThingName": "string",
  "Status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Arn](#)

The device's ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

[Certificates](#)

The device's configuration bundle.

Type: Base64-encoded binary data object

DeviceId

The device's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

IoTThingName

The device's IoT thing name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Status

The device's status.

Type: String

Valid Values: AWAITING_PROVISIONING | PENDING | SUCCEEDED | FAILED | ERROR | DELETING

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerErrorException

An internal error occurred.

HTTP Status Code: 500

ServiceQuotaExceededException

The request would cause a limit to be exceeded.

HTTP Status Code: 402

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RegisterPackageVersion

Registers a package version.

Request Syntax

```
PUT /packages/PackageId/versions/PackageVersion/patch/PatchVersion HTTP/1.1
Content-type: application/json
```

```
{
  "MarkLatest": boolean,
  "OwnerAccount": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

PackageId

A package ID.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\✓]+$`

Required: Yes

PackageVersion

A package version.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^([0-9]+\)\.([0-9]+)$`

Required: Yes

PatchVersion

A patch version.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-z0-9]+$`

Required: Yes

Request Body

The request accepts the following data in JSON format.

MarkLatest

Whether to mark the new version as the latest version.

Type: Boolean

Required: No

OwnerAccount

An owner account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: `^[0-9a-z_]+$`

Required: No

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerError

An internal error occurred.

HTTP Status Code: 500

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RemoveApplicationInstance

Removes an application instance.

Request Syntax

```
DELETE /application-instances/ApplicationInstanceId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ApplicationInstanceId

An application instance ID.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerError

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The target resource was not found.

HTTP Status Code: 404

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

SignalApplicationInstanceNodeInstances

Signal camera nodes to stop or resume.

Request Syntax

```
PUT /application-instances/ApplicationInstanceId/node-signals HTTP/1.1
Content-type: application/json
```

```
{
  "NodeSignals": [
    {
      "NodeInstanceId": "string",
      "Signal": "string"
    }
  ]
}
```

URI Request Parameters

The request uses the following URI parameters.

ApplicationInstanceId

An application instance ID.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_]+$`

Required: Yes

Request Body

The request accepts the following data in JSON format.

NodeSignals

A list of signals.

Type: Array of [NodeSignal](#) objects

Array Members: Minimum number of 1 item.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ApplicationInstanceId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ApplicationInstanceId](#)

An application instance ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

InternalServerError

An internal error occurred.

HTTP Status Code: 500

ServiceQuotaExceededException

The request would cause a limit to be exceeded.

HTTP Status Code: 402

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Tags a resource.

Request Syntax

```
POST /tags/ResourceArn HTTP/1.1
Content-type: application/json
```

```
{
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

ResourceArn

The resource's ARN.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^.+`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Tags

Tags for the resource.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^ . +$`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `^ . *$`

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The target resource was not found.

HTTP Status Code: 404

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Removes tags from a resource.

Request Syntax

```
DELETE /tags/ResourceArn?tagKeys=TagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ResourceArn

The resource's ARN.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^.+`

Required: Yes

TagKeys

Tag keys to remove.

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^.+`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The target resource was not found.

HTTP Status Code: 404

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateDeviceMetadata

Updates a device's metadata.

Request Syntax

```
PUT /devices/DeviceId HTTP/1.1
Content-type: application/json

{
  "Description": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

DeviceId

The device's ID.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Description

A description for the device.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `^\.*$`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "DeviceId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DeviceId

The device's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_]+$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The requestor does not have permission to access the target action or resource.

HTTP Status Code: 403

ConflictException

The target resource is in use.

HTTP Status Code: 409

InternalServerErrorException

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The target resource was not found.

HTTP Status Code: 404

ValidationException

The request contains an invalid parameter value.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS Panorama API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AlternateSoftwareMetadata](#)
- [ApplicationInstance](#)
- [ConflictExceptionErrorArgument](#)
- [Device](#)
- [DeviceJob](#)
- [DeviceJobConfig](#)
- [EthernetPayload](#)
- [EthernetStatus](#)
- [Job](#)
- [JobResourceTags](#)
- [LatestDeviceJob](#)
- [ManifestOverridesPayload](#)
- [ManifestPayload](#)
- [NetworkPayload](#)
- [NetworkStatus](#)
- [Node](#)
- [NodeFromTemplateJob](#)
- [NodeInputPort](#)
- [NodeInstance](#)
- [NodeInterface](#)

- [NodeOutputPort](#)
- [NodeSignal](#)
- [NtpPayload](#)
- [NtpStatus](#)
- [OTAJobConfig](#)
- [OutPutS3Location](#)
- [PackageImportJob](#)
- [PackageImportJobInputConfig](#)
- [PackageImportJobOutput](#)
- [PackageImportJobOutputConfig](#)
- [PackageListItem](#)
- [PackageObject](#)
- [PackageVersionInputConfig](#)
- [PackageVersionOutputConfig](#)
- [ReportedRuntimeContextState](#)
- [S3Location](#)
- [StaticIpConnectionInfo](#)
- [StorageLocation](#)
- [ValidationExceptionErrorArgument](#)
- [ValidationExceptionField](#)

AlternateSoftwareMetadata

Details about a beta appliance software update.

Contents

Version

The appliance software version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ApplicationInstance

An application instance on a device.

Contents

ApplicationInstanceId

The application instance's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: No

Arn

The application instance's ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

CreatedTime

When the application instance was created.

Type: Timestamp

Required: No

DefaultRuntimeContextDevice

The device's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: No

DefaultRuntimeContextDeviceName

The device's name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: No

Description

The application instance's description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `^.*$`

Required: No

HealthStatus

The application instance's health status.

Type: String

Valid Values: `RUNNING | ERROR | NOT_AVAILABLE`

Required: No

Name

The application instance's name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: No

RuntimeContextStates

The application's state.

Type: Array of [ReportedRuntimeContextState](#) objects

Required: No

Status

The application instance's status.

Type: String

Valid Values: DEPLOYMENT_PENDING | DEPLOYMENT_REQUESTED | DEPLOYMENT_IN_PROGRESS | DEPLOYMENT_ERROR | DEPLOYMENT_SUCCEEDED | REMOVAL_PENDING | REMOVAL_REQUESTED | REMOVAL_IN_PROGRESS | REMOVAL_FAILED | REMOVAL_SUCCEEDED | DEPLOYMENT_FAILED

Required: No

StatusDescription

The application instance's status description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

Tags

The application instance's tags.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: $^{\wedge} \cdot +\$$

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: $^{\wedge} \cdot *\$$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ConflictExceptionErrorArgument

A conflict exception error argument.

Contents

Name

The error argument's name.

Type: String

Required: Yes

Value

The error argument's value.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Device

A device.

Contents

Brand

The device's maker.

Type: String

Valid Values: AWS_PANORAMA | LENOVO

Required: No

CreatedTime

When the device was created.

Type: Timestamp

Required: No

CurrentSoftware

A device's current software.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

Description

A description for the device.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `^.*$`

Required: No

DeviceAggregatedStatus

A device's aggregated status. Including the device's connection status, provisioning status, and lease status.

Type: String

Valid Values: ERROR | AWAITING_PROVISIONING | PENDING | FAILED | DELETING | ONLINE | OFFLINE | LEASE_EXPIRED | UPDATE_NEEDED | REBOOTING

Required: No

DeviceId

The device's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: No

LastUpdatedTime

When the device was updated.

Type: Timestamp

Required: No

LatestDeviceJob

A device's latest job. Includes the target image version, and the update job status.

Type: [LatestDeviceJob](#) object

Required: No

LeaseExpirationTime

The device's lease expiration time.

Type: Timestamp

Required: No

Name

The device's name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: No

ProvisioningStatus

The device's provisioning status.

Type: String

Valid Values: AWAITING_PROVISIONING | PENDING | SUCCEEDED | FAILED | ERROR | DELETING

Required: No

Tags

The device's tags.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^\.+`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `^\.*`

Required: No

Type

The device's type.

Type: String

Valid Values: PANORAMA_APPLIANCE_DEVELOPER_KIT | PANORAMA_APPLIANCE

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeviceJob

A job that runs on a device.

Contents

CreatedTime

When the job was created.

Type: Timestamp

Required: No

DeviceId

The ID of the target device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_]+$`

Required: No

DeviceName

The name of the target device

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_]+$`

Required: No

JobId

The job's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: No

JobType

The job's type.

Type: String

Valid Values: OTA | REBOOT

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeviceJobConfig

A job's configuration.

Contents

OTAJobConfig

A configuration for an over-the-air (OTA) upgrade. Required for OTA jobs.

Type: [OTAJobConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EthernetPayload

A device's network configuration.

Contents

ConnectionType

How the device gets an IP address.

Type: String

Valid Values: `STATIC_IP` | `DHCP`

Required: Yes

StaticIpConnectionInfo

Network configuration for a static IP connection.

Type: [StaticIpConnectionInfo](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EthernetStatus

A device's Ethernet status.

Contents

ConnectionStatus

The device's connection status.

Type: String

Valid Values: CONNECTED | NOT_CONNECTED | CONNECTING

Required: No

HwAddress

The device's physical address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

IpAddress

The device's IP address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^((25[0-5]|2[0-4]\d|1\d\d|[1-9]?\d)\.(25[0-5]|2[0-4]\d|1\d\d|[1-9]?\d)\.(25[0-5]|2[0-4]\d|1\d\d|[1-9]?\d)\.(25[0-5]|2[0-4]\d|1\d\d|[1-9]?\d))|((6553[0-5]|655[0-2]\d|65[0-4]\d{2}|6[0-4]\d{3}|[1-5]\d{4}|[1-9]\d{0,3}))?``

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Job

A job for a device.

Contents

DeviceId

The target device's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: No

JobId

The job's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

JobResourceTags

Tags for a job.

Contents

ResourceType

The job's type.

Type: String

Valid Values: PACKAGE

Required: Yes

Tags

The job's tags.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^\.+`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `^\.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LatestDeviceJob

Returns information about the latest device job.

Contents

ImageVersion

The target version of the device software.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^\.+`

Required: No

JobType

The job's type.

Type: String

Valid Values: `OTA` | `REBOOT`

Required: No

Status

Status of the latest device job.

Type: String

Valid Values: `PENDING` | `IN_PROGRESS` | `VERIFYING` | `REBOOTING` | `DOWNLOADING` | `COMPLETED` | `FAILED`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ManifestOverridesPayload

Parameter overrides for an application instance. This is a JSON document that has a single key (`PayloadData`) where the value is an escaped string representation of the overrides document.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

PayloadData

The overrides document.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: `^.*$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ManifestPayload

A application verion's manifest file. This is a JSON document that has a single key (PayloadData) where the value is an escaped string representation of the application manifest (graph.json). This file is located in the graphs folder in your application source.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

PayloadData

The application manifest.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Pattern: ^.+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NetworkPayload

The network configuration for a device.

Contents

Ethernet0

Settings for Ethernet port 0.

Type: [EthernetPayload](#) object

Required: No

Ethernet1

Settings for Ethernet port 1.

Type: [EthernetPayload](#) object

Required: No

Ntp

Network time protocol (NTP) server settings.

Type: [NtpPayload](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NetworkStatus

The network status of a device.

Contents

Ethernet0Status

The status of Ethernet port 0.

Type: [EthernetStatus](#) object

Required: No

Ethernet1Status

The status of Ethernet port 1.

Type: [EthernetStatus](#) object

Required: No

LastUpdatedTime

When the network status changed.

Type: Timestamp

Required: No

NtpStatus

Details about a network time protocol (NTP) server connection.

Type: [NtpStatus](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Node

An application node that represents a camera stream, a model, code, or output.

Contents

Category

The node's category.

Type: String

Valid Values: BUSINESS_LOGIC | ML_MODEL | MEDIA_SOURCE | MEDIA_SINK

Required: Yes

CreatedTime

When the node was created.

Type: Timestamp

Required: Yes

Name

The node's name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9\-_\.]+$`

Required: Yes

NodeId

The node's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\.\.]+$`

Required: Yes

PackageId

The node's package ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\✓]+$`

Required: Yes

PackageName

The node's package name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9\-_]+$`

Required: Yes

PackageVersion

The node's package version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^([0-9]+)\.([0-9]+)$`

Required: Yes

PatchVersion

The node's patch version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-z0-9]+$`

Required: Yes

Description

The node's description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `^.*$`

Required: No

OwnerAccount

The account ID of the node's owner.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: `^[0-9a-z_]+$`

Required: No

PackageArn

The node's ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NodeFromTemplateJob

A job to create a camera stream node.

Contents

CreatedTime

When the job was created.

Type: Timestamp

Required: No

JobId

The job's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_]+$`

Required: No

NodeName

The node's name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9\-_]+$`

Required: No

Status

The job's status.

Type: String

Valid Values: PENDING | SUCCEEDED | FAILED

Required: No

StatusMessage

The job's status message.

Type: String

Required: No

TemplateType

The job's template type.

Type: String

Valid Values: RTSP_CAMERA_STREAM

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NodeInputPort

A node input port.

Contents

DefaultValue

The input port's default value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

Description

The input port's description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `^.*$`

Required: No

MaxConnections

The input port's max connections.

Type: Integer

Required: No

Name

The input port's name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `^[a-zA-Z0-9_]+$`

Required: No

Type

The input port's type.

Type: String

Valid Values: BOOLEAN | STRING | INT32 | FLOAT32 | MEDIA

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NodeInstance

A node instance.

Contents

CurrentStatus

The instance's current status.

Type: String

Valid Values: RUNNING | ERROR | NOT_AVAILABLE | PAUSED

Required: Yes

NodeInstanceId

The instance's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: Yes

NodeId

The node's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\.\]+$`

Required: No

NodeName

The instance's name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9\-_]+$`

Required: No

PackageName

The instance's package name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9\-_]+$`

Required: No

PackagePatchVersion

The instance's package patch version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-z0-9]+$`

Required: No

PackageVersion

The instance's package version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^([0-9]+\)\.([0-9]+)$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NodeInterface

A node interface.

Contents

Inputs

The node interface's inputs.

Type: Array of [NodeInputPort](#) objects

Required: Yes

Outputs

The node interface's outputs.

Type: Array of [NodeOutputPort](#) objects

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NodeOutputPort

A node output port.

Contents

Description

The output port's description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `^.*$`

Required: No

Name

The output port's name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `^[a-zA-Z0-9_]+$`

Required: No

Type

The output port's type.

Type: String

Valid Values: `BOOLEAN` | `STRING` | `INT32` | `FLOAT32` | `MEDIA`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NodeSignal

A signal to a camera node to start or stop processing video.

Contents

NodeInstanceId

The camera node's name, from the application manifest.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: Yes

Signal

The signal value.

Type: String

Valid Values: PAUSE | RESUME

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NtpPayload

Network time protocol (NTP) server settings. Use this option to connect to local NTP servers instead of `pool.ntp.org`.

Contents

NtpServers

NTP servers to use, in order of preference.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `(^[a-z0-9]+(-[a-z0-9]+)*\.)+[a-z]{2,}$|^((25[0-5]|2[0-4]\d|1\d\d|[1-9]?\d)\.)(25[0-5]|2[0-4]\d|1\d\d|[1-9]?\d)\.)(25[0-5]|2[0-4]\d|1\d\d|[1-9]?\d)\.)(25[0-5]|2[0-4]\d|1\d\d|[1-9]?\d))(: (6553[0-5]|655[0-2]\d|65[0-4]\d{2}|6[0-4]\d{3}|[1-5]\d{4}|[1-9]\d{0,3}))?$`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NtpStatus

Details about an NTP server connection.

Contents

ConnectionStatus

The connection's status.

Type: String

Valid Values: CONNECTED | NOT_CONNECTED | CONNECTING

Required: No

IpAddress

The IP address of the server.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^((25[0-5]|2[0-4]\d|1\d\d|[1-9]?\d)\.(25[0-5]|2[0-4]\d|1\d\d|[1-9]?\d)\.(25[0-5]|2[0-4]\d|1\d\d|[1-9]?\d)\.(25[0-5]|2[0-4]\d|1\d\d|[1-9]?\d))|(:((6553[0-5]|655[0-2]\d|65[0-4]\d{2}|6[0-4]\d{3}|[1-5]\d{4}|[1-9]\d{0,3}))?)?$`

Required: No

NtpServerName

The domain name of the server.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OTAJobConfig

An over-the-air update (OTA) job configuration.

Contents

ImageVersion

The target version of the device software.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^\.+`

Required: Yes

AllowMajorVersionUpdate

Whether to apply the update if it is a major version change.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OutPutS3Location

The location of an output object in Amazon S3.

Contents

BucketName

The object's bucket.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^ . + $`

Required: Yes

ObjectKey

The object's key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^ . + $`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PackageImportJob

A job to import a package version.

Contents

CreatedTime

When the job was created.

Type: Timestamp

Required: No

JobId

The job's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: No

JobType

The job's type.

Type: String

Valid Values: `NODE_PACKAGE_VERSION` | `MARKETPLACE_NODE_PACKAGE_VERSION`

Required: No

LastUpdateTime

When the job was updated.

Type: Timestamp

Required: No

Status

The job's status.

Type: String

Valid Values: PENDING | SUCCEEDED | FAILED

Required: No

StatusMessage

The job's status message.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PackageImportJobInputConfig

A configuration for a package import job.

Contents

PackageVersionInputConfig

The package version's input configuration.

Type: [PackageVersionInputConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PackageImportJobOutput

Results of a package import job.

Contents

OutputS3Location

The package's output location.

Type: [OutPutS3Location](#) object

Required: Yes

PackageId

The package's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\✓]+$`

Required: Yes

PackageVersion

The package's version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^([0-9]+\)\.([0-9]+)$`

Required: Yes

PatchVersion

The package's patch version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-z0-9]+$`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PackageImportJobOutputConfig

An output configuration for a package import job.

Contents

PackageVersionOutputConfig

The package version's output configuration.

Type: [PackageVersionOutputConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PackageListItem

A package summary.

Contents

Arn

The package's ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

CreatedTime

When the package was created.

Type: Timestamp

Required: No

PackageId

The package's ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9\-_\//]+$`

Required: No

PackageName

The package's name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9\-_]+$`

Required: No

Tags

The package's tags.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^ . +$`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `^ . *$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PackageObject

A package object.

Contents

Name

The object's name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: Yes

PackageVersion

The object's package version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^([0-9]+\)\.([0-9]+)$`

Required: Yes

PatchVersion

The object's patch version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-z0-9]+$`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PackageVersionInputConfig

A package version input configuration.

Contents

S3Location

A location in Amazon S3.

Type: [S3Location](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PackageVersionOutputConfig

A package version output configuration.

Contents

PackageName

The output's package name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9\-_\]+$`

Required: Yes

PackageVersion

The output's package version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^([0-9]+\)\.([0-9]+)$`

Required: Yes

MarkLatest

Indicates that the version is recommended for all users.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ReportedRuntimeContextState

An application instance's state.

Contents

DesiredState

The application's desired state.

Type: String

Valid Values: RUNNING | STOPPED | REMOVED

Required: Yes

DeviceReportedStatus

The application's reported status.

Type: String

Valid Values: STOPPING | STOPPED | STOP_ERROR | REMOVAL_FAILED |
REMOVAL_IN_PROGRESS | STARTING | RUNNING | INSTALL_ERROR | LAUNCHED |
LAUNCH_ERROR | INSTALL_IN_PROGRESS

Required: Yes

DeviceReportedTime

When the device reported the application's state.

Type: Timestamp

Required: Yes

RuntimeContextName

The device's name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^\.+`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3Location

A location in Amazon S3.

Contents

BucketName

A bucket name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[.]+$`

Required: Yes

ObjectKey

An object key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[.]+$`

Required: Yes

Region

The bucket's Region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[.]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

StaticIpConnectionInfo

A static IP configuration.

Contents

DefaultGateway

The connection's default gateway.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^.+`

Required: Yes

Dns

The connection's DNS address.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^.+`

Required: Yes

IpAddress

The connection's IP address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^((25[0-5]|2[0-4]\d|1\d\d|[1-9]?\d)\.(25[0-5]|2[0-4]\d|1\d\d|[1-9]?\d)\.(25[0-5]|2[0-4]\d|1\d\d|[1-9]?\d)\.(25[0-5]|2[0-4]\d|1\d\d|[1-9]?\d))(:((6553[0-5]|655[0-2]\d|65[0-4]\d{2}|6[0-4]\d{3}|[1-5]\d{4}|[1-9]\d{0,3})))?`

Required: Yes

Mask

The connection's DNS mask.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^\.+`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

StorageLocation

A storage location.

Contents

BinaryPrefixLocation

The location's binary prefix.

Type: String

Required: Yes

Bucket

The location's bucket.

Type: String

Required: Yes

GeneratedPrefixLocation

The location's generated prefix.

Type: String

Required: Yes

ManifestPrefixLocation

The location's manifest prefix.

Type: String

Required: Yes

RepoPrefixLocation

The location's repo prefix.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ValidationExceptionErrorArgument

A validation exception error argument.

Contents

Name

The argument's name.

Type: String

Required: Yes

Value

The argument's value.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ValidationExceptionField

A validation exception field.

Contents

Message

The field's message.

Type: String

Required: Yes

Name

The field's name.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request is expired

HTTP Status Code: 403

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 403

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

MalformedHttpRequestException

Problems with the request at the HTTP level, e.g. we can't decompress the body according to the decompression algorithm specified by the content-encoding.

HTTP Status Code: 400

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 401

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestAbortedException

Convenient exception that can be used when a request is aborted before a reply is sent back (e.g. client closed connection).

HTTP Status Code: 400

RequestEntityTooLargeException

Problems with the request at the HTTP level. The request entity is too large.

HTTP Status Code: 413

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

RequestTimeoutException

Problems with the request at the HTTP level. Reading the Request timed out.

HTTP Status Code: 408

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

UnrecognizedClientException

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

UnknownOperationException

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 404

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400