



API Reference

Amazon WorkMail



Amazon WorkMail: API Reference

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Amazon WorkMail	1
Amazon WorkMail Message Flow	1
Actions	2
Amazon WorkMail	5
AssociateDelegateToResource	8
AssociateMemberToGroup	12
AssumeImpersonationRole	16
CancelMailboxExportJob	19
CreateAlias	22
CreateAvailabilityConfiguration	26
CreateGroup	30
CreateImpersonationRole	34
CreateMobileDeviceAccessRule	39
CreateOrganization	45
CreateResource	50
CreateUser	54
DeleteAccessControlRule	59
DeleteAlias	62
DeleteAvailabilityConfiguration	65
DeleteEmailMonitoringConfiguration	67
DeleteGroup	69
DeleteImpersonationRole	72
DeleteMailboxPermissions	75
DeleteMobileDeviceAccessOverride	79
DeleteMobileDeviceAccessRule	82
DeleteOrganization	85
DeleteResource	89
DeleteRetentionPolicy	92
DeleteUser	95
DeregisterFromWorkMail	98
DeregisterMailDomain	101
DescribeEmailMonitoringConfiguration	104
DescribeEntity	107

DescribeGroup	110
DescribeInboundDmarcSettings	114
DescribeMailboxExportJob	117
DescribeOrganization	122
DescribeResource	127
DescribeUser	132
DisassociateDelegateFromResource	140
DisassociateMemberFromGroup	144
GetAccessControlEffect	148
GetDefaultRetentionPolicy	152
GetImpersonationRole	156
GetImpersonationRoleEffect	160
GetMailboxDetails	164
GetMailDomain	168
GetMobileDeviceAccessEffect	172
GetMobileDeviceAccessOverride	176
ListAccessControlRules	181
ListAliases	184
ListAvailabilityConfigurations	188
ListGroupMembers	192
ListGroups	196
ListGroupsForEntity	200
ListImpersonationRoles	204
ListMailboxExportJobs	208
ListMailboxPermissions	212
ListMailDomains	216
ListMobileDeviceAccessOverrides	219
ListMobileDeviceAccessRules	224
ListOrganizations	227
ListResourceDelegates	230
ListResources	234
ListTagsForResource	238
ListUsers	241
PutAccessControlRule	245
PutEmailMonitoringConfiguration	251
PutInboundDmarcSettings	254

PutMailboxPermissions	256
PutMobileDeviceAccessOverride	260
PutRetentionPolicy	264
RegisterMailDomain	268
RegisterToWorkMail	271
ResetPassword	275
StartMailboxExportJob	279
TagResource	284
TestAvailabilityConfiguration	287
UntagResource	291
UpdateAvailabilityConfiguration	293
UpdateDefaultMailDomain	296
UpdateGroup	299
UpdateImpersonationRole	302
UpdateMailboxQuota	306
UpdateMobileDeviceAccessRule	309
UpdatePrimaryEmailAddress	315
UpdateResource	319
UpdateUser	324
Amazon WorkMail Message Flow	330
GetRawMessageContent	331
PutRawMessageContent	335
Data Types	339
Amazon WorkMail	340
AccessControlRule	342
AvailabilityConfiguration	346
BookingOptions	348
Delegate	349
DnsRecord	350
Domain	352
EwsAvailabilityProvider	354
FolderConfiguration	356
Group	358
GroupIdentifier	360
ImpersonationMatchedRule	361
ImpersonationRole	362

ImpersonationRule	364
LambdaAvailabilityProvider	367
ListGroupsFilters	368
ListGroupsForEntityFilters	370
ListResourcesFilters	371
ListUsersFilters	373
MailboxExportJob	375
MailDomainSummary	378
Member	379
MobileDeviceAccessMatchedRule	381
MobileDeviceAccessOverride	382
MobileDeviceAccessRule	384
OrganizationSummary	389
Permission	391
RedactedEwsAvailabilityProvider	393
Resource	394
Tag	397
User	398
Amazon WorkMail Message Flow	400
RawMessageContent	401
S3Reference	403
Common Parameters	405
Common Errors	408

Welcome

Amazon WorkMail

WorkMail is a secure, managed business email and calendaring service with support for existing desktop and mobile email clients. You can access your email, contacts, and calendars using Microsoft Outlook, your browser, or other native iOS and Android email applications. You can integrate WorkMail with your existing corporate directory and control both the keys that encrypt your data and the location in which your data is stored.

The WorkMail API is designed for the following scenarios:

- Listing and describing organizations
- Managing users
- Managing groups
- Managing resources

All WorkMail API operations are Amazon-authenticated and certificate-signed. They not only require the use of the AWS SDK, but also allow for the exclusive use of AWS Identity and Access Management users and roles to help facilitate access, trust, and permission policies. By creating a role and allowing an IAM user to access the WorkMail site, the IAM user gains full administrative visibility into the entire WorkMail organization (or as set in the IAM policy). This includes, but is not limited to, the ability to create, update, and delete users, groups, and resources. This allows developers to perform the scenarios listed above, as well as give users the ability to grant access on a selective basis using the IAM model.

Amazon WorkMail Message Flow

The WorkMail Message Flow API provides access to email messages as they are being sent and received by a WorkMail organization.

Actions

The following actions are supported by Amazon WorkMail:

- [AssociateDelegateToResource](#)
- [AssociateMemberToGroup](#)
- [AssumeImpersonationRole](#)
- [CancelMailboxExportJob](#)
- [CreateAlias](#)
- [CreateAvailabilityConfiguration](#)
- [CreateGroup](#)
- [CreateImpersonationRole](#)
- [CreateMobileDeviceAccessRule](#)
- [CreateOrganization](#)
- [CreateResource](#)
- [CreateUser](#)
- [DeleteAccessControlRule](#)
- [DeleteAlias](#)
- [DeleteAvailabilityConfiguration](#)
- [DeleteEmailMonitoringConfiguration](#)
- [DeleteGroup](#)
- [DeleteImpersonationRole](#)
- [DeleteMailboxPermissions](#)
- [DeleteMobileDeviceAccessOverride](#)
- [DeleteMobileDeviceAccessRule](#)
- [DeleteOrganization](#)
- [DeleteResource](#)
- [DeleteRetentionPolicy](#)
- [DeleteUser](#)
- [DeregisterFromWorkMail](#)
- [DeregisterMailDomain](#)

- [DescribeEmailMonitoringConfiguration](#)
- [DescribeEntity](#)
- [DescribeGroup](#)
- [DescribeInboundDmarcSettings](#)
- [DescribeMailboxExportJob](#)
- [DescribeOrganization](#)
- [DescribeResource](#)
- [DescribeUser](#)
- [DisassociateDelegateFromResource](#)
- [DisassociateMemberFromGroup](#)
- [GetAccessControlEffect](#)
- [GetDefaultRetentionPolicy](#)
- [GetImpersonationRole](#)
- [GetImpersonationRoleEffect](#)
- [GetMailboxDetails](#)
- [GetMailDomain](#)
- [GetMobileDeviceAccessEffect](#)
- [GetMobileDeviceAccessOverride](#)
- [ListAccessControlRules](#)
- [ListAliases](#)
- [ListAvailabilityConfigurations](#)
- [ListGroupMembers](#)
- [ListGroups](#)
- [ListGroupsForEntity](#)
- [ListImpersonationRoles](#)
- [ListMailboxExportJobs](#)
- [ListMailboxPermissions](#)
- [ListMailDomains](#)
- [ListMobileDeviceAccessOverrides](#)
- [ListMobileDeviceAccessRules](#)

- [ListOrganizations](#)
- [ListResourceDelegates](#)
- [ListResources](#)
- [ListTagsForResource](#)
- [ListUsers](#)
- [PutAccessControlRule](#)
- [PutEmailMonitoringConfiguration](#)
- [PutInboundDmarcSettings](#)
- [PutMailboxPermissions](#)
- [PutMobileDeviceAccessOverride](#)
- [PutRetentionPolicy](#)
- [RegisterMailDomain](#)
- [RegisterToWorkMail](#)
- [ResetPassword](#)
- [StartMailboxExportJob](#)
- [TagResource](#)
- [TestAvailabilityConfiguration](#)
- [UntagResource](#)
- [UpdateAvailabilityConfiguration](#)
- [UpdateDefaultMailDomain](#)
- [UpdateGroup](#)
- [UpdateImpersonationRole](#)
- [UpdateMailboxQuota](#)
- [UpdateMobileDeviceAccessRule](#)
- [UpdatePrimaryEmailAddress](#)
- [UpdateResource](#)
- [UpdateUser](#)

The following actions are supported by Amazon WorkMail Message Flow:

- [GetRawMessageContent](#)

- [PutRawMessageContent](#)

Amazon WorkMail

The following actions are supported by Amazon WorkMail:

- [AssociateDelegateToResource](#)
- [AssociateMemberToGroup](#)
- [AssumeImpersonationRole](#)
- [CancelMailboxExportJob](#)
- [CreateAlias](#)
- [CreateAvailabilityConfiguration](#)
- [CreateGroup](#)
- [CreateImpersonationRole](#)
- [CreateMobileDeviceAccessRule](#)
- [CreateOrganization](#)
- [CreateResource](#)
- [CreateUser](#)
- [DeleteAccessControlRule](#)
- [DeleteAlias](#)
- [DeleteAvailabilityConfiguration](#)
- [DeleteEmailMonitoringConfiguration](#)
- [DeleteGroup](#)
- [DeleteImpersonationRole](#)
- [DeleteMailboxPermissions](#)
- [DeleteMobileDeviceAccessOverride](#)
- [DeleteMobileDeviceAccessRule](#)
- [DeleteOrganization](#)
- [DeleteResource](#)
- [DeleteRetentionPolicy](#)
- [DeleteUser](#)

- [DeregisterFromWorkMail](#)
- [DeregisterMailDomain](#)
- [DescribeEmailMonitoringConfiguration](#)
- [DescribeEntity](#)
- [DescribeGroup](#)
- [DescribeInboundDmarcSettings](#)
- [DescribeMailboxExportJob](#)
- [DescribeOrganization](#)
- [DescribeResource](#)
- [DescribeUser](#)
- [DisassociateDelegateFromResource](#)
- [DisassociateMemberFromGroup](#)
- [GetAccessControlEffect](#)
- [GetDefaultRetentionPolicy](#)
- [GetImpersonationRole](#)
- [GetImpersonationRoleEffect](#)
- [GetMailboxDetails](#)
- [GetMailDomain](#)
- [GetMobileDeviceAccessEffect](#)
- [GetMobileDeviceAccessOverride](#)
- [ListAccessControlRules](#)
- [ListAliases](#)
- [ListAvailabilityConfigurations](#)
- [ListGroupMembers](#)
- [ListGroups](#)
- [ListGroupsForEntity](#)
- [ListImpersonationRoles](#)
- [ListMailboxExportJobs](#)
- [ListMailboxPermissions](#)
- [ListMailDomains](#)

- [ListMobileDeviceAccessOverrides](#)
- [ListMobileDeviceAccessRules](#)
- [ListOrganizations](#)
- [ListResourceDelegates](#)
- [ListResources](#)
- [ListTagsForResource](#)
- [ListUsers](#)
- [PutAccessControlRule](#)
- [PutEmailMonitoringConfiguration](#)
- [PutInboundDmarcSettings](#)
- [PutMailboxPermissions](#)
- [PutMobileDeviceAccessOverride](#)
- [PutRetentionPolicy](#)
- [RegisterMailDomain](#)
- [RegisterToWorkMail](#)
- [ResetPassword](#)
- [StartMailboxExportJob](#)
- [TagResource](#)
- [TestAvailabilityConfiguration](#)
- [UntagResource](#)
- [UpdateAvailabilityConfiguration](#)
- [UpdateDefaultMailDomain](#)
- [UpdateGroup](#)
- [UpdateImpersonationRole](#)
- [UpdateMailboxQuota](#)
- [UpdateMobileDeviceAccessRule](#)
- [UpdatePrimaryEmailAddress](#)
- [UpdateResource](#)
- [UpdateUser](#)

AssociateDelegateToResource

Service: Amazon WorkMail

Adds a member (user or group) to the resource's set of delegates.

Request Syntax

```
{
  "EntityId": "string",
  "OrganizationId": "string",
  "ResourceId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

EntityId

The member (user or group) to associate to the resource.

The entity ID can accept *UserId or GroupID, Username or Groupname, or email*.

- Entity: 12345678-1234-1234-1234-123456789012 or S-1-1-12-1234567890-123456789-123456789-1234
- Email address: entity@domain.tld
- Entity: entity

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

OrganizationId

The organization under which the resource exists.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

ResourceId

The resource for which members (users or groups) are associated.

The identifier can accept *ResourceId*, *Resourcename*, or *email*. The following identity formats are available:

- Resource ID: r-0123456789a0123456789b0123456789
- Email address: resource@domain.tld
- Resource name: resource

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9._%+@-]+`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

UnsupportedOperationException

You can't perform a write operation against a read-only directory.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

AssociateMemberToGroup

Service: Amazon WorkMail

Adds a member (user or group) to the group's set.

Request Syntax

```
{
  "GroupId": "string",
  "MemberId": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

GroupId

The group to which the member (user or group) is associated.

The identifier can accept *GroupId*, *Groupname*, or *email*. The following identity formats are available:

- Group ID: 12345678-1234-1234-1234-123456789012 or S-1-1-12-1234567890-123456789-123456789-1234
- Email address: group@domain.tld
- Group name: group

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

MemberId

The member (user or group) to associate to the group.

The member ID can accept *UserID* or *GroupId*, *Username* or *Groupname*, or *email*.

- Member: 12345678-1234-1234-1234-123456789012 or S-1-1-12-1234567890-123456789-123456789-1234
- Email address: member@domain.tld
- Member name: member

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

OrganizationId

The organization under which the group exists.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

DirectoryServiceAuthenticationFailedException

The directory service doesn't recognize the credentials supplied by WorkMail.

HTTP Status Code: 400

DirectoryUnavailableException

The directory is unavailable. It might be located in another Region or deleted.

HTTP Status Code: 400

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

UnsupportedOperationException

You can't perform a write operation against a read-only directory.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AssumeImpersonationRole

Service: Amazon WorkMail

Assumes an impersonation role for the given WorkMail organization. This method returns an authentication token you can use to make impersonated calls.

Request Syntax

```
{
  "ImpersonationRoleId": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ImpersonationRoleId

The impersonation role ID to assume.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

OrganizationId

The WorkMail organization under which the impersonation role will be assumed.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

Response Syntax

```
{
  "ExpiresIn": number,
  "Token": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ExpiresIn

The authentication token's validity, in seconds.

Type: Long

Token

The authentication token for the impersonation role.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\x21-\x7e]+`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CancelMailboxExportJob

Service: Amazon WorkMail

Cancels a mailbox export job.

Note

If the mailbox export job is near completion, it might not be possible to cancel it.

Request Syntax

```
{
  "ClientToken": "string",
  "JobId": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClientToken

The idempotency token for the client request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\x21-\x7e]+`

Required: Yes

JobId

The job ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: [A-Za-z0-9-]+

Required: Yes

OrganizationId

The organization ID.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateAlias

Service: Amazon WorkMail

Adds an alias to the set of a given member (user or group) of WorkMail.

Request Syntax

```
{  
  "Alias": "string",  
  "EntityId": "string",  
  "OrganizationId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Alias

The alias to add to the member set.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 254.

Pattern: [a-zA-Z0-9._%+ -]{1,64}@[a-zA-Z0-9.-]+\.[a-zA-Z-]{2,}

Required: Yes

EntityId

The member (user or group) to which this alias is added.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 256.

Required: Yes

OrganizationId

The organization under which the member (user or group) exists.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EmailAddressInUseException

The email address that you're trying to assign is already created for a different user, group, or resource.

HTTP Status Code: 400

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

LimitExceededException

The request exceeds the limit of the resource.

HTTP Status Code: 400

MailDomainNotFoundException

The domain specified is not found in your organization.

HTTP Status Code: 400

MailDomainStateException

After a domain has been added to the organization, it must be verified. The domain is not yet verified.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateAvailabilityConfiguration

Service: Amazon WorkMail

Creates an AvailabilityConfiguration for the given WorkMail organization and domain.

Request Syntax

```
{
  "ClientToken": "string",
  "DomainName": "string",
  "EwsProvider": {
    "EwsEndpoint": "string",
    "EwsPassword": "string",
    "EwsUsername": "string"
  },
  "LambdaProvider": {
    "LambdaArn": "string"
  },
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClientToken

An idempotent token that ensures that an API request is executed only once.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\x21-\x7e]+`

Required: No

DomainName

The domain to which the provider applies.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Pattern: [a-zA-Z0-9.-]+

Required: Yes

EwsProvider

Exchange Web Services (EWS) availability provider definition. The request must contain exactly one provider definition, either `EwsProvider` or `LambdaProvider`.

Type: [EwsAvailabilityProvider](#) object

Required: No

LambdaProvider

Lambda availability provider definition. The request must contain exactly one provider definition, either `EwsProvider` or `LambdaProvider`.

Type: [LambdaAvailabilityProvider](#) object

Required: No

OrganizationId

The WorkMail organization for which the `AvailabilityConfiguration` will be created.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

LimitExceededException

The request exceeds the limit of the resource.

HTTP Status Code: 400

NameAvailabilityException

The user, group, or resource name isn't unique in WorkMail.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateGroup

Service: Amazon WorkMail

Creates a group that can be used in WorkMail by calling the [RegisterToWorkMail](#) operation.

Request Syntax

```
{  
  "HiddenFromGlobalAddressList": boolean,  
  "Name": "string",  
  "OrganizationId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[HiddenFromGlobalAddressList](#)

If this parameter is enabled, the group will be hidden from the address book.

Type: Boolean

Required: No

[Name](#)

The name of the group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: Yes

[OrganizationId](#)

The organization under which the group is to be created.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Syntax

```
{  
  "GroupId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

GroupId

The identifier of the group.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

DirectoryServiceAuthenticationFailedException

The directory service doesn't recognize the credentials supplied by WorkMail.

HTTP Status Code: 400

DirectoryUnavailableException

The directory is unavailable. It might be located in another Region or deleted.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

NameAvailabilityException

The user, group, or resource name isn't unique in WorkMail.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

ReservedNameException

This user, group, or resource name is not allowed in WorkMail.

HTTP Status Code: 400

UnsupportedOperationException

You can't perform a write operation against a read-only directory.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateImpersonationRole

Service: Amazon WorkMail

Creates an impersonation role for the given WorkMail organization.

Idempotency ensures that an API request completes no more than one time. With an idempotent request, if the original request completes successfully, any subsequent retries also complete successfully without performing any further actions.

Request Syntax

```
{
  "ClientToken": "string",
  "Description": "string",
  "Name": "string",
  "OrganizationId": "string",
  "Rules": [
    {
      "Description": "string",
      "Effect": "string",
      "ImpersonationRuleId": "string",
      "Name": "string",
      "NotTargetUsers": [ "string" ],
      "TargetUsers": [ "string" ]
    }
  ],
  "Type": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClientToken

The idempotency token for the client request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\x21-\x7e]+`

Required: No

Description

The description of the new impersonation role.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\^\\\x00-\x09\x0B\x0C\x0E-\x1F\x7F\x3C\x3E\x5C]+`

Required: No

Name

The name of the new impersonation role.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\^\\\x00-\x1F\x7F\x3C\x3E\x5C]+`

Required: Yes

OrganizationId

The WorkMail organization to create the new impersonation role within.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Rules

The list of rules for the impersonation role.

Type: Array of [ImpersonationRule](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: Yes

Type

The impersonation role's type. The available impersonation role types are READ_ONLY or FULL_ACCESS.

Type: String

Valid Values: FULL_ACCESS | READ_ONLY

Required: Yes

Response Syntax

```
{
  "ImpersonationRoleId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ImpersonationRoleId

The new impersonation role ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

LimitExceededException

The request exceeds the limit of the resource.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateMobileDeviceAccessRule

Service: Amazon WorkMail

Creates a new mobile device access rule for the specified WorkMail organization.

Request Syntax

```
{
  "ClientToken": "string",
  "Description": "string",
  "DeviceModels": [ "string" ],
  "DeviceOperatingSystems": [ "string" ],
  "DeviceTypes": [ "string" ],
  "DeviceUserAgents": [ "string" ],
  "Effect": "string",
  "Name": "string",
  "NotDeviceModels": [ "string" ],
  "NotDeviceOperatingSystems": [ "string" ],
  "NotDeviceTypes": [ "string" ],
  "NotDeviceUserAgents": [ "string" ],
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClientToken

The idempotency token for the client request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\x21-\x7e]+`

Required: No

Description

The rule description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\S\s]+`

Required: No

DeviceModels

Device models that the rule will match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

DeviceOperatingSystems

Device operating systems that the rule will match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

DeviceTypes

Device types that the rule will match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

DeviceUserAgents

Device user agents that the rule will match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

Effect

The effect of the rule when it matches. Allowed values are ALLOW or DENY.

Type: String

Valid Values: ALLOW | DENY

Required: Yes

Name

The rule name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\S\s]+`

Required: Yes

NotDeviceModels

Device models that the rule **will not** match. All other device models will match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

NotDeviceOperatingSystems

Device operating systems that the rule **will not** match. All other device operating systems will match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

NotDeviceTypes

Device types that the rule **will not** match. All other device types will match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

NotDeviceUserAgents

Device user agents that the rule **will not** match. All other device user agents will match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

OrganizationId

The WorkMail organization under which the rule will be created.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Syntax

```
{
  "MobileDeviceAccessRuleId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

MobileDeviceAccessRuleId

The identifier for the newly created mobile device access rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9_-]+`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

LimitExceededException

The request exceeds the limit of the resource.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateOrganization

Service: Amazon WorkMail

Creates a new WorkMail organization. Optionally, you can choose to associate an existing AWS Directory Service directory with your organization. If an AWS Directory Service directory ID is specified, the organization alias must match the directory alias. If you choose not to associate an existing directory with your organization, then we create a new WorkMail directory for you. For more information, see [Adding an organization](#) in the *WorkMail Administrator Guide*.

You can associate multiple email domains with an organization, then choose your default email domain from the WorkMail console. You can also associate a domain that is managed in an Amazon Route 53 public hosted zone. For more information, see [Adding a domain](#) and [Choosing the default domain](#) in the *WorkMail Administrator Guide*.

Optionally, you can use a customer managed key from AWS Key Management Service (AWS KMS) to encrypt email for your organization. If you don't associate an AWS KMS key, WorkMail creates a default, AWS managed key for you.

Request Syntax

```
{
  "Alias": "string",
  "ClientToken": "string",
  "DirectoryId": "string",
  "Domains": [
    {
      "DomainName": "string",
      "HostedZoneId": "string"
    }
  ],
  "EnableInteroperability": boolean,
  "KmsKeyArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Alias

The organization alias.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 62.

Pattern: `^(?!d-)([\da-zA-Z]+)([-][\da-zA-Z]+)*`

Required: Yes

ClientToken

The idempotency token associated with the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\x21-\x7e]+`

Required: No

DirectoryId

The AWS Directory Service directory ID.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `^d-[0-9a-f]{10}$`

Required: No

Domains

The email domains to associate with the organization.

Type: Array of [Domain](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

EnableInteroperability

When `true`, allows organization interoperability between WorkMail and Microsoft Exchange. If `true`, you must include a AD Connector directory ID in the request.

Type: Boolean

Required: No

KmsKeyArn

The Amazon Resource Name (ARN) of a customer managed key from AWS KMS.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws:kms:[a-z0-9-]*:[a-z0-9-]+:[A-Za-z0-9][A-Za-z0-9:_/+=@.-]{0,1023}`

Required: No

Response Syntax

```
{
  "OrganizationId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

OrganizationId

The organization ID.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

DirectoryInUseException

The directory is already in use by another WorkMail organization in the same account and Region.

HTTP Status Code: 400

DirectoryUnavailableException

The directory is unavailable. It might be located in another Region or deleted.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

LimitExceededException

The request exceeds the limit of the resource.

HTTP Status Code: 400

NameAvailabilityException

The user, group, or resource name isn't unique in WorkMail.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateResource

Service: Amazon WorkMail

Creates a new WorkMail resource.

Request Syntax

```
{  
  "Description": "string",  
  "HiddenFromGlobalAddressList": boolean,  
  "Name": "string",  
  "OrganizationId": "string",  
  "Type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Description

Resource description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

HiddenFromGlobalAddressList

If this parameter is enabled, the resource will be hidden from the address book.

Type: Boolean

Required: No

Name

The name of the new resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `[\w\-.]+(@[a-zA-Z0-9.\-]+\.[a-zA-Z0-9-]{2,})?`

Required: Yes

OrganizationId

The identifier associated with the organization for which the resource is created.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Type

The type of the new resource. The available types are equipment and room.

Type: String

Valid Values: ROOM | EQUIPMENT

Required: Yes

Response Syntax

```
{  
  "ResourceId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ResourceId

The identifier of the new resource.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^[a-f0-9]{32}$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

DirectoryServiceAuthenticationFailedException

The directory service doesn't recognize the credentials supplied by WorkMail.

HTTP Status Code: 400

DirectoryUnavailableException

The directory is unavailable. It might be located in another Region or deleted.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

NameAvailabilityException

The user, group, or resource name isn't unique in WorkMail.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

ReservedNameException

This user, group, or resource name is not allowed in WorkMail.

HTTP Status Code: 400

UnsupportedOperationException

You can't perform a write operation against a read-only directory.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateUser

Service: Amazon WorkMail

Creates a user who can be used in WorkMail by calling the [RegisterToWorkMail](#) operation.

Request Syntax

```
{
  "DisplayName": "string",
  "FirstName": "string",
  "HiddenFromGlobalAddressList": boolean,
  "LastName": "string",
  "Name": "string",
  "OrganizationId": "string",
  "Password": "string",
  "Role": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[DisplayName](#)

The display name for the new user.

Type: String

Length Constraints: Maximum length of 256.

Required: Yes

[FirstName](#)

The first name of the new user.

Type: String

Length Constraints: Maximum length of 256.

Required: No

HiddenFromGlobalAddressList

If this parameter is enabled, the user will be hidden from the address book.

Type: Boolean

Required: No

LastName

The last name of the new user.

Type: String

Length Constraints: Maximum length of 256.

Required: No

Name

The name for the new user. WorkMail directory user names have a maximum length of 64. All others have a maximum length of 20.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w\-\ .]+(@[a-zA-Z0-9\-\]+\.[a-zA-Z0-9-]{2,})?`

Required: Yes

OrganizationId

The identifier of the organization for which the user is created.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Password

The password for the new user.

Type: String

Length Constraints: Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

Role

The role of the new user.

You cannot pass *SYSTEM_USER* or *RESOURCE* role in a single request. When a user role is not selected, the default role of *USER* is selected.

Type: String

Valid Values: `USER` | `RESOURCE` | `SYSTEM_USER` | `REMOTE_USER`

Required: No

Response Syntax

```
{
  "UserId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

UserId

The identifier for the new user.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

DirectoryServiceAuthenticationFailedException

The directory service doesn't recognize the credentials supplied by WorkMail.

HTTP Status Code: 400

DirectoryUnavailableException

The directory is unavailable. It might be located in another Region or deleted.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

InvalidPasswordException

The supplied password doesn't match the minimum security constraints, such as length or use of special characters.

HTTP Status Code: 400

NameAvailabilityException

The user, group, or resource name isn't unique in WorkMail.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

ReservedNameException

This user, group, or resource name is not allowed in WorkMail.

HTTP Status Code: 400

UnsupportedOperationException

You can't perform a write operation against a read-only directory.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAccessControlRule

Service: Amazon WorkMail

Deletes an access control rule for the specified WorkMail organization.

Note

Deleting already deleted and non-existing rules does not produce an error. In those cases, the service sends back an HTTP 200 response with an empty HTTP body.

Request Syntax

```
{
  "Name": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

The name of the access control rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

OrganizationId

The identifier for the organization.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAlias

Service: Amazon WorkMail

Remove one or more specified aliases from a set of aliases for a given user.

Request Syntax

```
{
  "Alias": "string",
  "EntityId": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Alias

The aliases to be removed from the user's set of aliases. Duplicate entries in the list are collapsed into single entries (the list is transformed into a set).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 254.

Pattern: [a-zA-Z0-9._%+-]{1,64}@[a-zA-Z0-9.-]+\.[a-zA-Z-]{2,}

Required: Yes

EntityId

The identifier for the member (user or group) from which to have the aliases removed.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 256.

Required: Yes

OrganizationId

The identifier for the organization under which the user exists.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAvailabilityConfiguration

Service: Amazon WorkMail

Deletes the AvailabilityConfiguration for the given WorkMail organization and domain.

Request Syntax

```
{
  "DomainName": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

DomainName

The domain for which the AvailabilityConfiguration will be deleted.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Pattern: [a-zA-Z0-9.-]+

Required: Yes

OrganizationId

The WorkMail organization for which the AvailabilityConfiguration will be deleted.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteEmailMonitoringConfiguration

Service: Amazon WorkMail

Deletes the email monitoring configuration for a specified organization.

Request Syntax

```
{  
  "OrganizationId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

OrganizationId

The ID of the organization from which the email monitoring configuration is deleted.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteGroup

Service: Amazon WorkMail

Deletes a group from WorkMail.

Request Syntax

```
{  
  "GroupId": "string",  
  "OrganizationId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

GroupId

The identifier of the group to be deleted.

The identifier can be the *GroupId*, or *Groupname*. The following identity formats are available:

- Group ID: 12345678-1234-1234-1234-123456789012 or S-1-1-12-1234567890-123456789-123456789-1234
- Group name: group

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

OrganizationId

The organization that contains the group.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

DirectoryServiceAuthenticationFailedException

The directory service doesn't recognize the credentials supplied by WorkMail.

HTTP Status Code: 400

DirectoryUnavailableException

The directory is unavailable. It might be located in another Region or deleted.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

UnsupportedOperationException

You can't perform a write operation against a read-only directory.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteImpersonationRole

Service: Amazon WorkMail

Deletes an impersonation role for the given WorkMail organization.

Request Syntax

```
{
  "ImpersonationRoleId": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ImpersonationRoleId

The ID of the impersonation role to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

OrganizationId

The WorkMail organization from which to delete the impersonation role.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteMailboxPermissions

Service: Amazon WorkMail

Deletes permissions granted to a member (user or group).

Request Syntax

```
{
  "EntityId": "string",
  "GranteeId": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

EntityId

The identifier of the entity that owns the mailbox.

The identifier can be *UserId* or *Group Id*, *Username* or *Groupname*, or *email*.

- Entity ID: 12345678-1234-1234-1234-123456789012, r-0123456789a0123456789b0123456789, or S-1-1-12-1234567890-123456789-123456789-1234
- Email address: entity@domain.tld
- Entity name: entity

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

GranteeId

The identifier of the entity for which to delete granted permissions.

The identifier can be *UserId*, *ResourceID*, or *Group Id*, *Username* or *Groupname*, or *email*.

- Grantee ID:
12345678-1234-1234-1234-123456789012,r-0123456789a0123456789b0123456789, or
S-1-1-12-1234567890-123456789-123456789-1234
- Email address: grantee@domain.tld
- Grantee name: grantee

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

OrganizationId

The identifier of the organization under which the member (user or group) exists.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

DeleteMobileDeviceAccessOverride

Service: Amazon WorkMail

Deletes the mobile device access override for the given WorkMail organization, user, and device.

Note

Deleting already deleted and non-existing overrides does not produce an error. In those cases, the service sends back an HTTP 200 response with an empty HTTP body.

Request Syntax

```
{
  "DeviceId": "string",
  "OrganizationId": "string",
  "UserId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

DeviceId

The mobile device for which you delete the override. DeviceId is case insensitive.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: [A-Za-z0-9]+

Required: Yes

OrganizationId

The WorkMail organization for which the access override will be deleted.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

UserId

The WorkMail user for which you want to delete the override. Accepts the following types of user identities:

- User ID: 12345678-1234-1234-1234-123456789012 or S-1-1-12-1234567890-123456789-123456789-1234
- Email address: `user@domain.tld`
- User name: `user`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9._%+@-]+`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteMobileDeviceAccessRule

Service: Amazon WorkMail

Deletes a mobile device access rule for the specified WorkMail organization.

Note

Deleting already deleted and non-existing rules does not produce an error. In those cases, the service sends back an HTTP 200 response with an empty HTTP body.

Request Syntax

```
{
  "MobileDeviceAccessRuleId": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MobileDeviceAccessRuleId

The identifier of the rule to be deleted.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

OrganizationId

The WorkMail organization under which the rule will be deleted.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteOrganization

Service: Amazon WorkMail

Deletes an WorkMail organization and all underlying AWS resources managed by WorkMail as part of the organization. You can choose whether to delete the associated directory. For more information, see [Removing an organization](#) in the *WorkMail Administrator Guide*.

Request Syntax

```
{
  "ClientToken": "string",
  "DeleteDirectory": boolean,
  "ForceDelete": boolean,
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClientToken

The idempotency token associated with the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\x21-\x7e]+`

Required: No

DeleteDirectory

If true, deletes the AWS Directory Service directory associated with the organization.

Type: Boolean

Required: Yes

ForceDelete

Deletes a WorkMail organization even if the organization has enabled users.

Type: Boolean

Required: No

OrganizationId

The organization ID.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Syntax

```
{
  "OrganizationId": "string",
  "State": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

OrganizationId

The organization ID.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

State

The state of the organization.

Type: String

Length Constraints: Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteResource

Service: Amazon WorkMail

Deletes the specified resource.

Request Syntax

```
{
  "OrganizationId": "string",
  "ResourceId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

OrganizationId

The identifier associated with the organization from which the resource is deleted.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

ResourceId

The identifier of the resource to be deleted.

The identifier can accept *ResourceId*, or *ResourceName*. The following identity formats are available:

- Resource ID: r-0123456789a0123456789b0123456789
- Resource name: resource

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

UnsupportedOperationException

You can't perform a write operation against a read-only directory.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteRetentionPolicy

Service: Amazon WorkMail

Deletes the specified retention policy from the specified organization.

Request Syntax

```
{  
  "Id": "string",  
  "OrganizationId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Id

The retention policy ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

OrganizationId

The organization ID.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteUser

Service: Amazon WorkMail

Deletes a user from WorkMail and all subsequent systems. Before you can delete a user, the user state must be DISABLED. Use the [DescribeUser](#) action to confirm the user state.

Deleting a user is permanent and cannot be undone. WorkMail archives user mailboxes for 30 days before they are permanently removed.

Request Syntax

```
{
  "OrganizationId": "string",
  "UserId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[OrganizationId](#)

The organization that contains the user to be deleted.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

[UserId](#)

The identifier of the user to be deleted.

The identifier can be the *UserId* or *Username*. The following identity formats are available:

- User ID: 12345678-1234-1234-1234-123456789012 or S-1-1-12-1234567890-123456789-123456789-1234
- User name: user

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

DirectoryServiceAuthenticationFailedException

The directory service doesn't recognize the credentials supplied by WorkMail.

HTTP Status Code: 400

DirectoryUnavailableException

The directory is unavailable. It might be located in another Region or deleted.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

UnsupportedOperationException

You can't perform a write operation against a read-only directory.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeregisterFromWorkMail

Service: Amazon WorkMail

Mark a user, group, or resource as no longer used in WorkMail. This action disassociates the mailbox and schedules it for clean-up. WorkMail keeps mailboxes for 30 days before they are permanently removed. The functionality in the console is *Disable*.

Request Syntax

```
{  
  "EntityId": "string",  
  "OrganizationId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

EntityId

The identifier for the member to be updated.

The identifier can be *UserId*, *ResourceId*, or *GroupId*, *Username*, *Resourcename*, or *Groupname*, or *email*.

- Entity ID: 12345678-1234-1234-1234-123456789012, r-0123456789a0123456789b0123456789, or S-1-1-12-1234567890-123456789-123456789-1234
- Email address: entity@domain.tld
- Entity name: entity

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

OrganizationId

The identifier for the organization under which the WorkMail entity exists.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeregisterMailDomain

Service: Amazon WorkMail

Removes a domain from WorkMail, stops email routing to WorkMail, and removes the authorization allowing WorkMail use. SES keeps the domain because other applications may use it. You must first remove any email address used by WorkMail entities before you remove the domain.

Request Syntax

```
{
  "DomainName": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

DomainName

The domain to deregister in WorkMail and SES.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 209.

Pattern: [a-zA-Z0-9.-]+

Required: Yes

OrganizationId

The WorkMail organization for which the domain will be deregistered.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidCustomSesConfigurationException

You SES configuration has customizations that WorkMail cannot save. The error message lists the invalid setting. For examples of invalid settings, refer to [CreateReceiptRule](#).

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

MailDomainInUseException

The domain you're trying to change is in use by another user or organization in your account. See the error message for details.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeEmailMonitoringConfiguration

Service: Amazon WorkMail

Describes the current email monitoring configuration for a specified organization.

Request Syntax

```
{  
  "OrganizationId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

OrganizationId

The ID of the organization for which the email monitoring configuration is described.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Syntax

```
{  
  "LogGroupArn": "string",  
  "RoleArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LogGroupArn

The Amazon Resource Name (ARN) of the CloudWatch Log group associated with the email monitoring configuration.

Type: String

Length Constraints: Minimum length of 47. Maximum length of 562.

Pattern: `arn:aws:logs:[a-z\-\0-9]*:[0-9]{12}:log-group:([\.\-_/#A-Za-z0-9]+):.*$`

RoleArn

The Amazon Resource Name (ARN) of the IAM Role associated with the email monitoring configuration.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws:iam:[a-z0-9-]*:[a-z0-9-]+:[A-Za-z0-9][A-Za-z0-9:_/+=@.-]{0,1023}`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeEntity

Service: Amazon WorkMail

Returns basic details about an entity in WorkMail.

Request Syntax

```
{  
  "Email": "string",  
  "OrganizationId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Email

The email under which the entity exists.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 254.

Pattern: [a-zA-Z0-9._%+]{1,64}@[a-zA-Z0-9.-]+\.[a-zA-Z-]{2,}

Required: Yes

OrganizationId

The identifier for the organization under which the entity exists.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

Response Syntax

```
{  
  "EntityId": "string",  
  "Name": "string",  
  "Type": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

EntityId

The entity ID under which the entity exists.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 256.

Name

Username, GroupName, or ResourceName based on entity type.

Type: String

Length Constraints: Maximum length of 256.

Type

Entity type.

Type: String

Valid Values: GROUP | USER | RESOURCE

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeGroup

Service: Amazon WorkMail

Returns the data available for the group.

Request Syntax

```
{
  "GroupId": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

GroupId

The identifier for the group to be described.

The identifier can accept *GroupId*, *Groupname*, or *email*. The following identity formats are available:

- Group ID: 12345678-1234-1234-1234-123456789012 or S-1-1-12-1234567890-123456789-123456789-1234
- Email address: group@domain.tld
- Group name: group

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

OrganizationId

The identifier for the organization under which the group exists.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Syntax

```
{
  "DisabledDate": number,
  "Email": "string",
  "EnabledDate": number,
  "GroupId": "string",
  "HiddenFromGlobalAddressList": boolean,
  "Name": "string",
  "State": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DisabledDate

The date and time when a user was deregistered from WorkMail, in UNIX epoch time format.

Type: Timestamp

Email

The email of the described group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 254.

Pattern: `[a-zA-Z0-9._%+-]{1,64}@[a-zA-Z0-9.-]+\.[a-zA-Z-]{2,}`

EnabledDate

The date and time when a user was registered to WorkMail, in UNIX epoch time format.

Type: Timestamp

GroupId

The identifier of the described group.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 256.

HiddenFromGlobalAddressList

If the value is set to *true*, the group is hidden from the address book.

Type: Boolean

Name

The name of the described group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

State

The state of the user: enabled (registered to WorkMail) or disabled (deregistered or never registered to WorkMail).

Type: String

Valid Values: ENABLED | DISABLED | DELETED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeInboundDmarcSettings

Service: Amazon WorkMail

Lists the settings in a DMARC policy for a specified organization.

Request Syntax

```
{  
  "OrganizationId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

OrganizationId

Lists the ID of the given organization.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Syntax

```
{  
  "Enforced": boolean  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Enforced

Lists the enforcement setting of the applied policy.

Type: Boolean

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeMailboxExportJob

Service: Amazon WorkMail

Describes the current status of a mailbox export job.

Request Syntax

```
{  
  "JobId": "string",  
  "OrganizationId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

JobId

The mailbox export job ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: [A-Za-z0-9-]+

Required: Yes

OrganizationId

The organization ID.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

Response Syntax

```
{
  "Description": "string",
  "EndTime": number,
  "EntityId": "string",
  "ErrorInfo": "string",
  "EstimatedProgress": number,
  "KmsKeyArn": "string",
  "RoleArn": "string",
  "S3BucketName": "string",
  "S3Path": "string",
  "S3Prefix": "string",
  "StartTime": number,
  "State": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Description

The mailbox export job description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1023.

Pattern: `[\S\s]*`

EndTime

The mailbox export job end timestamp.

Type: Timestamp

EntityId

The identifier of the user or resource associated with the mailbox.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 256.

ErrorInfo

Error information for failed mailbox export jobs.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]*`

EstimatedProgress

The estimated progress of the mailbox export job, in percentage points.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

KmsKeyArn

The Amazon Resource Name (ARN) of the symmetric AWS Key Management Service (AWS KMS) key that encrypts the exported mailbox content.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws:kms:[a-z0-9-]*:[a-z0-9-]+:[A-Za-z0-9][A-Za-z0-9:_/+=@.-]{0,1023}`

RoleArn

The ARN of the AWS Identity and Access Management (IAM) role that grants write permission to the Amazon Simple Storage Service (Amazon S3) bucket.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws:iam:[a-z0-9-]*:[a-z0-9-]+:[A-Za-z0-9][A-Za-z0-9:_/+=@.-]{0,1023}`

S3BucketName

The name of the S3 bucket.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: [A-Za-z0-9.-]+

S3Path

The path to the S3 bucket and file that the mailbox export job is exporting to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1023.

Pattern: [A-Za-z0-9!_.*'()/-]+

S3Prefix

The S3 bucket prefix.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1023.

Pattern: [A-Za-z0-9!_.*'()/-]+

StartTime

The mailbox export job start timestamp.

Type: Timestamp

State

The state of the mailbox export job.

Type: String

Valid Values: RUNNING | COMPLETED | FAILED | CANCELLED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeOrganization

Service: Amazon WorkMail

Provides more information regarding a given organization based on its identifier.

Request Syntax

```
{  
  "OrganizationId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

OrganizationId

The identifier for the organization to be described.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Syntax

```
{  
  "Alias": "string",  
  "ARN": "string",  
  "CompletedDate": number,  
  "DefaultMailDomain": "string",  
  "DirectoryId": "string",  
  "DirectoryType": "string",  
  "ErrorMessage": "string",  
  "InteroperabilityEnabled": boolean,  
  "MigrationAdmin": "string",
```



```
"OrganizationId": "string",  
"State": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Alias](#)

The alias for an organization.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 62.

Pattern: `^(?!d-)([\da-zA-Z]+)([-][\da-zA-Z]+)*`

[ARN](#)

The Amazon Resource Name (ARN) of the organization.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws:workmail:[a-z0-9-]*:[a-z0-9-]+:[A-Za-z0-9][A-Za-z0-9:/_+=, @. -]{0,1023}`

[CompletedDate](#)

The date at which the organization became usable in the WorkMail context, in UNIX epoch time format.

Type: Timestamp

[DefaultMailDomain](#)

The default mail domain associated with the organization.

Type: String

Length Constraints: Maximum length of 256.

DirectoryId

The identifier for the directory associated with an WorkMail organization.

Type: String

Length Constraints: Maximum length of 256.

DirectoryType

The type of directory associated with the WorkMail organization.

Type: String

Length Constraints: Maximum length of 256.

ErrorMessage

(Optional) The error message indicating if unexpected behavior was encountered with regards to the organization.

Type: String

Length Constraints: Maximum length of 256.

InteroperabilityEnabled

Indicates if interoperability is enabled for this organization.

Type: Boolean

MigrationAdmin

The user ID of the migration admin if migration is enabled for the organization.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 256.

OrganizationId

The identifier of an organization.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

State

The state of an organization.

Type: String

Length Constraints: Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

DescribeResource

Service: Amazon WorkMail

Returns the data available for the resource.

Request Syntax

```
{
  "OrganizationId": "string",
  "ResourceId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

OrganizationId

The identifier associated with the organization for which the resource is described.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

ResourceId

The identifier of the resource to be described.

The identifier can accept *ResourceId*, *ResourceName*, or *email*. The following identity formats are available:

- Resource ID: r-0123456789a0123456789b0123456789
- Email address: resource@domain.tld
- Resource name: resource

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

Response Syntax

```
{
  "BookingOptions": {
    "AutoAcceptRequests": boolean,
    "AutoDeclineConflictingRequests": boolean,
    "AutoDeclineRecurringRequests": boolean
  },
  "Description": "string",
  "DisabledDate": number,
  "Email": "string",
  "EnabledDate": number,
  "HiddenFromGlobalAddressList": boolean,
  "Name": "string",
  "ResourceId": "string",
  "State": "string",
  "Type": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BookingOptions

The booking options for the described resource.

Type: [BookingOptions](#) object

Description

Description of the resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

DisabledDate

The date and time when a resource was disabled from WorkMail, in UNIX epoch time format.

Type: Timestamp

Email

The email of the described resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 254.

Pattern: `[a-zA-Z0-9._%+-]{1,64}@[a-zA-Z0-9.-]+\.[a-zA-Z-]{2,}`

EnabledDate

The date and time when a resource was enabled for WorkMail, in UNIX epoch time format.

Type: Timestamp

HiddenFromGlobalAddressList

If enabled, the resource is hidden from the global address list.

Type: Boolean

Name

The name of the described resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `[\w\-.]+(@[a-zA-Z0-9\-.]+\.[a-zA-Z0-9-]{2,})?`

ResourceId

The identifier of the described resource.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^r-[0-9a-f]{32}$`

State

The state of the resource: enabled (registered to WorkMail), disabled (deregistered or never registered to WorkMail), or deleted.

Type: String

Valid Values: ENABLED | DISABLED | DELETED

Type

The type of the described resource.

Type: String

Valid Values: ROOM | EQUIPMENT

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

UnsupportedOperationException

You can't perform a write operation against a read-only directory.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeUser

Service: Amazon WorkMail

Provides information regarding the user.

Request Syntax

```
{
  "OrganizationId": "string",
  "UserId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

OrganizationId

The identifier for the organization under which the user exists.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

UserId

The identifier for the user to be described.

The identifier can be the *UserId*, *Username*, or *email*. The following identity formats are available:

- User ID: 12345678-1234-1234-1234-123456789012 or S-1-1-12-1234567890-123456789-123456789-1234
- Email address: user@domain.tld
- User name: user

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

Response Syntax

```
{
  "City": "string",
  "Company": "string",
  "Country": "string",
  "Department": "string",
  "DisabledDate": number,
  "DisplayName": "string",
  "Email": "string",
  "EnabledDate": number,
  "FirstName": "string",
  "HiddenFromGlobalAddressList": boolean,
  "Initials": "string",
  "JobTitle": "string",
  "LastName": "string",
  "MailboxDeprovisionedDate": number,
  "MailboxProvisionedDate": number,
  "Name": "string",
  "Office": "string",
  "State": "string",
  "Street": "string",
  "Telephone": "string",
  "UserId": "string",
  "UserRole": "string",
  "ZipCode": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

City

City where the user is located.

Type: String

Length Constraints: Maximum length of 256.

Company

Company of the user.

Type: String

Length Constraints: Maximum length of 256.

Country

Country where the user is located.

Type: String

Length Constraints: Maximum length of 256.

Department

Department of the user.

Type: String

Length Constraints: Maximum length of 256.

DisabledDate

The date and time at which the user was disabled for WorkMail usage, in UNIX epoch time format.

Type: Timestamp

DisplayName

The display name of the user.

Type: String

Length Constraints: Maximum length of 256.

Email

The email of the user.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 254.

Pattern: `[a-zA-Z0-9._%+ -]{1,64}@[a-zA-Z0-9.-]+\.[a-zA-Z-]{2,}`

EnabledDate

The date and time at which the user was enabled for WorkMail usage, in UNIX epoch time format.

Type: Timestamp

FirstName

First name of the user.

Type: String

Length Constraints: Maximum length of 256.

HiddenFromGlobalAddressList

If enabled, the user is hidden from the global address list.

Type: Boolean

Initials

Initials of the user.

Type: String

Length Constraints: Maximum length of 256.

JobTitle

Job title of the user.

Type: String

Length Constraints: Maximum length of 256.

LastName

Last name of the user.

Type: String

Length Constraints: Maximum length of 256.

MailboxDevisionedDate

The date when the mailbox was removed for the user.

Type: Timestamp

MailboxProvisionedDate

The date when the mailbox was created for the user.

Type: Timestamp

Name

The name for the user.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w\-\.\]+(\@[a-zA-Z0-9\-\.\]+\.[a-zA-Z0-9-]{2,})?`

Office

Office where the user is located.

Type: String

Length Constraints: Maximum length of 256.

State

The state of a user: enabled (registered to WorkMail) or disabled (deregistered or never registered to WorkMail).

Type: String

Valid Values: ENABLED | DISABLED | DELETED

Street

Street where the user is located.

Type: String

Length Constraints: Maximum length of 256.

Telephone

User's contact number.

Type: String

Length Constraints: Maximum length of 256.

UserId

The identifier for the described user.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 256.

UserRole

In certain cases, other entities are modeled as users. If interoperability is enabled, resources are imported into WorkMail as users. Because different WorkMail organizations rely on different directory types, administrators can distinguish between an unregistered user (account is disabled and has a user role) and the directory administrators. The values are USER, RESOURCE, SYSTEM_USER, and REMOTE_USER.

Type: String

Valid Values: USER | RESOURCE | SYSTEM_USER | REMOTE_USER

ZipCode

Zip code of the user.

Type: String

Length Constraints: Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

DirectoryServiceAuthenticationFailedException

The directory service doesn't recognize the credentials supplied by WorkMail.

HTTP Status Code: 400

DirectoryUnavailableException

The directory is unavailable. It might be located in another Region or deleted.

HTTP Status Code: 400

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisassociateDelegateFromResource

Service: Amazon WorkMail

Removes a member from the resource's set of delegates.

Request Syntax

```
{
  "EntityId": "string",
  "OrganizationId": "string",
  "ResourceId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

EntityId

The identifier for the member (user, group) to be removed from the resource's delegates.

The entity ID can accept *UserId or GroupID, Username or Groupname, or email*.

- Entity: 12345678-1234-1234-1234-123456789012 or S-1-1-12-1234567890-123456789-123456789-1234
- Email address: entity@domain.tld
- Entity: entity

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

OrganizationId

The identifier for the organization under which the resource exists.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

ResourceId

The identifier of the resource from which delegates' set members are removed.

The identifier can accept *ResourceId*, *ResourceName*, or *email*. The following identity formats are available:

- Resource ID: r-0123456789a0123456789b0123456789
- Email address: resource@domain.tld
- Resource name: resource

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9._%+@-]+`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

UnsupportedOperationException

You can't perform a write operation against a read-only directory.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

DisassociateMemberFromGroup

Service: Amazon WorkMail

Removes a member from a group.

Request Syntax

```
{  
  "GroupId": "string",  
  "MemberId": "string",  
  "OrganizationId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

GroupId

The identifier for the group from which members are removed.

The identifier can accept *GroupId*, *Groupname*, or *email*. The following identity formats are available:

- Group ID: 12345678-1234-1234-1234-123456789012 or S-1-1-12-1234567890-123456789-123456789-1234
- Email address: group@domain.tld
- Group name: group

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

MemberId

The identifier for the member to be removed from the group.

The member ID can accept *UserID* or *GroupId*, *Username* or *Groupname*, or *email*.

- Member ID: 12345678-1234-1234-1234-123456789012 or S-1-1-12-1234567890-123456789-123456789-1234
- Email address: member@domain.tld
- Member name: member

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

OrganizationId

The identifier for the organization under which the group exists.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

DirectoryServiceAuthenticationFailedException

The directory service doesn't recognize the credentials supplied by WorkMail.

HTTP Status Code: 400

DirectoryUnavailableException

The directory is unavailable. It might be located in another Region or deleted.

HTTP Status Code: 400

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

UnsupportedOperationException

You can't perform a write operation against a read-only directory.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetAccessControlEffect

Service: Amazon WorkMail

Gets the effects of an organization's access control rules as they apply to a specified IPv4 address, access protocol action, and user ID or impersonation role ID. You must provide either the user ID or impersonation role ID. Impersonation role ID can only be used with Action EWS.

Request Syntax

```
{
  "Action": "string",
  "ImpersonationRoleId": "string",
  "IpAddress": "string",
  "OrganizationId": "string",
  "UserId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Action

The access protocol action. Valid values include ActiveSync, AutoDiscover, EWS, IMAP, SMTP, WindowsOutlook, and WebMail.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z]+

Required: Yes

ImpersonationRoleId

The impersonation role ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_-]+

Required: No

IpAddress

The IPv4 address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 15.

Pattern: ^(([0-9]|[1-9][0-9]|1[0-9]{2}|2[0-4][0-9]|25[0-5])\.){3}([0-9]|[1-9][0-9]|1[0-9]{2}|2[0-4][0-9]|25[0-5])\$

Required: Yes

OrganizationId

The identifier for the organization.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

UserId

The user ID.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 256.

Required: No

Response Syntax

```
{  
  "Effect": "string",  
  "MatchedRules": [ "string" ]
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Effect

The rule effect.

Type: String

Valid Values: ALLOW | DENY

MatchedRules

The rules that match the given parameters, resulting in an effect.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDefaultRetentionPolicy

Service: Amazon WorkMail

Gets the default retention policy details for the specified organization.

Request Syntax

```
{
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

OrganizationId

The organization ID.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Syntax

```
{
  "Description": "string",
  "FolderConfigurations": [
    {
      "Action": "string",
      "Name": "string",
      "Period": number
    }
  ],
  "Id": "string",
  "Name": "string"
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Description

The retention policy description.

Type: String

Length Constraints: Maximum length of 256.

FolderConfigurations

The retention policy folder configurations.

Type: Array of [FolderConfiguration](#) objects

Id

The retention policy ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_-]+

Name

The retention policy name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetImpersonationRole

Service: Amazon WorkMail

Gets the impersonation role details for the given WorkMail organization.

Request Syntax

```
{
  "ImpersonationRoleId": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ImpersonationRoleId

The impersonation role ID to retrieve.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

OrganizationId

The WorkMail organization from which to retrieve the impersonation role.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

Response Syntax

```
{
  "DateCreated": number,
  "DateModified": number,
  "Description": "string",
  "ImpersonationRoleId": "string",
  "Name": "string",
  "Rules": [
    {
      "Description": "string",
      "Effect": "string",
      "ImpersonationRoleId": "string",
      "Name": "string",
      "NotTargetUsers": [ "string" ],
      "TargetUsers": [ "string" ]
    }
  ],
  "Type": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DateCreated

The date when the impersonation role was created.

Type: Timestamp

DateModified

The date when the impersonation role was last modified.

Type: Timestamp

Description

The impersonation role description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\x00-\x09\x0B\x0C\x0E-\x1F\x7F\x3C\x3E\x5C]+`

ImpersonationRoleId

The impersonation role ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9_-]+`

Name

The impersonation role name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[^\x00-\x1F\x7F\x3C\x3E\x5C]+`

Rules

The list of rules for the given impersonation role.

Type: Array of [ImpersonationRule](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Type

The impersonation role type.

Type: String

Valid Values: FULL_ACCESS | READ_ONLY

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetImpersonationRoleEffect

Service: Amazon WorkMail

Tests whether the given impersonation role can impersonate a target user.

Request Syntax

```
{
  "ImpersonationRoleId": "string",
  "OrganizationId": "string",
  "TargetUser": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ImpersonationRoleId

The impersonation role ID to test.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

OrganizationId

The WorkMail organization where the impersonation role is defined.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

TargetUser

The WorkMail organization user chosen to test the impersonation role. The following identity formats are available:

- User ID: 12345678-1234-1234-1234-123456789012 or S-1-1-12-1234567890-123456789-123456789-1234
- Email address: user@domain.tld
- User name: user

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

Response Syntax

```
{
  "Effect": "string",
  "MatchedRules": [
    {
      "ImpersonationRuleId": "string",
      "Name": "string"
    }
  ],
  "Type": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Effect

Effect of the impersonation role on the target user based on its rules. Available effects are ALLOW or DENY.

Type: String

Valid Values: ALLOW | DENY

MatchedRules

A list of the rules that match the input and produce the configured effect.

Type: Array of [ImpersonationMatchedRule](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Type

The impersonation role type.

Type: String

Valid Values: FULL_ACCESS | READ_ONLY

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetMailboxDetails

Service: Amazon WorkMail

Requests a user's mailbox details for a specified organization and user.

Request Syntax

```
{  
  "OrganizationId": "string",  
  "UserId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

OrganizationId

The identifier for the organization that contains the user whose mailbox details are being requested.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

UserId

The identifier for the user whose mailbox details are being requested.

The identifier can be the *UserId*, *Username*, or *email*. The following identity formats are available:

- User ID: 12345678-1234-1234-1234-123456789012 or S-1-1-12-1234567890-123456789-123456789-1234
- Email address: user@domain.tld

- User name: user

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

Response Syntax

```
{
  "MailboxQuota": number,
  "MailboxSize": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

MailboxQuota

The maximum allowed mailbox size, in MB, for the specified user.

Type: Integer

Valid Range: Minimum value of 1.

MailboxSize

The current mailbox size, in MB, for the specified user.

Type: Double

Valid Range: Minimum value of 0.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetMailDomain

Service: Amazon WorkMail

Gets details for a mail domain, including domain records required to configure your domain with recommended security.

Request Syntax

```
{  
  "DomainName": "string",  
  "OrganizationId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

DomainName

The domain from which you want to retrieve details.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 209.

Pattern: [a-zA-Z0-9.-]+

Required: Yes

OrganizationId

The WorkMail organization for which the domain is retrieved.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

Response Syntax

```
{
  "DkimVerificationStatus": "string",
  "IsDefault": boolean,
  "IsTestDomain": boolean,
  "OwnershipVerificationStatus": "string",
  "Records": [
    {
      "Hostname": "string",
      "Type": "string",
      "Value": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DkimVerificationStatus

Indicates the status of a DKIM verification.

Type: String

Valid Values: PENDING | VERIFIED | FAILED

IsDefault

Specifies whether the domain is the default domain for your organization.

Type: Boolean

IsTestDomain

Specifies whether the domain is a test domain provided by WorkMail, or a custom domain.

Type: Boolean

OwnershipVerificationStatus

Indicates the status of the domain ownership verification.

Type: String

Valid Values: PENDING | VERIFIED | FAILED

Records

A list of the DNS records that WorkMail recommends adding in your DNS provider for the best user experience. The records configure your domain with DMARC, SPF, DKIM, and direct incoming email traffic to SES. See admin guide for more details.

Type: Array of [DnsRecord](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

MailDomainNotFoundException

The domain specified is not found in your organization.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetMobileDeviceAccessEffect

Service: Amazon WorkMail

Simulates the effect of the mobile device access rules for the given attributes of a sample access event. Use this method to test the effects of the current set of mobile device access rules for the WorkMail organization for a particular user's attributes.

Request Syntax

```
{
  "DeviceModel": "string",
  "DeviceOperatingSystem": "string",
  "DeviceType": "string",
  "DeviceUserAgent": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

DeviceModel

Device model the simulated user will report.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

DeviceOperatingSystem

Device operating system the simulated user will report.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

DeviceType

Device type the simulated user will report.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

DeviceUserAgent

Device user agent the simulated user will report.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

OrganizationId

The WorkMail organization to simulate the access effect for.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Syntax

```
{  
  "Effect": "string",  
  "MatchedRules": [  
    ...  
  ]  
}
```

```
{
  "MobileDeviceAccessRuleId": "string",
  "Name": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Effect

The effect of the simulated access, ALLOW or DENY, after evaluating mobile device access rules in the WorkMail organization for the simulated user parameters.

Type: String

Valid Values: ALLOW | DENY

MatchedRules

A list of the rules which matched the simulated user input and produced the effect.

Type: Array of [MobileDeviceAccessMatchedRule](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetMobileDeviceAccessOverride

Service: Amazon WorkMail

Gets the mobile device access override for the given WorkMail organization, user, and device.

Request Syntax

```
{
  "DeviceId": "string",
  "OrganizationId": "string",
  "UserId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

DeviceId

The mobile device to which the override applies. DeviceId is case insensitive.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: [A-Za-z0-9]+

Required: Yes

OrganizationId

The WorkMail organization to which you want to apply the override.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

UserId

Identifies the WorkMail user for the override. Accepts the following types of user identities:

- User ID: 12345678-1234-1234-1234-123456789012 or S-1-1-12-1234567890-123456789-123456789-1234
- Email address: user@domain.tld
- User name: user

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

Response Syntax

```
{
  "DateCreated": number,
  "DateModified": number,
  "Description": "string",
  "DeviceId": "string",
  "Effect": "string",
  "UserId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DateCreated

The date the override was first created.

Type: Timestamp

DateModified

The date the description was last modified.

Type: Timestamp

Description

A description of the override.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\S\s]+`

DeviceId

The device to which the access override applies.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `[A-Za-z0-9]+`

Effect

The effect of the override, ALLOW or DENY.

Type: String

Valid Values: ALLOW | DENY

UserId

The WorkMail user to which the access override applies.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

ListAccessControlRules

Service: Amazon WorkMail

Lists the access control rules for the specified organization.

Request Syntax

```
{
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

OrganizationId

The identifier for the organization.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Syntax

```
{
  "Rules": [
    {
      "Actions": [ "string" ],
      "DateCreated": number,
      "DateModified": number,
      "Description": "string",
      "Effect": "string",
      "ImpersonationRoleIds": [ "string" ],
    }
  ]
}
```

```
    "IpRanges": [ "string" ],
    "Name": "string",
    "NotActions": [ "string" ],
    "NotImpersonationRoleIds": [ "string" ],
    "NotIpRanges": [ "string" ],
    "NotUserIds": [ "string" ],
    "UserIds": [ "string" ]
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Rules

The access control rules.

Type: Array of [AccessControlRule](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAliases

Service: Amazon WorkMail

Creates a paginated call to list the aliases associated with a given entity.

Request Syntax

```
{
  "EntityId": "string",
  "MaxResults": number,
  "NextToken": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

EntityId

The identifier for the entity for which to list the aliases.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 256.

Required: Yes

MaxResults

The maximum number of results to return in a single call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The token to use to retrieve the next page of results. The first call does not contain any tokens.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]*|[a-zA-Z0-9/+=]{1,1024}`

Required: No

OrganizationId

The identifier for the organization under which the entity exists.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Syntax

```
{
  "Aliases": [ "string" ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Aliases

The entity's paginated aliases.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 254.

Pattern: `[a-zA-Z0-9._%+-]{1,64}@[a-zA-Z0-9.-]+\.[a-zA-Z-]{2,}`

NextToken

The token to use to retrieve the next page of results. The value is "null" when there are no more results to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]* | [a-zA-Z0-9/+=]{1,1024}`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAvailabilityConfigurations

Service: Amazon WorkMail

List all the AvailabilityConfiguration's for the given WorkMail organization.

Request Syntax

```
{
  "MaxResults": number,
  "NextToken": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The maximum number of results to return in a single call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The token to use to retrieve the next page of results. The first call does not require a token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]*|[a-zA-Z0-9/+=]{1,1024}`

Required: No

OrganizationId

The WorkMail organization for which the AvailabilityConfiguration's will be listed.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Syntax

```
{
  "AvailabilityConfigurations": [
    {
      "DateCreated": number,
      "DateModified": number,
      "DomainName": "string",
      "EwsProvider": {
        "EwsEndpoint": "string",
        "EwsUsername": "string"
      },
      "LambdaProvider": {
        "LambdaArn": "string"
      },
      "ProviderType": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AvailabilityConfigurations

The list of AvailabilityConfiguration's that exist for the specified WorkMail organization.

Type: Array of [AvailabilityConfiguration](#) objects

NextToken

The token to use to retrieve the next page of results. The value is `null` when there are no further results to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]* | [a-zA-Z0-9/+=]{1,1024}`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListGroupMembers

Service: Amazon WorkMail

Returns an overview of the members of a group. Users and groups can be members of a group.

Request Syntax

```
{
  "GroupId": "string",
  "MaxResults": number,
  "NextToken": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

GroupId

The identifier for the group to which the members (users or groups) are associated.

The identifier can accept *GroupId*, *Groupname*, or *email*. The following identity formats are available:

- Group ID: 12345678-1234-1234-1234-123456789012 or S-1-1-12-1234567890-123456789-123456789-1234
- Email address: group@domain.tld
- Group name: group

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

MaxResults

The maximum number of results to return in a single call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The token to use to retrieve the next page of results. The first call does not contain any tokens.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]* | [a-zA-Z0-9/+=]{1,1024}`

Required: No

OrganizationId

The identifier for the organization under which the group exists.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Syntax

```
{
  "Members": [
    {
      "DisabledDate": number,
      "EnabledDate": number,
      "Id": "string",
      "Name": "string",
      "State": "string",
      "Type": "string"
    }
  ],
  "NextToken": "string"
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Members

The members associated to the group.

Type: Array of [Member](#) objects

NextToken

The token to use to retrieve the next page of results. The first call does not contain any tokens.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]* | [a-zA-Z0-9/+=]{1,1024}`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListGroups

Service: Amazon WorkMail

Returns summaries of the organization's groups.

Request Syntax

```
{
  "Filters": {
    "NamePrefix": "string",
    "PrimaryEmailPrefix": "string",
    "State": "string"
  },
  "MaxResults": number,
  "NextToken": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filters

Limit the search results based on the filter criteria. Only one filter per request is supported.

Type: [ListGroupsFilters](#) object

Required: No

MaxResults

The maximum number of results to return in a single call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The token to use to retrieve the next page of results. The first call does not contain any tokens.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]*|[a-zA-Z0-9/+=]{1,1024}`

Required: No

OrganizationId

The identifier for the organization under which the groups exist.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Syntax

```
{
  "Groups": [
    {
      "DisabledDate": number,
      "Email": "string",
      "EnabledDate": number,
      "Id": "string",
      "Name": "string",
      "State": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Groups

The overview of groups for an organization.

Type: Array of [Group](#) objects

NextToken

The token to use to retrieve the next page of results. The value is "null" when there are no more results to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]* | [a-zA-Z0-9/+=]{1,1024}`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListGroupsForEntity

Service: Amazon WorkMail

Returns all the groups to which an entity belongs.

Request Syntax

```
{
  "EntityId": "string",
  "Filters": {
    "GroupNamePrefix": "string"
  },
  "MaxResults": number,
  "NextToken": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

EntityId

The identifier for the entity.

The entity ID can accept *UserId* or *GroupId*, *Username* or *Groupname*, or *email*.

- Entity ID: 12345678-1234-1234-1234-123456789012 or S-1-1-12-1234567890-123456789-123456789-1234
- Email address: entity@domain.tld
- Entity name: entity

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

Filters

Limit the search results based on the filter criteria.

Type: [ListGroupsForEntityFilters](#) object

Required: No

MaxResults

The maximum number of results to return in a single call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The token to use to retrieve the next page of results. The first call does not contain any tokens.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]*|[a-zA-Z0-9/+=]{1,1024}`

Required: No

OrganizationId

The identifier for the organization under which the entity exists.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Syntax

```
{  
  "Groups": [  
    ...  
  ]  
}
```

```
{
  "GroupId": "string",
  "GroupName": "string"
},
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Groups

The overview of groups in an organization.

Type: Array of [GroupIdentifier](#) objects

NextToken

The token to use to retrieve the next page of results. This value is `null` when there are no more results to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]*|[a-zA-Z0-9/+=]{1,1024}`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListImpersonationRoles

Service: Amazon WorkMail

Lists all the impersonation roles for the given WorkMail organization.

Request Syntax

```
{
  "MaxResults": number,
  "NextToken": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The maximum number of results returned in a single call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The token used to retrieve the next page of results. The first call doesn't require a token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]*|[a-zA-Z0-9/+=]{1,1024}`

Required: No

OrganizationId

The WorkMail organization to which the listed impersonation roles belong.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Syntax

```
{
  "NextToken": "string",
  "Roles": [
    {
      "DateCreated": number,
      "DateModified": number,
      "ImpersonationRoleId": "string",
      "Name": "string",
      "Type": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to retrieve the next page of results. The value is `null` when there are no results to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]*|[a-zA-Z0-9/+]{1,1024}`

Roles

The list of impersonation roles under the given WorkMail organization.

Type: Array of [ImpersonationRole](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListMailboxExportJobs

Service: Amazon WorkMail

Lists the mailbox export jobs started for the specified organization within the last seven days.

Request Syntax

```
{
  "MaxResults": number,
  "NextToken": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The maximum number of results to return in a single call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The token to use to retrieve the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]*|[a-zA-Z0-9/+=]{1,1024}`

Required: No

OrganizationId

The organization ID.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Syntax

```
{
  "Jobs": [
    {
      "Description": "string",
      "EndTime": number,
      "EntityId": "string",
      "EstimatedProgress": number,
      "JobId": "string",
      "S3BucketName": "string",
      "S3Path": "string",
      "StartTime": number,
      "State": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Jobs

The mailbox export job details.

Type: Array of [MailboxExportJob](#) objects

NextToken

The token to use to retrieve the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]* | [a-zA-Z0-9/+=]{1,1024}`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListMailboxPermissions

Service: Amazon WorkMail

Lists the mailbox permissions associated with a user, group, or resource mailbox.

Request Syntax

```
{
  "EntityId": "string",
  "MaxResults": number,
  "NextToken": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

EntityId

The identifier of the user, or resource for which to list mailbox permissions.

The entity ID can accept *UserId* or *ResourceId*, *Username* or *ResourceName*, or *email*.

- Entity ID: 12345678-1234-1234-1234-123456789012, or r-0123456789a0123456789b0123456789
- Email address: entity@domain.tld
- Entity name: entity

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

MaxResults

The maximum number of results to return in a single call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The token to use to retrieve the next page of results. The first call does not contain any tokens.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]*|[a-zA-Z0-9/+=]{1,1024}`

Required: No

OrganizationId

The identifier of the organization under which the user, group, or resource exists.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Syntax

```
{
  "NextToken": "string",
  "Permissions": [
    {
      "GranteeId": "string",
      "GranteeType": "string",
      "PermissionValues": [ "string" ]
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to use to retrieve the next page of results. The value is "null" when there are no more results to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]* | [a-zA-Z0-9/+]{1,1024}`

Permissions

One page of the user, group, or resource mailbox permissions.

Type: Array of [Permission](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListMailDomains

Service: Amazon WorkMail

Lists the mail domains in a given WorkMail organization.

Request Syntax

```
{
  "MaxResults": number,
  "NextToken": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The maximum number of results to return in a single call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The token to use to retrieve the next page of results. The first call does not require a token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]*|[a-zA-Z0-9/+=]{1,1024}`

Required: No

OrganizationId

The WorkMail organization for which to list domains.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Syntax

```
{
  "MailDomains": [
    {
      "DefaultDomain": boolean,
      "DomainName": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

MailDomains

The list of mail domain summaries, specifying domains that exist in the specified WorkMail organization, along with the information about whether the domain is or isn't the default.

Type: Array of [MailDomainSummary](#) objects

NextToken

The token to use to retrieve the next page of results. The value becomes `null` when there are no more results to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]*|[a-zA-Z0-9/+=]{1,1024}`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListMobileDeviceAccessOverrides

Service: Amazon WorkMail

Lists all the mobile device access overrides for any given combination of WorkMail organization, user, or device.

Request Syntax

```
{
  "DeviceId": "string",
  "MaxResults": number,
  "NextToken": "string",
  "OrganizationId": "string",
  "UserId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

DeviceId

The mobile device to which the access override applies.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: [A-Za-z0-9]+

Required: No

MaxResults

The maximum number of results to return in a single call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The token to use to retrieve the next page of results. The first call does not require a token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]*|[a-zA-Z0-9/+=]{1,1024}`

Required: No

OrganizationId

The WorkMail organization under which to list mobile device access overrides.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

UserId

The WorkMail user under which you list the mobile device access overrides. Accepts the following types of user identities:

- User ID: 12345678-1234-1234-1234-123456789012 or S-1-1-12-1234567890-123456789-123456789-1234
- Email address: `user@domain.tld`
- User name: `user`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9._%+@-]+`

Required: No

Response Syntax

```
{
  "NextToken": "string",
  "Overrides": [
    {
      "DateCreated": number,
      "DateModified": number,
      "Description": "string",
      "DeviceId": "string",
      "Effect": "string",
      "UserId": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to use to retrieve the next page of results. The value is “null” when there are no more results to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]*|[a-zA-Z0-9/+=]{1,1024}`

Overrides

The list of mobile device access overrides that exist for the specified WorkMail organization and user.

Type: Array of [MobileDeviceAccessOverride](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListMobileDeviceAccessRules

Service: Amazon WorkMail

Lists the mobile device access rules for the specified WorkMail organization.

Request Syntax

```
{
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

OrganizationId

The WorkMail organization for which to list the rules.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Syntax

```
{
  "Rules": [
    {
      "DateCreated": number,
      "DateModified": number,
      "Description": "string",
      "DeviceModels": [ "string" ],
      "DeviceOperatingSystems": [ "string" ],
      "DeviceTypes": [ "string" ],
    }
  ]
}
```

```
"DeviceUserAgents": [ "string" ],
"Effect": "string",
"MobileDeviceAccessRuleId": "string",
"Name": "string",
"NotDeviceModels": [ "string" ],
"NotDeviceOperatingSystems": [ "string" ],
"NotDeviceTypes": [ "string" ],
"NotDeviceUserAgents": [ "string" ]
}
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Rules

The list of mobile device access rules that exist under the specified WorkMail organization.

Type: Array of [MobileDeviceAccessRule](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListOrganizations

Service: Amazon WorkMail

Returns summaries of the customer's organizations.

Request Syntax

```
{
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The maximum number of results to return in a single call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The token to use to retrieve the next page of results. The first call does not contain any tokens.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]*|[a-zA-Z0-9/+=]{1,1024}`

Required: No

Response Syntax

```
{
```

```
"NextToken": "string",
"OrganizationSummaries": [
  {
    "Alias": "string",
    "DefaultMailDomain": "string",
    "ErrorMessage": "string",
    "OrganizationId": "string",
    "State": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to use to retrieve the next page of results. The value is "null" when there are no more results to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]*|[a-zA-Z0-9/+=]{1,1024}`

OrganizationSummaries

The overview of owned organizations presented as a list of organization summaries.

Type: Array of [OrganizationSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListResourceDelegates

Service: Amazon WorkMail

Lists the delegates associated with a resource. Users and groups can be resource delegates and answer requests on behalf of the resource.

Request Syntax

```
{
  "MaxResults": number,
  "NextToken": "string",
  "OrganizationId": "string",
  "ResourceId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The number of maximum results in a page.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The token used to paginate through the delegates associated with a resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]* | [a-zA-Z0-9/+=]{1,1024}`

Required: No

OrganizationId

The identifier for the organization that contains the resource for which delegates are listed.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

ResourceId

The identifier for the resource whose delegates are listed.

The identifier can accept *ResourceId*, *ResourceName*, or *email*. The following identity formats are available:

- Resource ID: r-0123456789a0123456789b0123456789
- Email address: resource@domain.tld
- Resource name: resource

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9._%+@-]+`

Required: Yes

Response Syntax

```
{
  "Delegates": [
    {
      "Id": "string",
      "Type": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Delegates

One page of the resource's delegates.

Type: Array of [Delegate](#) objects

NextToken

The token used to paginate through the delegates associated with a resource. While results are still available, it has an associated value. When the last page is reached, the token is empty.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]* | [a-zA-Z0-9/+=]{1,1024}`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

UnsupportedOperationException

You can't perform a write operation against a read-only directory.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListResources

Service: Amazon WorkMail

Returns summaries of the organization's resources.

Request Syntax

```
{
  "Filters": {
    "NamePrefix": "string",
    "PrimaryEmailPrefix": "string",
    "State": "string"
  },
  "MaxResults": number,
  "NextToken": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filters

Limit the resource search results based on the filter criteria. You can only use one filter per request.

Type: [ListResourcesFilters](#) object

Required: No

MaxResults

The maximum number of results to return in a single call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The token to use to retrieve the next page of results. The first call does not contain any tokens.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]*|[a-zA-Z0-9/+=]{1,1024}`

Required: No

OrganizationId

The identifier for the organization under which the resources exist.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Syntax

```
{
  "NextToken": "string",
  "Resources": [
    {
      "Description": "string",
      "DisabledDate": number,
      "Email": "string",
      "EnabledDate": number,
      "Id": "string",
      "Name": "string",
      "State": "string",
      "Type": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token used to paginate through all the organization's resources. While results are still available, it has an associated value. When the last page is reached, the token is empty.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]*|[a-zA-Z0-9/+=]{1,1024}`

Resources

One page of the organization's resource representation.

Type: Array of [Resource](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

UnsupportedOperationException

You can't perform a write operation against a read-only directory.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Service: Amazon WorkMail

Lists the tags applied to an WorkMail organization resource.

Request Syntax

```
{
  "ResourceARN": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ResourceARN

The resource ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws:workmail:[a-z0-9-]*:[a-z0-9-]+:[A-Za-z0-9][A-Za-z0-9:/_+=,@.-]{0,1023}`

Required: Yes

Response Syntax

```
{
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Tags

A list of tag key-value pairs.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListUsers

Service: Amazon WorkMail

Returns summaries of the organization's users.

Request Syntax

```
{
  "Filters": {
    "DisplayNamePrefix": "string",
    "PrimaryEmailPrefix": "string",
    "State": "string",
    "UsernamePrefix": "string"
  },
  "MaxResults": number,
  "NextToken": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filters

Limit the user search results based on the filter criteria. You can only use one filter per request.

Type: [ListUsersFilters](#) object

Required: No

MaxResults

The maximum number of results to return in a single call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The token to use to retrieve the next page of results. The first call does not contain any tokens.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]*|[a-zA-Z0-9/+=]{1,1024}`

Required: No

OrganizationId

The identifier for the organization under which the users exist.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Syntax

```
{
  "NextToken": "string",
  "Users": [
    {
      "DisabledDate": number,
      "DisplayName": "string",
      "Email": "string",
      "EnabledDate": number,
      "Id": "string",
      "Name": "string",
      "State": "string",
      "UserRole": "string"
    }
  ]
}
```


Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to use to retrieve the next page of results. This value is `null` when there are no more results to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[\S\s]*|[a-zA-Z0-9/+=]{1,1024}`

Users

The overview of users for an organization.

Type: Array of [User](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutAccessControlRule

Service: Amazon WorkMail

Adds a new access control rule for the specified organization. The rule allows or denies access to the organization for the specified IPv4 addresses, access protocol actions, user IDs and impersonation IDs. Adding a new rule with the same name as an existing rule replaces the older rule.

Request Syntax

```
{
  "Actions": [ "string" ],
  "Description": "string",
  "Effect": "string",
  "ImpersonationRoleIds": [ "string" ],
  "IpRanges": [ "string" ],
  "Name": "string",
  "NotActions": [ "string" ],
  "NotImpersonationRoleIds": [ "string" ],
  "NotIpRanges": [ "string" ],
  "NotUserIds": [ "string" ],
  "OrganizationId": "string",
  "UserIds": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Actions

Access protocol actions to include in the rule. Valid values include ActiveSync, AutoDiscover, EWS, IMAP, SMTP, WindowsOutlook, and WebMail.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z]+

Required: No

Description

The rule description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: [\u0020-\u00FF]+

Required: Yes

Effect

The rule effect.

Type: String

Valid Values: ALLOW | DENY

Required: Yes

ImpersonationRoleIds

Impersonation role IDs to include in the rule.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_-]+

Required: No

IpRanges

IPv4 CIDR ranges to include in the rule.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 1024 items.

Length Constraints: Minimum length of 1. Maximum length of 18.

Pattern: `^(([0-9]|[1-9][0-9]|1[0-9]{2}|2[0-4][0-9]|25[0-5])\.)?{3}([0-9]|[1-9][0-9]|1[0-9]{2}|2[0-4][0-9]|25[0-5])/([0-9]|12[0-9]|3[0-2])$`

Required: No

Name

The rule name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9_-]+`

Required: Yes

NotActions

Access protocol actions to exclude from the rule. Valid values include `ActiveSync`, `AutoDiscover`, `EWS`, `IMAP`, `SMTP`, `WindowsOutlook`, and `WebMail`.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z]+`

Required: No

NotImpersonationRoleIds

Impersonation role IDs to exclude from the rule.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9_-]+`

Required: No

NotIpRanges

IPv4 CIDR ranges to exclude from the rule.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 1024 items.

Length Constraints: Minimum length of 1. Maximum length of 18.

Pattern: `^(([0-9]|[1-9][0-9]|1[0-9]{2}|2[0-4][0-9]|25[0-5])\.){3}([0-9]|[1-9][0-9]|1[0-9]{2}|2[0-4][0-9]|25[0-5])/([0-9]|[12][0-9]|3[0-2])$`

Required: No

NotUserIds

User IDs to exclude from the rule.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 12. Maximum length of 256.

Required: No

OrganizationId

The identifier of the organization.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

UserIds

User IDs to include in the rule.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 12. Maximum length of 256.

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

LimitExceededException

The request exceeds the limit of the resource.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutEmailMonitoringConfiguration

Service: Amazon WorkMail

Creates or updates the email monitoring configuration for a specified organization.

Request Syntax

```
{
  "LogGroupArn": "string",
  "OrganizationId": "string",
  "RoleArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

LogGroupArn

The Amazon Resource Name (ARN) of the CloudWatch Log group associated with the email monitoring configuration.

Type: String

Length Constraints: Minimum length of 47. Maximum length of 562.

Pattern: `arn:aws:logs:[a-z\-\0-9]*:[0-9]{12}:log-group:([\.\-_/#A-Za-z0-9]+):*$`

Required: Yes

OrganizationId

The ID of the organization for which the email monitoring configuration is set.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

RoleArn

The Amazon Resource Name (ARN) of the IAM Role associated with the email monitoring configuration.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws:iam:[a-z0-9-]*:[a-z0-9-]+:[A-Za-z0-9][A-Za-z0-9:_/+=@.-]{0,1023}`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutInboundDmarcSettings

Service: Amazon WorkMail

Enables or disables a DMARC policy for a given organization.

Request Syntax

```
{  
  "Enforced": boolean,  
  "OrganizationId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Enforced

Enforces or suspends a policy after it's applied.

Type: Boolean

Required: Yes

OrganizationId

The ID of the organization that you are applying the DMARC policy to.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutMailboxPermissions

Service: Amazon WorkMail

Sets permissions for a user, group, or resource. This replaces any pre-existing permissions.

Request Syntax

```
{
  "EntityId": "string",
  "GranteeId": "string",
  "OrganizationId": "string",
  "PermissionValues": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

EntityId

The identifier of the user or resource for which to update mailbox permissions.

The identifier can be *UserId*, *ResourceID*, or *Group Id*, *Username*, *Resourcename*, or *Groupname*, or *email*.

- Entity ID: 12345678-1234-1234-1234-123456789012, r-0123456789a0123456789b0123456789, or S-1-1-12-1234567890-123456789-123456789-1234
- Email address: entity@domain.tld
- Entity name: entity

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

GranteeId

The identifier of the user, group, or resource to which to grant the permissions.

The identifier can be *UserId*, *ResourceID*, or *Group Id*, *Username*, *Resourcename*, or *Groupname*, or *email*.

- Grantee ID: 12345678-1234-1234-1234-123456789012, r-0123456789a0123456789b0123456789, or S-1-1-12-1234567890-123456789-123456789-1234
- Email address: grantee@domain.tld
- Grantee name: grantee

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

OrganizationId

The identifier of the organization under which the user, group, or resource exists.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

PermissionValues

The permissions granted to the grantee. `SEND_AS` allows the grantee to send email as the owner of the mailbox (the grantee is not mentioned on these emails). `SEND_ON_BEHALF` allows the grantee to send email on behalf of the owner of the mailbox (the grantee is not mentioned as the physical sender of these emails). `FULL_ACCESS` allows the grantee full access to the mailbox, irrespective of other folder-level permissions set on the mailbox.

Type: Array of strings

Valid Values: FULL_ACCESS | SEND_AS | SEND_ON_BEHALF

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutMobileDeviceAccessOverride

Service: Amazon WorkMail

Creates or updates a mobile device access override for the given WorkMail organization, user, and device.

Request Syntax

```
{
  "Description": "string",
  "DeviceId": "string",
  "Effect": "string",
  "OrganizationId": "string",
  "UserId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Description

A description of the override.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\S\s]+`

Required: No

DeviceId

The mobile device for which you create the override. DeviceId is case insensitive.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `[A-Za-z0-9]+`

Required: Yes

Effect

The effect of the override, ALLOW or DENY.

Type: String

Valid Values: ALLOW | DENY

Required: Yes

OrganizationId

Identifies the WorkMail organization for which you create the override.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

UserId

The WorkMail user for which you create the override. Accepts the following types of user identities:

- User ID: 12345678-1234-1234-1234-123456789012 or S-1-1-12-1234567890-123456789-123456789-1234
- Email address: `user@domain.tld`
- User name: `user`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9._%+@-]+`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutRetentionPolicy

Service: Amazon WorkMail

Puts a retention policy to the specified organization.

Request Syntax

```
{
  "Description": "string",
  "FolderConfigurations": [
    {
      "Action": "string",
      "Name": "string",
      "Period": number
    }
  ],
  "Id": "string",
  "Name": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Description

The retention policy description.

Type: String

Length Constraints: Maximum length of 256.

Pattern: `[\w\d\s\S\-\!?=,.;:'_]+`

Required: No

FolderConfigurations

The retention policy folder configurations.

Type: Array of [FolderConfiguration](#) objects

Required: Yes

Id

The retention policy ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_-]+

Required: No

Name

The retention policy name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

OrganizationId

The organization ID.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

LimitExceededException

The request exceeds the limit of the resource.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RegisterMailDomain

Service: Amazon WorkMail

Registers a new domain in WorkMail and SES, and configures it for use by WorkMail. Emails received by SES for this domain are routed to the specified WorkMail organization, and WorkMail has permanent permission to use the specified domain for sending your users' emails.

Request Syntax

```
{
  "ClientToken": "string",
  "DomainName": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClientToken

Idempotency token used when retrying requests.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\x21-\x7e]+`

Required: No

DomainName

The name of the mail domain to create in WorkMail and SES.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 209.

Pattern: `[a-zA-Z0-9.-]+`

Required: Yes

OrganizationId

The WorkMail organization under which you're creating the domain.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

LimitExceededException

The request exceeds the limit of the resource.

HTTP Status Code: 400

MailDomainInUseException

The domain you're trying to change is in use by another user or organization in your account.

See the error message for details.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RegisterToWorkMail

Service: Amazon WorkMail

Registers an existing and disabled user, group, or resource for WorkMail use by associating a mailbox and calendaring capabilities. It performs no change if the user, group, or resource is enabled and fails if the user, group, or resource is deleted. This operation results in the accumulation of costs. For more information, see [Pricing](#). The equivalent console functionality for this operation is *Enable*.

Users can either be created by calling the [CreateUser](#) API operation or they can be synchronized from your directory. For more information, see [DeregisterFromWorkMail](#).

Request Syntax

```
{
  "Email": "string",
  "EntityId": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Email

The email for the user, group, or resource to be updated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 254.

Pattern: [a-zA-Z0-9._%+-]{1,64}@[a-zA-Z0-9.-]+\.[a-zA-Z-]{2,}

Required: Yes

EntityId

The identifier for the user, group, or resource to be updated.

The identifier can accept *UserId*, *ResourceId*, or *GroupId*, or *Username*, *Resourcename*, or *Groupname*. The following identity formats are available:

- Entity ID: 12345678-1234-1234-1234-123456789012, r-0123456789a0123456789b0123456789, or S-1-1-12-1234567890-123456789-123456789-1234
- Entity name: entity

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

OrganizationId

The identifier for the organization under which the user, group, or resource exists.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

DirectoryServiceAuthenticationFailedException

The directory service doesn't recognize the credentials supplied by WorkMail.

HTTP Status Code: 400

DirectoryUnavailableException

The directory is unavailable. It might be located in another Region or deleted.

HTTP Status Code: 400

EmailAddressInUseException

The email address that you're trying to assign is already created for a different user, group, or resource.

HTTP Status Code: 400

EntityAlreadyRegisteredException

The user, group, or resource that you're trying to register is already registered.

HTTP Status Code: 400

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

MailDomainNotFoundException

The domain specified is not found in your organization.

HTTP Status Code: 400

MailDomainStateException

After a domain has been added to the organization, it must be verified. The domain is not yet verified.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ResetPassword

Service: Amazon WorkMail

Allows the administrator to reset the password for a user.

Request Syntax

```
{
  "OrganizationId": "string",
  "Password": "string",
  "UserId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

OrganizationId

The identifier of the organization that contains the user for which the password is reset.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Password

The new password for the user.

Type: String

Length Constraints: Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: Yes

UserId

The identifier of the user for whom the password is reset.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 256.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

DirectoryServiceAuthenticationFailedException

The directory service doesn't recognize the credentials supplied by WorkMail.

HTTP Status Code: 400

DirectoryUnavailableException

The directory is unavailable. It might be located in another Region or deleted.

HTTP Status Code: 400

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

InvalidPasswordException

The supplied password doesn't match the minimum security constraints, such as length or use of special characters.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

UnsupportedOperationException

You can't perform a write operation against a read-only directory.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartMailboxExportJob

Service: Amazon WorkMail

Starts a mailbox export job to export MIME-format email messages and calendar items from the specified mailbox to the specified Amazon Simple Storage Service (Amazon S3) bucket. For more information, see [Exporting mailbox content](#) in the *WorkMail Administrator Guide*.

Request Syntax

```
{
  "ClientToken": "string",
  "Description": "string",
  "EntityId": "string",
  "KmsKeyArn": "string",
  "OrganizationId": "string",
  "RoleArn": "string",
  "S3BucketName": "string",
  "S3Prefix": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClientToken

The idempotency token for the client request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\x21-\x7e]+`

Required: Yes

Description

The mailbox export job description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1023.

Pattern: `[\S\s]*`

Required: No

EntityId

The identifier of the user or resource associated with the mailbox.

The identifier can accept *UserId or ResourceId, Username or ResourceName, or email*. The following identity formats are available:

- Entity ID: 12345678-1234-1234-1234-123456789012, r-0123456789a0123456789b0123456789 , or S-1-1-12-1234567890-123456789-123456789-1234
- Email address: entity@domain.tld
- Entity name: entity

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9._%+@-]+`

Required: Yes

KmsKeyArn

The Amazon Resource Name (ARN) of the symmetric AWS Key Management Service (AWS KMS) key that encrypts the exported mailbox content.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws:kms:[a-z0-9-]*:[a-z0-9-]+:[A-Za-z0-9][A-Za-z0-9:_/+=@.-]{0,1023}`

Required: Yes

OrganizationId

The identifier associated with the organization.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

RoleArn

The ARN of the AWS Identity and Access Management (IAM) role that grants write permission to the S3 bucket.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws:iam:[a-z0-9-]*:[a-z0-9-]+:[A-Za-z0-9][A-Za-z0-9:_/+ =, @. -]{0,1023}`

Required: Yes

S3BucketName

The name of the S3 bucket.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[A-Za-z0-9.-]+`

Required: Yes

S3Prefix

The S3 bucket prefix.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1023.

Pattern: `[A-Za-z0-9!_.*'()/-]+`

Required: Yes

Response Syntax

```
{  
  "JobId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

JobId

The job ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: [A-Za-z0-9-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

LimitExceededException

The request exceeds the limit of the resource.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Service: Amazon WorkMail

Applies the specified tags to the specified WorkMailorganization resource.

Request Syntax

```
{
  "ResourceARN": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ResourceARN

The resource ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws:workmail:[a-z0-9-]*:[a-z0-9-]+:[A-Za-z0-9][A-Za-z0-9:/_+=,@.-]{0,1023}`

Required: Yes

Tags

The tag key-value pairs.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

TooManyTagsException

The resource can have up to 50 user-applied tags.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TestAvailabilityConfiguration

Service: Amazon WorkMail

Performs a test on an availability provider to ensure that access is allowed. For EWS, it verifies the provided credentials can be used to successfully log in. For Lambda, it verifies that the Lambda function can be invoked and that the resource access policy was configured to deny anonymous access. An anonymous invocation is one done without providing either a `SourceArn` or `SourceAccount` header.

Note

The request must contain either one provider definition (`EwsProvider` or `LambdaProvider`) or the `DomainName` parameter. If the `DomainName` parameter is provided, the configuration stored under the `DomainName` will be tested.

Request Syntax

```
{
  "DomainName": "string",
  "EwsProvider": {
    "EwsEndpoint": "string",
    "EwsPassword": "string",
    "EwsUsername": "string"
  },
  "LambdaProvider": {
    "LambdaArn": "string"
  },
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

DomainName

The domain to which the provider applies. If this field is provided, a stored availability provider associated to this domain name will be tested.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Pattern: [a-zA-Z0-9.-]+

Required: No

EwsProvider

Describes an EWS based availability provider. This is only used as input to the service.

Type: [EwsAvailabilityProvider](#) object

Required: No

LambdaProvider

Describes a Lambda based availability provider.

Type: [LambdaAvailabilityProvider](#) object

Required: No

OrganizationId

The WorkMail organization where the availability provider will be tested.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

Response Syntax

```
{
  "FailureReason": "string",
  "TestPassed": boolean
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

FailureReason

String containing the reason for a failed test if `TestPassed` is false.

Type: String

Length Constraints: Maximum length of 256.

TestPassed

Boolean indicating whether the test passed or failed.

Type: Boolean

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Service: Amazon WorkMail

Untags the specified tags from the specified WorkMail organization resource.

Request Syntax

```
{
  "ResourceARN": "string",
  "TagKeys": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ResourceARN

The resource ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws:workmail:[a-z0-9-]*:[a-z0-9-]+:[A-Za-z0-9][A-Za-z0-9: _/+ =, @. -]{0,1023}`

Required: Yes

TagKeys

The tag keys.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateAvailabilityConfiguration

Service: Amazon WorkMail

Updates an existing AvailabilityConfiguration for the given WorkMail organization and domain.

Request Syntax

```
{
  "DomainName": "string",
  "EwsProvider": {
    "EwsEndpoint": "string",
    "EwsPassword": "string",
    "EwsUsername": "string"
  },
  "LambdaProvider": {
    "LambdaArn": "string"
  },
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

DomainName

The domain to which the provider applies the availability configuration.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Pattern: [a-zA-Z0-9.-]+

Required: Yes

EwsProvider

The EWS availability provider definition. The request must contain exactly one provider definition, either EwsProvider or LambdaProvider. The previously stored provider will be overridden by the one provided.

Type: [EwsAvailabilityProvider](#) object

Required: No

[LambdaProvider](#)

The Lambda availability provider definition. The request must contain exactly one provider definition, either `EwsProvider` or `LambdaProvider`. The previously stored provider will be overridden by the one provided.

Type: [LambdaAvailabilityProvider](#) object

Required: No

[OrganizationId](#)

The WorkMail organization for which the `AvailabilityConfiguration` will be updated.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateDefaultMailDomain

Service: Amazon WorkMail

Updates the default mail domain for an organization. The default mail domain is used by the WorkMail AWS Console to suggest an email address when enabling a mail user. You can only have one default domain.

Request Syntax

```
{  
  "DomainName": "string",  
  "OrganizationId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

DomainName

The domain name that will become the default domain.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 209.

Pattern: [a-zA-Z0-9.-]+

Required: Yes

OrganizationId

The WorkMail organization for which to list domains.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

MailDomainNotFoundException

The domain specified is not found in your organization.

HTTP Status Code: 400

MailDomainStateException

After a domain has been added to the organization, it must be verified. The domain is not yet verified.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateGroup

Service: Amazon WorkMail

Updates attributes in a group.

Request Syntax

```
{
  "GroupId": "string",
  "HiddenFromGlobalAddressList": boolean,
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

GroupId

The identifier for the group to be updated.

The identifier can accept *GroupId*, *Groupname*, or *email*. The following identity formats are available:

- Group ID: 12345678-1234-1234-1234-123456789012 or S-1-1-12-1234567890-123456789-123456789-1234
- Email address: group@domain.tld
- Group name: group

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

HiddenFromGlobalAddressList

If enabled, the group is hidden from the global address list.

Type: Boolean

Required: No

OrganizationId

The identifier for the organization under which the group exists.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

UnsupportedOperationException

You can't perform a write operation against a read-only directory.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateImpersonationRole

Service: Amazon WorkMail

Updates an impersonation role for the given WorkMail organization.

Request Syntax

```
{
  "Description": "string",
  "ImpersonationRoleId": "string",
  "Name": "string",
  "OrganizationId": "string",
  "Rules": [
    {
      "Description": "string",
      "Effect": "string",
      "ImpersonationRuleId": "string",
      "Name": "string",
      "NotTargetUsers": [ "string" ],
      "TargetUsers": [ "string" ]
    }
  ],
  "Type": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Description

The updated impersonation role description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\x00-\x09\x0B\x0C\x0E-\x1F\x7F\x3C\x3E\x5C]+`

Required: No

ImpersonationRoleId

The ID of the impersonation role to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Name

The updated impersonation role name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [^\x00-\x1F\x7F\x3C\x3E\x5C]+

Required: Yes

OrganizationId

The WorkMail organization that contains the impersonation role to update.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

Rules

The updated list of rules.

Type: Array of [ImpersonationRule](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: Yes

Type

The updated impersonation role type.

Type: String

Valid Values: FULL_ACCESS | READ_ONLY

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

LimitExceededException

The request exceeds the limit of the resource.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateMailboxQuota

Service: Amazon WorkMail

Updates a user's current mailbox quota for a specified organization and user.

Request Syntax

```
{
  "MailboxQuota": number,
  "OrganizationId": "string",
  "UserId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MailboxQuota

The updated mailbox quota, in MB, for the specified user.

Type: Integer

Valid Range: Minimum value of 1.

Required: Yes

OrganizationId

The identifier for the organization that contains the user for whom to update the mailbox quota.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

UserId

The identifier for the user for whom to update the mailbox quota.

The identifier can be the *UserId*, *Username*, or *email*. The following identity formats are available:

- User ID: 12345678-1234-1234-1234-123456789012 or S-1-1-12-1234567890-123456789-123456789-1234
- Email address: user@domain.tld
- User name: user

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateMobileDeviceAccessRule

Service: Amazon WorkMail

Updates a mobile device access rule for the specified WorkMail organization.

Request Syntax

```
{
  "Description": "string",
  "DeviceModels": [ "string" ],
  "DeviceOperatingSystems": [ "string" ],
  "DeviceTypes": [ "string" ],
  "DeviceUserAgents": [ "string" ],
  "Effect": "string",
  "MobileDeviceAccessRuleId": "string",
  "Name": "string",
  "NotDeviceModels": [ "string" ],
  "NotDeviceOperatingSystems": [ "string" ],
  "NotDeviceTypes": [ "string" ],
  "NotDeviceUserAgents": [ "string" ],
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Description

The updated rule description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\S\s]+`

Required: No

DeviceModels

Device models that the updated rule will match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

DeviceOperatingSystems

Device operating systems that the updated rule will match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

DeviceTypes

Device types that the updated rule will match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

DeviceUserAgents

User agents that the updated rule will match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

Effect

The effect of the rule when it matches. Allowed values are ALLOW or DENY.

Type: String

Valid Values: ALLOW | DENY

Required: Yes

MobileDeviceAccessRuleId

The identifier of the rule to be updated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9_-]+`

Required: Yes

Name

The updated rule name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\S\s]+`

Required: Yes

NotDeviceModels

Device models that the updated rule **will not** match. All other device models will match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

NotDeviceOperatingSystems

Device operating systems that the updated rule **will not** match. All other device operating systems will match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

NotDeviceTypes

Device types that the updated rule **will not** match. All other device types will match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

NotDeviceUserAgents

User agents that the updated rule **will not** match. All other user agents will match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

OrganizationId

The WorkMail organization under which the rule will be updated.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdatePrimaryEmailAddress

Service: Amazon WorkMail

Updates the primary email for a user, group, or resource. The current email is moved into the list of aliases (or swapped between an existing alias and the current primary email), and the email provided in the input is promoted as the primary.

Request Syntax

```
{
  "Email": "string",
  "EntityId": "string",
  "OrganizationId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Email

The value of the email to be updated as primary.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 254.

Pattern: [a-zA-Z0-9._%+-]{1,64}@[a-zA-Z0-9.-]+\.[a-zA-Z-]{2,}

Required: Yes

EntityId

The user, group, or resource to update.

The identifier can accept *UserId*, *ResourceId*, or *GroupId*, *Username*, *ResourceName*, or *GroupName*, or *email*. The following identity formats are available:

- Entity ID: 12345678-1234-1234-1234-123456789012, r-0123456789a0123456789b0123456789, or S-1-1-12-1234567890-123456789-123456789-1234

- Email address: entity@domain.tld
- Entity name: entity

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

OrganizationId

The organization that contains the user, group, or resource to update.

Type: String

Length Constraints: Fixed length of 34.

Pattern: ^m-[0-9a-f]{32}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

DirectoryServiceAuthenticationFailedException

The directory service doesn't recognize the credentials supplied by WorkMail.

HTTP Status Code: 400

DirectoryUnavailableException

The directory is unavailable. It might be located in another Region or deleted.

HTTP Status Code: 400

EmailAddressInUseException

The email address that you're trying to assign is already created for a different user, group, or resource.

HTTP Status Code: 400

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

MailDomainNotFoundException

The domain specified is not found in your organization.

HTTP Status Code: 400

MailDomainStateException

After a domain has been added to the organization, it must be verified. The domain is not yet verified.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

UnsupportedOperationException

You can't perform a write operation against a read-only directory.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateResource

Service: Amazon WorkMail

Updates data for the resource. To have the latest information, it must be preceded by a [DescribeResource](#) call. The dataset in the request should be the one expected when performing another [DescribeResource](#) call.

Request Syntax

```
{
  "BookingOptions": {
    "AutoAcceptRequests": boolean,
    "AutoDeclineConflictingRequests": boolean,
    "AutoDeclineRecurringRequests": boolean
  },
  "Description": "string",
  "HiddenFromGlobalAddressList": boolean,
  "Name": "string",
  "OrganizationId": "string",
  "ResourceId": "string",
  "Type": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[BookingOptions](#)

The resource's booking options to be updated.

Type: [BookingOptions](#) object

Required: No

[Description](#)

Updates the resource description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 64.

Required: No

HiddenFromGlobalAddressList

If enabled, the resource is hidden from the global address list.

Type: Boolean

Required: No

Name

The name of the resource to be updated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `[\w\-\ .]+(@[a-zA-Z0-9\-\ .]+\.[a-zA-Z0-9-]{2,})?`

Required: No

OrganizationId

The identifier associated with the organization for which the resource is updated.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

ResourceId

The identifier of the resource to be updated.

The identifier can accept *ResourceId*, *ResourceName*, or *email*. The following identity formats are available:

- Resource ID: r-0123456789a0123456789b0123456789
- Email address: resource@domain.tld

- Resource name: resource

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

Type

Updates the resource type.

Type: String

Valid Values: ROOM | EQUIPMENT

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

DirectoryUnavailableException

The directory is unavailable. It might be located in another Region or deleted.

HTTP Status Code: 400

EmailAddressInUseException

The email address that you're trying to assign is already created for a different user, group, or resource.

HTTP Status Code: 400

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidConfigurationException

The configuration for a resource isn't valid. A resource must either be able to auto-respond to requests or have at least one delegate associated that can do so on its behalf.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

MailDomainNotFoundException

The domain specified is not found in your organization.

HTTP Status Code: 400

MailDomainStateException

After a domain has been added to the organization, it must be verified. The domain is not yet verified.

HTTP Status Code: 400

NameAvailabilityException

The user, group, or resource name isn't unique in WorkMail.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

UnsupportedOperationException

You can't perform a write operation against a read-only directory.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateUser

Service: Amazon WorkMail

Updates data for the user. To have the latest information, it must be preceded by a [DescribeUser](#) call. The dataset in the request should be the one expected when performing another DescribeUser call.

Request Syntax

```
{
  "City": "string",
  "Company": "string",
  "Country": "string",
  "Department": "string",
  "DisplayName": "string",
  "FirstName": "string",
  "HiddenFromGlobalAddressList": boolean,
  "Initials": "string",
  "JobTitle": "string",
  "LastName": "string",
  "Office": "string",
  "OrganizationId": "string",
  "Role": "string",
  "Street": "string",
  "Telephone": "string",
  "UserId": "string",
  "ZipCode": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

City

Updates the user's city.

Type: String

Length Constraints: Maximum length of 256.

Required: No

Company

Updates the user's company.

Type: String

Length Constraints: Maximum length of 256.

Required: No

Country

Updates the user's country.

Type: String

Length Constraints: Maximum length of 256.

Required: No

Department

Updates the user's department.

Type: String

Length Constraints: Maximum length of 256.

Required: No

DisplayName

Updates the display name of the user.

Type: String

Length Constraints: Maximum length of 256.

Required: No

FirstName

Updates the user's first name.

Type: String

Length Constraints: Maximum length of 256.

Required: No

HiddenFromGlobalAddressList

If enabled, the user is hidden from the global address list.

Type: Boolean

Required: No

Initials

Updates the user's initials.

Type: String

Length Constraints: Maximum length of 256.

Required: No

JobTitle

Updates the user's job title.

Type: String

Length Constraints: Maximum length of 256.

Required: No

LastName

Updates the user's last name.

Type: String

Length Constraints: Maximum length of 256.

Required: No

Office

Updates the user's office.

Type: String

Length Constraints: Maximum length of 256.

Required: No

OrganizationId

The identifier for the organization under which the user exists.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: Yes

Role

Updates the user role.

You cannot pass *SYSTEM_USER* or *RESOURCE*.

Type: String

Valid Values: `USER | RESOURCE | SYSTEM_USER | REMOTE_USER`

Required: No

Street

Updates the user's street address.

Type: String

Length Constraints: Maximum length of 256.

Required: No

Telephone

Updates the user's contact details.

Type: String

Length Constraints: Maximum length of 256.

Required: No

UserId

The identifier for the user to be updated.

The identifier can be the *UserId*, *Username*, or *email*. The following identity formats are available:

- User ID: 12345678-1234-1234-1234-123456789012 or S-1-1-12-1234567890-123456789-123456789-1234
- Email address: user@domain.tld
- User name: user

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: Yes

ZipCode

Updates the user's zipcode.

Type: String

Length Constraints: Maximum length of 256.

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

DirectoryServiceAuthenticationFailedException

The directory service doesn't recognize the credentials supplied by WorkMail.

HTTP Status Code: 400

DirectoryUnavailableException

The directory is unavailable. It might be located in another Region or deleted.

HTTP Status Code: 400

EntityNotFoundException

The identifier supplied for the user, group, or resource does not exist in your organization.

HTTP Status Code: 400

EntityStateException

You are performing an operation on a user, group, or resource that isn't in the expected state, such as trying to delete an active user.

HTTP Status Code: 400

InvalidParameterException

One or more of the input parameters don't match the service's restrictions.

HTTP Status Code: 400

OrganizationNotFoundException

An operation received a valid organization identifier that either doesn't belong or exist in the system.

HTTP Status Code: 400

OrganizationStateException

The organization must have a valid state to perform certain operations on the organization or its members.

HTTP Status Code: 400

UnsupportedOperationException

You can't perform a write operation against a read-only directory.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Amazon WorkMail Message Flow

The following actions are supported by Amazon WorkMail Message Flow:

- [GetRawMessageContent](#)
- [PutRawMessageContent](#)

GetRawMessageContent

Service: Amazon WorkMail Message Flow

Retrieves the raw content of an in-transit email message, in MIME format.

Request Syntax

```
GET /messages/messageId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

messageId

The identifier of the email message to retrieve.

Length Constraints: Minimum length of 1. Maximum length of 120.

Pattern: `[a-z0-9\ -]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
messageContent
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The response returns the following as the HTTP body.

messageContent

The raw content of the email message, in MIME format.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

The requested email message is not found.

HTTP Status Code: 404

Examples

In the following examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example gets the raw content of an in-transit email message and sends it to a text file named "test".

Sample Request

```
GET /messages/a1b2cd34-ef5g-6h7j-kl8m-npq9012345rs HTTP/1.1
Host: workmailmessageflow.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.273 Python/3.6.0 Windows/10 botocore/1.13.9
X-Amz-Date: 20191107T195012Z
Authorization: AUTHPARAMS
```

Sample Response

```
HTTP/1.1 200 OK
Cache-Control: no-cache
Content-Type: application/json
Date: Thu, 07 Nov 2019 19:50:12 GMT
x-amzn-RequestId: ea71f214-79c5-4f89-9d4e-1ab4c43ae0df
Content-Length: 1344
Connection: keep-alive

Subject: Hello World
From: =?UTF-8?Q?marymajor_marymajor?= <marymajor@example.com>
To: =?UTF-8?Q?mateojackson=40example=2Enet?= <mateojackson@example.net>
Date: Thu, 7 Nov 2019 19:22:46 +0000
Mime-Version: 1.0
Content-Type: multipart/alternative;
  boundary="=_EXAMPLE+"
References: <mail.1ab23c45.5de6.7f890g123hj45678@storage.wm.amazon.com>
X-Priority: 3 (Normal)
X-Mailer: Amazon WorkMail
Thread-Index: EXAMPLE
Thread-Topic: Hello World
Message-Id: <mail.1ab23c45.5de6.7f890g123hj45678@storage.wm.amazon.com>

This is a multi-part message in MIME format. Your mail reader does not
understand MIME message format.
--=_EXAMPLE+
Content-Type: text/plain; charset=UTF-8
Content-Transfer-Encoding: 7bit

hello world

--=_EXAMPLE+
Content-Type: text/html; charset=utf-8
Content-Transfer-Encoding: quoted-printable

<!DOCTYPE HTML><html>
<head>
<meta name=3D"Generator" content=3D"Amazon WorkMail v3.0-4510">
<meta http-equiv=3D"Content-Type" content=3D"text/html; charset=3Dutf-8">=

<title>testing</title>
</head>
```

```
<body>
<p style=3D"margin: 0px; font-family: Arial, Tahoma, Helvetica, sans-serif; font-size:
  small;">hello world</p>
</body>
</html>
--=_EXAMPLE+--
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutRawMessageContent

Service: Amazon WorkMail Message Flow

Updates the raw content of an in-transit email message, in MIME format.

This example describes how to update in-transit email message. For more information and examples for using this API, see [Updating message content with AWS Lambda](#).

Note

Updates to an in-transit message only appear when you call `PutRawMessageContent` from an AWS Lambda function configured with a synchronous [Run Lambda](#) rule. If you call `PutRawMessageContent` on a delivered or sent message, the message remains unchanged, even though [GetRawMessageContent](#) returns an updated message.

Request Syntax

```
POST /messages/messageId HTTP/1.1
Content-type: application/json

{
  "content": {
    "s3Reference": {
      "bucket": "string",
      "key": "string",
      "objectVersion": "string"
    }
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

messageId

The identifier of the email message being updated.

Length Constraints: Minimum length of 1. Maximum length of 120.

Pattern: `[a-z0-9\ -]*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

content

Describes the raw message content of the updated email message.

Type: [RawMessageContent](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidContentLocation

WorkMail could not access the updated email content. Possible reasons:

- You made the request in a region other than your S3 bucket region.
- The [S3 bucket owner](#) is not the same as the calling AWS account.
- You have an incomplete or missing S3 bucket policy. For more information about policies, see [Updating message content with AWS Lambda](#) in the *WorkMail Administrator Guide*.

HTTP Status Code: 400

MessageFrozen

The requested email is not eligible for update. This is usually the case for a redirected email.

HTTP Status Code: 400

MessageRejected

The requested email could not be updated due to an error in the MIME content. Check the error message for more information about what caused the error.

HTTP Status Code: 400

ResourceNotFoundException

The requested email message is not found.

HTTP Status Code: 404

Examples

In the following examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example illustrates one usage of PutRawMessageContent.

Sample Request

```
POST /messages/4e87856b-f02f-39d5-a029-9e39ace5b6f1 HTTP/1.1
Host: workmailmessageflow.us-east-1.amazonaws.com
Accept-Encoding: gzip, deflate
User-Agent: aws-cli/1.16.230 Python/3.7.5 Darwin/18.7.0 botocore/1.12.220
X-Amz-Date: 20210127T151129Z
Authorization: AUTHPARAMS
Content-Length: 81
Connection: close
```

```
{"content": {"s3Reference": {"bucket": "My-S3-Bucket", "key": "My-S3-Object-Key"}}
```

Sample Response

```
HTTP/1.1 200 OK
Cache-Control: no-cache
Content-Type: application/json
Date: Wed, 27 Jan 2021 15:11:30 GMT
x-amzn-RequestId: ddd7de94-a4eb-4af8-8c3f-1d16cf98b458
Content-Length: 2
Connection: Close
```

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The following data types are supported by Amazon WorkMail:

- [AccessControlRule](#)
- [AvailabilityConfiguration](#)
- [BookingOptions](#)
- [Delegate](#)
- [DnsRecord](#)
- [Domain](#)
- [EwsAvailabilityProvider](#)
- [FolderConfiguration](#)
- [Group](#)
- [GroupIdentifier](#)
- [ImpersonationMatchedRule](#)
- [ImpersonationRole](#)
- [ImpersonationRule](#)
- [LambdaAvailabilityProvider](#)
- [ListGroupFilters](#)
- [ListGroupForEntityFilters](#)
- [ListResourcesFilters](#)
- [ListUsersFilters](#)
- [MailboxExportJob](#)
- [MailDomainSummary](#)
- [Member](#)
- [MobileDeviceAccessMatchedRule](#)
- [MobileDeviceAccessOverride](#)
- [MobileDeviceAccessRule](#)
- [OrganizationSummary](#)
- [Permission](#)
- [RedactedEwsAvailabilityProvider](#)

- [Resource](#)
- [Tag](#)
- [User](#)

The following data types are supported by Amazon WorkMail Message Flow:

- [RawMessageContent](#)
- [S3Reference](#)

Amazon WorkMail

The following data types are supported by Amazon WorkMail:

- [AccessControlRule](#)
- [AvailabilityConfiguration](#)
- [BookingOptions](#)
- [Delegate](#)
- [DnsRecord](#)
- [Domain](#)
- [EwsAvailabilityProvider](#)
- [FolderConfiguration](#)
- [Group](#)
- [GroupIdentifier](#)
- [ImpersonationMatchedRule](#)
- [ImpersonationRole](#)
- [ImpersonationRule](#)
- [LambdaAvailabilityProvider](#)
- [ListGroupFilters](#)
- [ListGroupForEntityFilters](#)
- [ListResourcesFilters](#)
- [ListUsersFilters](#)
- [MailboxExportJob](#)

- [MailDomainSummary](#)
- [Member](#)
- [MobileDeviceAccessMatchedRule](#)
- [MobileDeviceAccessOverride](#)
- [MobileDeviceAccessRule](#)
- [OrganizationSummary](#)
- [Permission](#)
- [RedactedEwsAvailabilityProvider](#)
- [Resource](#)
- [Tag](#)
- [User](#)

AccessControlRule

Service: Amazon WorkMail

A rule that controls access to an WorkMail organization.

Contents

Actions

Access protocol actions to include in the rule. Valid values include `ActiveSync`, `AutoDiscover`, `EWS`, `IMAP`, `SMTP`, `WindowsOutlook`, and `WebMail`.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z]+`

Required: No

DateCreated

The date that the rule was created.

Type: Timestamp

Required: No

DateModified

The date that the rule was modified.

Type: Timestamp

Required: No

Description

The rule description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\u00FF]+`

Required: No

Effect

The rule effect.

Type: String

Valid Values: ALLOW | DENY

Required: No

ImpersonationRoleIds

Impersonation role IDs to include in the rule.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9_-]+`

Required: No

IpRanges

IPv4 CIDR ranges to include in the rule.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 1024 items.

Length Constraints: Minimum length of 1. Maximum length of 18.

Pattern: `^(([0-9]|[1-9][0-9]|1[0-9]{2}|2[0-4][0-9]|25[0-5])\.){3}([0-9]|[1-9][0-9]|1[0-9]{2}|2[0-4][0-9]|25[0-5])/([0-9]|[12][0-9]|3[0-2])$`

Required: No

Name

The rule name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_-]+

Required: No

NotActions

Access protocol actions to exclude from the rule. Valid values include ActiveSync, AutoDiscover, EWS, IMAP, SMTP, WindowsOutlook, and WebMail.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z]+

Required: No

NotImpersonationRoleIds

Impersonation role IDs to exclude from the rule.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_-]+

Required: No

NotIpRanges

IPv4 CIDR ranges to exclude from the rule.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 1024 items.

Length Constraints: Minimum length of 1. Maximum length of 18.

Pattern: `^(([0-9]|[1-9][0-9]|1[0-9]{2}|2[0-4][0-9]|25[0-5])\.)\){3}([0-9]|[1-9][0-9]|1[0-9]{2}|2[0-4][0-9]|25[0-5])/([0-9]|[12][0-9]|3[0-2])$`

Required: No

NotUserIds

User IDs to exclude from the rule.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 12. Maximum length of 256.

Required: No

UserIds

User IDs to include in the rule.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 12. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AvailabilityConfiguration

Service: Amazon WorkMail

List all the AvailabilityConfiguration's for the given WorkMail organization.

Contents

DateCreated

The date and time at which the availability configuration was created.

Type: Timestamp

Required: No

DateModified

The date and time at which the availability configuration was last modified.

Type: Timestamp

Required: No

DomainName

Displays the domain to which the provider applies.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Pattern: [a-zA-Z0-9.-]+

Required: No

EwsProvider

If ProviderType is EWS, then this field contains RedactedEwsAvailabilityProvider. Otherwise, it is not required.

Type: [RedactedEwsAvailabilityProvider](#) object

Required: No

LambdaProvider

If ProviderType is LAMBDA then this field contains LambdaAvailabilityProvider. Otherwise, it is not required.

Type: [LambdaAvailabilityProvider](#) object

Required: No

ProviderType

Displays the provider type that applies to this domain.

Type: String

Valid Values: EWS | LAMBDA

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BookingOptions

Service: Amazon WorkMail

At least one delegate must be associated to the resource to disable automatic replies from the resource.

Contents

AutoAcceptRequests

The resource's ability to automatically reply to requests. If disabled, delegates must be associated to the resource.

Type: Boolean

Required: No

AutoDeclineConflictingRequests

The resource's ability to automatically decline any conflicting requests.

Type: Boolean

Required: No

AutoDeclineRecurringRequests

The resource's ability to automatically decline any recurring requests.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Delegate

Service: Amazon WorkMail

The name of the attribute, which is one of the values defined in the UserAttribute enumeration.

Contents

Id

The identifier for the user or group associated as the resource's delegate.

Type: String

Length Constraints: Maximum length of 256.

Required: Yes

Type

The type of the delegate: user or group.

Type: String

Valid Values: GROUP | USER

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DnsRecord

Service: Amazon WorkMail

A DNS record uploaded to your DNS provider.

Contents

Hostname

The DNS hostname.- For example, `domain.example.com`.

Type: String

Length Constraints: Maximum length of 256.

Required: No

Type

The RFC 1035 record type. Possible values: CNAME, A, MX.

Type: String

Length Constraints: Maximum length of 256.

Required: No

Value

The value returned by the DNS for a query to that hostname and record type.

Type: String

Length Constraints: Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Domain

Service: Amazon WorkMail

The domain to associate with an WorkMail organization.

When you configure a domain hosted in Amazon Route 53 (Route 53), all recommended DNS records are added to the organization when you create it. For more information, see [Adding a domain](#) in the *WorkMail Administrator Guide*.

Contents

DomainName

The fully qualified domain name.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Pattern: [a-zA-Z0-9.-]+

Required: Yes

HostedZoneId

The hosted zone ID for a domain hosted in Route 53. Required when configuring a domain hosted in Route 53.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: [^\s*]

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EwsAvailabilityProvider

Service: Amazon WorkMail

Describes an EWS based availability provider. This is only used as input to the service.

Contents

EwsEndpoint

The endpoint of the remote EWS server.

Type: String

Length Constraints: Maximum length of 256.

Pattern: `https?://[A-Za-z0-9.-]+(:[0-9]+)?/.*`

Required: Yes

EwsPassword

The password used to authenticate the remote EWS server.

Type: String

Length Constraints: Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: Yes

EwsUsername

The username used to authenticate the remote EWS server.

Type: String

Length Constraints: Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FolderConfiguration

Service: Amazon WorkMail

The configuration applied to an organization's folders by its retention policy.

Contents

Action

The action to take on the folder contents at the end of the folder configuration period.

Type: String

Valid Values: NONE | DELETE | PERMANENTLY_DELETE

Required: Yes

Name

The folder name.

Type: String

Valid Values: INBOX | DELETED_ITEMS | SENT_ITEMS | DRAFTS | JUNK_EMAIL

Required: Yes

Period

The number of days for which the folder-configuration action applies.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 730.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Group

Service: Amazon WorkMail

The representation of an WorkMail group.

Contents

DisabledDate

The date indicating when the group was disabled from WorkMail use.

Type: Timestamp

Required: No

Email

The email of the group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 254.

Pattern: `[a-zA-Z0-9._%+-]{1,64}@[a-zA-Z0-9.-]+\.[a-zA-Z-]{2,}`

Required: No

EnabledDate

The date indicating when the group was enabled for WorkMail use.

Type: Timestamp

Required: No

Id

The identifier of the group.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 256.

Required: No

Name

The name of the group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

State

The state of the group, which can be ENABLED, DISABLED, or DELETED.

Type: String

Valid Values: ENABLED | DISABLED | DELETED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GroupIdentifier

Service: Amazon WorkMail

The identifier that contains the Group ID and name of a group.

Contents

GroupId

Group ID that matched the group.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 256.

Required: No

GroupName

Group name that matched the group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImpersonationMatchedRule

Service: Amazon WorkMail

The impersonation rule that matched the input.

Contents

ImpersonationRuleId

The ID of the rule that matched the input

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_-]+

Required: No

Name

The name of the rule that matched the input.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [^\x00-\x1F\x7F\x3C\x3E\x5C]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImpersonationRole

Service: Amazon WorkMail

An impersonation role for the given WorkMail organization.

Contents

DateCreated

The date when the impersonation role was created.

Type: Timestamp

Required: No

DateModified

The date when the impersonation role was last modified.

Type: Timestamp

Required: No

ImpersonationRoleId

The identifier of the impersonation role.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_-]+

Required: No

Name

The impersonation role name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [^\x00-\x1F\x7F\x3C\x3E\x5C]+

Required: No

Type

The impersonation role type.

Type: String

Valid Values: FULL_ACCESS | READ_ONLY

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImpersonationRule

Service: Amazon WorkMail

The rules for the given impersonation role.

Contents

Effect

The effect of the rule when it matches the input. Allowed effect values are ALLOW or DENY.

Type: String

Valid Values: ALLOW | DENY

Required: Yes

ImpersonationRuleId

The identifier of the rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Description

The rule description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [^\x00-\x09\x0B\x0C\x0E-\x1F\x7F\x3C\x3E\x5C]+

Required: No

Name

The rule name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [^\x00-\x1F\x7F\x3C\x3E\x5C]+

Required: No

NotTargetUsers

A list of user IDs that don't match the rule.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: No

TargetUsers

A list of user IDs that match the rule.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9._%+@-]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

LambdaAvailabilityProvider

Service: Amazon WorkMail

Describes a Lambda based availability provider.

Contents

LambdaArn

The Amazon Resource Name (ARN) of the Lambda that acts as the availability provider.

Type: String

Length Constraints: Minimum length of 49. Maximum length of 256.

Pattern: `arn:aws:lambda:[a-z]{2}-[a-z]+\d{1}:\d{12}:function:[a-zA-Z0-9\-_\.\.]+(:(\$LATEST|[a-zA-Z0-9\-_\.\.]+))?`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListGroupsFilters

Service: Amazon WorkMail

Filtering options for *ListGroups* operation. This is only used as input to Operation.

Contents

NamePrefix

Filters only groups with the provided name prefix.

Type: String

Length Constraints: Maximum length of 256.

Required: No

PrimaryEmailPrefix

Filters only groups with the provided primary email prefix.

Type: String

Length Constraints: Maximum length of 256.

Required: No

State

Filters only groups with the provided state.

Type: String

Valid Values: ENABLED | DISABLED | DELETED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListGroupsForEntityFilters

Service: Amazon WorkMail

Filtering options for *ListGroupsForEntity* operation. This is only used as input to Operation.

Contents

GroupNamePrefix

Filters only group names that start with the provided name prefix.

Type: String

Length Constraints: Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListResourcesFilters

Service: Amazon WorkMail

Filtering options for *ListResources* operation. This is only used as input to Operation.

Contents

NamePrefix

Filters only resource that start with the entered name prefix .

Type: String

Length Constraints: Maximum length of 256.

Required: No

PrimaryEmailPrefix

Filters only resource with the provided primary email prefix.

Type: String

Length Constraints: Maximum length of 256.

Required: No

State

Filters only resource with the provided state.

Type: String

Valid Values: ENABLED | DISABLED | DELETED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListUsersFilters

Service: Amazon WorkMail

Filtering options for *ListUsers* operation. This is only used as input to Operation.

Contents

DisplayNamePrefix

Filters only users with the provided display name prefix.

Type: String

Length Constraints: Maximum length of 256.

Required: No

PrimaryEmailPrefix

Filters only users with the provided email prefix.

Type: String

Length Constraints: Maximum length of 256.

Required: No

State

Filters only users with the provided state.

Type: String

Valid Values: ENABLED | DISABLED | DELETED

Required: No

UsernamePrefix

Filters only users with the provided username prefix.

Type: String

Length Constraints: Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MailboxExportJob

Service: Amazon WorkMail

The details of a mailbox export job, including the user or resource ID associated with the mailbox and the S3 bucket that the mailbox contents are exported to.

Contents

Description

The mailbox export job description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1023.

Pattern: `[\S\s]*`

Required: No

EndTime

The mailbox export job end timestamp.

Type: Timestamp

Required: No

EntityId

The identifier of the user or resource associated with the mailbox.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 256.

Required: No

EstimatedProgress

The estimated progress of the mailbox export job, in percentage points.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

JobId

The identifier of the mailbox export job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: [A-Za-z0-9-]+

Required: No

S3BucketName

The name of the S3 bucket.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: [A-Za-z0-9.-]+

Required: No

S3Path

The path to the S3 bucket and file that the mailbox export job exports to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1023.

Pattern: [A-Za-z0-9!_.*'()/-]+

Required: No

StartTime

The mailbox export job start timestamp.

Type: Timestamp

Required: No

State

The state of the mailbox export job.

Type: String

Valid Values: RUNNING | COMPLETED | FAILED | CANCELLED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MailDomainSummary

Service: Amazon WorkMail

The data for a given domain.

Contents

DefaultDomain

Whether the domain is default or not.

Type: Boolean

Required: No

DomainName

The domain name.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Pattern: [a-zA-Z0-9.-]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Member

Service: Amazon WorkMail

The representation of a user or group.

Contents

DisabledDate

The date indicating when the member was disabled from WorkMail use.

Type: Timestamp

Required: No

EnabledDate

The date indicating when the member was enabled for WorkMail use.

Type: Timestamp

Required: No

Id

The identifier of the member.

Type: String

Length Constraints: Maximum length of 256.

Required: No

Name

The name of the member.

Type: String

Length Constraints: Maximum length of 256.

Required: No

State

The state of the member, which can be ENABLED, DISABLED, or DELETED.

Type: String

Valid Values: ENABLED | DISABLED | DELETED

Required: No

Type

A member can be a user or group.

Type: String

Valid Values: GROUP | USER

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MobileDeviceAccessMatchedRule

Service: Amazon WorkMail

The rule that a simulated user matches.

Contents

MobileDeviceAccessRuleId

Identifier of the rule that a simulated user matches.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_-]+

Required: No

Name

Name of a rule that a simulated user matches.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\\S\\s]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MobileDeviceAccessOverride

Service: Amazon WorkMail

The override object.

Contents

DateCreated

The date the override was first created.

Type: Timestamp

Required: No

DateModified

The date the override was last modified.

Type: Timestamp

Required: No

Description

A description of the override.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\S\s]+`

Required: No

DeviceId

The device to which the override applies.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `[A-Za-z0-9]+`

Required: No

Effect

The effect of the override, ALLOW or DENY.

Type: String

Valid Values: ALLOW | DENY

Required: No

UserId

The WorkMail user to which the access override applies.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MobileDeviceAccessRule

Service: Amazon WorkMail

A rule that controls access to mobile devices for an WorkMail group.

Contents

DateCreated

The date and time at which an access rule was created.

Type: Timestamp

Required: No

DateModified

The date and time at which an access rule was modified.

Type: Timestamp

Required: No

Description

The description of a mobile access rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\S\s]+`

Required: No

DeviceModels

Device models that a rule will match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

DeviceOperatingSystems

Device operating systems that a rule will match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

DeviceTypes

Device types that a rule will match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

DeviceUserAgents

Device user agents that a rule will match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

Effect

The effect of the rule when it matches. Allowed values are ALLOW or DENY.

Type: String

Valid Values: ALLOW | DENY

Required: No

MobileDeviceAccessRuleId

The ID assigned to a mobile access rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_-]+

Required: No

Name

The name of a mobile access rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\\S\\s]+

Required: No

NotDeviceModels

Device models that a rule **will not** match. All other device models will match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [\\u0020-\\u00FF]+

Required: No

NotDeviceOperatingSystems

Device operating systems that a rule **will not** match. All other device types will match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

NotDeviceTypes

Device types that a rule **will not** match. All other device types will match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

NotDeviceUserAgents

Device user agents that a rule **will not** match. All other device user agents will match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OrganizationSummary

Service: Amazon WorkMail

The representation of an organization.

Contents

Alias

The alias associated with the organization.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 62.

Pattern: `^(?!d-)([\da-zA-Z]+)([-][\da-zA-Z]+)*`

Required: No

DefaultMailDomain

The default email domain associated with the organization.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Pattern: `[a-zA-Z0-9.-]+`

Required: No

ErrorMessage

The error message associated with the organization. It is only present if unexpected behavior has occurred with regards to the organization. It provides insight or solutions regarding unexpected behavior.

Type: String

Length Constraints: Maximum length of 256.

Required: No

OrganizationId

The identifier associated with the organization.

Type: String

Length Constraints: Fixed length of 34.

Pattern: `^m-[0-9a-f]{32}$`

Required: No

State

The state associated with the organization.

Type: String

Length Constraints: Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Permission

Service: Amazon WorkMail

Permission granted to a user, group, or resource to access a certain aspect of another user, group, or resource mailbox.

Contents

GranteeId

The identifier of the user, group, or resource to which the permissions are granted.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 256.

Required: Yes

GranteeType

The type of user, group, or resource referred to in GranteeId.

Type: String

Valid Values: GROUP | USER

Required: Yes

PermissionValues

The permissions granted to the grantee. `SEND_AS` allows the grantee to send email as the owner of the mailbox (the grantee is not mentioned on these emails). `SEND_ON_BEHALF` allows the grantee to send email on behalf of the owner of the mailbox (the grantee is not mentioned as the physical sender of these emails). `FULL_ACCESS` allows the grantee full access to the mailbox, irrespective of other folder-level permissions set on the mailbox.

Type: Array of strings

Valid Values: FULL_ACCESS | SEND_AS | SEND_ON_BEHALF

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RedactedEwsAvailabilityProvider

Service: Amazon WorkMail

Describes an EWS based availability provider when returned from the service. It does not contain the password of the endpoint.

Contents

EwsEndpoint

The endpoint of the remote EWS server.

Type: String

Length Constraints: Maximum length of 256.

Pattern: `https?://[A-Za-z0-9.-]+(:[0-9]+)?/.*`

Required: No

EwsUsername

The username used to authenticate the remote EWS server.

Type: String

Length Constraints: Maximum length of 256.

Pattern: `[\u0020-\u00FF]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Resource

Service: Amazon WorkMail

The representation of a resource.

Contents

Description

Resource description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

DisabledDate

The date indicating when the resource was disabled from WorkMail use.

Type: Timestamp

Required: No

Email

The email of the resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 254.

Pattern: `[a-zA-Z0-9._%+-]{1,64}@[a-zA-Z0-9.-]+\.[a-zA-Z-]{2,}`

Required: No

EnabledDate

The date indicating when the resource was enabled for WorkMail use.

Type: Timestamp

Required: No

Id

The identifier of the resource.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 256.

Required: No

Name

The name of the resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `[\w\-\.\]+(\@[a-zA-Z0-9.\-\]+\.[a-zA-Z0-9-]{2,})?`

Required: No

State

The state of the resource, which can be ENABLED, DISABLED, or DELETED.

Type: String

Valid Values: ENABLED | DISABLED | DELETED

Required: No

Type

The type of the resource: equipment or room.

Type: String

Valid Values: ROOM | EQUIPMENT

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

Service: Amazon WorkMail

Describes a tag applied to a resource.

Contents

Key

The key of the tag.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Value

The value of the tag.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

User

Service: Amazon WorkMail

The representation of an WorkMail user.

Contents

DisabledDate

The date indicating when the user was disabled from WorkMail use.

Type: Timestamp

Required: No

DisplayName

The display name of the user.

Type: String

Length Constraints: Maximum length of 256.

Required: No

Email

The email of the user.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 254.

Pattern: `[a-zA-Z0-9._%+-]{1,64}@[a-zA-Z0-9.-]+\.[a-zA-Z-]{2,}`

Required: No

EnabledDate

The date indicating when the user was enabled for WorkMail use.

Type: Timestamp

Required: No

Id

The identifier of the user.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 256.

Required: No

Name

The name of the user.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\w\-\.]+(\@[a-zA-Z0-9\-\]+\.[a-zA-Z0-9-]{2,})?`

Required: No

State

The state of the user, which can be ENABLED, DISABLED, or DELETED.

Type: String

Valid Values: ENABLED | DISABLED | DELETED

Required: No

UserRole

The role of the user.

Type: String

Valid Values: USER | RESOURCE | SYSTEM_USER | REMOTE_USER

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Amazon WorkMail Message Flow

The following data types are supported by Amazon WorkMail Message Flow:

- [RawMessageContent](#)
- [S3Reference](#)

RawMessageContent

Service: Amazon WorkMail Message Flow

Provides the MIME content of the updated email message as an S3 object. All MIME content must meet the following criteria:

- Each part of a multipart MIME message must be formatted properly.
- Attachments must be of a content type that Amazon SES supports. For more information, see [Unsupported Attachment Types](#).
- If any of the MIME parts in a message contain content that is outside of the 7-bit ASCII character range, we recommend encoding that content.
- Per [RFC 5321](#), the maximum length of each line of text, including the <CRLF>, must not exceed 1,000 characters.
- The message must contain all the required header fields. Check the returned error message for more information.
- The value of immutable headers must remain unchanged. Check the returned error message for more information.
- Certain unique headers can only appear once. Check the returned error message for more information.

Contents

s3Reference

The S3 reference of an email message.

Type: [S3Reference](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

S3Reference

Service: Amazon WorkMail Message Flow

Amazon S3 object representing the updated message content, in MIME format.

Note

The region for the S3 bucket containing the S3 object must match the region used for WorkMail operations. Also, for WorkMail to process an S3 object, it must have permission to access that object. For more information, see [Updating message content with AWS Lambda](#).

Contents

bucket

The S3 bucket name.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `^[a-z0-9][a-z0-9\-\-]*`

Required: Yes

key

The S3 key object name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[a-zA-Z0-9\-\-/*]*`

Required: Yes

objectVersion

If you enable versioning for the bucket, you can specify the object version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: . +

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400